

**BY ORDER OF THE COMMANDER
EGLIN AIR FORCE BASE**



EGLIN AIR FORCE BASE INSTRUCTION

91-206

9 SEPTEMBER 2010

Certified Current 02 June 2016

Safety

MUNITIONS SOURCE DATA

COMPLIANCE WITH THIS PUBLICATION IS MANDATORY

ACCESSIBILITY: Publications and forms are available on the e-publishing website at www.e-publishing.af.mil for downloading or ordering.

RELEASABILITY: There are no releasability restrictions on this publication.

OPR: AAC/SEW

Supersedes: AACI21-202,
12 September 2003

Certified by: AAC/SE
(Col Guidry)

Pages: 17

This instruction implements AFD 91-2, *Safety Program*, and AFMAN 91-201, *Explosives Safety Standards*, by assigning responsibilities and establishing procedures for acquisition and review of source data necessary to ensure safe and efficient hazard classification, inspection, storage, transportation and disposal of new munitions and munitions components as defined in Attachment 1, Glossary of References and supporting information. It applies to the 46th Test Group (46 TG) and to all AAC activities and tenants at Eglin Air Force Base (AFB) involved in munitions acquisition, research, development, testing, evaluation or modification. The 46th Test Group shall follow locally established procedures outlined in the Holloman AFB Supplement 1 to AFI 21-201, *Conventional Munitions Maintenance Management* for developing and approving adequate technical data to support safe and efficient storage, handling, inspection, shipment, maintenance, and modification of munitions items delivered to Holloman AFB. Changes to the Holloman AFB Supplement will be coordinated with AAC/SEW and AAC/SES. Refer recommended changes and questions about this publication to the Office of Primary Responsibility (OPR) using the AF Form 847, *Recommendation for Change of Publication*; route AF Form 847s from the field through the appropriate functional's chain of command. Ensure that all records created as a result of processes prescribed in this publication are maintained in accordance with Air Force Manual (AFMAN) 33-363, *Management of Records*, and disposed of in accordance with Air Force Records Information System (AFRIMS) Records Disposition Schedule (RDS) located at <https://my.af.mil/afirms/afirms/afirms/rims.cfm>.

SUMMARY OF CHANGES

This document is substantially revised and must be completely reviewed. This revision updates required data elements IAW Technical Order (TO) 11A-1-47, *Ammunition and Explosives*

Hazard Classification Procedures, and the latest Data Item Descriptions (DID); shortens the routine processing time for Technical Data for Munitions Packages (TDM PACKAGE) to 10 working days; defines the process for submitting and coordinating unclassified TDM PACKAGEs electronically via Livelink; adds guidance on requesting explosives hazard classification; consolidates the publication of all required data into a single expanded template; mandates inclusion of U.S. standard equivalents with metric units of measurement; and adds a glossary of references and supporting information.

1.	Policy on Preparation and Delivery of Source Data.	2
2.	Source Data Information Requirements.	3
3.	Routing, Review, Approval and Rescission Process:	3
4.	Responsibilities:	4
5.	Forms Adopted.	6
Attachment 1—GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION		7
Attachment 2—TECHNICAL DATA PACKAGE GUIDE.		9
Attachment 3—TECHNICAL DATA PACKAGE TEMPLATE		15

1. Policy on Preparation and Delivery of Source Data. The timely preparation and delivery of accurate, adequate source data is a fundamental prerequisite for receipt, delivery, or use of new munitions and munitions components. No missions will be placed on the operations order until all required source data have been reviewed and approved IAW paragraph 3 of this instruction. New munitions and munitions components shipped to the 46 TG or Eglin AFB without a required TDM PACKAGE will be suspended and disposition action taken as appropriate.

1.1. AAC Systems Safety (AAC/SES) will evaluate all new munitions and munitions components, live or inert, for hazardous content and the need for a TDM PACKAGE. Hazardous content includes but is not limited to any material classified by Code of Federal Regulations (CFR) Title 49 as Non-Regulated or assigned to Department of Transportation (DOT) Hazard Classes 1-9. Items not already assigned a final hazard classification may also require assignment of an interim hazard classification (IHC) by AAC/SES IAW AFMAN 91-201, *Explosives Safety Standards*, and TO 11A-1-47 if they will be stored on DoD property, transported to DoD Property, or transported under a DoD contract.

1.2. A minimum of 10 working days will be allocated for routine electronic processing and review of an unclassified TDM PACKAGE. Additional time will be needed to process classified information, documents which must be converted to electronic format or TDM PACKAGE submissions which fail to include all required information. Additional time will also be needed if key personnel, including alternates, are not available. Because of the compressed 10-day review process, it is imperative all information be submitted correctly and be formatted IAW Attachment 3. Expedited processing of TDM PACKAGEs may be requested IAW AAC Plan 70, *Crisis/Command Directed Rapid Response Testing Plan*.

1.3. Transportation of new munitions and munitions components shall not begin until sufficient data on its hazards and functioning have been provided to the 96th Civil Engineering Squadron's Explosive Ordnance Disposal (EOD) Flight (96 CES/CESD) and safe handling and recovery procedures (SHARP) have been developed and approved.

2. Source Data Information Requirements. Data Items will be submitted to AAC/SES & SEW IAW Attachment 2 as required by DI-SAFT-81299, *Explosive Hazard Classification Data*, DI-SAFT-80931, *Explosive Ordnance Disposal Data*, and DI-SAFT-80182, *Technical Data for Munitions* (TDM). If metric units of measurement are used, include U.S. standard equivalents.

2.1. When the required DID information is already published in other technical documents (e.g. Preliminary TOs, Developmental Program Manuals, Procedural Support Data, other service Technical Manuals, etc.), the responsible Test Engineer (TE) will provide AAC/SES & SEW the published documents with a cover memorandum in the format of Attachment 3. Specifically identify where the required information can be found in the accompanying technical document and/or where different data is to be applied.

2.1.1. Air Force technical documents will be given precedence when documents are available from both the Air Force and another source. For example, if a manufacturer's manual for an item does not mandate a pre-use inspection and an Air Force technical manual does, the Air Force manual would take precedence.

2.1.2. When new munitions or munitions component are very similar to an item already detailed in a technical document, the technical document for the 'like-item' may be considered for use with the new item. To request use of a technical document for a like-item as source data for a new item, the responsible TE will provide AAC/SES the like-item technical document with a cover letter identifying any differences between the new item and the like-item.

3. Routing, Review, Approval and Rescission Process:

3.1. Initial TDM PACKAGE Submittal. Test customers will compile the required source data and submit it for initial review via the Livelink electronic approval process. Customers without direct access to Livelink will provide source data to their assigned 46th Test Wing (46 TW) test engineer (TE) for submittal through Livelink.

3.1.1. The preferred electronic format for submitting source data is as a Microsoft Word document using Times New Roman font. Source data may also be submitted in Adobe Acrobat format but may require more time to process. Approved electronic TDM PACKAGES will be published in Adobe Acrobat PDF format. Sample TDM PACKAGES are available as reference documents in Livelink.

3.1.2. Classified data cannot be placed on Livelink and must be delivered to reviewers via secure means and media. Test customers who wish to exclude proprietary information from TDM PACKAGES should identify pertinent data elements in the TDM PACKAGE submittal and provide contact information so reviewers can evaluate the proprietary information separately.

3.1.3. TDM PACKAGE Supplements and Revisions. Test customers can make changes to existing TDM PACKAGES by submitting a request via Livelink to AAC/SES. The supplement memo must specify which section of the TDM PACKAGE is affected and

the exact wording of the change itself. AAC/SES may require a revision to the existing TDM PACKAGE if the number of supplements becomes unworkable or the changes are substantial.

3.2. TDM PACKAGE Routing and Approval. Initial TDM PACKAGE submittals, changes, supplements and revisions will be routed using Livelink whenever possible. Once AAC/SES has determined a TDM PACKAGE is required and provided initial review, the submittal will be routed through AAC/SEW, 46 MXS/MXMWMC and 46 MXG/MXQ for review. After all offices have completed their reviews, AAC/SEW will approve for EOD source data and AAC/SES will approve for System Safety and forward to 46 MXG/MXQ for their endorsement. TDM PACKAGE changes, supplements and revisions will be routed the same way. 96 CES/ CESD and 46 MXS/MXMWMC will be notified automatically via Livelink of all approved TDM PACKAGE submittals, changes, supplements and revisions.

3.3. Annual Review of TDM PACKAGES and IHCs. TDM PACKAGES and IHCs will be reviewed annually by the test customer or by the assigned 46 TW TE to validate continued use and currency of provided information. Annual review dates will be based upon the date of initial approval or be one year from the date of last approved supplement or revision, whichever is latest. If the TDM PACKAGE is not formatted IAW Attachment 2, the customer or TE must submit a revision to AAC/SES and state in the cover letter that the old TDM PACKAGE is superseded.

3.3.1. 46 MXS/MXMWMC will suspend items from issue and use when their TDM PACKAGE annual review is overdue by 30 days. If a TDM PACKAGE annual review is still overdue after 90 days, an AF Form 191, *Ammunition Disposition Request (ADR)*, will be processed IAW AFI 21-201, *Conventional Munitions Maintenance Management*, to authorize disposal or return to origin. Attendant expenses involved will be charged to the project's Job Order Number (JON).

3.3.2. Test customers must maintain an active JON for each TDM PACKAGE against which annual review charges can be applied.

3.4. Rescinding TDM PACKAGES. Test customers or assigned TEs will ensure TDM PACKAGES are rescinded via Livelink when no longer needed. Before a TDM PACKAGE is rescinded, the owner must verify with 46 MXS/MXMWMA that no affected items remain on Eglin. Rescinded TDM PACKAGES may be reinstated at a later date provided the munitions data is still current and in the proper format.

4. Responsibilities:

4.1. Test customers will:

4.1.1. Compile munitions source data IAW Attachment 2 and send it to AAC/SES or the assigned 46 TW TE IAW section 3.1 above prior to shipment of items to Eglin AFB.

4.1.2. Review TDM PACKAGES and IHCs annually IAW section 3.3 above.

4.1.3. Ensure munitions packaging complies with 49 CFR. Request support from the Container Integrated Product Team (IPT) when the IHC from AAC/SES cannot be used as the packaging authority. They will evaluate munitions packing, handling, and transportation data IAW 49 CFR to determine the need for a Certificate of Equivalency (COE) or a Competent Authority Approval (CAA). COEs are valid for shipment of

hazardous materials within the Continental United States (CONUS). If International shipments are to be made that will involve public transportation infrastructure (roads, docks, rails, etc.), a CAA will be required.

4.1.4. Request Shelf/Service Life extensions from AAC/SES. Serious consideration must be given to safety and serviceability prior to requesting extensions. Many bulk explosives and propellants become unstable over time and can auto-ignite and explode. Test Engineers/Program Managers are responsible for gathering certified documentation to justify shelf/service life extension.

4.1.5. Determine if stability testing is required for bulk explosives and propellants. This information can be obtained from item manufacturers or organizations such as the AFRL High Explosive Research and Development (HERD) Facility. If testing is necessary, identify the time interval (in months) to conduct stability testing and who will conduct the testing.

4.1.6. Coordinate with the 46 TW Munitions Storage Area (MSA) before shipping items to Eglin which require special storage or handling (e.g. classified, weather-sensitive, etc.). The MSA has limited capabilities for providing secure alarmed inside storage.

4.1.7. Generate M-Series Work Cards in accordance with AACI 21-101, *Local Technical Order Writing Procedures*, if items will need to be transported outside of their shipping container. **Note:** If items remain in their original DOT shipping container, Eglin personnel can use general tie-down procedures as outlined in T.O. 11-1-38, *Positioning and Tie-Down Procedures Nonnuclear Munitions*, for transportation on Eglin AFB.

4.2. AAC/SES (Systems Safety) will:

4.2.1. Review demilitarization code for accuracy for each item according to AFMAN 23-110V2CD, *USAF Supply Manual*.

4.2.2. Review TDM PACKAGES for compliance with the requirements of this instruction relative to the 46 MXS Munitions Storage Area storage and maintenance requirements. Advise the test customer or assigned TE of any deficiencies in the TDM PACKAGE relative to this.

4.2.3. Assign an Interim Hazard Classification (IHC), Storage Compatibility Group, and UN number for munitions being stored or tested on Eglin AFB.

4.2.4. Ensure the TDM responsible organization has addressed hazard mitigation requirements relative to 46 MXS Munitions Storage Area storage and maintenance requirements.

4.2.5. Coordinate changes to munitions TDM PACKAGES with the test customer or assigned TE, AAC/SEW and 46 MXG/MXQ. Ensure changes do not affect safety.

4.2.6. Extend the shelf and/or service life of a munitions item only after Test/Program Manager provides certified documentation of analysis supporting safety and serviceability of the asset after shelf/service life extension.

4.2.7. Attach a copy of the approved TDM PACKAGE cover letter generated through System Safety (AAC/SES) and Weapons Safety (AAC/SEW) to the TDM PACKAGE in Livelink.

4.3. AAC/SEW (Weapons Safety) will review and approve initial TDM PACKAGE submittals, changes, supplements, revisions and ensure they contain sufficient information for the Munitions Flight (46 MXS/MXMW) and the EOD Flight (96 CES/CESD) to safely accomplish their missions.

4.4. 46 MXG/MXQ (Quality Assurance) will review and approve initial TDM PACKAGE submittals, changes, supplements and revisions for the 46 MXG.

4.5. 96 CES/CESD (EOD) will develop safe handling and recovery procedures (SHARP) as required following receipt of TDM PACKAGES.

4.6. 46 MXS/MXMWMC (Munitions Inspection) will:

4.6.1. Review and coordinate on initial TDM PACKAGE submittals, changes, supplements and revisions.

4.6.2. Prepare a DD Form 1348-6, *DoD Single Line Item Requisition System Document*, on each local stock number assigned.

4.6.3. Receive, inspect and store all munitions items with approved technical data.

4.6.4. Suspend and place in condition code J (suspended from issue and use, condition unknown) all munitions items received without an approved TDM PACKAGE.

4.6.4.1. Notify AAC/SEW, 46 MXG/MXQ and the test customer or assigned TE that munitions items have been suspended until an approved TDM PACKAGE is received.

4.6.4.2. Schedule impounded assets for condition code change if an approved TDM PACKAGE is received within 30 days. Allow ten working days for condition code change to be applied.

4.6.4.3. If an approved TDM PACKAGE is not received after 30 days of suspension, an AF Form 191 will be processed IAW AFI 21-201 to authorize disposal or return to origin. Attendant expenses involved will be charged to the project's JON.

5. Forms Adopted. AF Form 847, *Recommendation for Change of Publication*

AF Form 191, *Ammunition Disposition Request (ADR)*

DD Form 1348-6, *DoD Single Line Item Requisition System Document*

SAL M. NODJOMIAN, Colonel, USAF
Commander

Attachment 1**GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION*****References***

DoD 5160.62-D, *Single Manager Responsibility for Military EOD Technology and Training (EODT&T)*

AFI 21-201, *Conventional Munitions Maintenance Management*

AFJI 32-3002, *Interservice Responsibilities for Explosive Ordnance Disposal*

AFMAN 91-201, *Explosives Safety Standards*

T.O. 00-5-3, *Technical Order Life Cycle Management*

T.O. 11A-1-10, *Munitions Surveillance Program and Serviceability Procedures*

T.O. 11A-1-47, *Ammunition and Explosives Hazard Classification Procedures*

DI-SAFT-80931B, *Explosive Ordnance Disposal Data*

DI-SAFT-81299B, *Explosive Hazard Classification Data*

Abbreviations and Acronyms

ADR— Ammunition Disposition Request

CAA— Competent Authority Approval

CFR— Code of Federal Regulations

COE— Certificate of Equivalency

DOM— Date of Manufacture

DOT— Department of Transportation

EMR— Electromagnetic Radiation

IHC— Interim Hazard Classification

IPT— Integrated Product Team

JON— Job Order Number

MSA— Munitions Storage Area

TDM PACKAGE— Technical Data for Munitions Package

TE— Test Engineer

SHARP— Safe Handling and Recovery Procedures

Terms

Inert— Contains no explosives, active chemicals, pyrotechnics or any type of battery.

Livelihood— A web-based application used for all aspects of documentation management including project management, workflows and documentation tracking.

Net Explosives Weight—The total quantity of explosives material or pyrotechnics.

New Munitions or Munitions Components— Developmental or modified explosive ordnance or non-developmental foreign ordnance, test articles, components and certain explosive commercial products.

Non-Developmental— Not being evaluated for development.

Working Days— Days other than weekends or Federal holidays.

Attachment 2**TECHNICAL DATA PACKAGE GUIDE.**

Note: This attachment is only to be used as a guide; do not submit Attachment 2 with the Technical Data Package. Indicate "Not Available" for data values which have not yet been determined.

DATE: _____

MEMORANDUM FOR AAC/SES & SEW

46 MXG/MXQI

FROM: [Originating Office (Project Officer/Telephone No.)]

SUBJECT: Technical Data/Hazard Classification Request for [Nomenclature]

1. Item Description:**1.1. Identification**

1.1.1. Name: (Official designation/nomenclature of the ordnance, including any common names and any known foreign designations)

1.1.2. National or Local Stock Number (if assigned)

1.1.3. Part number: (Product code or other unique identifier).

1.1.4. System Used On: (System or next higher assembly of which the subject item is a part).

1.1.5. Application: (A brief general description of the normal application of the ordnance item plus optional applications).

1.1.6. Markings: (All external markings, paintings and colors. Markings may include ordnance designation, loading information, settings, index marks, time scales, manufacturer's marks, instructional notes, lot numbers and color code designators.).

1.1.7. Other Ordnance Used With This Item: (Fuze data shall state what bombs, dispensers, projectiles, landmines, grenades or rocket warheads they are used with; bomb data shall state what fuzes, rockets, fin assemblies or guidance units may be used; dispensers, clusters, launchers and certain projectiles shall include all sub munitions which could be loaded. If new fusing is used in conjunction with a munitions item, completed information on the fuze is required IAW requirements herein).

1.2. Physical Description.

1.2.1. Visual Description: (An overall narrative physical description of the appearance and condition of the item in the unarmed, pre-armed, and armed conditions. Include dimensions and unpackaged weight).

1.2.2. Drawings and Schematics: (Illustrations of the configuration of the explosive item, and the relationship of the item's parts as assembled. Include illustrations of the relationship of the explosive item to other items in the system).

1.2.3. Composition and Shell Material: (Include material specifications such as type of material [e.g. steel, aluminum, Bakelite, etc.] and thickness of material).

1.2.4. Description of all major sections, subassemblies, fuze safety features, classified materials and hazardous components or material. If sections will be shipped or stored separately, define the hazardous item(s) in each component. (Include their purpose, function, and method of operation. This includes available illustrations necessary to understand functioning with appropriate callouts for major sections, subassemblies, hazardous components, power sources; plus arming, safing and firing subcomponents. Include a cross-reference to reports detailing design safety features and operational or safety tests but place the document files inside the Supporting Documents section of Livelink).

1.2.5. Hazardous Materials: (A general description of all toxic or hazardous materials and liquids; explosive main-charges, subassemblies and firing trains; hydraulics, or pneumatic pressure sources and routing. Describe electric voltage sources and circuits, thermal or chemical energy sources, mechanical hazards, fuels and oxidizers. Include explosive or chemical formulation and the weights of explosive or chemical material. Describe any other item that could present a physical threat to the safety of personnel. For items containing a liquid or gas, include the name or type of liquid or gas; physical state; nominal pressure/pressure range in psi as well as cubic inches of material if pressurized; quantity in both pounds and gallons of liquid; vapor pressure; and flash point. If batteries are installed, state which type (NICAD, lithium, alkaline, etc.). Include any known Environmental Protection Agency (EPA) approved disposal information relating to the above items).

1.2.5.1. Explosives or chemical formulation: (Include type, composition, and total weight of each explosive or chemical subassembly in the item [e.g., detonator, booster, squib, rocket motor, etc.]).

1.2.5.2. Weight of explosives or chemical material: (Oxidizer volume, propellant volume, propellant weight, filler volume, filler weight, fired weight, oxidizer weight, etc.).

1.2.6. Net Explosive Weight per Item: (The total weight of all explosive materials in an item).

1.2.7. Electrical power sources for fuzes that contain stored, electrical energy for fuze firing (e.g., Electronic Safe & Arm Fuze (ESAF) devices, thermal or wet cell batteries, firing capacitors, etc.) and operation information for arming and firing circuits. **Note:** Recommend any data from battery bleed-down tests and all-fire/no-fire tests be provided as part of this. Recommend any data from extending a battery performance test beyond the required munitions performance standards to the no-fire level as described below also be provided.

1.2.7.1. No-Fire Time and All-Fire Level: (If known, include time from munitions power activation until voltage achieves a "no-fire" level of the munitions most sensitive electrical firing component to initiate an explosive firing train or event. No-fire level is the maximum power level at which the munition cannot fire. The test to determine no-fire level shall use the same electrical load (circuitry drain) and normal munitions or system power as would a fielded munition. Test data shall also reflect the "all-fire" level of the munition. All-fire level is the power necessary for ordnance to function as designed. Include analytical reports produced from test instrumentation that monitored the voltage throughout the life span of a battery or firing capacitor from the time of system activation to the point the battery or firing capacitor decays to a no-fire level. EOD considers the time it takes for a munition to essentially safe itself by waiting a prescribed amount of time based upon tested bleed-down times in worst-case conditions that the munitions fusing system may be found in a dud-fired scenario.

Documentation of these values shall be included in a Report of Test that describes the: overall

test setup procedures, equipment used to monitor and measure electrical power, test objectives and test results.

1.2.8. Designed Influence Sensitivity or Activation Levels: (Required for influence-actuated ordnance such as magnetic, acoustic or pressure activated mines. Also state arm time and/or revolutions/distance to arm).

1.3. Functional Description and Operational Sequence: (Include the step-by-step sequence of events from the initial pre-arming action through arming and functioning. The functional sequence description should be supported by graphical illustrations with callouts depicting critical components described during the sequence of operation or functional description(s). Electrical block or circuit diagrams should include all electrically-initiated ordnance items and all power sources, firing capacitor switches and bleeder resistors. Computer graphics depicting cutaway illustrations, as appropriate, should show internal components).

2. Inspection Procedures:

2.1. Provide inspection procedures for inspecting item. If specific inspection criteria are required other than inspecting the outer container(s), they must be specifically stated.

2.2. Warnings, Cautions and Notes. List warnings, cautions and notes which should draw special attention to handling the item (e.g. armed or hazardous condition indicators). Format headers as follows:

WARNING

(An operating or maintenance procedure, practice, condition, statement, etc., which if not strictly observed, could result in injury to or death of personnel.)

CAUTION

(An operating or maintenance procedure, practice, condition, statement, etc., which if not strictly observed, could result in damage to or destruction of equipment or loss of mission effectiveness.)

NOTE

(An essential operating or maintenance procedure, condition or statement, which must be emphasized.)

2.3. Defects. (List any critical/major/minor defects that render the item unsafe or unserviceable such as corrosion, punctures, dents, leaks, arm indicators and safing devices.)

2.3.1. Critical Defects. (A critical defect is one that is likely to result in hazardous or unsafe conditions for individuals using, transporting or maintaining munitions; a defect that is likely to cause the destruction of/or serious damage to the weapon or launcher under normal training or combat conditions.)

2.3.2. Major Defects. (A major defect is a defect other than critical, that is likely to result in failure during use or which precludes or reduces materially, the usability of the item for its intended use.)

2.3.3. Minor Defects. (A minor defect is a defect other than critical or major that is not likely to result in failure during use. It does not affect use or operation of the item, but should be corrected prior to issue.)

2.3.4. Corrective Actions. (List any authorized actions to correct defects.)

2.4. Periodic Inspection Interval and Percentage. (List periodic inspection (PI) time interval in months and percentage sample size (percentage of total quantity stored which must be inspected as part of the periodic inspection) for items to be maintained in storage. The item will otherwise be considered PI exempt.)

2.5. Stability Testing Interval and Agency. (For bulk and exposed explosives/propellants, identify time frame in months to conduct stability testing and who will conduct the testing.)

3. Packaging Data:

3.1. Description of Packaging (A narrative description of how each item is packaged and secured. Include type, size and gross weight. {e.g. wood, cardboard, metal, etc.}.)

3.1.1. Number of items per inner package.

3.1.2. Number of inner packages per outer package.

3.2. Required DOT Labels and Markings (Markings must comply with TO 11A-1-10, *Munitions Serviceability Procedures and 49 CFR.*)

3.3. Provide container disposition instructions (reusable container, ship to destination or destroy when empty. If reusable, provide shipping information disposition, address and POC for receipt).

3.4. Desiccation Requirements (e.g. how many units to install per container).

3.5. Illustration of packing and shipping containers.

4. Storage Criteria and Limitations:

4.1. Shelf Life in Months. (The shelf life identifies how long from the date of manufacture an item in prescribed packaging and storage conditions can be considered serviceable. Shelf life should be based on scientific evidence as recommended by the manufacturer.

4.2. Service Life in Months. (The Service Life is the length of time an item can remain installed in operating configuration or in actual usage. If service life is shorter than shelf life, clearly define what starts the service life [e.g. item removed from container; item placed in ready use configuration] and if the service life can be stopped [e.g. item placed back into original packaging configuration]. Unless otherwise specified, service life will be considered as starting on the date item is issued from the MSA. Expiration date for service life will be the last day of expiration month regardless of actual expiration date [service life date will not exceed shelf life date of an item].)

4.3. Date of Manufacture (The DOM must also be marked on the item packaging.)

4.4. Temperature limits. (Provide minimum and maximum exposure limits.)

4.5. Humidity Requirements. (Identify how often in months the humidity of an item in storage must be checked.)

4.6. Stacking Height. (Identify how many shipping containers may be stacked on top of each other. If stacking is forbidden, specify "One.")

4.7. Requirement for special storage (e.g. classified, weather-sensitive, alarmed, etc.)

5. Special Handling Criteria:

5.1. Special handling procedures (include fragile areas to avoid and specify grounding points).

5.2. Special equipment required for handling the item (e.g. conductive wrist straps).

5.3. Drop heights from which items may be considered unserviceable:

5.3.1. Drop height in the container

5.3.2. Drop height out of the container

5.4. Personal Protective Equipment (list any PPE required for normal handling and when the equipment is to be used [e.g. gloves for PCP-treated wooden boxes].)

6. Special Tie-Down Procedures:

6.1. For transportation on Eglin Main and the Eglin Reservation, Eglin personnel can use general tie-down procedures as outlined in T.O. 11-1-38, *Positioning and Tie-Down Procedures Nonnuclear Munitions*, for munitions items, provided the items remain in their original DOT shipping container.

6.2. Transporting items out of their container will require the use of MHU-series munitions trailers; test managers must generate M-Series Work Cards in accordance with AACI 21-101, *Local Technical Order Writing Procedures*.

7. Emergency Procedures:

7.1. State any unique procedures that must be accomplished or taken into consideration in an emergency (e.g. fire, armed condition, etc.). If none, state so.

7.2. Information on any known sensitivity of item to external energy (e.g. electromagnetic, heat, radiological, etc.) that could accidentally function item if it was damaged or disassembled.

7.3. Emergency Protective Equipment (e.g. gas mask, self contained breathing apparatus, etc.) for hazardous/toxic solids, liquids or gaseous materials likely to be encountered. If material safety data sheets (MSDS) are available, include a cross-reference in the TDM PACKAGE but place the MSDS files inside the Supporting Documents section of Livelink.

7.4. Disassembly procedures. (If disassembly is possible, describe step-by-step the normal disassembly of the item required for EOD to separate the explosive and hazardous components from the item body. This would include installation of safing devices, protective devices, cable disconnections and tools required. Include computer graphics illustrations or drawings as appropriate to help illustrate difficult procedures. Include separate procedures for varying item configurations if possible/required.)

8. Demilitarization Information:

8.1. A live munitions item or an item containing batteries of any type would reflect a [G] code.

8.2. An inert munitions item would reflect [B] code.

9. Munition Security Classification: (Include Controlled Item Code [CIC] and CAC if assigned. For classified items, state the classification instead of saying, "classified.")

10. Unit Cost:

10.1. List cost per component if multiple components are sent or packaged separately.

11. Additional Information:

- 11.1. List the original TDM PACKAGE requester's address, phone number, e-mail address, etc., for the munitions item.
- 11.2. List the name, phone number and e-mail address for responsible Test Engineer/Program Manager from Eglin AFB. Include at least two local points of contact.
- 11.3. Include any other pertinent information as applicable.
- 11.4. Additional EOD data. If available, inclusion of the following useful data is optional but recommended.
 - 11.4.1. Fittings and Features (All fittings and features, which will differentiate the item from a similar item within a class or family of ordnance items. Features or fittings should be visible and obvious without touching or disassembling the item.)
 - 11.4.2. Thread specifications.
 - 11.4.3. Level II engineering drawings of the components with external views and internal cutaways
 - 11.4.4. Detailed Dimensions (cartridge case length, maximum diameter, minimum diameter, maximum thickness, minimum thickness, maximum total length, minimum total length, fuze maximum exposed length, fuze minimum exposed length, maximum height, minimum height, maximum width, minimum width).

Attachment 3**TECHNICAL DATA PACKAGE TEMPLATE**

NOTE: This attachment is only to be used as a template; do not submit Attachment 3 with the Technical Data Package. Indicate "Not Available" for applicable data values.

DATE: _____

MEMORANDUM FOR AAC/SES & SEW

46 MXG/MXQI

FROM: (Originating Office (Project Officer/Telephone No.))

SUBJECT: Technical Data/Hazard Classification Request for (Nomenclature).

1. Item Description:

1.1. Identification.

1.1.1. Name.

1.1.2. National or Local Stock Number (if assigned).

1.1.3. Part number.

1.1.4. System Used On.

1.1.5. Application.

1.1.6. Markings.

1.1.7. Other Ordnance Used With This Item.

1.2. Physical Description.

1.2.1. Visual Description.

1.2.2. Drawings and Schematics.

1.2.3. Composition and Shell Material.

1.2.4. Description of all major sections, subassemblies, fuze safety features, classified materials, and hazardous components or material.

1.2.5. Hazardous Materials.

1.2.6. Net Explosive Weight per Item.

1.2.7. Electrical power sources and operation information for fuze arming and firing circuits.

1.2.7.1. No-Fire Time and All-Fire Level.

1.2.8. Designed Influence Sensitivity or Activation Levels.

1.3. Functional Description and Operational Sequence.

2. Inspection Procedures:

2.1. Provide inspection procedures for inspecting item.

- 2.2. Warnings, Cautions and Notes.
- 2.3. Defects.
 - 2.3.1. Critical Defects.
 - 2.3.2. Major Defects.
 - 2.3.3. Minor Defects.
 - 2.3.4. Corrective Actions.
- 2.4. Periodic Inspection Interval and Percentage.
- 2.5. Stability Testing Interval and Agency.

3. Packaging Data:

- 3.1. Description of Packaging.
 - 3.1.1. Number of items per inner package.
 - 3.1.2. Number of inner packages per outer package.
- 3.2. Required DOT Labels and Markings.
- 3.3. Provide container disposition instructions.
- 3.4. Desiccation Requirements, and if required, how many units to install per container.
- 3.5. Illustration of packing and shipping containers.

4. Storage Criteria and Limitations:

- 4.1. Shelf Life in Months.
- 4.2. Service Life in Months.
- 4.3. Date of Manufacture.
- 4.4. Temperature limits.
- 4.5. Humidity Requirements.
- 4.6. Stacking Height.
- 4.7. Requirement for special storage.

5. Special Handling Criteria:

- 5.1. Special handling procedures.
- 5.2. Special equipment required for handling the item.
- 5.3. Drop heights from which items may be considered unserviceable:
 - 5.3.1. Drop height in the container.
 - 5.3.2. Drop height out of the container.
- 5.4. Personal Protective Equipment.

6. Special Tie-Down Procedures:

6.1. For transportation on Eglin Main and the Eglin Reservation, Eglin personnel can use general tie-down procedures as outlined in T.O. 11-1-38, *Positioning and Tie-Down Procedures Nonnuclear Munitions*, for munitions items, provided the items remain in their original DOT shipping container.

6.2. Transporting items out of their container will require the use of MHU-series munitions trailers; test managers must generate M-Series Work Cards in accordance with AACI 21-101, *Local Technical Order Writing Procedures*.

7. Emergency Procedures:

7.1. State any unique procedures that must be accomplished or taken into consideration in an emergency (e.g. fire, armed condition, etc.). If none, state so.

7.2. Information on any known sensitivity of item to external energy (e.g. electromagnetic, heat, radiological, etc.) that could accidentally function item if it was damaged or disassembled.

7.3. Emergency Protective Equipment.

7.4. Disassembly procedures

8. Demilitarization Information:

8.1. A live munitions item or an item containing batteries of any type would reflect a [G] code.

8.2. An inert munitions item would reflect [B] code.

9. Munition Security Classification: (Include Controlled Item Code [CIC] and CAC if assigned. For classified items, state the classification instead of saying, "classified.")

10. Unit Cost:

10.1. List cost per component if multiple components are sent or packaged separately.

11. Additional Information:

11.1. List the original TDM PACKAGE requester's address, phone number, e-mail address, etc., for the munitions item.

11.2. List the name, phone number and e-mail address for responsible Test Engineer/Program Manager from Eglin AFB. Include at least two local points of contact.

11.3. Include any other pertinent information as applicable.

11.4. Additional EOD data.