

**BY ORDER OF THE SECRETARY
OF THE AIR FORCE**

**AIR FORCE MANUAL 11-2E-3G,
VOLUME 3**



3 NOVEMBER 2022

**18TH WING
Supplement**

30 JUNE 2026

Flying Operations

E-3G OPERATIONS PROCEDURES

COMPLIANCE WITH THIS PUBLICATION IS MANDATORY

ACCESSIBILITY: This publication is available for downloading or ordering on the e-Publishing website at www.e-Publishing.af.mil

RELEASABILITY: There are no releasability restrictions on this publication

OPR: ACC/A3C

Certified by: AF/A3T
(Maj Gen Albert G. Miller)

Pages: 115

(18WG)

OPR: 18OG/OGV

Certified by: 18OG/CC
(Col David A. Deptula)

Supersedes: AFI11-2E-3V3_18WGSUP, 12 October 2016

Pages: 115

This manual implements Air Force Policy Directive (AFPD) 11-2, *Aircrew Operations* and Air Force Manual (AFMAN) 11-202 Volume 3, *Flight Operations*. It establishes effective and safe operations of the E-3G Airborne Warning and Control System (AWACS). It applies to all civilian employees and uniformed members of the Regular Air Force and the Air Force Reserve operating E-3G aircraft. It does not apply to the Air National Guard or the United States Space Force. The applicable SORN F011 AF XO A, Aviation Resource Management System (ARMS) membership programs is available at <http://dpclo.defense.gov/Privacy/SORNs.aspx>. Ensure all records generated as a result of processes prescribed in this publication adhere to Air Force Instruction (AFI) 33-322, *Records Management and Information Governance Program*, and are disposed in accordance with (IAW) the Air Force Records Disposition Schedule, which is located in the Air Force Records Information Management System. Refer recommended changes and questions about this publication to the office of primary responsibility (OPR) listed above using the Department of the Air Force (DAF) Form 847, *Recommendation for Change of Publication*; route

DAF Forms 847 from the field, through the appropriate Major Command (MAJCOM) channels to Air Combat Command/Airborne Command and Control Systems Branch (ACC/A3CA). Forward approved recommendations to ACC/A3CA. MAJCOMs Direct Reporting Units (DRUs), and Field Operating Agencies (FOAs) forward proposed MAJCOM/DRU/FOA-level supplements to this volume to Air Force Flight Standards Agency/Flight Directives (AFFSA/XOF), through ACC/A3CA, for approval prior to publication IAW AFI 11-200, *Aircrew Training, Standardization/Evaluation, and General Operations Structure*. The issuing office provides copies of approved and published supplements to ACC/A3CA, and the user MAJCOM/DRU/FOA OPRs. Field units below MAJCOM/DRU/FOA level forward copies of their supplements to this publication to their parent MAJCOM/DRU/FOA OPR for post publication review. The authorities to waive wing/unit level requirements in this publication are identified with a Tier (“T-0, T-1, T-2, T-3”) number following the compliance statement. See Department of the Air Force Manual (DAFMAN) 90-161, *Publishing Processes and Procedures* for a description of the authorities associated with the Tier numbers. Submit requests for waivers through the chain of command to the appropriate Tier waiver approval authority, or alternately, to the requestor’s commander for non-tiered compliance items. The use of the name or mark of any specific manufacturer, commercial product, commodity, or service in this publication does not imply endorsement by the Department of the Air Force. Compliance with the attachments in this publication is mandatory.

(18WG) Air Force Manual (AFMAN) 11-2E-3G, Volume 3, *E-3G Operations Procedures*, 3 November 2022, is supplemented as follows: This publication prescribes the operating policies, procedures, and restrictions for all aircrew members operating E-3G aircraft and mission equipment from Kadena Air Base (AB), Japan. It applies to ground support personnel. It applies to 18th Wing (18 WG) and Temporary Duty (TDY) E-3G units at Kadena AB. Ensure all records generated as a result of processes prescribed in this publication adhere to Air Force Instruction (AFI) 33-322, *Records Management and Information Governance Program*, and are disposed in accordance with (IAW) the Air Force Records Disposition Schedule, which is located in the Air Force Records Information Management System. Refer recommended changes and questions about this publication to the office of primary responsibility (OPR) using the DAF Form 847, *Recommendation for Change of Publication*; route DAF Forms 847 from the field through the appropriate functional chain of command.

Chapter 1—GENERAL INFORMATION	8
1.1. Scope.....	8
1.2. Roles and Responsibilities.....	8
1.3. Deviations.....	8
1.4. Waivers.....	8
1.5. Explanation of New Terms.....	8
1.6. Distribution.....	9
Chapter 2—MISSION PLANNING	10
2.1. Responsibilities.....	10

2.2.	Forms and Logs.	10
2.3.	Fuel Conservation.	10
2.4.	Navigational Charts.	10
2.5.	Mission Planning Requirements.	11
2.6.	Theater Procedures.	12
Chapter 3—AIRCREW OPERATING PROCEDURES		13
3.1.	Pilot in Command (PIC) Responsibilities.	13
3.2.	Crew Manning.	13
3.3.	Crew Rest/Flight Duty Period (FDP).....	14
3.4.	Pre-Mission Duties.	15
3.5.	Minimum Equipment.	15
3.6.	Communications.	15
3.7.	Air Battle Manager (ABM)-Assisted/Directed Rendezvous Responsibilities.	16
3.8.	Radar Radiation Restrictions.	16
3.9.	On-Station Procedures.	16
3.10.	Aircraft Location Monitoring.	16
3.11.	Airborne Warning and Control System (AWACS) Monitor.	17
3.12.	Transportation of Passengers.	17
3.13.	Debriefings.....	18
3.14.	Flying Clothing/Equipment.	18
3.15.	Aircraft Security at Enroute Stops/Destination.....	19
3.16.	Personal Publications Requirements.....	19
3.17.	Aircraft Recall/Diversion.....	19
3.18.	Transition Training.	19
3.19.	Crew Coordination Drills (CCD).....	20
3.20.	Aircraft Cleanliness.	20
3.21.	Aircraft Configuration for Static Display.	20
3.22.	Readiness Postures.....	20
3.23.	Maximum Flight Duty Period (FDP) for Readiness Posture one (RP-1), Readiness Posture three (RP-3).	21
3.24.	Post-Alert Compensation Time.....	21
Chapter 4—FLIGHT CREW OPERATING PROCEDURES		22
4.1.	Adverse Weather.....	22

	4.2.	Takeoff and Landing Data (TOLD)/Restrictions.....	23
	4.3.	Takeoff and Landing Guidance.....	25
	4.4.	Touch-and-Go Landings.....	25
	4.5.	In-Flight Simulated Emergency/Engine-Out Procedures.....	26
	4.6.	Landing Attitude Demonstrations.....	27
	4.7.	Preflight.....	27
	4.8.	Engine Start/Taxi.....	28
	4.9.	Frequency Monitoring.....	28
	4.10.	Altitude Monitoring.....	28
	4.11.	Departure.....	28
	4.12.	Enroute Navigation.....	29
Table	4.1.	E-3 Communications, Navigation, and Surveillance (CNS)/Air Traffic Management (ATM) Certifications.....	30
Table	4.2.	E-3B/C/G Communications, Navigation, and Surveillance (CNS)/Air Traffic Management (ATM)Operational Approvals.....	32
	4.13.	On-Station.....	34
	4.14.	Arrival and Approach.....	34
	4.15.	Simulator-Only Maneuvers.....	35
	4.16.	Occupancy of Flight Crew Duty Positions.....	35
	4.17.	Mid-Air Collision Avoidance.....	35
	4.18.	Equipment on the Flight Deck.....	36
	4.19.	In-Flight Meals.....	36
	4.20.	Fuel Requirements.....	36
	4.21.	Aircraft Ground Refueling.....	36
	4.22.	Fuel Jettisoning.....	37
	4.23.	Aircraft Interior Lighting.....	37
	4.24.	In-Flight Engine Failure.....	37
	4.25.	In-Flight Troubleshooting.....	37
	4.26.	Cockpit Voice Recorder (CVR).....	37
	4.27.	Flight Control Malfunctions.....	37
	4.28.	Divert Charts.....	37
	4.29.	Air-to-Air Refueling (AAR) Restrictions/Procedures.....	37
	4.30.	Post-Air-to-Air refueling (AAR) Procedures.....	38

4.31.	Formation Restrictions.....	39
4.32.	Abnormal Configurations.	39
4.33.	Three-Engine Ferry Flights.....	39
4.34.	Suspected Engine Compressor Stall/Surge on the Ground.	39
4.35.	Automatic Dependent Surveillance–Broadcast (ADS-B) In Devices.....	39
Chapter 5—MISSION CREW OPERATING PROCEDURES		40
5.1.	General.....	40
5.2.	Mission Crew Communications.....	40
5.3.	Mission Commander (MC).....	40
5.4.	Section Lead in Command (SLIC).	40
5.5.	Supervision of Sections.	41
5.6.	Weapons Controllers (Air Battle Manager [ABM]/Others as qualified).	42
5.7.	Active Sensor Operator (ASO).	42
5.8.	Datalink Operator (DLO).....	42
5.9.	Mission System Operator (MSO).	43
5.10.	Passive Sensor Operator (PSO).	43
5.11.	Internet Protocol Enabled Communication (IPEC) Operator.	44
5.12.	Airborne Radio Operator.	44
5.13.	Airborne Data Systems Technician (ADST).	44
5.14.	Airborne Radar Technician (ART).	45
5.15.	Establishing Operations-Normal.....	45
5.16.	Assuming Station.	47
5.17.	Voice Tell and Recording Procedures.	48
5.18.	Electronic Combat (EC) Procedures.....	48
5.19.	Identification Procedures.	49
5.20.	Control Procedures.	49
5.21.	Communications Procedures.	50
5.22.	Off-Station Procedures.	50
Chapter 6—FLIGHT PATH MANAGEMENT (FPM), OPERATIONAL RISK MANAGEMENT (ORM), CREW RESOURCE MANAGEMENT (CRM), THREAT AND ERROR MANAGEMENT (TEM)		51
6.1.	Flight Path Management.....	51
6.2.	Operational Risk Management (ORM).....	51

6.3.	Crew Resource Management/Threat and Error Management (CRM/TEM).....	51
6.4.	Automation Management.	52
6.5.	Flight Path Management (FPM) Pilot Flying (PF) and Pilot Monitoring (PM) Duties.	53
6.6.	Advisory Calls.	55
Table 6.1.	Climb Out Advisory Calls.	56
Table 6.2.	Descent Advisory Calls.	56
Table 6.3.	Non-precision Approach Advisory Calls.....	57
Table 6.4.	Precision Approach Advisory Calls.....	58
6.7.	Critical Action Coordination.....	59
6.8.	Stabilized Approach.....	60
Chapter 7—(Added-18WG) E-3 LOCAL OPERATING PROCEDURES		62
7.1.	(Added-18WG) General.....	62
7.2.	(Added-18WG) Aircrew Operating Procedures.	64
7.3.	(Added-18WG) Flight Crew Operating Procedures.	65
7.4.	(Added-18WG) Mission Crew Operating Procedures.	70
Attachment 1—GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION		73
Attachment 2—E-3 BAGGAGE AND EQUIPMENT LOADING		88
Attachment 3—E-3 PASSENGER BRIEFING GUIDE		90
Attachment 4—(Added-18WG) KOREAN THEATER AIR CONTROL SYSTEM (KTACS) OPERATIONS		92
Attachment 5—(Added-18WG) OPERATIONAL RISK MANAGEMENT (ORM)		97
Attachment 6—(Added-18WG) PERSONAL EQUIPMENT		98
Attachment 7—(Added-18WG) REQUIRED PUBLICATIONS		99
Attachment 8—(Added-18WG) FLIP REQUIREMENTS		100
Attachment 9—(Added-18WG) AIRCRAFT COCKING PROCEDURES		101
Attachment 10—(Added-18WG) ALTERNATE LISTING		107
Attachment 11—(Added-18WG) DIVERSION CARD KADENA AREA DIVERT AIRFIELDS		108
Attachment 12—(Added-18WG) CREW BRIEFING GUIDE (INITIAL AND EXECUTION)		109

Attachment 13—(Added-18WG) FLIGHT CREW BRIEFING GUIDE (P-SORTIE/SPECIALIZED)

111

Attachment 14—(Added-18WG) HANGAR LAUNCH PROCEDURES

114

Chapter 1

GENERAL INFORMATION

1.1. Scope. This manual, in conjunction with other governing directives, prescribes those procedures applicable to the operation of E-3 aircraft under most circumstances. It is not a substitute for sound judgment. Procedures not specifically addressed may be accomplished if they enhance safe and effective mission accomplishment.

1.2. Roles and Responsibilities.

1.2.1. Major Command (MAJCOM). MAJCOMs will provide guidance and approve waivers (as required), where specified throughout this manual. **(T-2)**

1.2.2. Pilot in Command (PIC). The PIC is the aircrew member designated by competent authority, regardless of rank, as being responsible for, and is the final authority for the operation of the aircraft. The PIC will ensure the aircraft is not operated in a careless, reckless, or irresponsible manner. **(T-3)**

1.2.3. Aircrew. Individuals designated on the flight authorization are responsible to fulfill specific aeronautical tasks regarding operating USAF aircraft as specified in this manual or by other competent, supplemental authority.

1.2.4. Mission Crew. See **Chapter 5** for a detailed roles and responsibilities section for mission crew positions.

1.3. Deviations. Deviations from mandatory requirements in this manual require specific approval of the waiver authority unless an urgent requirement or an aircraft emergency dictates otherwise. In that case, the PIC will take the appropriate action to ensure the safety of crewmembers/passengers and the aircraft. **(T-1)**

1.4. Waivers. Tier waiver authorities (T-0, T-1, T-2, T-3) have been added to all mandated unit compliance items (wing level and below) as prescribed by DAFMAN 90-161 and AFMAN 11-202 Volume 3, *Flight Operations*. Forward waiver requests through appropriate channels to the MAJCOM/Director of Operations (A3) for approval. All approvals will include an expiration date. **(T-2)** Air Combat Command Standardization and Evaluations Branch (ACC/A3TV) and ACC/A3CA are the offices of coordinating responsibility for all waiver requests to this manual.

1.5. Explanation of New Terms. This document is written to increase flexibility of squadron and crew leadership. Definitions are expanded to allow tailored crew complements.

1.5.1. Air Battle Manager (ABM) refers to aircrew members that have completed the Air Battle Manager syllabus and hold a qualification as an "ABM".

1.5.1.1. The term Section Lead (SL) refers an ABM that holds the SL certification.

1.5.1.2. The term Active Sensor Operator (ASO) refers to an ABM who is responsible for sensor operations. This crew position can be held by an ABM after "ASO certification".

1.5.1.3. The term Passive Sensor Operator (PSO) refers to an ABM whose responsibilities include the configuration and optimization of the passive sensor.

1.5.2. Because of changes regarding multiple qualifications, the term Weapons Controllers can refer to anyone being evaluated to applicable areas to control aircraft.

1.5.2.1. The term Mission System Operator (MSO) refers to aircrew that have completed the “Mission System Operator” syllabus and hold a qualification as an MSO.

1.5.2.2. The term Datalink Operator (DLO) refers to an MSO or ABM that hold a datalink certification.

1.5.3. The following technician crew positions and associated acronyms have been added.

1.5.3.1. Airborne Radio Operator (ARO) refers to a technician that has completed technician conversion or initial qualification training and is qualified on all associated communications systems and the Link 11 datalink.

1.5.3.2. Airborne Data Systems Technician (ADST) refers to a technician that has completed technician conversion or initial qualification training and is qualified on all associated mission computing systems, passive detection system (PDS), and the Link 16 datalink.

1.6. Distribution. Issue this manual to E-3 aircrew members IAW local procedures.

Chapter 2

MISSION PLANNING

2.1. Responsibilities. The Aircraft Commander (AC) is responsible for mission planning. The Section Lead in Command (SLIC) is responsible for preparing the crew for and executing mission taskings. The operations functions of the unit will support both efforts. Flying crews may perform their own mission planning or units may utilize a Mission Planning Cell (MPC). The MPC will designate qualified individuals to perform mission planning and/or conduct briefings. **(T-3)** Units will develop specific procedures to ensure all aircrew members are thoroughly prepared for each flight. **(T-3)**

2.2. Forms and Logs. Appropriate Group Commander (GP/CC), or GP/CC-designated representative, will develop/specify flight plans, logs, and mission forms. **(T-3)** Existing Air Force (AF) and MAJCOM forms should be used to the maximum extent possible.

2.3. Fuel Conservation. Aircrew and mission planners will manage aviation fuel as a limited commodity and precious resource. **(T-3)** Fuel optimization will be considered throughout all phases of mission planning and execution. **(T-3)** Excessive ramp and recovery fuel adds to aircraft gross weight, which increases fuel consumption. Do not ferry extra fuel beyond optimum requirements for safe mission accomplishment and training objectives. Aircrew and mission planners will optimize flight plans and flight routing for fuel efficiency. **(T-3)** In-flight procedures such as climb/descent profiles and power settings should also be considered for efficient fuel usage. Aircrew should employ the following aviation fuel optimization measures without compromising flight safety or jeopardizing mission/training accomplishment:

2.3.1. Optimize fuel loads. Mission plan for the required ramp and recovery fuel. Ensure ramp fuel is correct upon arrival at aircraft.

2.3.2. Minimize Auxiliary Power Unit (APU) use. Use ground power units when practical.

2.3.3. Delay engine start time. Establish and implement local engine start time standards.

2.3.4. Minimize aircraft weight through optimized fuel loads and reduction of equipment not necessary to accomplish the mission.

2.3.5. Establish Command and Control (C2) and flight following procedures to ensure timely notification of mission changes/cancellations to avoid unnecessary or unproductive flight time.

2.4. Navigational Charts.

2.4.1. Annotate an appropriately scaled navigational chart (electronic or paper) with the route of flight and the following:

2.4.1.1. Special Use Airspace (SUA) within the altitude structure and within 50 Nautical miles (NM) of the route of flight/orbit airspace per the Air Force Pamphlet (AFPAM) 11-216, *Air Navigation*. **(T-3)** [With-DMA] Display SUA overlay on the Integrated Multi-Function Display (IMFD) when applicable. **(T-3)** Crews may use electronic navigational charts in lieu of paper navigational charts.

2.4.1.2. Mission airspace/E-3 orbit airspace with altitude blocks. For E-3 Air-to-Air Refueling (AAR) airspace, label AAR Initial Point (ARIP), AAR Control Point (ARCP), and AAR Exit Point. Annotate any applicable restrictions. **(T-3)** [With-DMA] Display orbit Letter of Agreement (LOA) boundaries and air refueling information on the IMFD. **(T-3)**

2.4.1.3. Emergency airfields sufficient to cover the route of flight. [With-DMA, Display airfield overlay on IMFD as needed]. **(T-3)**

2.4.1.4. High terrain within 50 NM of the route of flight. **(T-3)** [With-DMA, not applicable (N/A) Enhanced Ground Proximity Warning System (EGPWS).]

2.4.1.5. Air Defense Identification Zone boundaries within 50 NM of the route of flight. [With-DMA, Display on IMFD.] **(T-3)**

2.4.1.6. Equal Time Point (ETP) and Flight Information Region (FIR) boundaries as required. [With-DMA, Display on IMFD.] **(T-3)**

2.4.2. Annotate an Operational Navigation Chart (ONC), or larger scale, with the planned departure/arrival airfield and the following. [With-DMA, Utilize Flight Management System (FMS) and DRAGON avionics to display appropriate navigational procedure.]

2.4.2.1. Planned departure/arrival procedure and Special Departure Procedures (SDPs). [With-DMA, SPD will be displayed as secondary flight plan overlay]. **(T-3)**

2.4.2.2. Highest terrain or obstacle within 50 NM along expected route of flight. [With-DMA, N/A due to EGPWS.]

2.4.2.3. Units may specify flight plan requirements and procedures in their local chapters to meet specialized mission requirements.

2.5. Mission Planning Requirements. The appropriate GP/CC may waive requirements contained in this paragraph if deemed necessary to accomplish a specific mission. **(T-3)**

2.5.1. Briefings/Debriefings.

2.5.1.1. All aircrew members will attend these briefings unless excused by the AC/SLIC or local procedures dictate otherwise. **(T-3)**

2.5.1.2. The AC/SLIC will brief and debrief all crewmembers to ensure safe and effective mission accomplishment. **(T-3)** Aircrew may use locally developed mission specific briefing guides to enhance mission planning and briefing efficiency and effectiveness.

2.5.1.3. Units will develop and document guidance for items that are commonly briefed as “standard.” **(T-3)** Items in unit standards and those items understood by all participants may be briefed as “standard.” The purpose of unit or local standards is to reduce the briefing time of administrative tasks to allow for concentration on the mission. Aircrew will use these procedures unless conditions, objectives, or execution dictates the AC/SLIC to brief as “non-standard”. **(T-3)**

2.5.2. Passengers. The AC will assign a crewmember to be responsible for passengers and/or Distinguished Visitors (DVs); reference [paragraph 3.12](#) for minimum responsibilities. **(T-3)**

2.5.3. Aircraft and Aircrew Status. Aircraft and aircrew status will be briefed/addressed as appropriate. **(T-3)**. Aircraft status will be obtained on the day of the flight from the appropriate maintenance unit, including open discrepancies from the Air Force Technical Order (AFTO) Form 781A, *Maintenance Discrepancy and Work Document*. **(T-3)** Aircrew status will be obtained from ARMS personnel. **(T-3)**

2.5.4. ABM-Assisted Rendezvous. The AC or Navigator (NAV) will review the AAR rendezvous procedures and techniques with the ABM in charge of assisting the rendezvous. **(T-3)**. The ABM will be provided with the following information:

2.5.4.1. Location of rendezvous: AAR Control Time (ARCT), ARIP, ARCP coordinates in degrees latitude (LAT)/longitude (LONG), and AAR altitudes. **(T-3)**

2.5.4.2. Rendezvous geometry and communications: Desired tanker offset and turn range, desired calls, alternate procedures, and transponder codes. **(T-3)**

2.5.5. ABM-Directed Rendezvous. The ABM will brief the flight crew on the AAR rendezvous procedures to include AAR rendezvous type, altitude, and anticipated turn ranges and turn direction. **(T-3)**

2.5.6. Orbit Planning. The flight crew will coordinate with the SLIC to determine optimum orbit configuration based on tasking and orbit limitations. **(T-3)**

2.5.7. Mission Crew Planning. The SLIC will ensure mission activities are planned according to applicable procedures, assess the impact of equipment limitations, adjust taskings as necessary, and assign crew members to develop an employment plan. **(T-3)** The SLIC will guide and conduct a final review of planning. **(T-3)**

2.6. Theater Procedures. The unit tasked to support an area of operations will develop theater procedures (classified/unclassified) and make them available to the crew upon implementation of a contingency Operation Plan (OPLAN) for deployment to the theater. **(T-3)**

Chapter 3

AIRCREW OPERATING PROCEDURES

3.1. Pilot in Command (PIC) Responsibilities. Squadron Commander (SQ/CC), Detachment Commander (DETCO), or designated representative must designate an AC, Instructor Pilot (IP), or Evaluator Pilot as the PIC for all flights on a flight authorization form IAW DAFMAN 11-401, *Aviation Management*, and applicable supplements. **(T-3)** The PIC is responsible for the safe and effective flight operations. The aircrew is responsible to the PIC for the successful accomplishment of all flight activities IAW AFMAN 11-202 Volume 3 and applicable MAJCOM supplements. PIC responsibilities and/or authorities include:

- 3.1.1. Managing crew resources and safe mission accomplishment.
- 3.1.2. Crew welfare.
- 3.1.3. Final word for requesting or accepting any waivers affecting the crew or mission.
- 3.1.4. Coordinating with the SLIC regarding any portion of the flight affecting mission accomplishment.

3.2. Crew Manning.

3.2.1. Guidance for aircrew manning for operational employment is normally IAW AFI 65-503, *US Air Force Cost and Planning Factors*. Mission crew manning may vary by the type of mission flown. Squadron Directors of Operations (SQ/DO), DETCO, or designated representative may tailor aircrew manning to meet operational requirements. In the Northern Command (NORTHCOM) area of responsibility (AOR), the mission crew may be augmented with North American Aerospace Defense Command (NORAD) personnel, if required.

3.2.2. Minimum flight crew manning includes two pilots (one qualified AC), NAV, and Flight Engineer (FE). [With-DMA] Minimum flight crew manning includes two pilots (one qualified AC), and FE.

3.2.3. Minimum mission crew manning to power up the mission systems includes SLIC, ASO (see [paragraph 5.7.](#)), Airborne Radar Technician (ART), ADST and an ARO. **(T-3)** Battle Management Team (BMT) manning may vary by the type of mission flown.

3.2.3.1. The SLIC and ASO can be the same crewmember.

3.2.3.2. An ASO is only required when the active sensors will be operated.

3.2.4. Minimum mission crew manning for control of aircraft (in addition to the minimum power-up crew) will include at least one qualified weapons controller supervised by a SL or SLIC current for control. **(T-3)**

3.2.5. Unless waived by the SQ CC/DO, inexperienced ADSTs will fly with an experienced ADST, inexperienced ARTs will fly with an experienced ART, and inexperienced FEs will fly with an experienced FE. **(T-3)**

3.2.6. Flight Crew Augmentation. In addition to the normal flight crew, minimum crew augmentation will consist of an additional AC, NAV, and FE who are qualified and current in the duties that will be performed. **(T-3)** Adding flight crewmembers after the first takeoff in a crew duty period is not considered augmentation. SQ/CC, DETCO, or designated representative will determine the augmented mission crew compliment. **(T-3)** [With-DMA] Minimum crew augmentation consists of an additional AC and FE who are qualified and current in the duties that will be performed.

3.3. Crew Rest/Flight Duty Period (FDP). Crew rest, FDP, and augmented aircrew FDP guidance is provided in AFMAN 11-202V3, *Flight Operations*, and applicable MAJCOM supplements with the following additional guidance:

3.3.1. Units/Aircrews will limit basic FDP to 12 hours and augmented FDP to 16 hours with any of the following inoperative: autopilot, altitude hold, or any axis of the autopilot. **(T-2)** If an autopilot malfunction occurs after departure, the AC, after consideration of operational risk and mission requirements, may request GP/CC approval to continue to normal maximum basic FDP, as applicable.

3.3.2. Non-Duty Time. Crewmembers will be afforded 12 hours of non-duty time after a flight before reporting for normal non-flying duties, unless waived by SQ/DO for operational necessity. **(T-3)**

3.3.3. Crew Rest Timing. Crew rest for successive flight activity will begin 1 hour after final landing (engine shutdown) from previous flight activity, or when the last crewmember departs after completing required aircrew duties, whichever occurs later.

3.3.4. Crew Rest for Deploying/Redeploying Aircrews. Ground time between landing and subsequent takeoff will not be planned for less than 18 hours when transitioning four time zones or more, unless waived by applicable GP/CC. This does not apply to “Ops Stops” made within an aircrew duty period. This restriction applies only to initial reporting prior to commencement of a new mission. It does not apply to multi-day missions that are in progress.

3.3.5. Management of Air Force Reserve Command (AFRC) Crewmembers. The on-scene commander or E-3 DETCO is responsible for the effective management of aircrews. **(T-3)** An element of that responsibility is the effective use of the Reserve associate aircrew personnel during their periods of availability. There is no guarantee that missions will always be completed at scheduled Mission End Time (MET). Therefore, it is incumbent upon Reserve associate crewmembers to make available sufficient time to accommodate unavoidable delays in returning to home station. Scheduled Return Time (SRT) will be calculated as MET plus 24 hours for routine exercise and operational deployments. **(T-3)** SRT(s) for contingencies and missions of unknown duration will be determined by the 513d Air Control Group Commander (513 ACG/CC) and 552d Operations Group Commander (552 OG/CC) or the requesting authority in coordination with HQ AFRC. **(T-3)** The SRT will be determined and placed on the initial and subsequent flight authorizations until the mission is complete. **(T-3)** The overall objective is to recover aircrews on schedule and provide scheduling stability. Two essential elements of this concept are realistic determination of SRT(s) based on mission duration and conscientious management by the on-scene commander or DETCO to ensure return of reserve associate aircrews by the MET. Except in uncontrollable or unusual circumstances, Reserve associate crewmembers must be assured that their missions will be complete within the SRT. **(T-3)** The Reserve associate AC and SLIC will be provided a copy

of all mission itinerary changes. **(T-3)** Delays in return of Reserve associate personnel beyond their SRT will be coordinated through the 552 OG/CC and 513 ACG/CC, and concurred with by the aircrew. **(T-3)** Every available means will be used to return Reserve associate crewmembers to home station to meet the SRT. **(T-3)** If Reserve associate aircrew (or members) cannot extend past the SRT, the on-scene commander will verify whether military or contract means of transportation is available. If no such means are available, the on-scene commander or DETCO will use the most expeditious means, including commercial air, to return Reserve associate personnel to home station. **(T-3)**

3.4. Pre-Mission Duties. The AC, in coordination with the SLIC and DO/DETCO, may adjust crew report time to meet mission requirements. Crew report times will allow sufficient time to accomplish all preflight activities IAW locally prescribed guidance. Normally, use a show time of 3+30 hours prior to takeoff for sorties planned by aircrew and flown on the same day. If an MPC is used, the SQ/DO or MPC Chief will set the show time. The technicians and FE should arrive at the aircraft 1+30 hours prior to the scheduled takeoff time. All other crewmembers show at the aircraft no later than 1 hour prior to the scheduled takeoff time. On the day of the mission, aircrew may only be scheduled for duties related to the mission.

3.5. Minimum Equipment. The 552 OG is the Combat Air Forces (CAF) lead for developing and maintaining the Minimum Equipment List (MEL) for use by all AWACS units. The MEL is a guide to determine operable equipment required for safe flight. 552 OG will forward a copy of the MEL to ACC/A3CA, PACAF Flight Operations (PACAF/A3T), and Air Force Reserve Command Combat Division (AFRC/A3D). **(T-3)**

3.6. Communications.

3.6.1. Required Communication. Communicate the following to the applicable Command Post or operations center, unless local directives or tactical deception requirements specify otherwise: **Note:** Crew position identified at end of action is responsible for ensuring communication is made.

3.6.1.1. Maintenance discrepancies, which will delay preflight or takeoff. (AC or designated rep)

3.6.1.2. Engine start time. Notify Base Defense Operations Center (BDOC) at least 10 minutes prior to starting engines, when appropriate. (AC/Copilot (CP))

3.6.1.3. Anytime equipment malfunctions, or an incident occurs that will adversely affect mission accomplishment. (AC/SLIC)

3.6.1.4. Actual takeoff time. (NAV) [With-DMA, FE].

3.6.1.5. Significant changes in mission timing. (NAV) [With-DMA, AC or designated rep].

3.6.1.6. Maintenance codes and estimated time of arrival (ETA) prior to final landing. (ARO)

3.6.1.7. Revised ETA (if changed by more than 15 minutes) when in Ultra High Frequency (UHF) radio contact. (NAV) [With-DMA, AC or designated rep].

3.6.1.8. Sortie block time and flight duration. (NAV) [With-DMA, AC or designated rep].

3.6.2. Aircraft landing status and System Capability Codes (“Maintenance Codes”). The FE and each technician will provide the maintenance codes to the ARO prior to landing. **(T-3)** Use the Aircraft Landing Status and System Capability Codes as defined in DAFI 21-101, *Aircraft and Equipment Maintenance Management*, and applicable MAJCOM supplements.

3.7. Air Battle Manager (ABM)-Assisted/Directed Rendezvous Responsibilities. The ABM will provide information to assist the flight crew in accomplishing the rendezvous and for situational awareness. **(T-3)**

3.7.1. Communications. Internal coordination between the flight crew and the ABM during the rendezvous will be over Net 1. **(T-3)** Other crewmembers should minimize use of Net 1 for 30 minutes before the ARCT until after the refueling is complete, unless required for safety of flight. During Directed Rendezvous, ABMs will voice vectors, altitude changes, and any other directive calls over the primary AAR frequency as appropriate for emissions control (EMCON) procedures being utilized IAW Allied Technical Publication (ATP)-3.3.4.2., *Air-to-Air Refueling*, ATP-56 Edition C Version 1. **(T-3)**

3.7.2. Procedures. The ABM will execute the pre-planned type of rendezvous as coordinated with the AC, SLIC, NAV, and tanker. **(T-3)** The ABM will pass bearing, range, and offset of the tanker as prebriefed/required. **(T-3)** Flight crew will advise the SLIC when to terminate ABM assistance and when the mission systems may be configured for AAR. **(T-3)**

3.8. Radar Radiation Restrictions. Do not radiate the mission radar at or below transition level due to the potential for conflict with Visual Flight Rules (VFR) traffic that may pass closer than 650 feet vertically and 1,300 feet horizontally. However, aircrew may operate the mission radar at or below transition flight level within equipment limitations during contingency operations, emergency situations, and special operations.

3.9. On-Station Procedures.

3.9.1. NAV [With-DMA, Flight Crew] will notify the SLIC of orbit intercept over Net 1 along with altitude, winds aloft, and any changes to planned orbit. **(T-3)** Winds aloft should be briefed if assuming on-station outside of the orbit.

3.9.2. Fly mission orbits at best endurance indicated airspeed whenever practical, but not lower than maneuver speed for computed maximum bank angle. **(T-3)** Limit bank angle if operational necessity exists. The FE will brief the AC and coordinate with the NAV [With-DMA, Pilot] of the maximum bank angle and minimum computed indicated airspeed in this case. **(T-3)**

3.10. Aircraft Location Monitoring. Flight and mission crew share responsibility of aircraft location monitoring relative to a preplanned flight path. The SLIC, NAV [With-DMA, N/A], and AC will coordinate location and orbit pattern changes. **(T-3)**

3.10.1. Pilots will monitor the E-3 location via Global Positioning System (GPS) Integrated Navigation System (GINS), and radio navigation aids when within range. **(T-3)** [With-DMA, N/A]. The AC will ensure separate steering solutions are selected on the AC’s and CP’s Control Display Unit (CDU). **(T-3)**

3.10.2. The NAV [With-DMA, Pilots] will establish a radio navigation fix or line of position between the closest point of the E-3 orbit and the threat area as a “be-no” or “no flying beyond” line for all E-3 orbits. **(T-3)** This information will be passed to the SLIC. **(T-3)** [With-DMA, Display threat areas on IMFD. **(T-3)**]

3.10.3. The AC, CP, and NAV [With-DMA, N/A] positions will be occupied, except for periods of crew relief, during flights within 25 NM of an established prohibited area or within 50 NM of a potentially hostile border. **(T-3)** Whenever possible, use aircraft displays or Electronic Flight Bag (EFB) to display prohibited areas within 25 NM of current position.

3.10.4. The AC and SLIC are responsible to ensure safe separation between the E-3 and other aircraft when flying in Warning Areas, Military Operating Areas (MOAs), Restricted Areas, or Air Traffic Control (ATC)-assigned working areas with other aircraft.

3.10.5. The SLIC must have at least a stand-behind position at an operational console, with access to monitor coordination and safety frequencies as required by the mission. **(T-3)**

3.10.6. The AWACS monitor and SLIC must maintain awareness of the E-3’s position and altitude. E-3G crewmembers will use E-3 Mode C pressure altitude information when making AWACS monitor calls. **(T-3)** If the accuracy of the E-3 symbol is in doubt, consider worst case location, and coordinate with the flight crew to take immediate action to reposition the aircraft in order to avoid the prohibited/threat areas.

3.11. Airborne Warning and Control System (AWACS) Monitor. The SLIC will designate an AWACS monitor to provide traffic advisories to the flight crew during flight under Due Regard and when the mission radar or Identification, Friend, or Foe (IFF) are operating. **(T-3)** At any other time, an AWACS monitor may be used as determined by the PIC. AWACS monitor will notify the flight crew and SLIC when AWACS monitor assumes monitor duties and whenever AWACS monitor is terminated, (provide a brief explanation for the reason). **(T-3)** Normally, the ABM providing ABM-Assisted or ABM-Directed AAR Rendezvous will also perform AWACS monitor responsibilities. **(T-3)** AWACS monitor will pass track information on climbing/descending and/or maneuvering aircraft which could pose a threat to the E-3 with the following parameters and format, or as briefed by the PIC. **(T-3)**

3.11.1. For ATC-controlled airspace: Tracks that are $\pm 1,000$ feet (IFF Mode C) or $\pm 3,000$ feet (radar measured) of E-3 altitude and 15 NM from the E-3, if the track is on a heading towards, overtaking, or passing in front of the E-3.

3.11.2. For uncontrolled airspace: Tracks which are $\pm 3,000$ feet of E-3 altitude and 15 NM from the E-3, if the track is on a heading towards, overtaking, or passing in front of the E-3.

3.11.3. Pass the tracks to the flight crew over Net 1 giving magnetic bearing (rounded to the nearest 10 degrees from the E-3), range, altitude, crossing information about the traffic, and whether the track altitude is radar measured or IFF reported. AWACS monitor should monitor ATC frequency for increased SA and to prevent interference between flight crew and ATC.

3.12. Transportation of Passengers.

3.12.1. Space-A Passengers. Space-A passengers will not normally fly on the E-3 due to mission and training requirements. **(T-3)**

3.12.2. Responsibility. The crewmember(s) designated by the AC as responsible for passengers or DVs will supervise passenger movement, especially on the flight line, and familiarize the passengers with the aircraft interior, to include assigned seats and survival equipment. **(T-3)** Brief passengers according to AFMAN 11-202 Volume 3 using **Attachment 3** of this manual as a guide prior to engine start and assist/direct passengers in the event of an aircraft emergency.

3.12.3. Engine running passenger off-load. Shut down engines on the left side of the aircraft and position an aircrew member at the bottom of the stairs to assist passengers. If left engines are shutdown, the TAXI BACK or an approved checklist for the given situation may be used.

3.12.4. Passenger Comfort. Pilots should make every effort to enhance the comfort of passengers. Flight operations should be planned for the minimum use of drag devices and maneuvers, which might cause discomfort or apprehension.

3.13. Debriefings.

3.13.1. Debrief maintenance as soon as practical after engine shutdown. The AC, FE, ART, ADST, ARO, and any crewmember making an entry in the AFTO Form 781A will attend. **(T-3)** SLs and/or SLICs should attend if time permits.

3.13.2. Debrief intelligence, if required. Utilize sensor reconstruction to facilitate intelligence debrief, as necessary.

3.13.3. The AC/SLIC will ensure that a mission debrief is accomplished. **(T-3)** Aircrew should use locally developed debriefing guides (developed IAW AFMAN 11-202 Volume 3 and AFTTP 3-3.IPE, *Integrated Planning and Employment*) to ensure that a comprehensive analysis of mission accomplishment and mission effectiveness is completed.

3.14. Flying Clothing/Equipment.

3.14.1. All aircrew members will wear or carry the minimum items of clothing and equipment according to AFI 11-301V1, *Aircrew Flight Equipment (AFE) Program*, DAFI 36-3802, *Force Support Readiness Programs*, AFMAN 11-202V3, AFI 48-127, *Occupational Noise and Hearing Conservation Program*, DAFMAN 91-203, *Air Force Occupational Safety, Fire, and Health Standards*. **(T-1)** PIC will determine clothing and equipment to be worn or carried aboard all flights commensurate with mission, climate, and terrain involved. **(T-3)** All crewmembers will have issued Nomex® flight gloves in their possession. **(T-3) Note:** Air Force Safe-to-Fly aircrew flight equipment letters are reviewable at <https://usaf.dps.mil/sites/21562/AFE/Safe%20to%20Fly/Forms/AllItems.aspx>

3.14.2. Keep equipment clear of all entry doors, hatches and all emergency equipment during all ground and flight operations. The FE, ARO, and ART will ensure that these areas are clear of obstructions during their preflight inspection. **(T-3)** It is the responsibility of each crewmember to store/secure their personal and professional equipment carried onboard. Excess personal and professional gear should be secured in the J-compartment (or as directed).

3.15. Aircraft Security at Enroute Stops/Destination.

3.15.1. The AC is responsible for ensuring aircraft security at enroute stops. Secure the aircraft as a Protection Level 2 resource IAW DAFI 31-101, *Integrated Defense (ID)*, as supplemented by MAJCOM. This requires a US entry controller (at least one per every two aircraft) and restricted access. ACs will provide a copy of the flight orders and passenger manifest (as applicable) to the entry controller as a way to identify personnel authorized to enter the aircraft and those crewmembers designated to have escort privileges. **(T-3)** Perimeter patrol can be accomplished by host nation security, but the entry controller must be US security personnel or a US E-3 crewmember. In addition, equipment classified as SECRET (that cannot be removed from the aircraft) must be safeguarded by US security personnel or a US E-3 crewmember. TOP SECRET material must be safeguarded by US security personnel or a US E-3 crewmember with TOP SECRET clearance. Only the AC may release security forces from guarding the aircraft. The Wing Commander (WG/CC) owning the aircraft is the waiver authority to the paragraph.

3.15.2. The SLIC, or AC if a SLIC is not available, is responsible for the security of classified documents and software. While deployed or during enroute stops, classified documents such as “Communications Security (COMSEC)” and software can be stored on the aircraft when US security personnel are used as the entry controller. Store “COMSEC” in the Command Post during stops at locations where no US security personnel are available. The SLIC/AC will designate crewmember(s) to remain with the aircraft if a Command Post is unavailable in order to provide security for software and “COMSEC”. **(T-3)**

3.16. Personal Publications Requirements. Guidance directing local units to issue each crewmember publications is provided in AFI 11-215, *Flight Manuals Program* and applicable supplements. MAJCOMs may authorize the use of electronic publications through supplements to this manual. Wings may authorize the creation and use of locally developed checklists when/if Tech Order-derived checklists do not exist or are inadequate.

3.17. Aircraft Recall/Diversion. With the exception of pilot proficiency sorties, challenge any recall or diversion of an E-3 using the appropriate authentication for the theater of operation unless received over secure communications.

3.18. Transition Training.

3.18.1. Flight crews will not conduct transition when scheduled takeoff or final landing is between 0000L and 0600L without SQ/DO approval. **(T-3)**

3.18.2. When performing transition with mission crew and technicians on board, flight crews will not exceed 4+00 hours total transition time. **(T-3)** However, flight crews will not conduct more than 1+30 hours of consecutive transition without SQ/DO approval.

3.18.3. Aircrews will mission plan and secure SQ/DO (or higher) approval prior to departure for sorties where off-station transition is intended. **(T-3)** Aircrew may “drop-in” to airfields designated as “familiar” by the GP/CC in local supplements without pre-flight mission planning/approval.

3.18.4. Transition duty day is a period of 12 hours that starts and runs concurrently with the maximum flight duty period of each flight deck crewmember. Transition may be accomplished with crewmembers onboard that have exceeded transition duty day provided they are not occupying their primary flight crew duty position or performing flight crew instructor or Flight Examiner duties. GP/CC can approve requests to extend transition duty day to 16 hours. 513 ACG may perform transition training on local training missions provided duty day does not exceed 16 hours and actual flying time does not exceed 12 hours.

3.19. Crew Coordination Drills (CCD). Thoroughly plan, brief, practice, and debrief the CCD (e.g., Ditching, Crash Landing, Loss of Pressurization, Nuclear Event, Smoke or Fumes, and Fuselage Fire drills) during each training sortie when the mission profile allows. The following procedures apply:

3.19.1. The AC and SLIC will coordinate prior to initiation and make every effort to inform all instructors and evaluators of CCD timing in order to maximize training. **(T-3)**

3.19.2. Operational requirements will not be interrupted. **(T-3)**

3.19.3. Doors and hatches will not be opened, and equipment will not be powered down. **(T-2)** However, if a CCD is performed after calling “off-station,” a normal equipment power down may be incorporated into the drill in anticipation of landing the aircraft.

3.19.4. Passengers will be briefed about the CCD but will not participate. **(T-3)**

3.19.5. The AC will make a Public Address (PA) announcement at the start of the CCD vulnerability period, upon execution of the drill, and at the conclusion of the drill. **(T-3)**

3.20. Aircraft Cleanliness. AC and SLIC are responsible for aircraft cleanliness and order after a mission. All crewmembers are responsible for removing or stowing their personal and professional items prior to departing the aircraft.

3.21. Aircraft Configuration for Static Display. Whenever an E-3 is on static display and opened for viewing, there will be a passenger stand at each open door. **(T-3)** Aircrew members will be positioned at any open hatches. **(T-3)** ACs will ensure proper safety/security precautions are taken to protect the aircraft, passengers, and crew. **(T-3)** Reference DAFI 11-209, *Participation in Aerial Events*, and MAJCOM supplements.

3.22. Readiness Postures.

3.22.1. Readiness Posture One (RP-1) denotes an aircraft and crew capable of launching within 1 hour from notification. Crews designated for RP-1 alert duty should normally be housed in a designated alert facility. Crews must have twelve hours of pre-alert crew rest prior to assuming RP-1 alert duty. **(T-2)**

3.22.2. Readiness Posture Three (RP-3) denotes an aircraft and crew capable of launching within 3 hours from notification. twelve hours of pre-alert crew rest is required prior to assuming RP-3 alert duty. **(T-2)**

3.22.3. Readiness Posture Fifteen (RP-15) is not an alert status but denotes an aircraft and crew capable of launching 15 hours after notification. The RP-15 crew will be present for normal duty each day and carry cell phones, or appropriate chat interface device, for notification. **(T-3)** Crew rest begins at notification.

3.23. Maximum Flight Duty Period (FDP) for Readiness Posture one (RP-1), Readiness Posture three (RP-3).

3.23.1. Aircrews will not exceed 12 hours (16 hours for augmented crews) for RP-1 and RP-3 FDP. **(T-2)**

3.23.2. Guidance on alert duty scheduling, RP-1/RP-3 FDP extensions, flight duty on alert, and maximum number of days on alert is provided in the MAJCOM Supplements to AFMAN 11-202V3.

3.24. Post-Alert Compensation Time.

3.24.1. Units will compensate aircrews 1 day for every 4 days on alert duty if alert duty is performed away from normal quarters (e.g., alert facility or billeting) for a period of 96 hours or more, unless waived by the applicable GP/CC or designated representative. **(T-3)**

3.24.2. No compensatory time is authorized if alert duty was performed in normal quarters.

Chapter 4

FLIGHT CREW OPERATING PROCEDURES

4.1. Adverse Weather. Refer to Air Force Handbook (AFH) 11-203 Volume 1, *Weather for Aircrews* and AFH 11-203 Volume 2, *Weather for Aircrews-Products and Services*, for familiarization with weather, weather services, and products.

4.1.1. Icing Restrictions. Flight crews will not fly into areas of forecast or reported severe icing. **(T-3)** Avoid prolonged operation (cruise flight, holding, etc.) in areas of moderate icing. Aircrew will confirm the intensity and type of associated icing with weather personnel when freezing fog, freezing drizzle, or freezing rain is forecast or reported. **(T-2)**

4.1.1.1. Freezing/frozen precipitation (freezing rain, drizzle, snow, fog, or temperatures near 0°C, etc.) may cause ice or frost to accumulate on aircraft surfaces. Crews will be familiar with and follow all procedures and restrictions in Technical Order (T.O.) 1E-3A-1/1E-3G(II)-1, *Flight Manual*, and T.O. 1E-3A-1-1, *Performance Manual*, regarding de-ice/anti-ice procedures and reference T.O. 42C-1-2, *Anti-icing, Deicing, and Defrosting of Parked Aircraft* for further guidance. **(T-1)**

4.1.1.2. Flight crews will reference published winter operations guidance to determine approved de-icing fluids. **(T-1)** Type I and Type II de-icing fluids do not provide any anti-icing benefit, and, therefore, do not have holdover times. As a guide, for approved anti-icing fluids, crews may use published anti-icing holdover times IAW T.O. 42C-1-2 and winter season holdover tables available on the Federal Aviation Administration (FAA) website. **Caution:** The guidelines may not be consistent with federally approved weather intensity definitions used by qualified National Weather Service, FAA, or USAF weather personnel in developing forecasts or official weather observation reporting.

4.1.1.3. The holdover time begins when anti-icing fluid is first applied and is affected by intensity/type of precipitation, time, temperature, and type/dilution of mixture. PIC will use this information to determine when holdover time is exceeded and re-apply fluid if required. **(T-3)**

4.1.1.4. The PIC will ensure the following information is received from the de-icing ground crew after anti-icing is complete:

4.1.1.4.1. Type and Brand of Fluid (Type IV, Kilfrost ABC-S Plus, Octagon MaxFlight, etc.). **(T-3)**

4.1.1.4.2. Percentage of fluid to water (for example, 60/40 is 60% fluid and 40% water). **(T-3)**.

4.1.1.4.3. Time anti-icing operations were initiated (Local Time). All holdover times are based on this value. **(T-3)**

4.1.1.4.4. Date (DD-MMM-YY) based on Local Time. **(T-3)**

4.1.1.5. PICs will ensure a visual inspection is completed no sooner than 5 minutes prior to departure. **(T-3)**

4.1.2. Turbulence Restrictions. Aircrew will not fly into areas of forecast or reported severe turbulence. **(T-3)** This includes actual or forecast areas of “moderate to occasional severe” turbulence or “moderate to severe” turbulence. Aircrew will make every effort to avoid areas of reported moderate turbulence. **(T-3)** The AC will consult weather personnel and develop contingency routing if moderate turbulence is forecasted along the planned route of flight. **(T-3)**

4.1.2.1. Crews will attempt to confirm the type of aircraft the forecast turbulence applies to, or what type of aircraft reported the encounter, to gain a more accurate picture of the route of flight. **(T-3)**

4.1.2.2. The PIC is responsible for ensuring all aircrew/passengers are seated, with seat belts fastened, when areas of moderate or greater turbulence are encountered or anticipated.

4.1.3. Thunderstorm Avoidance. Pilots will neither file a flight plan nor intentionally fly into an area of known or forecasted thunderstorm activity when the weather radar is inoperative or unusable and thunderstorm activity cannot be visually circumnavigated. **(T-3)**

4.1.3.1. During flight, avoid thunderstorms by at least 20 NM at or above flight level (FL) FL230 and 10 NM below FL230. **(T-3)**

4.1.3.2. In the vicinity of the airport, maintain at least 5 NM separation from heavy rain showers. **Note:** Approaches or departures may be authorized by the appropriate GP/CC if thunderstorms are officially observed to be closer than 10 NM (but not less than 5 NM) from the airport IAW AFMAN 11-202V3, the thunderstorm must not be producing any hazardous conditions (such as hail, lightning, strong winds, gust fronts, heavy rain, wind shear, or microburst) at the airport, and must not be forecast or observed to be moving in the direction of the route of flight (to include the planned missed approach corridor, if applicable). **(T-3)**

4.1.4. Lightning Avoidance. The following conditions are most conducive to lightning strikes and prolonged flight in them should be avoided:

4.1.4.1. When the temperature is $\pm 8^{\circ}\text{C}$ or $\pm 5,000$ feet of the freezing level.

4.1.4.2. In clouds or in any intensity of precipitation or turbulence associated with thunderstorm activity.

4.1.5. Destination Requirements (for filing purposes). An alternate will be filed if forecast destination weather does not satisfy requirements and/or forecast surface winds (intermittent or prevailing) exceed appropriate runway condition reading (RCR) limits IAW this manual, AFMAN 11-202V3, and aircraft T.O.s.

4.2. Takeoff and Landing Data (TOLD)/Restrictions.

4.2.1. An FE will compute all initial TOLD during mission planning, utilizing an authorized TOLD computer program or T.O. 1E-3A-1-1. **(T-3)**

4.2.1.1. A pilot or additional FE on the sortie will crosscheck this data using the computer program or T.O. 1E-3A-1-1.

4.2.1.2. The applicable GP/CC may authorize use of Mission Accomplishment Planning Methods when operational/contingency missions dictate, IAW T.O. 1E-3A-1-1.

4.2.2. Rolling Takeoffs. Rolling takeoffs are authorized IAW T.O. 1E-3A-1/1E-3G(II)-1.

4.2.3. Reduced Power Takeoffs. The following information is provided in addition to that found in T.O. 1E-3A-1-1:

4.2.3.1. Use reduced power takeoffs when practical.

4.2.3.2. Actual inboard takeoff rated thrust (TRT) should be displayed on the inboard exhaust pressure ratio (EPR) bugs for quick reference in the event TRT is required.

4.2.3.3. Reduced thrust takeoffs may be accomplished on a wet runway IAW T.O. 1E-3A-1/1E-3G(II)-1 and T.O. 1E-3A-1-1.

4.2.3.4. Reduced thrust takeoffs are permitted with falling precipitation unless precipitation is moderate or greater.

4.2.4. Tailwind Takeoffs. Takeoffs with tailwinds are not recommended but may be performed if required due to operational considerations. If a tailwind takeoff is performed, a tailwind component of up to 10 knots may be allowed, provided that the data does not exceed allowable T.O. 1E-3A-1-1 limits.

4.2.5. Crosswinds.

4.2.5.1. Unless further restricted by aircraft gross weight or emergency conditions, the maximum crosswind component (including gusts) for takeoff and landing for RCR 26/23 is 25 knots; RCR 15 is 20 knots; RCR 10 is 15 knots. **(T-3)** If RCR falls between the RCR values, use the lower RCR restrictions. **(T-2)** Operation at higher crosswind values requires specific approval by applicable GP/CC.

4.2.5.2. CPs are limited to a maximum takeoff/landing component of 15 knots unless under IP/Flight Examiner supervision. **(T-3)**

4.2.6. Runway and Taxiway. Minimum runway length and width for takeoff or landing is 7,000 x 135 feet, unless waived by GP/CC. Minimum taxiway width is 75 feet unless waived by GP/CC.

4.2.6.1. Takeoff and land on the longest suitable runway available unless operational considerations dictate.

4.2.6.2. Intersection takeoffs will not be performed unless operational necessity dictates. In such a situation, follow MAJCOM directives.

4.2.7. Runway Condition Reading (RCR). At airfields that report runway condition code(s) (RwyCC), refer to the FIH for the Runway Condition Assessment Matrix (RCAM) and associated conversion per code.

4.2.7.1. Aircraft will not takeoff or land when reported RCR is less than 10. **(T-2)** The applicable GP/CC may waive the minimum RCR to 7 when operational necessity warrants.

4.2.7.2. Do not taxi with an RCR less than 7. **(T-2)**

4.2.7.3. If RCR is unknown or less than 7, E-3 maintenance personnel are authorized to tow the E-3 with crew onboard to a known area of RCR of 7 or greater. E-3 maintenance personnel will comply with current DAFMAN 91-203 restrictions by complying with operational risk management (ORM) assessment and approval requirements, See **Chapter 6. (T-2)**

4.2.8. Landings. Except in emergency situations, the following apply:

4.2.8.1. Computed landing distance plus 1,000 feet must not exceed runway available. **(T-3)**

4.2.8.2. Full stop landings with less than 40 degrees of flaps are not permitted. **(T-3)**

4.2.8.3. If it appears that the actual touchdown will occur beyond the first 1/3 or 3,000 feet (whichever is less) of the runway length, pilots will go-around. **(T-3)**

4.2.8.4. Make no more than one full stop in a 30-minute period. **(T-3)**

4.3. Takeoff and Landing Guidance.

4.3.1. AC Responsibilities.

4.3.1.1. A qualified AC will make all takeoffs and landings when weather is below 300 foot ceiling and/or 1 statute mile (SM) visibility or when a DV (Code 4, Code 4 equivalent, or higher) is on board as a passenger. **(T-2)** IPs may takeoff or land in either seat under the conditions above; however, a CP will not occupy the left seat. **(T-2)**

4.3.1.2. An AC, IP, or Flight Examiner will make all approaches and landings during aircraft emergencies. **(T-2)**

4.3.2. CP Takeoffs and Landings.

4.3.2.1. CPs may perform takeoffs and landings if the weather is at least 300 foot ceiling and 1 SM visibility, or published minimums, whichever is higher. During takeoffs and landings, an IP/Flight Examiner or an AC that is certified to supervise CP landings IAW local certification guidance must properly supervise CPs. **(T-3)**

4.3.2.2. CPs must be certified by the SQ/CC as “Experienced” in order to accomplish takeoffs and/or landings under the supervision of an experienced AC with passengers onboard (no DVs Code 4 or higher). **(T-3)**

4.4. Touch-and-Go Landings. Accomplish touch-and-go landings under the following conditions:

4.4.1. IP/Flight Examiner supervision. **(T-2)**

4.4.2. Minimum weather required is 300 foot ceiling and 1 SM visibility. **(T-2)**

4.4.3. Crosswind component does not exceed the following (including gusts): Dry runway-15 knots. Wet runway-10 knots. **(T-2)**

4.4.4. No passengers on board. **(T-2)**

4.4.4.1. The following are not considered passengers for this restriction: Wing supervisors, E-3 maintenance personnel, USAF aircrew qualified in other aircraft, Air Force Academy (AFA)/Air Force Reserve Officer Training Corps (AFROTC) cadets, FAA/ATC personnel, weapons directors, ACC TRSS Detachment 6 personnel not on aeronautical orders, Airborne Command Element (ACE) team members, Mission Essential Personnel (MEP), Security Forces, Intelligence personnel, and US customs personnel flying under the provisions of DAFMAN 11-401 and MAJCOM supplement.

4.4.4.2. The following are not considered passengers for this restriction with applicable GP/CC approval prior to takeoff: military members not on aeronautical orders who are awaiting training, Computer Support Group (CSG) personnel conducting in-flight software testing, and Mission Crew Training (MCT) and Flight Crew Training (FCT) contract instructors in direct support of training and operations.

4.4.5. The following length/width criteria apply: Dry runway--9,000 feet x 135 feet minimum; wet runway--10,000 feet x 135 feet minimum. **(T-2)**

4.4.6. On wet runways:

4.4.6.1. Pilot flying (PF) will Touchdown in the first 2,000 feet of the runway or initiate a go-around. **(T-2)**

4.4.6.2. Conduct touch-and-go landings at flaps 50 degrees only. **(T-2)**

4.4.6.3. Normally display the actual charted go-around EPR on the inboard EPR “bugs” for quick reference in the event go-around EPR is required while airborne. Outboard EPR “bugs” should display 1.50 EPR.

4.4.6.4. Touch-and-go landings are permitted with falling precipitation (e.g., drizzle or light rain), provided the precipitation is not moderate to heavy, not producing a Runway Condition Code (RCC) worse than 5.

4.4.6.5. Landing surface (67.5 feet left and right of centerline) is completely clear of slush and the minimum RCR reading for any portion of the runway is 10. **(T-2)**

4.5. In-Flight Simulated Emergency/Engine-Out Procedures.

4.5.1. The IP/AC will alert all crewmembers in the cockpit prior to performing simulated Emergency Procedures. **(T-3)**

4.5.2. In an actual emergency, all training and simulated emergency procedures will be terminated. **(T-3)** Training will resume only when the AC determines no hazards to safe aircraft operation exists. **(T-3)**

4.5.3. Except for simulated engine-out landings, restore all aircraft systems to normal operation prior to landing. **(T-3)**

4.5.4. IP/Flight Examiner supervision is required for all flaps 14, flaps 25, and flaps 25-to-50 approaches/landings/touch-and-go's. **(T-3)** Prior to performing a flaps 14 approach/landing, update the brake energy limited landing weight and landing distance limited landing weight and brief differences to normal configuration habit patterns, emphasizing the gear lowering sequence. **(T-3)**

4.5.5. Simulated engine-out maneuver restrictions:

- 4.5.5.1. Simulated engine-out takeoffs are prohibited. **(T-2)**
- 4.5.5.2. Simulated two-engine operations are prohibited. **(T-2)**
- 4.5.5.3. Do not accomplish actual engine shutdown in flight. **(T-2)** A reduction in thrust can adequately simulate training in aircraft control procedures.
- 4.5.5.4. Limit all in-flight simulated engine-out activity to a gross weight of 270,000 lbs. or less, with rudder boost on. **(T-2)**
- 4.5.5.5. Pilots performing simulated engine-out touch-and-go landings will follow normal four-engine takeoff procedures. **(T-2)**
- 4.5.5.6. No passengers on board. **(T-2)** (See [paragraph 4.4.4.](#))
- 4.5.5.7. ACs/First Pilots (FP) certified to do so by their SQ/CC, IAW local supplements, may accomplish simulated engine-out missed approaches, go-arounds, and full-stop landings in visual meteorological conditions (VMC) (day or night) without IP/Flight Examiner supervision.
- 4.5.5.8. Initiate all planned simulated engine-out missed approaches/go-arounds no lower than 200 feet height above touchdown (HAT). **(T-2)**
- 4.5.5.9. During a simulated engine-out approach, establish symmetrical thrust on all engines when safe and practical if an unplanned go-around or missed approach is executed.
- 4.5.5.10. Day weather conditions must be at or above published circling minimums. **(T-2)**
- 4.5.5.11. Night weather conditions must be at or above 1,000 foot ceiling and 2 SMs visibility or circling minimums, whichever is higher. **(T-2)**

4.6. Landing Attitude Demonstrations. Landing attitude demonstrations may only be accomplished by IP/Flight Examiner or ACs under IP/Flight Examiner supervision. **(T-2)** The following restrictions apply:

- 4.6.1. Must be accomplished four engine only. **(T-3)**
- 4.6.2. Dry runway only with normal touch-and-go conditions and restrictions. **(T-3)**
- 4.6.3. Flaps 40 or 50 only. **(T-3)**
- 4.6.4. Go-around will be initiated if aircraft touches down during the initial roundout. **(T-3)**
- 4.6.5. Go-around will be initiated with no less than 4,000 feet of runway remaining. **(T-3)**

4.7. Preflight.

- 4.7.1. When very important person (VIP) stand or air stairs are unavailable, crews will arm escape slides at unopened doors to facilitate a rapid ground egress. **(T-3)**
- 4.7.2. Receiver Autonomous Integrity Monitoring (RAIM) will normally be enabled at all times.
- 4.7.3. [With-DMA] AUTONAV will normally be enabled for Embedded GPS INU (EGI)/Internal Navigation Unit (INU) ground alignment.

4.7.4. To confirm proper INU alignment, the NAV will check the INU true headings prior to engine start and confirm they are within 1 degree of each other and cross-checked with the Altitude and Heading Reference System (AHRS). [With-DMA, N/A]. (T-3)

4.7.5. Verify baggage and equipment are loaded IAW [Attachment 2](#).

4.8. Engine Start/Taxi.

4.8.1. Aircrews will close entry doors and arm escape slides prior to the removal or placement of VIP Stand or Air Stairs. (T-3)

4.8.2. The occupants of both pilot seats will have their seat belt fastened while taxiing/towing and will wear their shoulder harness during critical phases of flight. (T-3)

4.8.3. Taxi speed in the parking area or any congested area will be slow enough to accommodate a wing walker. (T-3)

4.8.4. The NAV will monitor GINS ground speed during taxi operations. [With-DMA, N/A]. (T-3)

4.8.5. The NAV [With-DMA, Pilots] will use the weather radar to scan the departure path prior to takeoff to avoid flying into areas of heavy precipitation and/or possible associated turbulence. (T-3)

4.8.6. At the hammerhead, flight crews will verify the accuracy of the GINS position. [With-DMA, N/A]. (T-3)

4.9. Frequency Monitoring. All flight crew will monitor the briefed primary radio frequency during all phases of flight unless directed otherwise by the AC. (T-3) The AC will ensure at least one emergency frequency and mission interphone are always monitored. (T-3) All flight deck crewmembers will monitor UHF/Very High Frequency (VHF) guard, as operational conditions permit. (T-3) During critical phases of flight, the AC will designate at least one flight crewmember to monitor guard. (T-3) Pilots have the option to monitor guard during critical phases of flight based on current workload. C2 or other frequencies to be monitored will be designated by the AC. (T-3) The observer's seat occupant will be briefed on the relationship between the pilot's Flight Deck Audio Panel (FDAP) and the observer's interphone to prevent extraneous radio transmissions. (T-3)

4.10. Altitude Monitoring. While operating at less than 2,000 feet above the ground, the Pilot Monitoring (PM) will inform the PF anytime the indicated altitude varies more than 100 feet from the desired altitude, or if the aircraft appears to be dangerously close to terrain or obstructions. (T-3) (See [Chapter 6](#).)

4.10.1. [With-DMA, N/A] The NAV will back up the Pilots in observing and reporting these deviations along with notifying the pilots of the computed minimum ground speed. (T-3)

4.11. Departure.

4.11.1. Planning. During mission planning, the flight crew will determine a gross weight that ensures E-3 performance will meet or exceed departure requirements. (T-3) **Note:** If E-3 performance is unable to meet the published climb gradient at the desired gross weight, decrease fuel load, use other applicable approved departure methods described below, or delay until more favorable conditions exist.

4.11.2. Special Departure Procedures (SDP). SDP data is retrieved via the Jeppesen™ Runway Analysis (JRA) Tool on the MilPlanner™ website <https://www.milplanner.com/>. Password and Identification (ID) will be provided via local Flight Crew Information File (FCIF). SDP data for airports that are not currently supported can be requested via email to the JRA Ops Data Airport Data Team. A link to do so is found on the MilPlanner™ website. **Note:** Crews must be certified in order to execute SDPs. **(T-3)**

4.11.3. VFR departures require GP/CC approval. **(T-2)** ACs may consider VFR departures if unable to comply with Instrument Flight Rules (IFR) climb gradient requirements and the mission justifies the increased risk.

4.12. Enroute Navigation.

4.12.1. Fly great circle routes to the maximum extent practical. Random Area Navigation (RNAV)/direct routing may be flown according to Flight Information Publication (FLIP) General Planning (GP). NAVs will annotate changes to the route of flight on the navigational chart unless safety of flight dictates other priorities [With-DMA, N/A]. **(T-3)** NAVs [With-DMA, Pilots] will compute revised ETAs [With-DMA add, by FMS] and brief ETA(s) to significant events. **(T-3)** Waypoints or patterns entered into the navigation system will be crosschecked by an additional flight crewmember. **(T-3)**

4.12.2. [With-DMA, N/A] The NAV will log a full navigational fix, suitable for dead reckoning, prior to leaving radio navigation aid coverage. **(T-3)** Log additional fixes as required to ensure safe mission accomplishment. The NAV will also perform periodic crosschecks of navigation equipment, intended route, cleared route to identify navigation errors, prevent inadvertent deviations, and ensure equipment is performing within tolerances. **(T-3)** At a minimum, perform these crosschecks after level-off, prior to AAR, during orbit intercepts, and when assuming on-station. The NAV will log the time and aircraft position as part of these crosschecks. **(T-3)** The NAV will notify the AC (and SLIC as required) of any discrepancies or malfunctions. **(T-3)**

4.12.3. Special Qualification Airspace Navigation. The E-3 is approved for operation in Required Navigation Performance (RNP) airspace with operational limitations based on GINS [With-DMA, EGI] navigational equipment. See **Table 4.1** for E-3 Communications, Navigation, and Surveillance (CNS)/Air Traffic Management (ATM) Certifications and **Table 4.2** for E-3B/C/G CNS/ATM Operational Approvals. Reference AFMAN 11-202V3, FLIP GP and the following guidance for RNP requirements:

4.12.3.1. [With DMA, N/A] The E-3 may operate in RNP-10 airspace without time limits when “GPS only” or “GPS/INS-blended” mode of navigation is selected.

4.12.3.2. The E-3 may operate in RNP-10 airspace in “INS-only” mode for 6.2 hours from the time the EGIs were commanded to the NAV mode or the last aligned, whichever is later.

4.12.3.3. Updates are IAW RNP/Basic Area Navigation (BRNAV) update and contingency procedures in this manual.

Table 4.1. E-3 Communications, Navigation, and Surveillance (CNS)/Air Traffic Management (ATM) Certifications.

Airspace/Equipment Type	Certified	Operational Approval	Training Required	Notes
VHF FM Immunity	Yes	Yes	No	
8.33 kHz VHF Radios	Yes	Yes	No	
EGPWS	Yes	Yes	Yes	Training incorporated in IQT and DCT
Elementary Mode S	Yes	Yes	No	
Enhanced Mode S	Yes	Yes	No	
ADS-B Out	Yes	No	Yes	Training incorporated in IQT and DCT
Mode 5 L1/L2	Yes	Yes	Yes	Procedures IAW with MAJCOM and AOR SPINS.
CPDLC/ACARS	Yes	Yes	Yes	Training incorporated in IQT and DCT. CPDLC Reference: ICAO GOLD
TCAS II V7.0 (ACAS)	Yes	Yes	Yes	Training incorporated in IQT and DCT.
RVSM	Yes	Yes	Yes	Jet specific entry requirements IAW para. 4.12.6
NAT MNPS (RNP 12.6)	Yes	Yes	Yes	Training IAW Overseas employment section of Aircrew Proficiency Program
RNAV 5 (BRNAV)	Yes	Yes	No	Enroute Airspace
RNAV 2	Yes	Yes	No	Enroute Airspace (NAS Q and T Routes)
RNAV 1	Yes	Yes	Yes	Terminal Airspace (RNAV SID/STAR) Training incorporated in IQT and DCT
RNP 10/ RNAV 10	Yes	Yes	No	Oceanic and Remote Navigation Airspace
RNP 5.0	Yes	Yes	No	European Enroute Airspace
RNP 4.0	Yes	Yes	No	Oceanic Airspace
RNP 2.0	Yes	Yes	No	Enroute Airspace
RNP 1.0	Yes	Yes	Yes	Terminal Airspace Training incorporated in IQT and DCT
RNP 0.3	Yes	Yes	No	Approach Airspace
RNP 0.1	No	No	N/A	No WAAS or Radius to Fix capabilities
RNP APCH (1,2)	Yes	Yes	Yes	(ICAO only) RNP APCH is equivalent to (NAS only) RNAV (GPS) are the same thing.

				Reference AFMAN 11-202 V3
RNP AR APCH	No	No	N/A	Special Authorization is required.
RNAV (GPS) APCH (1,2)	Yes	Yes	Yes	Training incorporated in IQT and DCT
RNAV (RNP) APCH	No	No	N/A	Special Authorization is required.
PBN transition to conventional Final Approach	Yes	Yes	Yes	Training incorporated in IQT and DCT. See AFMAN 11-202 V3
LNAV minimums (2)	Yes	Yes	Yes	Training incorporated in IQT and DCT
LNAV/VNAV minimums (2)	Yes	No	N/A	Currently unable to fly due to DAFIF database errors. See E-3G II (DRAGON) CNS/ATM Operational Approval 13 Jul 20
LP/ LPV	No	No	N/A	
Notes:				
1. DMA are not capable of flying Radius to Fix (RF) procedures.				
2. RNAV and RNP APCH procedures will be flown with Flight Director guidance and the auto-pilot not coupled.				

Table 4.2. E-3B/C/G Communications, Navigation, and Surveillance (CNS)/Air Traffic Management (ATM) Operational Approvals.

Airspace/Equipment Type	Certified	Operational Approval	Training Required	Notes
VHF FM Immunity	Yes	Yes	No	
8.33 kHz VHF Radios	Yes	Yes	No	
EGPWS	No	No	N/A	
Elementary Mode S	Yes	Yes	No	
Enhanced Mode S	No	No	N/A	
ADS-B Out	No	No	N/A	
Mode 5 L1/L2	No	No	N/A	
CPDLC/ACARS	No	No	N/A	
TCAS II V7.0 (ACAS)	Yes	Yes	Yes	Training incorporated in IQT and DCT.
RVSM	Yes	Yes	Yes	Jet specific entry requirements IAW paragraph. 4.12.6.
NAT MNPS	Yes	Yes	Yes	Training IAW Overseas employment section of Aircrew Proficiency Program
RNAV 5 (BRNAV)	Yes	Yes	No	Enroute Airspace
RNAV 2	No	No	N/A	Enroute Airspace (NAS Q and T Routes)
RNAV 1	No	No	N/A	Terminal Airspace (RNAV SID/STAR)
RNP 10/ RNAV 10	Yes	Yes	No	Oceanic and Remote Navigation Airspace
RNP 5.0	Yes	Yes	No	European Enroute Airspace
RNP 4.0	No	No	N/A	Oceanic Airspace
RNP 2.0	No	No	N/A	Enroute Airspace
RNP 1.0	No	No	N/A	Terminal Airspace
RNP 0.3	No	No	N/A	Approach Airspace
RNP 0.1	No	No	N/A	
RNP APCH (1,2)	No	No	N/A	
RNP AR APCH	No	No	N/A	
RNAV (GPS) APCH (1,2)	No	No	N/A	
RNAV (RNP) APCH	No	No	N/A	
PBN transition to conventional Final Approach	No	No	N/A	
LNAV minimums (2)	No	No	N/A	
LNAV/VNAV minimums (2)	No	No	N/A	
LP/ LPV	No	No	N/A	

Notes:

1. DMA are not capable of flying Radius to Fix (RF) procedures.
2. RNAV and RNP APCH procedures will be flown with Flight Director guidance and the auto-pilot not coupled.

4.12.4. B-RNAV (RNAV5) Airspace. Compliance includes navigation accuracy within 5 NM of actual position 95 percent of the time. B-RNAV accuracy criteria are RNAV5.

4.12.4.1. The E-3 may operate in B-RNAV/RNAV5 airspace without time limits when “GPS-only” or “GPS/INS-blended” mode of navigation is selected.

4.12.4.2. The E-3 may operate in BRNAV/RNAV5 airspace in “INS-only” mode for 2.0 hours from the time the EGIs were commanded to the NAV mode or the last aligned, whichever is later.

4.12.5. RNP/B-RNAV Flight Planning. The PIC will review airspace requirements (i.e., specific RNP level and contingency actions, etc.) and assess mission impact when flying in RNP airspace. **(T-0)** Reference International Civil Aviation Organization (ICAO) State specific Aeronautical Information Publication (AIP) and FLIP AP for specific route requirements.

4.12.5.1. Enroute. At the RNP/B-RNAV entry point both EGIs must be operational, and RAIM must be ON and operational. **(T-0)**

4.12.5.2. Accomplish periodic crosschecks of all available navigation sources, intended route, and cleared route to identify navigation errors and prevent inadvertent deviation from ATC cleared routes. Advise ATC of the deterioration or failure of navigation equipment below navigation performance requirements and coordinate appropriate actions.

4.12.6. Reduced Vertical Separation Minimums (RVSM) Airspace/Equipment/Operations. Airspace where RVSM is applied is considered special qualification airspace. The airspace requires both primary altimeters, the autopilot (to include the altitude hold function), the altitude alerter system, and an operational IFF transponder before entry into RVSM airspace. Before entering RVSM airspace, flight crews will advise ATC of any RVSM equipment failures and request a new clearance. **(T-0)** The following are RVSM operational procedures:

4.12.6.1. Autopilot. The autopilot must be engaged during level cruise except when circumstances, such as the need to re-trim the aircraft, require disengagement. **(T-3)**

4.12.6.2. Altimeters. Crosscheck altimeters every hour to ensure they agree \pm 200 ft. **(T-3)**

4.12.7. Trans-oceanic flights. To minimize trans-oceanic Gross Navigational Errors (GNE):

4.12.7.1. NAVs will accomplish a coast out/in fix during trans-oceanic flights or when the aircraft is operating out of radio aid range. **(T-3)** For trans-oceanic flights, NAVs will compute an ETP. **(T-3)** Additionally, the NAV will annotate the time over an oceanic checkpoint on the navigational chart. **(T-3)** The aircraft heading will be crosschecked with the planned heading. **(T-3)** The NAV will annotate the aircraft position on the navigational chart approximately 10 minutes after each oceanic waypoint is passed. **(T-3)**

4.12.7.2. [With-DMA] Pilot(s) will accomplish a coast out/in fix during trans-oceanic flights or when the aircraft is operating out of radio aid range. **(T-3)** For trans-oceanic flights, Pilot(s) will compute an ETP. **(T-3)** Additionally Pilot(s) will annotate the time over an oceanic checkpoint on the navigational chart. **(T-3)** The aircraft heading will be crosschecked with the planned heading. **(T-3)**

4.13. On-Station.

4.13.1. The ARO will normally control the use of high frequency HF 1. **(T-3)** The AC will coordinate with the ARO if the flight crew requires its use. **(T-3)** The SLIC/ARO will coordinate with the AC if the mission crew requires the use of either of the flight crew's VHF or UHF radios. **(T-3)**

4.13.2. Pilots and NAVs [With-DMA, NAV N/A] will closely monitor the first complete trip around the orbit after initial intercept to ensure the aircraft is maintaining proper orbit. **(T-3)**

4.13.3. The AC has the responsibility and final authority for determining when the aircraft should depart station considering all applicable factors (e.g., forecast enroute and destination weather, enroute winds, icing, mission requirements, fuel requirements, training requirements). **(T-3)**

4.13.3.1. Within 1 hour after assuming station or AAR, the flight crew will compute "bingo fuel" and report remaining station time to the SLIC. **(T-3)** If AAR is planned after orbit, make a similar computation allowing enough fuel so that in the event of a missed AAR, the aircraft can land at the destination or a preplanned alternate with the required fuel minimums.

4.13.3.2. If fuel requirements necessitate a modification to on-station duration, orbit pattern, or altitude, the AC will notify the SLIC. **(T-3)**

4.13.3.3. Aircrews will evaluate weather considerations within 1 hour after assuming station and make periodic weather checks as required. **(T-3)** This check may include enroute, AAR track, landing base, and alternate base weather.

4.13.3.4. Crews should fly an alternate mission in lieu of dumping fuel to adjust gross weight should an equipment malfunction or an inability to complete an assigned mission occur. Alternate missions should be planned and briefed during mission planning day.

4.14. Arrival and Approach.

4.14.1. Approach Briefing. Prior to a starting descent from cruise altitude, the PF the approach will brief the crew IAW T.O. 1E-3A-1/1E-3G(II)-1 and AFMAN 11-202V3 requirements. **(T-3)** During an approach, the Pilots and NAV [With-DMA, the Pilots and FE] will each have a separate Terminal Approach Procedure and/or Standard Terminal Arrival Route (STAR) booklet, or electronic equivalent, available for use during the descent briefing and for reference during the approach. **(T-3)** The PM and the NAV [With-DMA, FE] will monitor their respective instruments, all radio transmissions by the controlling agency, and advise the PF the approach of any deviations from the prescribed procedures or instructions. **(T-3)**

4.14.2. Instrument Approach Advisory Calls. Crew will make mandatory approach advisory calls IAW [Table 6.3](#) and [Table 6.4](#). **(T-2)**

4.14.3. The NAV will monitor altitude and report deviations. [With-DMA, N/A] **(T-2)**

4.14.4. Priorities. Upon commencing the final approach (glideslope interception or departing the final approach fix (FAF)), flight crewmembers will avoid unnecessary distractions. **(T-2)** Priorities are monitoring the approach/landing and completing the BEFORE LANDING checklist. All activities not associated with the approach/landing checklist accomplishment will cease. **(T-2)**

4.15. Simulator-Only Maneuvers. The following maneuvers will be practiced in the flight simulator only:

4.15.1. Aborted takeoff. **(T-0)**

4.15.2. Engine failure(s) during takeoff and/or climbout to traffic pattern altitude. **(T-0)**

4.15.3. Two-engine operations (cruise, approach, go-around, and/or landing). **(T-0)**

4.15.4. Three-engine rudder boost out operations (cruise, approach, go-around, and/or landing). **(T-0)**

4.15.5. Initial Buffet/Stick Shaker Recovery. **(T-0)**

4.15.6. Unusual Attitudes. **(T-0)**

4.15.7. Flaps-up touch-and-go landing. **(T-0)**

4.16. Occupancy of Flight Crew Duty Positions.

4.16.1. ACs and FPs may perform their duties from either seat. CPs must be certified by the SQ/CC IAW local supplements in order to perform duties in the Left Seat during critical phases of flight under IP/Flight Examiner supervision. **(T-3)**

4.16.2. During non-critical phases of flight, if the AC or CP leaves the flight deck, the FE position must be occupied by a qualified FE or be under the supervision of an instructor/Flight Examiner. **(T-3)**

4.16.3. During critical phases of flight or simulated/actual emergencies, unqualified Pilots or Pilots not in training to achieve qualification in the E-3, will not occupy any flight crew duty positions. **(T-3)** Rated Pilot General/Flag officers flying under provisions of MAJCOM guidance are exempt. Waiver authority is MAJCOM/Directorate of Operations (A3). Reference DAFMAN 11-401 for exceptions, which apply to commanders, key supervisors, and general officers.

4.17. Mid-Air Collision Avoidance.

4.17.1. Occupy all flight deck seats [With-DMA, Seat 4 is N/A] below FL180 to the maximum extent practical. Crews will maintain an IFR clearance for separation and use autopilot whenever practical. **(T-2)** The Pilots and NAV [With-DMA, NAV N/A] will use available systems to search for traffic. **(T-2)** The observer (seat 5), when available, will be on headset and actively scan for traffic. **(T-3)**

4.17.2. Accomplish seat changes for the AC or CP position with the autopilot and altitude hold engaged, as practical. Initiate seat changes while stabilized in the IFR traffic pattern, extended VFR traffic pattern or when above 10,000 feet Mean Sea Level (MSL) during climbs and descents. Emphasize clearing during the seat change.

4.18. Equipment on the Flight Deck. Hold crew equipment and publications on the flight deck to a minimum, commensurate with mission requirements. Stowed equipment must not prevent rapid egress from the flight deck.

4.19. In-Flight Meals. The PF and PM should not eat meals at the same time and their meals should consist of different menu items if prepared by the same flight kitchen or organization.

4.20. Fuel Requirements. For planning purposes, fuel reserves on all flights will be 18,000 pounds over the destination (or alternate when required) initial approach fix, or IAW AFMAN 11-202 Volume 3, whichever is greater. **(T-0)** Fuels listed herein are minimum required fuels. The PIC may plan to arrive overhead with more fuel based on the dynamics of the mission (e.g., weather enroute, airport environment, etc.).

4.20.1. Fuel required at the initial approach fix at the original destination will allow a penetration and an approach, then a climb to optimum altitude, and an arrival over the alternate initial approach fix with 18,000 pounds of fuel or greater. **(T-0)**

4.20.2. Minimum landing fuel for flights on an IFR clearance is 15,000 pounds. **(T-0)** “Minimum Fuel” will normally be declared to the controlling agency when it is determined that the aircraft may land at the intended destination with 15,000 pounds of fuel remaining or less. However, if the destination airfield is VFR, and after the aircraft is established in the airfield’s radar and/or visual traffic pattern, practice approaches and landings may be conducted until 12,000 pounds of fuel remain, provided center of gravity (CG) limits are not exceeded or weather conditions deteriorate below VFR.

4.20.3. “Emergency Fuel” will be declared to the controlling agency when it is determined the aircraft may land at the intended destination with 10,000 pounds of fuel or less. **(T-0)**

4.20.4. When extraordinary mission requirements dictate, GP/CC may approve reduced fuel reserves (provided they meet or exceed AFMAN 11-202V3 requirements) down to: Initial Approach Fix-12,000 pounds, Minimum Fuel-10,000 pounds, Emergency Fuel-8,000 pounds.

4.21. Aircraft Ground Refueling. FEs are authorized to refuel the aircraft. When refueling/defueling aircraft at bases where E-3 maintenance support is not available, FEs will reference T.O. 1E-3A-2-7-5CL-1, *Refueling and Defueling*, T.O. 00-25-172, *Ground Servicing of Aircraft and Static Grounding/Bonding*, and T.O. 1E-3A-2-7, *Ground Handling-Servicing and Airframe*. **(T-2)**

4.21.1. The FE will notify the local fire department anytime adequate portable firefighting equipment is unavailable or any condition listed under Abnormal Conditions, Section 1, T.O. 00-25-172, exists. **(T-2)** The FE will inform the fire department of the abnormal condition and parking spot/location of aircraft. **(T-2)** The FE should be informed by the fire chief of the estimated response time or if a standby fire truck needs to be in position prior to servicing. Communication capability will be immediately available.

4.21.2. The AC may approve other crewmembers to serve as refueling team members if base support is limited or nonexistent. At a minimum, there will be a fireguard at the fire extinguisher and a member next to the fuel truck/tank operator. Maintain positive communication throughout the entire refueling process. **(T-2)** The FE will brief all team members on the use of fire equipment, safety precautions, and emergency shutdown procedures. **(T-3)**

4.22. Fuel Jettisoning. Crews will conduct fuel dumping only to reduce gross weight in an emergency or for operational necessity. **(T-3)** When circumstances permit, dump above 5,000 feet Above Ground Level (AGL) over unpopulated areas or in designated fuel dump areas. Crews will advise the appropriate air traffic control agency of intentions, altitude, and location when jettisoning fuel, and when the operation is complete. **(T-2)** Make the appropriate entry on the AFTO Forms 781A and AFTO Form 781H, *Aerospace Vehicle Flight Status and Maintenance*.

4.23. Aircraft Interior Lighting. During ground/flight operation, minimize flight deck lighting. During night parking, do not use the high-level flight deck lighting until after the aircraft is chocked and brakes are released. This allows the pilots to ensure that the aircraft does not roll.

4.24. In-Flight Engine Failure. During peacetime training missions, if an engine is shutdown in flight, terminate the mission and land as soon as practical, IAW T.O. 1E-3A-1/1E-3G(II)-1. During contingency operations, if an engine is shutdown in flight, mission requirements may necessitate continuing the sortie unless safety of flight is compromised.

4.25. In-Flight Troubleshooting. After flight manual emergency procedures are complete, aircrews will not conduct in-flight troubleshooting. **(T-1)**

4.26. Cockpit Voice Recorder (CVR). If involved in a mishap or incident, after landing and terminating the emergency, pull the CVR power circuit breakers.

4.27. Flight Control Malfunctions.

4.27.1. The following procedures will be adhered to when maintenance "Redballs" the jet for primary flight control malfunctions during preflight or ground operations. The AC will evaluate the malfunction with maintenance personnel and determine actions necessary to provide an airworthy aircraft. **(T-1)** If the malfunction cannot be isolated to a particular part and/or repaired within a suitable amount of time, the aircraft will be returned to maintenance for repair. **(T-1)**

4.28. Divert Charts. Units will develop divert charts or tables to cover their local operating areas and publish them in their local chapter to this manual. **(T-3)** Information will include divert airfields, headings, distances, flight times, fuel requirements, and cruise altitudes. Aircrews will carry electronic or hard copy of these products on all flights. **(T-3)**

4.29. Air-to-Air Refueling (AAR) Restrictions/Procedures.

4.29.1. Aircrews will conduct AAR procedures IAW ATP, 3.3.4.2, *Air-to-Air Refueling*, and national annexes. **(T-2)** Plan to AAR with a CG forward of 32% Mean Aerodynamic Chord (MAC). AAR can be accomplished outside of these limits provided it is thoroughly briefed prior to conducting AAR. **Note:** Air-to-air refueling has been successfully accomplished in flight tests up to 33.5% MAC.

4.29.2. Aircrews will not accomplish AAR during training missions when conditions are encountered which, in the opinion of the AC or boom operator, result in marginal control of the aircraft or the boom. **(T-2)**

4.29.3. Aircrews will not accomplish AAR if any primary flight control malfunctions are encountered or with the series yaw damper inoperative. **(T-1)**

4.29.4. Aircrews will not accomplish AAR without disconnect capability. **(T-2)** In exceptional circumstances, such as an actual fuel emergency, or when an operational necessity exists, at AC discretion, manual boom latching may be performed. The AC must coordinate with the tanker crew before conducting manual boom latching procedures. **(T-2)**

4.29.5. Boom Envelope Demonstrations will be conducted under IP/Flight Examiner supervision. **(T-2)**. The boom operator will initiate and ensure disconnect capability before demonstrating limits IAW ATP-3.3.4.2. **(T-2)**

4.29.6. FPs. Non-AAR qualified FPs are authorized to fly up to the precontact position from either pilot's seat with an AC in the other seat. Non-AAR qualified FPs must be under IP/Flight Examiner supervision in order to approach the contact position. **(T-2)** AAR qualified FPs are authorized to fly to the contact position from either pilot's seat with an experienced AC in the other seat.

4.29.7. CPs. Non-AAR qualified CPs are authorized to fly up to the pre-contact position from the right seat with an AC in the left seat. Non-AAR qualified CPs must be under IP/Flight Examiner supervision in order to approach the contact position. **(T-2)** AAR qualified CPs are authorized to fly to the contact position from the right seat with an experienced AC in the left seat. Left seat certified CPs may perform AAR from the left seat while under IP/Flight Examiner supervision.

4.29.8. ACs/CPs undergoing initial qualification or upgrade training may conduct a rendezvous up to 1 NM from the tanker without IP/Flight Examiner supervision.

4.29.9. To allow time to establish communications with ATC, discontinue AAR at least 3 minutes prior to the end of track and descend to the bottom of the altitude block.

4.29.10. Loss of Radio Contact. If radio contact is not established or lost with the tanker on the AAR frequency, follow "Loss of Radio Contact" guidance IAW ATP-3.3.4.2.

4.30. Post-Air-to-Air refueling (AAR) Procedures. Use the following procedures after completion of AAR to achieve safe separation from the tanker:

4.30.1. The receiver pilot will maintain stabilized in the contact position while requesting or initiating a boom disconnect and will remain stabilized until confirming, either visually or verbally, that the boom is clear. **(T-2)**

4.30.2. After confirmation that the boom is clear, the receiver pilot will begin to move aft to the pre-contact position. **(T-2)** Once this separation has been attained, the receiver pilot will slowly descend at approximately 500 to 1,000 feet per minute (fpm), establish a power setting that will ensure increasing vertical separation, and avoid under-running the tanker during descent. **(T-2)**

4.30.3. The pilots will establish a minimum of 1,000 feet vertical separation between the receiver and the tanker. **(T-2)** Pilots will not make any turns from the established AAR heading/course during the descent phase unless safety of flight dictates.

4.30.3.1. Pilots will establish 1,000 feet vertical separation and engage autopilot (if available) before initiating the post-air refueling checklist. **(T-2)** Slipway doors may be closed (to reduce noise) and autopilot circuit breaker may be reset (to ensure autopilot is available) [With-DMA, N/A] once the boom is clear and a descent has been established.

4.30.3.2. To ensure safe separation during the separation maneuver, the PM and the NAV will monitor the positions of all tankers in the formation by whatever means possible (visual, weather radar, air-to-air TACAN, etc.). **(T-2)**

4.30.3.3. If the receiver cannot descend to establish the required vertical separation, the receiver will move back to the pre-contact position and request that the tanker initiate a climb to obtain a minimum of 1,000 feet vertical separation. **(T-2)**

4.31. Formation Restrictions. The enroute cell and air refueling formations described in ATP-3.3.4.2. are the only authorized formations. Crews will only fly these formations when specifically tasked; using the procedures published in the appropriate tech orders. **(T-2)**

4.32. Abnormal Configurations. Aircrew will not fly missions with known abnormal configurations unless approved by the applicable GP/CC. **(T-2)** Abnormal configurations can include operations with only six or seven brakes, partial spoilers, inoperative antiskid, etc.

4.33. Three-Engine Ferry Flights. Aircrew will not conduct three-engine ferry flights unless specifically approved by applicable MAJCOM/A3. **(T-1)**

4.34. Suspected Engine Compressor Stall/Surge on the Ground. If aircrew experience a known or suspected engine compressor stall/surge while on the ground, the aircraft will be returned to maintenance and the condition will be written up in the AFTO Form 781A.

4.35. Automatic Dependent Surveillance–Broadcast (ADS-B) In Devices. ADS-B in devices are approved for use on non-DRAGON modified E-3s.

Chapter 5

MISSION CREW OPERATING PROCEDURES

5.1. General. This chapter contains roles and responsibilities for mission crew positions. This information is in addition to AFMAN 11-202V3, AFI 11-214, *Air Operations Rules and Procedures*, AFTTP 3-1.AWACS, *Tactical Employment*, AFTTP 3-3.AWACS, *Combat Aircraft Fundamentals* and AFTTP 3-1.TACS, *Tactical Employment*, T.O. 1E-3A-43-1-1, *Flight Manual, USAF Series, E-3 Aircraft Mission Systems Operations*, T.O. 1E-3A-43-1-1-1, *Supplemental Flight Manual*.

5.2. Mission Crew Communications.

5.2.1. The programmed mission nets are always available. Crews should utilize tactical chat, when available, to pass information that is not time critical. **(T-2)**

5.2.2. The PA system is for use in emergencies and CCDs. Except for emergency checklist items, use of the PA by the mission crew is restricted to the SLIC.

5.3. Mission Commander (MC). The MC is responsible to the Joint/Combined Forces Air Component Command (J/CFACC) for execution of Mission Type Orders (MTOs). Any rated E-3 officer, certified for mission command, can act as an MC and execute MTOs, when the assigned mission requires. The MC should not perform duties in a primary crew position (i.e., SLIC, ABM, or AC) while conducting mission command duties unless authorized by the SQ/CC. Commanders should weigh the complexity of the mission and whether or not the MC will have sufficient time and situational awareness to conduct mission command from the primary duty position without interfering with the operation of the E-3 weapons system. If required, consider adding an additional crewmember to allow the MC to focus on external responsibilities.

5.4. Section Lead in Command (SLIC). The SLIC is responsible to the appropriate commander for the safe, efficient, and successful employment of the E-3 weapons system. The SLIC is responsible for the leadership, management, and supervision of the mission crew. The SLIC will:

5.4.1. Execute command directives and perform battle management functions as required, to include transmitting, receiving, authenticating, and executing command messages. **(T-3)**

5.4.2. Manage the air battle with appropriate command authorities and direct tactical action IAW applicable operations orders (OPORDs), operations plans (OPLANS), Air Tasking Order (ATO), Operational Tasking Data Link (OPTASKLINK), Special Instructions (SPINS), Joint Air Operations Plan (JAOP), and Rules of Engagement (ROE). **(T-3)**

5.4.2.1. Assign and supervise responsibilities based on qualifications, certifications, and currencies of assigned crewmembers. **(T-3)**

5.4.2.2. Assign and supervise primary sensor/system operators. Monitor and maintain sensor quality for mission duration. **(T-3)**

5.4.2.3. Supervise all aircraft control activity (ABM/Others as qualified) IAW AFTTP 3-3.AWACS, AFTTP 3-3.IPE, AFTTP 3-2.5, *Multi-Service Brevity Codes*, AFTTP 3-2.8, *Multi-Service Tactics, Techniques, and Procedures for Air Control Communication* and applicable procedures/standards. **(T-3)**

5.4.2.4. Ensure the crew is thoroughly briefed and prepared to meet mission tasking. Have a thorough understanding of the capabilities and tactics of hostile and friendly forces. **(T-3)**

5.4.2.5. Notify the AC and mission crew of all situations that could adversely affect safety of flight operations or mission accomplishment. **(T-3)** Coordinate with the AC on tactical positioning of the E-3 to ensure safe and efficient mission execution. **(T-3)**

5.4.3. Supervise the technicians and safely operate the E-3 weapons system IAW technical orders. **(T-3)** Ensure mission systems are configured and system information is current and correct to meet mission tasking. **(T-3)** Supervise the communications, data processing and display, and sensor system functions to ensure effective support of mission objectives. **(T-3)**

5.4.4. Be responsible for the completion of the AFTO Form 46, *Prepositioned Aircrew Flight Equipment*. **(T-3)**

5.4.5. Manage the orderly transfer of station responsibility as focal point between the E-3 crew and Higher Headquarters (HHQ), as well as the mission crew and flight crew. **(T-3)** Supervise coordination with lateral C2. **(T-3)**

5.4.5.1. Declare “on-station” when the E-3 is operations-normal IAW mission requirements, is in position to accomplish the assigned mission, and the mission crew have completed their station assumption requirements. **(T-3)**

5.4.5.2. Notify the appropriate command authorities of the “ops-normal/on-station” status and other reports, as specified by theater directives and any deviations from mission tasking. **(T-3)**

5.4.5.3. Approve/coordinate downtime for scheduled/unscheduled maintenance. **(T-3)** Assess equipment malfunctions and determine impact on the assigned mission. **(T-3)** Coordinate with the AC to assess the risk of continued use (AC is responsible for the safety of the aircraft). **(T-3)**

5.4.6. When operating in the NORTHCOM AOR, the SLIC will:

5.4.6.1. Act as or appoint a NORAD Certified Crewmember (NCCM) responsible for receiving and communicating message traffic concerning any Emergency Action Message (EAM)/Quick Reaction Message (QRM) and/or Tabular Report (TAB) IAW established guidance. **(T-3)**

5.4.6.2. Orient the mission crew with NORAD C2 functions and identify responsibilities and authorities of NORAD-assigned AWACS missions. **(T-3)**

5.5. Supervision of Sections. The SLIC will assign a SL to each battle management area (BMA) or functional assignment, based on qualifications, certifications, and currencies of crewmembers. **(T-3)** SLs are responsible to the SLIC for conduct of the air battle or execution of their assigned function. The SL will:

5.5.1. Supervise assigned operators (ABM/MSO) for battle management and allocation of crew resources in support of the mission and/or emergency procedures. **(T-3)**

5.5.2. Maintain data on friendly and enemy orders of battle as it affects their role. **(T-3)** Estimate and/or predict the capabilities of hostile forces. **(T-3)** Develop a plan, or plans, which organize friendly counter forces, and defeat/negate the threat to accomplish mission objectives. Maintain current, relevant, and accurate tactical situational awareness. **(T-3)**

5.5.3. Direct the air battle to ensure the accomplishment of assigned missions, including pairing effects/weapons/sensors against assigned targets. **(T-3)** Notify the SLIC and ASO of any suspected emergency IFF/ Selective Identification Feature (SIF) returns or triangular distress patterns. **(T-3)**.

5.5.4. Execute/Coordinate the Identification function IAW AFTTP 3-3.AWACS and local procedures. Supervise the detection, tracking, reporting, identification, and recording of surveillance data. **(T-3)**

5.5.5. Coordinate directly with the ASO/PSO to obtain optimum sensor configurations. **(T-3)**

5.5.6. Develop and maintain the communications worksheet for their assigned section. Coordinate communications changes with the SLIC/ARO. **(T-3)**

5.6. Weapons Controllers (Air Battle Manager [ABM]/Others as qualified). Weapons controllers are responsible for the direction, monitoring, and flight following of assigned aircraft during tactical and operational missions. **(T-3)** They are responsible for extracting data from theater and command directives for C2 of the air battle. **(T-3)** Conduct battle management IAW AFTTP 3-3.IPE, AFTTP 3-3.AWACS, AFTTP 3-2.5, AFTTP 3-2.8, JAOP and local procedures. Weapons Controllers will:

5.6.1. Locate, identify, and monitor tracking of aircraft assigned for control. **(T-3)**

5.6.2. Control aircraft against assigned targets. **(T-3)**

5.6.3. Direct air refueling missions consistent with prescribed EMCON procedures. **(T-3)**

5.6.4. Coordinate with other crewmembers and external agencies, as applicable, on matters pertaining to airspace assignment and flight safety. **(T-3)**

5.6.5. Ensure orderly and expeditious recovery of assigned aircraft. **(T-3)**

5.7. Active Sensor Operator (ASO).

5.7.1. The ASO is responsible to the assigned SL of the BMT to which they are assigned for all surveillance radar functions. The ASO will:

5.7.1.1. Monitor and direct the accurate collection, display, and dissemination of surveillance radar data and advise the crew of surveillance radar capabilities. **(T-3)**

5.7.1.2. Notify the SLIC whenever Electronic Attack (EA) is experienced and coordinate Electronic Protection (EP) actions. **(T-3)**

5.7.1.3. Notify the SLIC and SL of any suspected emergency IFF/selective identification feature (SIF) returns or triangular distress patterns. **(T-3)**

5.8. Datalink Operator (DLO). The DLO is responsible to the appropriate SL for enabling multi-link operations IAW Joint/Regional/Sector Interface Control Officer (J/R/SICO) guidance and AFTTP 3-3.AWACS. **(T-3)** The DLO will:

5.8.1. Coordinate data link modifications (filters, duties, ID usage) with the Joint/Regional Interface Control Cell (J/RICC). **(T-3)**

5.8.2. Implement changes in interface configuration as directed. **(T-3)**

5.8.3. Implement data link filters as stated in the OPTASKLINK or Tactical Operational Data (TACOPDAT). **(T-3)**. **Note:** Any changes to filters must be approved by the JICO. **(T-3)**

5.8.4. Utilize the Interface Control Network (ICN) and Datalink Coordination Net (DCN) to coordinate with J/R/SICO and other multi-link participants using directed net procedures if required by the NCS. **(T-2)**

5.8.5. Monitor track exchange (surveillance, weapons, and ES) and coordinate with SLs if required. **(T-3)**

5.8.6. Provide recommendations to JICO for data link changes. Forward changes to E-3 initial exchange requirements (IERS) to the JICO through the appropriate agency (i.e., Mission Planning Team (MPT), Air Control Wing Requirements (ACW/XR), Operations Group Exercises (OSOE), etc.). **(T-3)**

5.8.7. Coordinate with the SLIC and ADST/ARO, as required, in the establishment and operation of data links. **(T-3)**

5.8.8. Establish data links for the Joint Tactical Information Distribution System (JTIDS) Network Library for JTIDS and Tactical Digital Information Link (TADIL) A during Continental United States (CONUS) operations IAW established joint operating procedures. **(T-3)**

5.8.9. Establish data link operations outside CONUS according to local theater directives and the OPTASKLINK. **(T-3)**

5.9. Mission System Operator (MSO). MSOs perform various roles depending on the mission and BMT to which they are assigned. Roles range from; support the direction, monitoring, and flight following of assigned aircraft during tactical and air refueling missions. Support the BMT IAW AFTTP 3-3.IPE, AFTTP 3-3.AWACS, AFTTP 3-2.5, AFTTP 3-2.8, and local procedures; perform surveillance functions as directed by the SL; analyze Electronic Support (ES) data from on-board and off-board sensors, fuse that data with other on-board and off-board sensors, then disseminate a comprehensive ES picture both internally and externally. The MSO is responsible to the SL/ABM of the BMT to which they are assigned. **(T-3)**

5.9.1. MSOs will coordinate both internally and externally to perform force accountability, battle management, ES, and ID functions as assigned within the BMT/crew. **(T-3)**

5.9.2. Estimate and/or predict the capabilities of hostile forces and friendly forces relative to the Electronic Order of Battle (EOB), and advise the PSO/SL. **(T-3)**

5.10. Passive Sensor Operator (PSO). The PSO is responsible to the SL of the BMT to which they are assigned for the operation of the Electronic Support Measures (ESM) subsystem. The PSO will:

5.10.1. Monitor the accurate collection, display, and dissemination of ES data. **(T-3)**

5.10.2. Coordinate with external agencies to ensure the accuracy of ES data. **(T-3)**

5.10.3. Perform a systematic checkout of the ESM/PDS and brief the SLIC on the results. **(T-3)**

5.10.4. Complete an ESM log post-flight for any flight that anomalous system behavior or database mis-IDs occur and forward this information to the appropriate Electromagnetic Support Team (EST) representative. **(T-3)**

5.10.5. Debriefing intel on emitters of interest. **(T-3)**

5.10.6. Provide electronic IDs to ID matrices, as required, for mission crews and tactical battle management when the PDS is operational. **(T-3)** In the event that simultaneous activity with emitters and fighters requires the PSO to dedicate focus in one area; the PSO will coordinate with the SL to manage PSO effort prioritization. **(T-3)**

5.11. Internet Protocol Enabled Communication (IPEC) Operator.

5.11.1. The IPEC Operator will be a certified (P) MSO and/or (S) ABM. **(T-3)** The operator will be responsible for initialization, operation and maintenance of IPEC. All ADSTs will remain primary for Transitional Networking Capability (TNC)/SIC but will serve as a backup for IPEC. **(T-3)** ADST IPEC System knowledge will be maintained to a minimum level of 2b, ensuring familiarity with the system in the event no mission crew members are available, or assistance is required. **(T-3)**

5.12. Airborne Radio Operator. AROs perform communication functions.

5.12.1. The ARO is responsible to the AC/SLIC for the proper maintenance and operation of communications related equipment. **(T-3)** The ARO will:

5.12.1.1. Evaluate equipment status of the Communications Functional Group (CFG) and advise the SLIC of its capabilities to support mission requirements. **(T-3)**

5.12.1.2. Tune, configure, and operate clear and secure voice communications systems and communication nets to support mission requirements. **(T-3)**

5.12.1.3. Coordinate, obtain, use, and control COMSEC material and equipment. **(T-3)**

5.12.1.4. Perform frequency management; recommend and make required communications changes. **(T-3)**

5.12.1.5. Configure and operate datalink equipment and software. **(T-3)**

5.12.1.6. Compile and transmit required in-flight and position reports to appropriate facilities. **(T-3)**

5.13. Airborne Data Systems Technician (ADST). The ADST is responsible to the SLIC for the operation, monitoring, and in-flight maintenance of the Mission Computing System (MCS), Data Display Group, Electronic Support Measures Group (ESMG), Secure Iridium™ Communications (SIC) and Onboard Test Monitor and Maintenance functional groups, and JTIDS. **(T-3)** The ADST will:

5.13.1. Perform loading, power-on, and monitor performance of the MCS. **(T-3)**

5.13.2. Perform power-on of the ESM system and monitor performance. **(T-3)**

5.13.3. Evaluate equipment status of MCS and advise the SLIC of its capabilities to support mission requirements.

5.13.4. Monitor the status of mission computing connected avionics equipment, service peripheral equipment, and perform diagnostic maintenance programs. **(T-3)**

5.13.5. Perform in-flight troubleshooting and fault isolation using utilities programs where needed to enable replacement/restart of hardware or software as required. **(T-3)**

5.13.6. Establish and maintain connectivity with SIC equipment. **(T-3)**

5.13.7. In cooperation with DLO, configure, operate, and monitor JTIDS equipment and software. **(T-3)**

5.14. Airborne Radar Technician (ART). The ART is responsible to the SLIC for the operation and maintenance of the radar and IFF systems and their subsystems. **(T-3)** The ART will:

5.14.1. Initiate and monitor the Surveillance Radar Functional Systems and Identification Functional Systems including performance levels throughout the mission. **(T-3)**

5.14.2. Perform radar equipment test (Fault Isolation) routines and other checkouts. **(T-3)**

5.14.3. Troubleshoot malfunctions in sensor systems and repair or replace equipment as required. **(T-3)**

5.14.4. Initiate and monitor associated test equipment to optimize performance of sensor systems. **(T-3)**

5.14.5. During deployment or dispersed base operations, if there is no conflict with flying responsibilities (e.g., crew rest and duty day), the ART will assist ground-based personnel with maintenance activities when required. **(T-3)**

5.14.6. Coordinate with the SLIC/ASO on radar operating parameters (e.g., dedicated time test azimuth, second-time-around-thresholds, etc.), and on detection, analysis, and response to EA. **(T-3)**

5.15. Establishing Operations-Normal.

5.15.1. SLIC is responsible to ensure systems are adequately operational to conduct the assigned mission. **(T-3)** The SLIC will:

5.15.1.1. Establish 'Ops-Normal' criteria during planning if minimum equipment is not defined by local/theater guidance. **(T-3)**

5.15.1.2. Coordinate with the AC on equipment issues which affect aircraft systems. **(T-3)**

5.15.1.3. Approve continued operations of malfunctioning mission equipment that would affect the mission. **(T-3)**

5.15.1.4. Evaluate the impact of using degraded equipment against the mission tasking and the inability to meet that tasking. **(T-3)**

5.15.2. Active Sensor Management/Procedures. Prior to assuming station, the ASO will:

5.15.2.1. Perform IFF sensor checks, radar sensor checks, and quality control/systems check out to determine the optimum radar/IFF settings and configurations for the mission. **(T-3)**

5.15.2.2. Brief the SLIC on the results of the checks and the final radar setup. **(T-3)**

5.15.3. IFF Sensor Check. Perform a systematic checkout of the IFF, to include all operational Transmitters as soon as they become available. If equipment malfunctions, the Active Sensor Operator will accomplish an additional check once the unit is back online. **(T-3)** If a previously unchecked Transmitter unit comes online, the Active Sensor Operator will, again, accomplish an additional check. **(T-3)** As a minimum, the Active Sensor Operator will check:

5.15.3.1. Maximum Range. Measure the maximum range of the IFF by determining the range of an IFF sensor return with a consistent (three out of seven returns) data trail. **(T-3)**

5.15.3.2. IFF Jitter. Check in all quadrants, as close as possible to, but not beyond, 250 NM from the E-3. Measure jitter as sideways displacement of returns from a straight-line path. Normally jitter up to 3 NM is acceptable. **(T-3)**

5.15.3.3. Quality. The overall quality of the IFF will be determined by checking consistency of data trails, and when radar becomes available, the mileage difference between the IFF and radar sensor returns. **(T-3)** Normally, returns within 2 NM are acceptable. Accomplish this check within a radius of 250 NM from the E-3.

5.15.3.4. Resolution of IFF Overloads. Monitor IFF counts and make necessary adjustments to resolve overload conditions and minimize the loss of IFF data. **(T-3)**

5.15.3.5. Mode 5 Test. Report Mode 5 operational when correlated Mode 5 returns are displayed. **(T-3)** With DRAGON, perform Mode 5 loop test to validate the E-3's Mode 5 transponder.

5.15.4. Radar Sensor Check. Time permitting, the ASO will check as many RF sets as possible and select a primary and secondary RF set for the mission. **(T-3)** The ASO will use identical radar settings for each RF set checked for accurate comparison. **(T-3)** Radar mode will include both the Doppler™ and Beyond the Horizon (BTH) radars. **(T-3)** A sensor quality check must be made when established in the orbit area if a checkout was accomplished prior to arrival to the orbit area. The radar check will include:

5.15.4.1. Doppler™/BTH Maximum Range. **(T-3)** Determine the maximum Doppler™ range from the situation indicator display presentation using data trails with a minimum 40% blip-scan ratio (3 out of 7 scans have radar returns). A single data point, present or history, may be used to determine the maximum BTH range from the situation indicator display presentation.

5.15.4.2. Quality. **(T-3)** Radar quality is determined by the percentage of all IFF returns within a 250 NM radius of the E-3 that have consistent discernible radar data trails. In addition, consider the overall consistency of the radar presentation. Use the following criteria to assess the overall quality of the radar: Good = Greater than 75%, Fair = Between 50 to 75%, Poor = Less than 50%.

5.15.4.3. System Counts. **(T-3)** On applicable form, log the Doppler™, BTH, and Mode 3 counts for comparison of radar frequencies. Time of day, operating location, traffic density areas, and radar mode of operation may significantly affect the ratio of these figures.

5.15.5. Quality Control (QC)/Systems Check Out. **(T-3)** Once the sensors have been initially checked and declared operational, the ASO is not required to re-accomplish a full sensor check unless the applicable sensor system is powered down or if the ART accomplishes a Fault Isolation Test (FIT) on the radar system, e.g., after QC. In circumstances, such as post-AAR, where sensors are transferred but not powered down, the ASO will, at minimum, accomplish a quality check of radar and IFF systems prior to declaring them operational. **(T-3)**

5.15.6. Radar Setup. **(T-3)** The ASO must consider the effects of the E-3 flight parameters on sensor performance and attempt to optimize checkout within these constraints. **(T-3)** The assessment of overall air picture quality will be the primary factor in determining the optimum RF set. After selecting the optimum RF set, the ASO will declare the radar operational. **(T-3)** When multiple E-3 flights operate in an area, the ASO will perform frequency de-confliction. **(T-3)**

5.15.7. Data Link Procedures and Operation. **(T-3)** Data link is the primary means of passing E-3 information and are established by the DLO according to, *Joint Multi-Tactical Data Link (TDL) Operating Procedures*, for the JTIDS Network Library for JTIDS and TADIL A during CONUS operations. Data link operations outside CONUS are established according to local theater directives and the OPTASKLINK.

5.15.8. Passive Sensor Operator Procedures. A PSO/ABM will coordinate to ensure PDS is loaded with an appropriate database. **(T-3)** The PSO/ABM will also coordinate with the SLIC when PDS is downloaded, and operational. In addition, advise the SLIC, ADST, and all SLs of any system degradation. **(T-3)** Only a PSO/ABM will declare ESM operational. **(T-3)** Perform checks on ESM to ensure operational status and determine optimal sensor set-up. The PSO/ABM will brief the SLIC on the results of these checks. **(T-3)** At a minimum, check:

5.15.8.1. Reception in Frequency Range. **(T-3)** Check to ensure 360-degree reception of signals within all three bands: Low (500-1999 MHz), Medium (2000-7999 MHz), and High (8000-18000 MHz). This is a subjective check, but there should be several indications within each band on different azimuths.

5.15.8.2. Triangulation. **(T-3)** Check that triangulation is occurring in all quadrants. Triangulation for each frequency band is not required. The statuses of “Triangulating,” “Monitoring for Divergence”, and “Diverged” all count to verify the system is working. Triangulation accuracy will be verified by a triangulation quality check conducted by verifying a triangulated site location against known emitter locations such as ATC radars, NAVAIDS, ECR sites etc. to an EEP accuracy of 10nm x 4nm (Major/Minor ellipse) or better. **(T-3)** This check can be accomplished at any point throughout the mission. Lack of correlation to a known emitting site for triangulation should not prevent ESM from being called operational and will be reported to the SLIC. **(T-3)**

5.15.8.3. Check that the correct map is loaded. **(T-3)**

5.15.8.4. Check that the average scan rate is below 8 seconds. **(T-3)**

5.16. Assuming Station. The SLIC is responsible for determining whether station assumption requirements are met. Unless otherwise defined in local/theater guidance, the following conditions should be met or alibied prior to station assumption:

5.16.1. Conduct database checks as appropriate.

5.16.2. Radar and IFF are configured for mission use.

5.16.3. Contact with ground agencies or agency to be relieved has been established (voice/chat).

5.16.4. Active Sensor correlation check. IFF-only operations are authorized according to this manual and theater operating instructions IAW FAA Order JO 7610.4 series or ATC LOA. IFF-only operations require a sensor correlation check to be accomplished.

5.16.4.1. Format should be Voice Tell format IAW AFTTP 3-3.IPE. Tracks used must be within 3 NM or less to be considered a good sensor correlation.

5.16.4.2. Data link correlation checks may be used instead of voice checks if accurate real-time data is being exchanged.

5.16.4.3. Internal correlation checks are considered complete if all navigation equipment is functioning properly and RADAR and IFF have been declared operational.

5.16.5. Coordinate procedures with the responsible Military Radar Unit (MRU) prior to assuming station when operating as an Airborne Radar Unit (ARU). When operating in Canada, the E-3 will comply with the TC (Transport Canada)/Department of National Defense (DND) agreement (short title, "AWACS Agreement") between Director General Air Doctrine and Operations Department National Defense, and Director Air Traffic Services Department of Transportation.

5.16.5.1. Employ as Tactical Monitor (TM) IAW applicable guidance during planned exercise or daily training under the following conditions:

5.16.5.1.1. Responsibility for the ATC released airspace lies with the military aircraft that scheduled and are flying within the SUA/ Air Traffic Control Assigned Airspace (ATCAA). These aircraft must comply with Autonomous Operations for air traffic control purposes while in the SUA/ATCAA.

5.16.5.1.2. TMs do not accept responsibility for SUA/ATCAA.

5.16.5.1.3. TMs will provide necessary tactical information/guidance for the military aircraft operating in SUA/ATCAA to complete mission training.

5.16.5.2. When operating as TM, AWACS crews should not normally contact ATC during mission planning or during mission execution. Monitoring ATC frequencies for situational awareness is encouraged but contact with ATC should only be established in extraordinary situations.

5.16.6. Check assigned voice frequencies / radio transmitters for usability.

5.16.7. Designated crewmembers monitoring Guard frequencies (VHF for duration of on station, UHF while aircraft are under control).

5.16.8. The E-3 is in a position to accomplish the assigned mission.

5.17. Voice Tell and Recording Procedures. When the E-3 is in an environment with units not capable of data link interface, voice tell may be needed to share a common tactical picture. The E-3 will voice tell HOSTILE/FAKER, UNKNOWN/PENDING, and Emergency tracks unless the receiving agency directs cease tell. Tell all other priorities on request only. Live tracks have priority over simulated tracks. Voice tell will be IAW AFTTP 3-3.IPE or theater directives. **(T-3).**

5.18. Electronic Combat (EC) Procedures. The SLIC/ASO will monitor/coordinate EP actions. **(T-3)** See AFTTP 3-1.AWACS and AFTTP 3-3.AWACS for complete EA/EP counter-tactics. Use the following baseline procedures for noise jamming against the E-3 radar:

5.18.1. The ASO, PSO, and ART will coordinate on any unusual sensor activity to determine whether the source is external or internal and type of interface if able. **(T-3)** If no explanation can be determined and the source is external, submit an Air Force Spectrum Interference Reporting System (AFSIRS) report.

5.18.2. Make every effort in an EA environment to obtain active data on all EA targets. Whenever possible, use cooperative passive tracking. If cooperative support is not available, use self-passive tracking.

5.18.3. When self-triangulating, to determine if one of several previously active tracking returns is a suspected EA emitter, the ASO/ABM/MSO will extrapolate the suspected track on its last known heading, speed, and altitude, before initiating a passive track. **(T-3)**

5.18.4. The ASO will keep the SLIC/SL advised on status of passive tracks. **(T-3)** When the ASO is confident that the passive track has correlated with the jammer's location, notify the SL that the track has "stabilized" and enable display to all consoles. In the event of burn-through, the ASO, in coordination with the SLIC and IAW ROE, may "validate" the track as a jammer and associate the track with active data. **(T-3)**

5.19. Identification Procedures. The theater SPINS/ROE dictate which systems/platforms can complete the ID matrix. Some platforms can fulfill the ID matrix based on their organic capability or based on their integration capability (voice or data link) with other ID-capable platforms.

5.19.1. If the E-3 can fulfill the ID matrix and has the ability to declare a contact hostile, any ABM on board the E-3 can complete the ID matrix. The SLIC may restrict this and retain hostile declaration authority or delegate it as mission needs dictate.

5.19.2. The PSO should ensure PDS data link filters are set correctly. PSO will coordinate with the SIGINT ID Authority (SIA) for selecting specific emitters to tell out during the mission. **(T-3)** Reporting procedures will be IAW theater directives and AFTTP 3-1.AWACS. **(T-3)**.

5.20. Control Procedures. On-station control procedures will be IAW AFI 11-214 and AFTTP 3-2.8. **(T-3)** SLIC will notify the flight crew when aircraft are under control. **(T-3)** With coordination, the SL may control aircraft when simultaneous missions are not in progress. Aircrew providing control will be current unless under supervision, per AFMAN 11-2E-3G Volume 1, *E-3 Aircrew Training*.

5.20.1. Airspace and Aircraft Handoff. Use of airspace will be IAW FAA JO 7610.4, *Special Operations*, appropriate LOA and, local guidance. **(T-0)** Handoff procedures IAW applicable LOA. **(T-0)** A designated ABM will monitor the handoff frequency once performing station assumption duties until termination of aircraft control. **(T-3)**

5.20.2. Tracking. During all operations, ABM/MSO will ensure the J3.2 air track/local track and sensor data of controlled aircraft are within 2 NM of each other. **(T-3)**

5.20.3. Controlled Aircraft Emergency Procedures. For aircraft with in-flight emergencies, the ABM performing the handoff will use the word "Emergency" at the beginning of transmissions to the recovery agency, as well as add "Emergency" to the callsign of the affected player.

5.21. Communications Procedures.

5.21.1. Radio Procedures. Adhere to communications discipline at all times. All crewmembers will use proper International Civil Aviation Organization phraseology, phonetic alphabet, R/T procedures outlined in Allied Communications Publications (ACP) 121, *Communications Instructions – General*, and applicable supplements, AFTTP 3-3.IPE, AFTTP 3-2.5 and, AFTTP 3-2.8. **(T-0)**

5.21.2. Phone Patches. Units will establish phone patch procedures in their local chapter. **(T-3)**

5.21.3. Callsigns. Always use the aircraft callsign when transmitting messages of flight safety, aircraft movement, and radio calls required by this manual. Mission crewmembers will use the mission crew callsign when communicating with the respective controlling or monitoring agency, aircraft under their control, or as briefed. **(T-3)**

5.22. Off-Station Procedures. The SLIC will ensure external agencies are aware the E-3 has departed station and the assigned mission has been handed over. **(T-3)** All crewmembers will complete post-mission reports as directed by local procedure. The SLIC/AC will debrief the crew, appropriate command authorities, and unit agencies as required.

Chapter 6

FLIGHT PATH MANAGEMENT (FPM), OPERATIONAL RISK MANAGEMENT (ORM), CREW RESOURCE MANAGEMENT (CRM), THREAT AND ERROR MANAGEMENT (TEM)

6.1. Flight Path Management. The term “flight path” applies any time the aircraft is in motion, including taxiing the aircraft. Flight Path Management is the planning, execution, and assurance of the aircraft’s guidance, trajectory, and energy state--in flight or on the ground. All flight deck aircrew members must ensure that effective Flight Path Management is a primary and shared responsibility during all phases of flight. Flight Path Management is comprised of 3 aspects (Planning, Executing and Monitoring):

6.1.1. Planning. Developing a thorough understanding of the aircraft’s desired flight path. Planning is dynamic and includes changes driven by the mission, environmental considerations, and clearances from authorities, such as ATC. **Note:** For the purposes of this document, a clearance is the flight path of the aircraft, as normally defined by the assigned ATC clearance. Typically, two pilots must hear/read, understand, anticipate its impact, and comply with the clearance, unless otherwise deemed necessary for the safe conduct of the flight. Other flight deck crewmembers who have the training, ability and authority to do so should assist with clearance acceptance.

6.1.2. Executing. The process through which the aircrew controls the aircraft and achieves compliance with the desired flight path.

6.1.3. Monitoring. The process through which aircrew members monitor compliance with the desired (planned) flight path. Effectively monitoring the flight path is a critical Threat and Error Management (TEM) task that discovers and corrects Flight Path Management errors that might lead to flight path deviations or Undesired Aircraft States (UAS). As a primary and shared responsibility, monitoring is equally as important as controlling the aircraft. Monitoring requirements vary depending on phase of flight and on situations encountered within each phase of flight. Aircrews should anticipate flight situations or phases where they will be most vulnerable to flight path deviations (Areas of Vulnerability – AOVs) and strategically manage workload and distractions to maximize monitoring during these AOVs.

6.2. Operational Risk Management (ORM). ORM is a logic based, common sense approach to making calculated decisions on human, material, and environmental factors before, during, and after all operations. USAF policy on ORM is contained in AFI 90-802, *Risk Management*. PICs will accomplish ORM worksheets IAW MAJCOM and local guidance as part of preflight activities. **(T-2)**

6.2.1. Flying units will develop a local ORM program to include personal ORM assessment for all missions and accomplished by all crewmembers at the beginning of each flight duty period. **(T-3)**

6.3. Crew Resource Management/Threat and Error Management (CRM/TEM).

6.3.1. CRM is the effective use of all available resources, people, weapon systems, facilities, equipment, and environment by individuals or crews to safely and efficiently accomplish an assigned mission or task.

6.3.2. TEM is a structured, proactive, systems approach that is intuitively, logically, and flexibly designed. It builds on multiple layers of defenses to identify, prevent, and mitigate threats and/or trap or mitigate inevitable human errors to avoid UAS and potential mishaps. See AFMAN 11-290, *Cockpit/Crew Resource Management and Threat & Error Management Program* or applicable MAJCOM supplement for additional information.

6.3.3. "Time Out". "Time Out" is the common assertive statement for use by all crewmembers. The use of "Time Out" is intended to:

6.3.3.1. Provide a clear warning sign of a deviation or loss of situational awareness.

6.3.3.2. Provide an opportunity to break the error chain before a mishap occurs.

6.3.3.3. Notify all crewmembers when someone sees the aircraft or crew departing from established guidelines, the briefed scenario, or that someone is simply uncomfortable with the developing conditions.

6.3.3.4. As soon as possible after a "Time Out" has been called, the aircrew will take the following actions:

6.3.3.5. Safety permitting, stabilize the aircraft. **(T-2)**

6.3.3.6. The initiating crewmember will voice their concerns to the crew. **(T-2)**

6.3.3.7. The PIC will provide all other crewmembers with the opportunity to voice inputs relative to the stated concerns. **(T-2)**

6.3.3.8. After considering all inputs, the PIC will direct the aircrew to continue the current course of action or direct a new course of action. **(T-2)**

6.4. Automation Management.

6.4.1. Aircraft automation systems are tools intended to enhance safety, maximize efficiency, improve operational capabilities, and reduce pilot workload. **Note:** Although automation can assist with seeing and avoiding conflicting traffic, at least one pilot should maintain visual outside awareness.

6.4.2. Flight Automation. Pilots should maintain proficiency in the use of all flight automation levels and the skills required to seamlessly shift between those levels. Available flight automation levels vary between aircraft and may include many combinations of flight director guidance and autopilot modes including partial automation. The level of flight automation used shall permit both pilots to maintain situational awareness and a comfortable distribution of workload. If the use of flight automation creates a loss of situational awareness or results in task saturation, the pilot should shift to a less demanding level or disconnect the automation entirely and re-establish the desired aircraft flight path. Pilots should choose an appropriate flight automation level consistent with changing flight environments and balanced with the requirement to maintain manual flying skills.

6.4.2.1. The PF will determine, announce, and fly the aircraft using the appropriate level of flight automation IAW Standard Operating Procedures (SOPs), flight manual guidance, and applicable regulations. **(T-2)** The PM will acknowledge the announcement. **(T-2)**

6.4.3. Information Automation (IA). Managing information is an important aspect of FPM. The quantity and type of information available to the aircrew has substantially changed and will continue to change. IA is automation devoted to the management and presentation of relevant information to flight crews. Examples of IA systems include the EFB, Aircraft Communications Addressing and Reporting System (ACARS), moving map displays, performance management calculations, multi-function displays, data uplink, alerting systems including lights and audible and tactile alerts, and FMS display unit pages and scratch pads.

6.4.3.1. Aircrew members must be proficient in the use of automated systems and in accessing and interpreting automated information, determining its reliability, and understanding how to use the acquired information. These tasks must occur seamlessly throughout the flight to prevent distraction from primary flight path management tasks.

6.4.3.2. Head-Up/Head-Down Policy. Establish clear roles for computer-related tasks. One pilot should always remain "head-up." Announce "pilot head-down" or "copilot head-down" when the task requires prolonged attention within the flight deck. Other than momentary occasions, any crewmember who observes both pilots "heads-down" at the same time (other than instrument flying) shall announce the issue to the aircrew without delay. (T-2)

6.4.4. Verbalize, Verify, and Monitor (VVM). VVM is a closed-loop system of communication designed to significantly reduce aircraft automation errors. Aircrews will utilize VVM practices unless safety of flight requires a temporary deviation from these requirements. (T-2) VVM consists of a three-step process:

6.4.4.1. Verbalize. Prior to making changes to the selected/armed flight guidance (including altitude), the crewmember performing the action VERBALIZES the intended change(s).

6.4.4.2. Verify. The appropriate crewmember(s) VERIFY the intended changes *prior* to execution. The crewmember(s) responds to the intended change(s) by verbally confirming the change or notifies the challenging crewmember of an issue and/or concern. When necessary, visual cues confirming intended change(s) are acceptable but are not normally the primary method for confirmation. If visual cues are used, when time allows, ensure all appropriate flight deck crewmembers are aware of the executed action by verbally reviewing the executed action.

6.4.4.3. Monitor. Once the intended action(s) has/have been confirmed and "executed," crewmembers continually MONITOR the aircraft to ensure the expected performance is achieved by staying vigilant and situationally aware.

6.5. Flight Path Management (FPM) Pilot Flying (PF) and Pilot Monitoring (PM) Duties. There must be a clear understanding of the PF and the PM duties at all times. The terms PF and PM are used to designate pilot roles and procedural duties when the aircraft is in motion or as designated by T.O. guidance. Controlling and monitoring the aircraft flight path is the highest priority of the PF and PM, regardless of automation level.

6.5.1. PF/PM roles may change throughout a flight. Transfer of PF and PM roles must be clear to all primary crewmembers. The transfer will be expressed using a three-part aircraft control transference statement and should be done positively with verbal assignment and verbal acceptance to include a short brief of aircraft state, as necessary. Depending on the situation, it is suggested that the transference statement include airspeed, altitude, heading, and/or automation configuration. An example is as follows: Pilot: "Copilot's aircraft. We're level at flight level 310 at 275 knots and the autopilot is engaged in heading mode; heading 3-0-0." Copilot: "Understood. Copilot's aircraft." Pilot: "Copilot's aircraft."

6.5.2. PF. The pilot at the flight controls who is in direct maneuvering control of the aircraft. The PF is primarily responsible to control and monitor the aircraft's flight path (including auto flight systems, if engaged). The PF is secondarily responsible to monitor non-flight path actions (e.g., radio communications, aircraft systems) but must never allow these activities to interfere with their primary responsibility. The PF should also recognize when the PM is not adequately monitoring the flight path and make the PM aware of this deviation. Assigning non-flight path-related tasks to the PF should generally be avoided. If the PF must engage in activities that distract from flight path control tasks, the PF should transfer aircraft control to the other pilot, and then assume the PM role.

6.5.3. Pilot Monitoring. In addition to Mission Design Series (MDS)-specific T.O. guidance, the PM is the pilot at the flight controls who is not in direct maneuvering control of the aircraft, yet is primarily responsible to actively monitor the aircraft's flight path, intervening if necessary within pre-established parameters. The PM supports the PF by accomplishing non-flight path actions (e.g., radio communications, aircraft systems) but should continue to monitor the flight path.

6.5.4. Pilot Monitoring (PM) Behaviors. An effective PM should:

6.5.4.1. Be knowledgeable of all policies and procedures related to monitoring the flight path (e.g., callouts).

6.5.4.2. Recognize when the PF is not adequately controlling the flight path. This includes pilot task loading and signs of diminished performance (e.g., lack of communication, channelized attention, and failure to make required callouts, etc.).

6.5.4.3. Be aware of applicable common errors regarding monitoring the flight path. This includes appropriate methods of recognizing precursors and signs of degraded monitoring and on resolving monitoring errors and/or lapses.

6.5.4.4. Be competent regarding the concept of Areas of Higher Vulnerability (AoHV). If the PM recognizes the flight phases or situations when they are most vulnerable to flight path deviations (including when little time exists to correct deviations), then tasks can be planned strategically and workload managed to maximize flight path monitoring during those phases.

6.5.4.5. Be knowledgeable of CRM/TEM principles and human performance vulnerabilities related to monitoring, the importance of monitoring, and the approved practices that achieve effective monitoring of the flight path.

6.5.4.6. Be aware of system failures that may distract from effective monitoring and proper flight path management.

6.5.4.7. Be able to manage distractions that interfere with monitoring the flight path by managing task priorities and effectively switching between other tasks and monitoring of the flight path so that flight path vigilance is always maintained. The PM should be able to apply task management strategies that enable pilots to use charts, EFB, ACARS, etc. While also effectively monitoring the flight path and airplane energy state.

6.5.4.8. Employ intervention methods that can be used to help the PF regain proper control of the flight path (e.g., calling out deviations, levels of assertiveness).

6.5.4.9. Have a working understanding of automated flight guidance and flight control systems. The PM should understand what happens ‘next’ given a certain set of flight circumstances, and the reasons why. The knowledge should incorporate FMS degradations, failures, and operational consequences requiring flight crew action, known flight guidance and flight control system-behavioral challenges and environmental/circumstantial traps (e.g., vectors off and on a STAR during a “descend via” clearance) that are known to lead to flight path-related errors.

6.5.5. Be able to sufficiently collaborate with the PF to transition seamlessly between combinations/levels of flight guidance or flight control automation (including manual flight) by anticipating, recognizing, and recovering from known flight guidance system-behavioral challenges (e.g., subtle mode reversions). **Note:** Flight guidance includes FMS and flight control (includes autopilot and autothrottles).

6.6. Advisory Calls.

6.6.1. The PF will announce intentions for departures, arrivals, approaches, and when circumstances require deviating from normal procedures. **(T-2)** Should any crewmember be unsure of the PF's intentions, they will ask for clarification prior to accomplishment. **(T-2)** Unless otherwise directed, all primary crewmembers (as applicable) will acknowledge mandatory calls. **(T-2)**

6.6.2. The PM will make all normal advisory calls except those designated for other crewmembers by MDS-specific T.O. guidance and this manual. **(T-2) Exception:** Automated aircraft advisories satisfy this requirement if acknowledged by a primary crewmember, typically the PF (using the format below). Additionally, aircrew members (PM or otherwise) will advise the crew anytime the primary radio is changed. **(T-2)** If aircraft specific Flight Manual callouts vary from the callouts listed in the tables below, the Flight Manual callouts take precedence (e.g., Cat II/III callouts).

6.6.3. Advisory Calls: Refer to **Tables 6.1** through **Table 6.4** for a listing of mandatory advisory calls, responses, and aircrew actions.

Table 6.1. Climb Out Advisory Calls.

Climb Out	PM Call	PF Response
Transition Altitude	“Transition Altitude, 29.92, Set” (or 1013)	“29.92, Set” (or 1013)
1000’ below assigned altitude	“(Altitude passing) climbing (Altitude Assigned)”	“Leveling at (Altitude Assigned)”
Within 200 feet of assigned altitude	“Approaching level off”	
<p>Note: Altitudes will be announced in the following format: Below Transition Altitude: (12,500’) “One Two Thousand Five Hundred” Above Transition Altitude: (19,000’) “Flight Level One Niner Zero”</p>		

Table 6.2. Descent Advisory Calls.

Descent	PM Call	PF Response
Transition Level	“Transition Level, (local altimeter), Set”	“(local altimeter), Set”
1000 feet above assigned altitude	“(Altitude passing) descending (Altitude Assigned)”	“Leveling at (Altitude Assigned)”
Within 200 feet of assigned altitude	“Approaching level off”	
<p>Note: Note: Altitudes will be announced in the following format: Below Transition Altitude: (12,500’) “One Two Thousand, Five Hundred” Above Transition Altitude: (19,000’) “Flight Level One Niner Zero”</p>		

Table 6.3. Non-precision Approach Advisory Calls.

Non-precision Approaches (1)	PM Call	PF Response
100 feet above FAF Altitude	“100 above”	
1000 feet above touchdown	“1000, Stable (or deviation)”	“1000, stable (or deviation), cleared and configured” or “1000, stable (or deviation), configured, awaiting clearance”
100 feet above step down altitude	“100 above”	“100”
500 feet above touchdown	“500, Stable” or “Go-Around, unstable”	“500” or “Going Around”
100 feet above Minimum Descent Altitude (MDA)	“100 above”	“Continuing”, “Landing”, or “Going Around”
At MDA	“Minimums”	
Runway environment in sight: Called only if breaking out of weather inside the FAF	“Runway in Sight”	“Continuing”, “Landing”, or “Going Around”
Missed Approach Point (MAP)	“Missed Approach Point” (2)	“Landing” or “Going Around”
<p>Notes:</p> <p>1. Refer to stabilized approach guidance in paragraph 6.8.1. Note: Pilots should determine and reference HAT for the approach to be flown using the most practical means available. Radar altimeter height provides a convenient reference but may not provide consistent stabilized approach callouts due to terrain along the approach. Touch Down Zone Elevation (TDZE) or Threshold Crossing Height (TCH/THRE/THR) provides accurate elevation but may not always be published for the desired runway.</p> <p>2. If the PF has stated “landing” then this call is not required.</p>		

Table 6.4. Precision Approach Advisory Calls.

Precision Approaches (1)	PM Call	PF Response
100 feet above glideslope intercept altitude	“100 above”	N/A
1000 feet above touchdown	“1000, Stable (or deviation)”	“1000, stable (or deviation), cleared and configured” or “1000, stable (or deviation),
500 feet above touchdown	“500, Stable” or “Go-Around, unstable”	“500” or “Going Around”
100 feet above Decision Height (DH) / Decision Altitude (DA)	“100 above”	“100”
At DH/DA	“Minimums” (4)	(2)
Only Approach Lights in sight (CAT I ILS)	“Approach lights in sight”	“Continuing” (3)
Runway environment in sight: Called only if breaking out of weather inside the FAF.	“Runway in sight”	“Landing” or “Going Around”
Approach Lights and/or Runway environment not in sight	“Go-around”	“Going Around”
At 100 feet above TDZE (CAT I ILS)	“100 feet” (4)	“Landing” or “Going Around”

Notes:

1. Refer to stabilized approach guidance in **paragraph 6.8.1. Note:** Pilots should determine and reference HAT for the approach to be flown using the most practical means available. Radar altimeter height provides a convenient reference but may not provide consistent stabilized approach callouts due to terrain along the approach. TDZE or TCH/THRE/THR provides accurate elevation but may not always be published for the desired runway.
2. The PF will announce his/her intentions to either land, continue (CAT I) or go-around. **(T-2)** Respond with the intention to land if runway environment is in sight, will remain in sight throughout touchdown and the aircraft is in a position for a safe landing. **(T-2)**
3. With weather at CAT I minimums on a CAT II ILS, the pilot may not see the runway environment at DA; however, the initial portion of the approach lights may be visible. The pilot may continue to 100’ HAT with reference to the approach lights only. The pilot may not descend below 100 feet above touchdown zone elevation using the approach lights as reference unless the red terminating bars or the red side row bars are distinctly visible and identifiable and/or the runway environment is in sight. **(T-2)**
4. If the pilot flying has stated “landing” then this call is not required.

6.6.4. Deviation Advisories. IAW sound CRM/TEM practices, aircrew members will inform the PF when flight path deviations exceed (or will exceed) tolerances and no attempt is being made to correct the deviation. **(T-2)** Tolerances are defined by MDS specified SOPs. In absence of MDS SOPs, use the most restrictive of MDS specific Volume 2 criteria, standards, or flight manual guidance. **(T-2)** Any crewmember noticing a potential terrain and/or obstruction issue will immediately notify the PF. **(T-2)** The PF will take immediate corrective action. **(T-2)** This is especially important during critical phases of flight, nighttime, night vision goggle (NVG) ops, and/or instrument conditions.

6.6.4.1. Under normal flight conditions, deviations observed in excess of heading (+/- 5 degrees), airspeed (+10/-5 knots), or altitude (+/- 100 feet) will be announced by any aircrew member using clear and concise terminology (example: "XX knots fast). **(T-2)** When conducting planned maneuvers with tolerances different than those listed above, comply with AFTTP 3-3 guidance for "Terminate criteria". **(T-2)**

6.6.5. Emergency Advisories. Any crewmember detecting an existing or impending emergency condition will immediately inform the AC. **(T-2)** The PF will take necessary action to establish and/or maintain control of the aircraft and call for the appropriate checklist. **(T-2)**

6.7. Critical Action Coordination. During an emergency, as a general guideline the AC should attempt to assume control of the aircraft unless it has been determined that safety of flight would be compromised by assuming control (e.g., AC is not at the controls during the induction of the emergency). Those actions that are flight critical/irreversible in nature must always be confirmed by two crewmembers. **(T-2)** These actions include, but are not limited to: placing the throttles to cut-off, pulling the engine fire handle, discharging agent, dumping fuel, and other actions determined to be critical in the aircraft flight manual. Critical Action Coordination is performed as follows:

6.7.1. Flight deck crewmembers verbally and visually identify the affected control (e.g., "CONFIRM NUMBER ONE"). The crewmember performing the action points to the affected control. The crewmember monitoring the action verbally and visually confirms the proper control is selected (e.g., "NUMBER ONE CONFIRMED"). The crewmember performing the action then actuates the affected control. **Note:** During any emergency, the AC normally notifies the crew of the emergency, and the PM normally notifies all others concerned, such as ground control, tower, etc.

6.7.2. Rejected Takeoff (RTO) Decision Making. The RTO/Continue Takeoff decision making process is dynamic, time critical, and may be complex. Aircrew can mitigate takeoff hazards by building a shared mental model of the takeoff including Take-Off and Landing Data, aircraft systems, weight and balance, terrain, environmental conditions, high-speed vs. low-speed reject risks. The PIC is the final decision authority and should ensure a clear understanding of expected crew actions.

6.8. Stabilized Approach. Unstable approaches are primary contributors to numerous military and civilian mishaps. Stabilized approaches are essential for the safe operation of aircraft and are mandatory. The following criteria define specific parameters that mitigate risk during this critical phase of flight. This philosophy requires aircrew to take immediate corrective actions to stabilize the approach when outside designated parameters. Although tactical approaches are inherently less constrained, they must still result in the aircraft arriving at a position in space in an appropriate configuration and within acceptable parameters that will permit a safe landing consistent with aircraft flight manual restrictions as well as performance manual assumptions and limitations.

6.8.1. Stabilized Approach Criteria. The following stabilized approach criteria applies to all approaches and will be emphasized and briefed for every approach. **Note:** Use an abbreviated briefing for multiple approaches conducted in the same terminal area.

6.8.1.1. Aircraft is in landing configuration. **(T-2) Note:** Final flap configuration may be delayed but will be briefed.

6.8.1.2. Airspeed is appropriate for the configuration and conditions.

6.8.1.3. Sink rate is no greater than 1000 fpm. **(T-2) Note:** Under certain conditions (weather, terrain, etc.) some approaches may require greater than a 1000 fpm descent rate. This increased sink rate will be briefed. **(T-2)**

6.8.1.4. All briefings and checklists are complete unless contrary to T.O. guidance. **(T-2)**

6.8.1.5. Aircraft is on the correct track. **(T-2)**

6.8.1.6. Aircraft is in the correct bank angle to maintain proper approach track for instrument, circling, or visual approach. **(T-2)**

6.8.1.7. Power set to maintain the descent profile at approach speed. **(T-2)**

6.8.1.8. Momentary minor corrections or deviations are acceptable and defined as:

6.8.1.8.1. Airspeed: +10/-5 knots from target. **(T-2)**

6.8.1.8.2. Bank Angle: +/- 15 degrees from target. **(T-2)**

6.8.1.8.3. Rate of Descent: +/- 300 FPM from target. **(T-2)**

6.8.2. Stabilized Approach Procedures. The following procedures apply to all approaches.

6.8.2.1. At 1000 feet HAT, the stable criteria in [paragraph 6.8.1](#) apply or as determined by specific MDS SOPs, standards, or T.O. guidance.

6.8.2.1.1. If these criteria are not met at 1000 feet HAT, the PM will announce the deviation and the PF will take immediate corrective action. **(T-2)** PM will state “1000, XXXX,” where “XXXX” equates to a concise description of the unstable characteristic(s) which clearly relay to the PF what actions are required to return the aircraft to a stable platform. Example: “1000, 15 fast.” **(T-2)**

6.8.2.1.2. If criteria are met, PM will state “1000, stable.”

6.8.2.2. Between 1000 feet and 500 feet HAT:

6.8.2.2.1. Parameters are the same as those in [paragraph 6.8.1](#).

- 6.8.2.2.2. If these criteria are not maintained, the PM will announce the deviation using the “XXXX” Format (Example: “15 fast”) and the PF will take immediate corrective action. **(T-2)**
- 6.8.2.3. At 500 feet HAT:
- 6.8.2.3.1. Parameters are the same as those in **paragraph 6.8.1**. If accomplishing a VFR or circling approach, aircraft must meet all parameters in **paragraph 6.8.1** and also be in a safe position to land.
- 6.8.2.3.2. If criteria are met, PM will state “500, stable.”
- 6.8.2.3.3. If unstable or not in final flap configuration at 500 feet HAT, the PM will call “Go around” and the PF will execute a go-around. **(T-2)**
- 6.8.2.4. From 500 feet HAT to the runway, if these parameters are exceeded the PM or any other crewmember will announce “Go around” and the PF will execute a go-around. **(T-2)**
- 6.8.3. Descent Planning and Energy Management. Awareness of maneuver entry parameters and energy management is crucial to meeting the stabilized approach criteria on every approach. Aircrews will ensure the aircraft is following the planned descent profile. All non-tactical descents should follow a normal descent profile IAW AFMAN 11-202V3 procedures and techniques in the absence of ATC or FLIP guidance. All tactical descents should follow published tactical procedures/profiles. When unforeseen interruptions alter the planned descent, immediately correct any deviations. It may be necessary to hold, request vectors, or take alternate actions in order to comply with the planned descent profile.
- 6.8.4. Visual Transition. It is imperative for aircrews to review the airfield environment. Identify key features such as approach light type, airfield lighting, geographic layout/configuration of runways, taxiways, and/or ramps to the max extent possible. This study will take place during the crew mission briefing and reviewed again prior to descent. **(T-2)**
- 6.8.5. Missed Approach/Go-Around. Aircrews will conduct a thorough briefing for anticipated missed approach/go-around scenarios. **(T-2)** This briefing will include a discussion of specific crewmember duties. **(T-2)** **Note:** Execute missed approach/go-around IAW the Flight Manual and AFMAN 11-202V3 procedures.
- 6.8.6. Aviation Safety Action Program (ASAP). ASAP is an identity-protected, self-reporting system that is integral to reducing mishaps and improving operations and training. ASAP is designed for Airmen to report information and concepts critical to resolving mishap precursors and to share this information across AF aviation communities. The information is used to reduce mishaps through operational, logistic, maintenance, training, and procedural enhancements.
- 6.8.7. Data generated from the ASAP process is not used for monitoring personnel performance or to initiate punitive or adverse action. Violations of the Uniform Code of Military Justice (UCMJ) or criminal statute should not be reported via ASAP. Aircrews reporting incidents involving personal injury and/or aircraft damage should contact unit or local safety offices for appropriate guidance. The ASAP Report Submission, Fatigue Submission, and ASAP Scoreboard websites are accessible at <https://afsas.safety.af.mil/>.

Chapter 7 (Added-18WG)

E-3 LOCAL OPERATING PROCEDURES

7.1. (Added-18WG) General. This supplement is not intended to be a single source document for procedures contained in other directives and instruction.

7.1.1. (Added-18WG) Deviations and Waivers. The procedures and requirements contained in this supplement will not be waived or altered unless approved by the 18th Operations Group Commander (18 OG/CC) or designated representative. Do not deviate from the policies and guidance in this publication under normal circumstances, except for safety, or when it is necessary to protect the crew or aircraft from a situation not covered by this publication and immediate action is required. The aircraft commander has ultimate authority and responsibility for the course of action to be taken. All deviations or exceptions without a waiver will be reported through proper channels to 961 AACS/DO.

7.1.2. (Added-18WG) Squadron Aviation Resource Management (SARM) Responsibilities.

7.1.2.1. (Added-18WG) The SARM will process flight order requests and prepare the flight training review documents for AC/SLIC review prior to scheduled mission planning. The SARM will:

7.1.2.1.1. (Added-18WG) Prepare a Go/No-Go and load list and have them available no later than 1 hour prior to the initial mission planning meeting.

7.1.2.1.2. (Added-18WG) Complete the flight authorization and have it available for AC/SLIC review prior to the final mission planning meeting.

7.1.2.2. (Added-18WG) The SARM will prepare, maintain, and store mission forms kits.

7.1.2.3. (Added-18WG) The SARM will maintain, Duties Not to Include Flying (DNIF) roster, and the squadron's Go/No-Go roster. SARM will run a complete squadron Go/No-Go at the end of each week. These reports will be located in a central location and easily viewable by all crew members for late additions.

7.1.2.4. (Added-18WG) Mission Execution Folder. The SARM will assemble the mission execution folder. The folder will contain at a minimum one copy of the following:

7.1.2.4.1. (Added-18WG) AC/SLIC Form Review Checklist.

7.1.2.4.2. (Added-18WG) Flight Authorization Request (load list).

7.1.2.4.3. (Added-18WG) Go/No-Go review.

7.1.2.4.4. (Added-18WG) Operational Risk Management (ORM) Worksheet.

7.1.2.4.5. (Added-18WG) Air Force Technical Order (AFTO) Form 781, *Arms Aircrew/Mission Flight Data Document*, and Department of Defense (DD) Form 2131, *Passenger Manifest*.

7.1.2.4.6. (Added-18WG) Mission Accomplishment Report (MAR).

7.1.2.5. **(Added-18WG)** Visiting Aircrew Members. Individuals not assigned or attached to the 961 AACCS desiring a flight on an E-3 will comply with DAFMAN 11-401. Individuals assigned to other E-3 units will comply with AFMAN11-202V2_PACAFSUP_18OGSUP, *Aircrew Standardization/Evaluation Program*, Attachment 13, and applicable inter-fly agreements.

7.1.2.5.1. **(Added-18WG)** As authorized by DAFMAN 11-401 and all subordinate supplements, authorized personnel may fly on the E-3 in Mission Essential Personnel (MEP) status. All requests will be coordinated with the AC/SLIC to determine impact on planned training events and must be approved by the 961 AACCS/DO. Assistant Directors of Operations (ADOs) will draft a memo for record requesting MEP status and coordinate with 18 OG/CC or designated representative for approval. Verbal approval is allowed if time is critical.

7.1.3. **(Added-18WG)** Go/No-Go Program. Procedures for the conduct of the Go/No-Go program will include the following:

7.1.3.1. **(Added-18WG)** Aircrew Responsibilities. Crew members will review Flight Crew Information File (FCIF) Volumes I and V and certify knowledge through Patriot Excalibur (PEX). During mission planning, aircrew will initial the sortie detail report to certify that their personal information is correct. On the day of the flight, aircrew will sign in on the flight authorization in pen which confirms one's personal information is correct, knowledge of all FCIFs, all required flight publications are posted, and flying equipment requirements are met IAW [Attachment 7](#) and [Attachment 8](#). Individual ORM score will also be annotated on the Flight Authentication (FA).

7.1.3.1.1. **(Added-18WG)** Aircrew and SARM will comply with requirements outlined in the 961 AACCS Squadron Commander's Go/No-Go Policy letter.

7.1.3.2. **(Added-18WG)** FCIF Procedures While Deployed. When deployed, the AC/SLIC will ensure that paper or electronic versions of the current FCIFs are available to all crew members during mission planning and prior to flight. PEX will be the primary means for verifying that the FCIFs are current. When FCIFs are unavailable for review, the detachment commander (DETCO)/AC may be briefed via telephone, internet or fax to pass the information to the crew. If FCIFs are published the day of the flight, the AC will brief the crew prior to stepping to the aircraft.

7.1.4. **(Added-18WG)** Aircrew DNIF Responsibilities.

7.1.4.1. **(Added-18WG)** Aircrew members will notify their flight commander immediately after being placed on DNIF status. If a qualified crew member on cocking crew duty is placed on DNIF status, a written statement from the flight surgeon must be on the DD Form 2992, *Medical Recommendation for Flying or Special Operational Duty*, clearing the individual to perform these non-flying duties. Aircrew members will report to the flight surgeon no later than the morning of the duty day following the end of the DNIF period for medical evaluation. Crew members will verify the SARM has received their DD

Form 2992, *Medical Recommendation for Flying or Special Operational Duty*, from Aeromedical Services Information Management System (ASIMS), extending their DNIF or returning them to flight status. Crew members placed on DNIF status after mission planning or while in crew rest will immediately notify the AC/SLIC unless the AC and SLIC are in crew rest. In this event, the crew member will notify the SQ/DO or ADO.

7.1.5. (Added-18WG) Personal Equipment.

7.1.5.1. **(Added-18WG) Flying Clothing/Equipment.** All aircrew will wear or carry the minimum clothing requirements as outlined in [Attachment 6](#).

7.1.6. (Added-18WG) Unit Publications.

7.1.6.1. **(Added-18WG)** Applicable publications will be available through the FCIF library, individual issue, or from electronic sources (e.g. EFBs).

7.2. (Added-18WG) Aircrew Operating Procedures.

7.2.1. **(Added-18WG) Crew Manning.** A basic crew is comprised of an AC, CP, FE, ARO, ADST, SLIC, one SL, four ABMs, DLO, two MSOs, and an Airborne Radar Technician (ART). Changes to crew loads will be according to mission needs and approved by the SQ/DO/CC.

7.2.2. **(Added-18WG) Minimum Turn Time.** Do not plan consecutive sorties with the same aircrew, with less than 16 hours turn time from landing to subsequent takeoff, unless required to meet mission tasking and approved by the CC, or DETCO. If an individual flies three consecutive sorties with less than 16 hours turn time, they will be given at least 36 hours off prior to their next takeoff. If mission requirements necessitate less than 36 hours time off, CC, or DETCO approval is required.

7.2.3. **(Added-18WG) Command and Control.** The 961 AACS exercises command and control of E-3 resources through the 18th Wing Command Post (call sign “Keystone”) in conjunction with Squadron Operations (call sign “Fireside”).

7.2.3.1. **(Added-18WG) OPCON.** The Commander, Pacific Air Forces (COMPACAF) exercises OPCON directly over PACAF wings (i.e., not through the NAFs). Therefore, COMPACAF has OPCON of PACAF-assigned E-3s. All PACAF-assigned E-3s will be tactically controlled (TACON) to COMPACAF unless specified differently below.

7.2.3.1.1. **(Added-18WG) E-3s participating in Joint Theater Intelligence/Surveillance/Reconnaissance (ISR) missions** will be OPCON to 613 Air Operations Center (AOC).

7.2.3.1.2. **(Added-18WG) E-3s operating inside the Korean theater during armistice/Korean Theater Air Control System (KTACS) missions** are TACON to 7 AF/CC and remain OPCON to COMPACAF. All PACAF-assigned E-3s operating outside of Korea remain TACON to COMPACAF.

7.2.3.2. **(Added-18WG) OPCON Transfer.** When OPCON is transferred to another command, all crew members are responsible for reviewing the applicable host unit read files, FCIFs, etc. Conflicts between host unit and home unit guidance should be identified to the DETCO or applicable OG/CC. If the conflict cannot be resolved, follow the most restrictive guidance that ensures flight safety.

7.3. (Added-18WG) Flight Crew Operating Procedures.

7.3.1. (Added-18WG) Kadena AB Fuel Requirements.

7.3.1.1. (Added-18WG) “Off-island Bingo” – fuel required to arrive at the Kadena AB Initial Approach Fix (IAF) with the minimum amount of fuel to fly one approach, accomplish a missed approach, and arrive overhead at a suitable weather alternate IAW AFMAN 11-202, Volume 3, General Flight Rules, with 18,000 lbs of fuel. Flight crews will compute Off-Island Bingo on all sorties and a weather check will be accomplished within 1-hour of reaching Off-Island Bingo. If the weather at Kadena does not require an alternate and the current/forecast crosswinds are within limits, crews may use On-Island bingo requirements. When an alternate is required, ACs will notify the Operations Supervisor of the planned alternate in use. This may be accomplished during the Operations Supervisor briefing completed before flight. The AC is responsible for alternate selection; primary Off-Island alternates are MCAS Iwakuni, Osan AB, Yokota AB, Misawa AB, and Andersen AFB.

7.3.1.2. (Added-18WG) “On-island Bingo” – Aircrews will arrive at the Kadena AB IAF with a minimum of 24,000 lbs of fuel. This provides 30 minutes of holding fuel prior to required divert to Marine Corps Air Station (MCAS) Futenma (primary) or Naha AB (secondary). When the VFR pattern is open, runway is dry, and cross-winds are 15 knots or less, landing fuel may be reduced to 18,000 lbs. During Kadena AB single runway operations crews are required to arrive at the Kadena AB IAF with 33,000 lbs of fuel and landing fuel may be reduced to 28,000 lbs, if established in the VFR pattern. **Exception:** If MCAS Futenma and Naha AB runways are available crews may use standard on-island bingo, additionally if the VFR pattern is open, runway is dry, and cross-winds are 15 knots or less, landing fuel may be reduced to 21,000 lbs.

7.3.1.3. (Added-18WG) The Operations Supervisor must approve use of On-Island Bingo if an alternate is required IAW AFMAN 11-202, Volume 3, for Kadena AB. Use of MCAS Futenma or Naha AB as an alternate requires close coordination with 18 OSS weather shop.

7.3.1.4. (Added-18WG) Missed AAR Procedures. Missions will not normally be planned to utilize a missed AAR alternate (i.e., AAR will not normally be scheduled after bingo time). If there are extenuating circumstances that require the use of such an alternate, the AC will coordinate with the CC/DO or a designated representative (ADO/operations supervisor) the day prior to the mission. At a minimum, coordination will include selection of an appropriate alternate and notification procedures in the event of a missed AAR divert.

7.3.2. (Added-18WG) Pre-departure Procedures.

7.3.2.1. (Added-18WG) Filing Flight Plan. Flight plans will be sent to Kadena Base Operations not less than 1-hour and no more than 24 hours before departure. A flight crew member will contact Base Operations to verify receipt of flight plan.

7.3.2.2. (Added-18WG) Handheld Global Positioning System (GPS) Kits. The handheld GPS kits may be maintained as part of the aircraft installed life support equipment. The in-service GPS kits are not to be used for training/familiarization. Training GPS units are available for sign-out from Aircrew Flight Equipment.

7.3.2.3. **(Added-18WG)** DD Form 365-4, *Weight and Balance Clearance Form F – Transport/Tactical*. On flights originating from Kadena AB, the AC will sign DD Form 365-4 and give it to maintenance personnel before starting engines. For off-station sorties, the DD Form 365-4 may be filed at Base Operations together with DD Form 1801, *International Flight Plan, DoD*.

7.3.2.4. **(Added-18WG)** Downgrading a Red X for One-Time Flight. To clear the Red X on the AFTO Form 781A, *Maintenance Discrepancy and Work Document*, the owning MXG/CC or a representative designated to downgrade Red X conditions will enter in the corrective action block a statement as follows: “Red X changed to Red Dash for the purpose of one-time flight to (Destination Station),” and if applicable, “with en route stop at (name station).” If the MXG/CC or designated representative is not available to sign the “Inspected By” block, continue the corrective action statement: “One-time flight authorized by (Name, Rank, Title, Organization).”

7.3.2.4.1. **(Added-18WG)** Off-Station Downgrade. If the aircraft is located off station, the AC will contact the SQ/CC for coordination with home station MXG/CC or designated representative to obtain a faxed copy of written approval or verbal approval over the phone. The AC will then sign the “Inspected By” block and initial the “Symbol” block. In the next open block of the AFTO Form 781A, enter a Red Slash in the “Symbol” block and current date in the “Date Disc” block. In the “Discrepancy” block, enter the original discrepancy with a descriptive statement of temporary repair or inspection accomplished to make the aircraft airworthy for a one-time flight. Also, enter restrictions to normal flight operation of systems/equipment such as gear operation, pressurization, altitude, or airspeed limitations. Sign the “Discovered By” block (normally, the same person that downgraded the Red X).

7.3.3. **(Added-18WG)** Taxi Procedures.

7.3.3.1. **(Added-18WG)** Off-Station Procedures. At locations without E-3 taxi lines, ACs will brief a clear taxi plan with the crew chief prior to entering the aircraft. This discussion should focus on the initial turn direction, potential obstructions, and the location of the lead marshaller and wing walkers.

7.3.3.2. **(Added-18WG)** Clear Water Rinses (L-11 Rinse Facility). E-3 aircraft at Kadena will be clear water rinsed IAW T.O. 1-1-691, *Aircraft Weapons Systems -- Cleaning and Corrosion Control and Prevention Aerospace and Non-Aerospace equipment*. Crews will taxi through the L-11 Rinse Facility after every flight, provided it is open and no reason exists not to (e.g., bird strike, hydraulic/controlability malfunctions, etc.). Rinse facility operations are specified in Kadena AB Instruction 13-204, *Airfield Operating Instruction*.

7.3.3.2.1. **(Added-18WG)** Configuration/Taxi Procedures. Accomplish normal after-landing checklist items EXCEPT do not shut down any operating engine or start the APU until the aircraft is through the Rinse Facility. When approaching the service apron, lower the flaps and raise the spoilers prior to entering in order to rinse the maximum amount of area. Turn off landing lights prior to entering the wash. Once completed, reconfigure flaps, spoilers, engines and APU IAW the After-Landing Checklist while taxiing to park.

7.3.4. (Added-18WG) On-Station Procedures.

7.3.4.1. (Added-18WG) Trans-Oceanic Flights & Flights outside NAVAID range.

7.3.4.1.1. (Added-18WG) The AC will accomplish a Gross Navigational Error (GNE) coast out/in fix and compute an equal time point (ETP). Additionally, an ETP will be calculated anytime the planned route of flight takes the E-3 more than 90 minutes away from a useable aerodrome, utilizing 3 Engine drift down altitude for ETP calculations.

7.3.4.1.2. (Added-18WG) Trans-oceanic flight will be defined as any flight where the E-3 will be out of NAVAID range for longer than 1 hour.

7.3.4.1.3. (Added-18WG) Crews will monitor ATC/Aeronautical Radio, Incorporated (ARINC) and VHF/UHF Guard frequencies at all times when on an oceanic clearance. It is advisable for crews to monitor VHF transoceanic common (123.45 MHz) as well.

7.3.5. (Added-18WG) AAR Procedures.

7.3.5.1. (Added-18WG) Local AAR Procedures. The following procedures are applicable to 18th Wing E-3s and all visiting E-3s air refueling with 909th Air Refueling Squadron (909 ARS) KC-135s in any local AAR track within 300nm of Kadena AB.

7.3.5.1.1. (Added-18WG) Emission Control (EMCON) Procedures. EMCON 2 will be standard for AAR operations in the local area. Deviations must be coordinated and approved by aircrews and controllers and be in compliance with Section 8 of the T.O. 1E-3G(II)-1, and Allied Tactical Publication (ATP)-3.3.4.2, *Air to Air Refueling Manual*.

7.3.5.1.2. (Added-18WG) Opportune AAR Coordination. E-3 aircrews desiring opportune AAR will contact the operations supervisor for tanker availability.

7.3.5.2. (Added-18WG) When an operational requirement exists as defined in AFMAN11- 202V3_PACAFSUP, crews are approved by the 18 OG/CC to use gross weights that restrict the aircraft to a 2.0G load limit. Crews will observe the appropriate reduced load limits in the “Gross Weight Limit Versus Altitude and Maneuvering Load Limits” figure in T.O. 1E-3G(II)-1, Section 5. Crews will also ensure that aircraft center of gravity limitations are observed.

7.3.5.3. (Added-18WG) Fuel On-Load Verification. FEs will verify fuel on load with the boom operator and log this amount in the AFTO Form 781H (Reverse), *Aerospace Vehicle Flight Status and Maintenance* [Servicing Data].

7.3.6. (Added-18WG) Diversion Instructions.

7.3.6.1. (Added-18WG) Should the aircraft need to divert for weather or safety reasons, the following apply:

7.3.6.1.1. **(Added-18WG)** The preferred divert bases for Kadena-based E-3s are MCAS Iwakuni, Osan AB, Yokota AB, Misawa AB, Andersen AFB, MCAS Futenma and Naha AB. MCAS Futenma will be used as a preferred divert base for sorties scheduled to recover at Kadena AB. Selection of an alternate airfield will be in accordance with AFMAN 11-202, Volume 3, and based on existing/forecasted weather conditions, airfield status and fuel on board (see [Attachment 12](#) and [Attachment 13](#)). These bases are only recommendations and do not preclude the pilot from selecting an alternate location coordinated with the Operations Supervisor or Squadron DO.

7.3.6.1.2. **(Added-18WG)** After landing, the AC/SLIC will contact the 18th Wing Command Post (DSN 315-634-1800) and provide takeoff and landing times, durations, and any other information. If unable to contact the 18th Wing Command Post, contact the 5 AF Command Post (DSN 315-225-2536/9905). During normal duty hours (or as directed by the Ops Sup), information should be passed to the CC/DO/operations supervisor.

7.3.7. **(Added-18WG)** Pattern Training and Procedures.

7.3.7.1. **(Added-18WG)** Non-Kadena Transition. Per AFMAN11-202V3_PACAFSUP, the unit OG/CC will establish the boundaries of the local flying area and definition of local training versus off-station sorties. Approval authority for cross country/off-station training is the OG/CC. The following airfields are normally used for transition training for E-3 operations and are considered the local flying area: Kadena AB, Osan AB, Yokota AB, Kunsan AB, Misawa AB, Iwakuni AB, Elmendorf AFB and Andersen AFB. SQ/CC, DO, DETCO or Operations Supervisor will be notified of non-home station transition training.

7.3.8. **(Added-18WG)** Ops Stops and Engine Running Crew Changes (ERCC). ERCCs will be coordinated and published in the weekly flying schedule. Both will be considered one sortie for maintenance through-flight purposes. Two sorties will be logged on the AFTO Form 781 IAW DAFMAN 11-401, *Aviation Management*. Crews will follow the Memorandum of Agreement between the 961 AACS and 718 AMXS concerning ERCCs. The primary purpose of an ERCC is to allow weapons to de-plane to make fighter debrief and allow flight deck to continue local transition training.

7.3.8.1. **(Added-18WG)** Airborne crew will notify 961 AACS squadron operations of maintenance status and VIP transportation requirements. The operations supervisor will notify the 961 AMU Production Superintendent no later than 30 minutes prior to aircraft's arrival.

7.3.8.2. **(Added-18WG)** If the aircraft is code 3, the operations supervisor will coordinate with the 961 AMU leadership and 961/DO for a decision on whether to continue or cancel the ERCC.

7.3.9. **(Added-18WG)** RCR 15 Guidance.

7.3.9.1. **(Added-18WG)** SQ/CC or SQ/DO approval is required. If SQ/CC or SQ/DO is not an experienced AC, they will coordinate with the designated Technical Representative (IP, experienced AC, or IFE). Prior to approval, crews will coordinate with the Operations Supervisor to verify current field conditions. Aircrew coordinate requests through the DETCO when deployed. RCR 15 data should only be used for crosswinds.

7.3.9.2. **(Added-18WG)** Off-station. ACs will obtain a Runway Friction Characteristics Evaluation report from the airfield's GIANT report attachments, or coordinate with airfield operations to obtain the latest runway friction report to confirm the runway meets T.O. 1E-3G(II)-1-1, *Performance Manual, USAF Series E-3G Aircraft (with DRAGON)*, requirements.

7.3.10. **(Added-18WG)** Bird Strikes.

7.3.10.1. **(Added-18WG)** Aircrews will refer to Kadena Air Base Plan 91-212 in the event of a bird strike. Following a suspected bird strike, do not use rinse facilities so safety and maintenance personnel can examine the remains. Crews will file an 18 WG Form 82, *18th Wing Aviation Incident Initial Report*, after landing.

7.3.11. **(Added-18WG)** In-flight Emergencies.

7.3.11.1. **(Added-18WG)** Single Source Coordination. All ground support should be channeled through one individual, usually the Operations Supervisor or Tech Rep, to minimize confusion and multiple source inputs during a critical phase of flight/emergency. Once the in-flight emergency (IFE) aircraft is in the terminal area, only the Tech Rep and IFE crew should transmit on the IFE frequency. Other supervisors should not transmit on the IFE frequency unless the transmission is required to prevent a mishap. Any and all assistance should be provided as requested by the aircrew and Tech Rep only.

7.3.11.2. **(Added-18WG)** Fuel Jettison. Fuel dumping will be conducted IAW Kadena AB Instruction 13-204. E-3 aircrews will jettison fuel between the KAD 120 and 170 radials, from 30-50 DME. Altitude: As high as practical, but at least 5,000 feet AGL. Advise ATC of intentions, altitude and location prior to and upon completion of fuel dump. Naha approach may not be familiar with Kadena local fuel dump location.

7.3.11.3. **(Added-18WG)** Immediate Landing Directed. If the aircraft is directed to land immediately, ensure the directions are clearly understood between the Operations Supervisor and the AC. The fuel jettison criteria in Kadena AB Instruction 13-204 must be met. If the criteria cannot be met, the AC should use other means of reducing gross weight.

7.3.11.4. **(Added-18WG)** Alternate Manual Landing Gear Extension Procedures. The FE will annotate in red ink that the nose gear down lock pin is installed in the AFTO Form 781A. During the maintenance debrief, the AC will ensure maintenance personnel are aware the procedure was performed.

7.3.11.5. **(Added-18WG)** Post Emergency Requirements. An in-flight or ground emergency, air abort for aircraft system malfunction, dropped object, or any high mishap potential incident must be reported to the 961 AACS Safety Office (961 AACS/SE) within 24 hours of the incident. The AC will fill out 18 WG Form 82, *18th Wing Aviation Incident Initial Report*, and e-mail (preferred) or fax a copy to the 18 WG/SE, and 961 AACS/CC/DO/SE as soon as practical after landing. When operating at an off- island location, notify the host base safety office as well.

7.3.12. **(Added-18WG)** Pilot Weather Categories.

7.3.12.1. **(Added-18WG)** Category A (Tier I). ACs who have been certified by their squadron commander may fly approaches to published minimums or 200 feet height above touchdown (HAT) and 1/2 mile visibility, whichever is greater. This certification will be posted in the member's training folder.

7.3.12.2. **(Added-18WG)** Category B (Tier II). ACs who do not meet Category A (Tier I) criteria may fly approaches to published minimums or 300 feet HAT/height above aerodrome (HAA) and one mile visibility, whichever is greater. Category B (Tier II) minimums can be waived to Category A (Tier I) minimums by the 18 OG/CC/CD or the appropriate OG/CC/CD when OPGON has been given to another command.

7.3.13. **(Added-18WG)** E-3 flight operations under Due Regard.

7.3.13.1. **(Added-18WG)** Military operational situations may not lend themselves to ICAO flight procedures; e.g., military contingencies, classified missions, politically sensitive missions, and some training activities. Flight under "due regard" or "operational" conditions obligates the AC to act as his/her own air traffic control and to separate his/her aircraft from all other air traffic. There must be "due regard for the safety of navigation of civil aircraft" when flight is not being conducted under ICAO flight procedures.

7.3.13.2. **(Added-18WG)** E-3 Due Regard Special Instructions.

7.3.13.2.1. **(Added-18WG)** AC will ensure route of flight does not activate commercial airline TCAS TA/RA. If the tactical situation permits, the AC will ensure TCAS is operational with Mode 3A and 3C on within 20 nm of an active air route. AC will maintain 10nm lateral spacing or 3k' vertical spacing from airline traffic. AC will maintain visual with traffic if weather conditions permit. Caution should be given as airliners may climb or descend without warning. AC will ensure flight deck monitors applicable sector ATC frequency and UHF/VHF guard.

7.3.13.2.2. **(Added-18WG)** SLIC (assisted by SL/ABM if able) will ensure there is no conflicting airline traffic. SLIC will ensure vectors are given to the AC to maintain 10nm lateral spacing or 3K' vertical spacing from airline traffic.

7.4. **(Added-18WG)** Mission Crew Operating Procedures.

7.4.1. **(Added-18WG)** Pre-departure Procedures.

7.4.1.1. **(Added-18WG)** Liquid Cooling System (LCS) Resistivity Procedures. If inlet resistivity level below 3 MΩ/cm is encountered during the ART's preflight, the ART is required to perform the Ethylene Glycol and Water (EGW) Resistivity Check procedure in T.O. 1E-3G-43-1-1, *Flight Manual, USAF Series, E-3G Aircraft Mission Systems Operations*. If the inlet resistivity level remains below 3 MΩ/cm after performing the procedure, the ART will then request an Environmental Control System (ECS) technician to evaluate the LCS. After the technician has validated the resistive level, the following guidance will be adhered to:

7.4.1.1.1. **(Added-18WG)** For an LCS resistive level between 1.5 and 3.0 MΩ/cm, the ART will coordinate with the SLIC, FE, and ECS technician to collectively decide whether to accept the aircraft for out-and-back sorties. The resistive filter will be changed prior to departure for TDYs and deployments.

7.4.1.1.2. **(Added-18WG)** LCS EGW Leak Procedures. For an LCS resistive level less than or equal to 1.5 MΩ/cm, the filters will be changed and the resistive level will be verified. EGW Leak Procedures are outlined in T.O. 1E-3G-43-1-1 for abnormal conditions. The ART will contact the FE and maintenance if an EGW leak is found during preflight. There is no tolerance for an EGW leak. Maintenance will ground the aircraft until the leak is corrected.

7.4.1.2. **(Added-18WG)** Supplemental Oxygen Considerations.

7.4.1.2.1. **(Added-18WG)** MA-1 Portable Oxygen Bottle.

7.4.1.2.1.1. **(Added-18WG)** Aircraft will normally have a minimum of 10 fast-filling MA-1 portable oxygen bottles on board. Prior to accepting an aircraft with less than 10 fast-filling oxygen bottles, the AC and SLIC will assess the operational/safety impact based on crew makeup and mission profile (i.e. P- Sortie, over water, number of personnel on board). Aircrew members will be able to differentiate between slow and fast fill oxygen bottles. Fast-fill bottles will be prioritized for firefighter and runner duties (on firefighter masks including those in the lower lobes and above seats 9, 12, 15 and 22).

7.4.1.2.1.2. **(Added-18WG)** When more than 10 fast-fill bottles are on-board, the AC/SLIC will determine the location of the additional bottles. These bottles should be readily accessible to a runner looking for an extra bottle.

7.4.1.2.2. **(Added-18WG)** Emergency Personal Oxygen System (EPOS).

7.4.1.2.2.1. **(Added-18WG)** Prior to flight, the AC/SLIC will ensure that one EPOS is distributed to each crew member sitting in seats not equipped with system oxygen while performing duties away from their assigned seat. Passengers should be distributed one EPOS when sitting in seats not equipped with system oxygen.

7.4.1.2.2.2. **(Added-18WG)** The EPOS will not be used during a simulated emergency.

7.4.1.2.2.3. **(Added-18WG)** Suggested Liquid Oxygen Quantity (LOX). Pilot proficiency sorties should be serviced to a minimum of 45 liters. Deploying/Tailswap aircraft should be serviced to a full system or 75 liters. All mission/HHQ sorties should be serviced to a minimum of 55 liters of LOX. Any requests for additional LOX above this amount will be made to the 718 AMXS/Production Supervisor during the fuel request the day prior to flight. If aircrew show at an aircraft that is serviced with less than the suggested totals, the AC will assess the LOX requirements based on the mission profile prior to accepting the aircraft for flight. FEs should contact the squadron's operations desk as soon as practical after discovering an under-serviced LOX tank to determine the AC's intentions.

7.4.2. **(Added-18WG)** The comm cords at seats 6 and 7 will be at least 30 feet in length, seats 11, 17, and 24 will be minimum 12 feet in length, and seat 25 will be at least 50 feet in length (if mission requires, deviations from these lengths may be made at the SLIC's discretion as long as it does not impact firefighter duties and crew safety). Comm cords will be marked as follows to identify the various lengths: 12 foot cords are banded with a blue band; 30 foot cords are banded with a yellow band; 50 foot cords are banded with a red band. These special length comm cords will not be moved or removed from their assigned position unless inoperable. If inoperable, an AFTO Form 781 entry will be made to inform maintenance where the inoperable cord is located.

7.4.3. **(Added-18WG)** To the maximum extent on all mission sorties, crews will utilize Mardam-Bey Internet Relay Chat (MIRC) for AOC coordination, crew proficiency, and to maintain technical expertise.

7.4.3.1. **(Added-18WG)** SLs will be the primary MIRC monitor and maintain situational awareness in the relevant Pacific Command (PACOM) threat awareness windows.

7.4.4. **(Added-18WG)** Aircraft Cleanup Procedures. SLIC will designate crewmembers to clean the galley and collect all trash before leaving the aircraft.

CHARLES S. CORCORAN,
Maj Gen, USAF
Acting DCS, Operations

(18WG)

JOHN B. GALLEMORE
Brigadier General, USAF
Commander, 18th Wing

Attachment 1**GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION*****References***

- (Added-18WG)** ACCR 525-4 (S), *UNC/CFC Armistice ROE (U)*, 30 Sep 1999
- (Added-18WG)** ACCR 55-20 (S), *Theater Air Control and Employment Procedures (U)*, 14 September 2009
- (Added-18WG)** ACCR 55-3 (S), *ID and IFF/SIF Procedures (U)*, 1 July 2005
- (Added-18WG)** ACCR 55-9 (U), *Procedures for Use of Training Areas*, 1 July 2017
- ACP 121, *Communications Instructions – General*, October 2010
- AFH 11-203V1, *Weather for Aircrews*, 12 January 2012
- AFH 11-203V2, *Weather for Aircrews-Products and Services*, 13 August 2015
- AFI 11-200, *Aircrew Training, Standardization/Evaluation, and General Operations Structure*, 3 May 2022
- AFI 11-214, *Air Operations Rules and Procedures*, 8 July 2020
- AFI 11-215, *Flight Manuals Program*, 25 March 2019
- AFI 11-301V1, *Aircrew Flight Equipment (AFE) Program*, 10 October 2017
- AFI 90-802, *Risk Management*, 1 April 2019
- AFI 33-322, *Records Management and Information Governance Program*, 23 March 2020
- AFI 48-127, *Occupational Noise and Hearing Conservation Program*, 26 February 2016
- AFI 65-503, *US Air Force Cost and Planning Factors*, 13 July 2018
- AFMAN 11-202V3, *Flight Operations*, 10 January 2022
- AFMAN 11-290, *Cockpit/Crew Resource Management and Threat & Error Management Program*, 25 October 2021
- AFMAN 11-2E-3GV1, *E-3 Aircrew Training*, [Pending Publication]
- AFMAN 11-2E-3GV2, *E-3 Aircrew Evaluation Criteria*, [Pending Publication]
- (Added-18WG)** AFMAN11-202V2_PACAFSUP_18OGSUP, *Aircrew Standardization/Evaluation Program*, 22 November 2019
- (Added-18WG)** AFMAN11-202V3_PACAFSUP, *Flight Operations*, 31 August 2023
- (Added-18WG)** AFMAN11-214, *Air Operations Rules and Procedures*, 29 November 2022
- (Added-18WG)** AFMAN11-301, *Aircrew Flight Equipment (AFE)*, 23 September 2025
- AFPAM 11-216, *Air Navigation*, 1 March 2001
- AFPD 11-2, *Aircrew Operations*, 31 January 2019
- AFPD 11-4, *Aviation Service*, 12 April 2019

AFTTP 3-1.AWACS, *Tactical Employment*, 16 August 2022

AFTTP 3-1.TACS, *Tactical Employment*, 19 November 2014

AFTTP 3-2.5, *Multi-Service Brevity Codes*, 01 Jul 2016

AFTTP 3-2.8, *Multi-Service Tactics, Techniques, and Procedures for Air Control Communication*, February 2020

AFTTP 3-3.AWACS, *Combat Aircraft Fundamentals*, 16 August 2022

AFTTP 3-3.IPE, *Integrated Planning and Employment*, 3 April 2020

ATP-3.3.4.2., *Air-to-Air Refueling*, ATP-56 Edition C Version 1, November 2013

DAFI 11-209, *Participation in Aerial Events*, 20 May 2021

DAFI 21-101, *Aircraft and Equipment Maintenance Management*, 16 January 2020

DAFI 31-101, *Integrated Defense (ID)*, 25 March 2020

DAFI 36-3802, *Force Support Readiness Programs*, 9 January 2019

DAFMAN 11-401, *Aviation Management*, 27 October 2020

DAFMAN 90-161, *Publishing Processes and Procedures*, 15 April 2022

DAFMAN 91-203, *Air Force Occupational Safety, Fire, and Health Standards*, 25 March 2022

FAA JO 7610.4, *Special Operations*, 15 August 2019

(Added-18WG) KADENAABI 13-204, *Airfield Operating Instruction*, 23 May 2024

(Added-18WG) T.O. 1-1-691, *Aircraft Weapons Systems -- Cleaning and Corrosion Control and Prevention Aerospace and Non-Aerospace equipment*, 17 December 2024

T.O. 1E-3A-1, *Flight Manual, USAF Series E-3B, E-3C, and E-3G Aircraft*, 1 February 2014

T.O. 1E-3A-1-1, *Performance Manual, USAF Series E-3B, E-3C, and E-3G Aircraft*, 1 November 2011

(Added-18WG) T.O. 1E-3A-2-7, *Ground Handling-Servicing and Airframe*, 9 December 2024

(Added-18WG) T.O. 1E-3A-2-7-5CL-1, *Refueling and DeFueling*, 15 May 2024

(Added-18WG) T.O. 1E-3A-5-2, *Loading Data, USAF Series E-3B, E-3C, and E-3G Aircraft*, 1 January 2020

T.O. 1E-3G(II)-1, *Flight Manual, USAF Series E-3G Aircraft (with DRAGON)*, [Pending Publication]

T.O. 1E-3A-2-7, *Ground Handling-Servicing and Airframe*, 15 August 2014

T.O. 1E-3A-2-7-5CL-1, *Refueling and DeFueling*, 15 July 2018

T.O. 1E-3A-43-1-1, *Flight Manual, USAF Series, E-3 Aircraft Mission Systems Operations*, 1 July 2009

T.O. 1E-3A-43-1-1-1, *Supplemental Flight Manual*, (15 December 2016)

T.O. 1E-3A-5-2, *Loading Data, USAF Series E-3B, E-3C, and E-3G Aircraft*, 8 July 2013

(Added-18WG) T.O. 1E-3G(II)-1-1, *Performance Manual, USAF Series E-3G Aircraft (with DRAGON)*, 1 May 2024

(Added-18WG) T.O. 1E-3G-43-1-1, *Flight Manual, USAF Series, E-3G Aircraft Mission Systems Operations*, 8 October 2024

(Added-18WG) T.O. 1E-3G-5-1, *Sample Basic Weight Checklists*, 19 January 2024

T.O. 42C-1-2, *Anti-icing, Deicing, and Defrosting of Parked Aircraft*, 11 May 2007

T.O. 00-25-172, *Ground Servicing of Aircraft and Static Grounding/Bonding*, 6 September 2019

Adopted Forms

(Added-18WG) 18 WG Form 82, *18th Wing Aviation Incident Initial Report*

(Added-18WG) 961 AACS Form 49, *Mission Summary*

AFTO Form 46, *Prepositioned Aircrew Flight Equipment*

(Added-18WG) AFTO Form 781, *Arms Aircrew/Mission Flight Data Document*

AFTO Form 781A, *Maintenance Discrepancy and Work Document*

AFTO Form 781H, *Aerospace Vehicle Flight Status and Maintenance*

DAF Form 847, *Recommendation for Change of Publication*

(Added-18WG) DD Form 1801, *International Flight Plan, DoD*

(Added-18WG) DD Form 2131, *Passenger Manifest*

(Added-18WG) DD Form 2992, *Medical Recommendation for Flying or Special Operational Duty*

DD Form 365-4, *Weight and Balance Clearance Form F-Transport/Tactical*

Abbreviations and Acronyms

AAR—Air-to-Air Refueling

(Added-18WG) AB—Air Base

ABM—Air Battle Manager

AC—Aircraft Commander

ACAS—Airborne Collision Avoidance System

ACARS—Aircraft Communications Addressing and Reporting System

ACC—Air Combat Command

(Added-18WG) ACCR—Air Component Command Regulation

ACE—Airborne Command Element

ACG—Air Control Group

ACP—Allied Communications Publications

ACW/XR—Air Control Wing Requirements

(Added-18WG) ADO—Assistant Director of Operations
ADST—Airborne Data Systems Technician
ADS-B—Automatic Dependent Surveillance–Broadcast
AFA—Air Force Academy
AFI—Air Force Instruction
AFMAN—Air Force Manual
AFPD—Air Force Policy Directive
AFRC—Air Force Reserve Command
AFROTC—Air Force Reserve Officer Training Corps
AFTO—Air Force Technical Order
AFPD—Air Force Policy Directive
AFSIRS—Air Force Spectrum Interference Reporting System
AGL—Above Ground Level
AHRS—Altitude and Heading Reference System
AIP—Aeronautical Information Publication
(Added-18WG) AIRADS—Airfield Advisories
(Added-18WG) AOC—Air Operations Center
AoHV—Areas of Higher Vulnerability
(Added-18WG) AOI—Area of Interest
AOR—Area of Responsibility
AOV—Area of Vulnerability
(Added-18WG) AR—Aerial Refueling
ARCP—AAR Control Point
ARCT—AAR Control Time
(Added-18WG) ARINC—Aeronautical Radio, Incorporated
ARIP—AAR Initial Point
ARMS—Aviation Resource Management System
ARO—Airborne Radio Operator
ART—Airborne Radar Technician
ARU—Airborne Radar Unit
ASAP—Aviation Safety Action Program
(Added-18WG) ASIMS—Aeromedical Services Information Management System

ASO—Active Sensor Operator

(Added-18WG) ASRR—Airfield Suitability Restrictions Report

ATC—Air Traffic Control

ATCAA—Air Traffic Control Assigned Airspace

ATM—Air Traffic Management

ATO—Air Tasking Order

ATP—Allied Technical Publication

APCH—Approach

APU—Auxiliary Power Unit

AWACS—Airborne Warning and Control System

A3—Director of Operations

A3T—Flight Operations

BDOC—Base Defense Operations Center

BMA—Battle Management Area

BMT—Battle Management Team

BRNAV—Basic Area Navigation

BTH—Beyond the Horizon

CAF—Combat Air Forces

CC—Commander

CCD—Crew Coordination Drill

CDU—Control Display Unit

CFG—Communications Functional Group

CG—Center of Gravity

CNS—Communications, Navigation, and Surveillance

(Added-18WG) COMPACAF—Commander, Pacific Air Forces

CONUS—Continental United States

CP—Copilot

CPDLC—Controller Pilot Data Link Communications

CRM/TEM—Crew Resource Management/Threat and Error Management

CSG—Computer Support Group

CVR—Cockpit Voice Recorder

C2—Command and Control

DA—Decision Altitude

DAFI—Department of the Air Force Instruction

DAFIF—Digital Aeronautical Flight Information File

DAFMAN—Department of the Air Force Manual

DCN—Datalink Coordination Net

DCT—DRAGON Conversion Training

DD—Department of Defense

DDI—Digital Display Indicator

DETCO—Detachment Commander

DH—Decision Height

DLO—Datalink Operator

DMA—DRAGON Modified Aircraft

(Added-18WG) DMZ—Demilitarized Zone

DND—Department of National Defense

(Added-18WG) DNIF—Duties Not to Include Flying

DO—Director of Operations

DRAGON—Diminishing Manufacturing Sources Replacement of Avionics for Global Operations and Navigation

DRU—Direct Reporting Unit

DV—Distinguished Visitor

EA—Electronic Attack

EAM—Emergency Action Messages

EC—Electronic Combat

(Added-18WG) ECN—En Route Change Notice

(Added-18WG) ECS—Environmental Control System

EFB—Electronic Flight Bag

EGI—Embedded GPS INU

EGPWS—Enhanced Ground Proximity Warning System

(Added-18WG) EGW—Ethylene Glycol and Water

(Added-18WG) ELINT—Electronic Intelligence

EMCON—Emissions Control

EOB—Electronic Order of Battle

EP—Electronic Protection

(Added-18WG) EPOS—Emergency Personal Oxygen System

EPR—Exhaust Pressure Ratio

(Added-18WG) ER—Exceptional Release

(Added-18WG) ERCC—Engine Running Crew Change

ES—Electronic Support

ESM—Electronic Support Measures

ESMG—Electronic Support Measures Group

EST—Electromagnetic Support Team

ETA—Estimated Time of Arrival

ETP—Equal Time Point

(Added-18WG) FA—Flight Authorization

FAA—Federal Aviation Administration

FAF—Final Approach Fix

FCIF—Flight Crew Information File

FCT—Flight Crew Training

FDAP—Flight Deck Audio Panel

FDP—Flight Duty Period

FE—Flight Engineer

(Added-18WG) FIH—Flight Information Handbook

FIR—Flight Information Region

FIT—Fault Isolation Test

FL—Flight Level

FLIP—Flight Information Publication

FM—Frequency Modulation

FMS—Flight Management System

FOA—Field Operating Agency

FP—First Pilot

FPM—Flight Path Management

fpm—Feet Per Minute

GINS—Global Positioning System Integrated Navigation System

GNE—Gross Navigational Errors

GP—General Planning (reference FLIP GP)

GPS—Global Positioning System
GP/CC—Group Commander
(Added-18WG) HAA—Height Above Aerodrome
HAT—Height Above Touchdown
HF—High Frequency
HHQ—Higher Headquarters
IA—Information Automation
(Added-18WG) IAF—Initial Approach Fix
IAW—In Accordance With
ICAO—International Civil Aviation Organization
ICN—Interface Control Network
ID—Identification or Integrated Defense
IERS—Initial Exchange Requirements
(Added-18WG) IFE—In-Flight Emergency
IFF—Identification, Friend, or Foe
IFR—Instrument Flight Rules
IMFD—Integrated Multi-Function Display
INS—Inertial Navigation System
INU—Inertial Navigation Unit
IP—Instructor Pilot (an “I” prefix designates an instructor in that crew position, e.g., IFE)
IPEC—Internet Protocol Enabled Communications
IQT—Initial Qualification Training
(Added-18WG) ISR—Intelligence/Surveillance/Reconnaissance
JAOP—Joint Air Operations Plan
JFACC—Joint Force Air Component Commander
JICC—Joint Information Coordination Center
JICO—Joint Interface Control Officer
JRA—Jeppesen™ Runway Analysis
JTIDS—Joint Tactical Information Distribution System
J/CFACC—Joint/Combined Forces Air Component Command
(Added-18WG) KTACS—Korean Theater Air Control
(Added-18WG) KTO—Korean Theater of Operations

LAT—Latitude

(Added-18WG) LCS—Liquid Cooling System

LNAV—Lateral Navigation

LOA—Letter of Agreement

(Added-18WG) LOB—Line of Bearing

LONG—Longitude

(Added-18WG) LOX—Liquid Oxygen

MAC—Mean Aerodynamic Chord

MAJCOM—Major Command

MAP—Missed Approach Point

(Added-18WG) MAR—Mission Accomplishment Report

MC—Mission Commander

(Added-18WG) MCAS—Marine Corps Air Station

(Added-18WG) MCRC—Master Control Reporting Center

MCS—Mission Computing System

MCT—Mission Crew Training

MDA—Minimum Descent Altitude

MDS—Mission Design Series

MEP—Mission Essential Personnel

MEL—Minimum Equipment List

MET—Mission End Time (AFRC only)

(Added-18WG) MIRC—Mardam Bey Internet Relay Chat

MOA—Military Operating Area

MPC—Mission Planning Cell

MPT—Mission Planning Team

MRU—Military Radar Unit

MSL—Mean Sea Level

MSO—Mission System Operator

MTO—Mission Type Order

NAT MNPS—North Atlantic Minimum Navigational Performance Specification

NAV—Navigator

NAS—National Airspace System

NCCM—NORAD Certified Crewmember
(Added-18WG) NLG—Nose Landing Gear
NM—Nautical Mile
NORAD—North American Aerospace Defense Command
NORTHCOM—Northern Command
(Added-18WG) NOTAMS—Notices to Airmen
NVG—Night
NWRO—NORAD Weapons Resource Officer
N/A—Not Applicable
OBS—On-Board Spare
OG—Operations Group
ONC—Operational Navigation Chart
OOM—Onboard/Offboard Media
OPCON—Operational Control
OPLAN—Operation Plan
OPORD—Operation Order
OPR—Office of Primary Responsibility
OPTASKLINK—Operational Tasking Data Link
ORM—Operational Risk Management
OSOE—Operations Group Exercises
PA—Public Address
(Added-18WG) PAA—Pacific, Australasia and Antarctica
PACAF—Pacific Air Forces
PAX—Passengers
PBN—Performance Based Navigation
(Added-18WG) PCN—Planning Change Notices
PDS—Passive Detection System
(Added-18WG) PEX—Patriot Excalibur
PF—Pilot Flying
PIC—Pilot in Command
PM—Pilot Monitoring
PSO—Passive Sensor Operator

QC—Quality Control

QRM—Quick Reaction Message

RAIM—Receiver Autonomous Integrity Monitoring

RCC—Runway Condition Code

RCR—Runway Condition Reading

RCAM—Runway Condition Assessment Matrix

RF—Radius to Fix

(Added-18WG) RFI—Radio Frequency Interference

RICC—Regional Interface Control Cell

RICO—Regional Interface Control Officer

RMA—Removable Media Assembly

RNAV—Random Area Navigation

RNP—Required Navigation Performance

ROE—Rules of Engagement

(Added-18WG) ROK—Republic of Korea

(Added-18WG) ROKAF—Republic of Korea Air Force

RP-1—Readiness Posture One

RP-3—Readiness Posture Three

RP-15—Readiness Posture Fifteen

RTO—Rejected Takeoff

RVSM—Reduced Vertical Separation Minimums

RwyCC—Runway Condition Code

R/T—Receive/Transmit

(Added-18WG) SARM—Squadron Aviation Resource Management

SDP—Special Departure Procedure

SIA—SIGINT ID Authority

SIC—Secure Iridium™ Communication

SICO—Sector Interface Control Officer

SIF—Selective Identification Feature

SL—Section Lead (as a member of the BMT construct)

SLIC—Section Lead in Command

SM—Statute Mile

SOP—Standard Operating Procedure
SPINS—Special Instructions
SQ/CC—Squadron Commander
SRT—Scheduled Return Time (AFRC only)
STAR—Standard Terminal Arrival Route
SUA—Special Use Airspace
TAB—Tabular Report
(Added-18WG) TACON—Tactical Control
TACOPDAT—Tactical Operational Data
TACAN—Tactical Air Navigation System
(Added-18WG) TACREP—Tactical Reports
TACS—Theater Air Control System
TADIL—Tactical Digital Information Link
TC—Transport Canada
TCAS—Traffic Collision Avoidance System
TCH/THRE/THR—Threshold Crossing Height
(Added-18WG) TCN—Terminal Change Notice
TDL—Tactical Data Link
TDY—Temporary Duty
TDZE—Touch Down Zone Elevation
TEM—Threat and Error Management
TM—Tactical Monitor
TNC—Transitional Networking Capability
T.O.—Technical Order
TOLD—Takeoff/Landing Data
TRT—Takeoff Rated Thrust
UAS—Undesired Aircraft States
UCMJ—Uniform Code of Military Justice
UHF—Ultra-High Frequency
VFR—Visual Flight Rules
VHF—Very High Frequency
VIP—Very Important Person

VNAV—Vertical Navigation

VMC—Visual Meteorological Conditions

(Added-18WG) VPN—Voice Product Net

VVM—Verbalize, Verify, and Monitor

WAAS—Wide Area Augmentation System

WG—Wing

Office Symbols

ACC/A3C—Air Combat Commands Command and Control, Intelligence, Surveillance and Reconnaissance Operations Division

ACC/A3CA—Air Combat Command Airborne Command and Control

ACC TRSS—Air Combat Command Training Support Squadron

ACC/A3TV—Air Combat Command Standardization and Evaluations Branch

AF/A3T—Air Force Training and Readiness Directorate

AFFSA/XOF—Air Force Flight Standards Agency/Flight Directives

AFRC/A3D—Air Force Reserve Command Combat Division

PACAF/A3T—PACAF Flight Operations

513 ACG/CC—513d Air Control Group Commander

552 OG/CC—552d Operations Group Commander

Terms

Air Battle Manager—Generic term to refer to any aircrew with the Air Force Specialty Code 13B.

Air Battle Manager (ABM)—An aircrew member that has graduated from formal training of the approved ‘Air Battle Manager Syllabus’.

Aircrew—Use this term to describe the complete complement of personnel required to fly an operational mission. It composes both the flight crew and the mission crew.

Active Sensor Operator—The member of the BMT that is operating the radar and IFF settings, executing ID processes, and managing datalink employment. Could be an ABM, ASO, or another crewmember that is qualified in the applicable areas from AFMAN 11-2E-3G Volume 2. *E-3 Aircrew Evaluation Criteria*.

Battle Management Team (BMT)—Subset of the mission crew responsible for conducting the BMC2 mission of the E-3 including battlespace awareness, battle management, and decision superiority. It consists of the Mission Commander (MC), Section Lead in Command (SLIC), Active Sensor Operator (ASO), Passive Sensor Operator (PSO), Air Battle Manager (ABM), and Mission System Operator (MSO). The composition of this team varies based on the mission.

Critical Phases of Flight—Critical phases of flight are takeoff, AAR, flight below 5,000 feet AGL, approach, landing, and any other maneuver listed in this manual requiring IP/Flight Examiner supervision.

Flight Crew—The flight crew is responsible for the safe ground and flight operations of the E-3 aircraft. It consists of an AC, FP or CP, NAV, and FE. For purposes of this manual, FCT personnel are considered flight crewmembers; however, contractor personnel will not occupy primary E-3 crew positions during critical phases of flight.

Group Commander (GP/CC)—For sorties under AFRC Operational Control (OPCON), the 970th Airborne Air Control Squadron Operations and Training (O and T) officer (or designated representative) acts as the applicable GP/CC.

Instructor/Flight Examiner Supervision—Instructor/Flight Examiner supervision requires an instructor/Flight Examiner who is qualified and current in the position and the maneuver that will be performed. Individuals not qualified or current in the aircraft, require instructor/Flight Examiner supervision for the activity in which they are unqualified or noncurrent. For unqualified or noncurrent Pilots, IP/Flight Examiner supervision requires the IP/Flight Examiner to be in one of the Pilots' seats with immediate access to the controls while the maneuver is being performed. For all other crewmembers, instructor/Flight Examiner supervision requires over-the-shoulder observation of the unqualified/non-current crewmember. During critical phases of flight, flight crew instructors/Flight Examiners are allowed to stand, all others will be at the discretion of the PIC.

Mission Crew—The mission crew consists of those individuals responsible for the C2, surveillance, communications/electronic, and management functions, to include the control and monitoring of assigned aircraft, sensor management, internal and external communications management for mission operations, and onboard systems maintenance. It consists of the BMT and the Technicians.

Mission End Time (MET)—(AFRC only) The scheduled day and time a flight crew is planned to return to home station from an exercise or deployment. The MET will be published in the monthly OPLAN, rotation schedule, flying schedule, and/or OPORD, as necessary. The MET is the baseline for computing SRT.

Mission System Operator (MSO)—An aircrew member that has graduated from formal training of the approved "Mission System Operator" syllabus.

NORAD Battle Staff—The battle staff assists the crew performing aerial operations within the NORAD AOR. The battle staff is responsible for managing the air battle and carrying out the required C2 functions. It has the responsibility and authority, as directed by the appropriate commander, to ensure the most effective use of assigned resources to accomplish the mission. The NCCM is an ACC/PACAF E-3 crewmember specifically trained to support the NORAD mission. Supported commanders may also provide a NORAD Airborne Battle Commander (NABC) and NORAD Weapons Resource Officer (NWRO). PACAF/AFRC E-3 crewmembers will be trained and certified by local procedures using a command-approved syllabus.

Passive Sensor Operator (PSO)—Member of the BMT that operates the PDS to provide full ES integration capability or may be another crewmember that is qualified to operate PDS in a limited capacity.

Section Lead (SL)—A generic term to refer to the leader of a section of the BMT broken down by BMA or function; could be an ASO, PSO or ABM.

Scheduled Return Time (SRT)—(AFRC only) A force management tool used by the on-scene commander to assure return of the Reserve associate personnel to home station before the expiration of their active-duty orders. The SRT is calculated MET plus 24 hours.

Technicians—Those crewmembers responsible for operation of special mission equipment on board the E-3 during flight. Includes the ADST, ART, and ARO.

Transition—Practice multiple takeoffs, simulated emergency patterns, low approaches and touch and go landings. Transition timing begins when the aircraft crosses the threshold on the first approach.

Weapons Controller—A member of the BMT that is qualified in the applicable areas to control aircraft.

Wing Commander—For sorties under AFRC OPCON the 513 ACG/CC (or designated representative) acts as the WG/CC.

Attachment 2

E-3 BAGGAGE AND EQUIPMENT LOADING

A2.1. Flight Engineer (FE) Responsibilities:

A2.1.1. Verify an AFTO Form 781A entry was made when On-Board Spare (OBS) kits are loaded.

A2.1.2. Ensure the removal of the forward two metal boxes of the OBS kits after arrival at a Temporary Duty (TDY) location, if the stay will be longer than 3 days.

A2.1.3. Ensure only enough cleaning supplies are stored in the galley compartment to clean the area for one mission. Store the remaining cleaning supplies and all onboard bench stock in the dedicated crew chief box in the aft lower lobe.

A2.2. Loading Procedures. The following loading procedures apply to all E-3 operations. For more specific guidelines, refer to the following T.O.s: 1E-3A-1, 1E-3A-5-1, 1E-3A-5-2, and 1E-3A-2-7.

A2.2.1. OBS Kits. An OBS kit consists of as many as five metal boxes and one fiberglass box containing an inertial navigation unit (INU). If maintenance requires OBS kits, install the five metal boxes in the forward lower lobe using the rail system described in T.O. 1E-3A-2-7. Any other method of securing the metal boxes in the forward lower lobe is not acceptable. Secure the INU in the “J” compartment with cargo straps. Weight of OBS kits vary. The actual weight is annotated on each box. The FE will verify the weights of each box and its location were annotated on the AFTO Form 781A. **(T-3)** For mission planning purposes, use the standard weight of 650 pounds in the forward lower lobe and 127 pounds in “J” compartment. Make adjustments on Department of Defense (DD) Form 365-4, *Weight and Balance Clearance Form F – Transport/Tactical*, as necessary. After arrival at a TDY location, if the stay will be longer than 3 days, remove at least the forward two metal OBS kit boxes from the aircraft to allow for better access to the area for firefighting, etc., if the location has a means of securing the kits.

A2.2.2. Technical Orders. Carry one case of T.O.s when an OBS kit is loaded. Store in the “J” compartment and secure with cargo straps.

A2.2.3. Toolbox:

A2.2.3.1. Secure the in-flight toolbox carried by the ARO/ART in the “J” compartment with cargo straps or forward luggage compartment.

A2.2.3.2. When a crew chief toolbox is required; secure it at the tie down point in the aft lower lobe or in “J” compartment with cargo straps.

A2.2.4. Crew Baggage. In order to facilitate loading, crewmembers and passengers (PAX) will maximize the use of soft luggage (e.g., issued B-4, A-3, and hang-up bags) for exercises and deployments. **(T-3)** Crewmembers should be aware that proper aircraft/loading requires strapping the load down tightly in order to prevent load shifting. Crewmembers are normally allowed a baggage limit of 25 pounds on short term TDYs (7 days or less) and 55 pounds on

longer deployments. However, if on mission planning day, weight appears to be critical, the AC and FE will determine the maximum allowable baggage weight and inform crewmembers and passengers of how much they will be allowed to carry. Baggage will be secured at a height no higher than 40 inches in “J” compartment. Small, carry-on type baggage may be stacked higher than 40 inches provided they are secured at or below 40 inches.

A2.2.5. Jackets and Garment Bags. Jackets and lightweight garment bags may be stored on the clothing rack next to the lavatory.

A2.2.6. SF6. Up to four additional SF6 bottles, empty or full, may be stored in the aft lower lobe. Bottles will be secured in the SF6 storage racks, if the aircraft is modified. If not modified, use cargo straps, and up to four small bottles can be stored.

A2.2.7. Removable Media Assembly (RMA)/Onboard/Offboard Media (OOM)/TNC/SIC/IPEC Kits. Store these kits in the area under the Digital Display Indicator (DDI) at seat 8 (E-3B/C) or in the luggage area or “J” compartment (E-3G).

A2.2.8. Additional Baggage/Equipment. “J” compartment loading will be accomplished IAW T.O. 1E-3A-5-2.

A2.2.9. General:

A2.2.9.1. Mission crewmembers should store professional gear (pubs/helmet bag) either in “J” compartment or at their individual consoles in a manner that will minimize movement of gear.

A2.2.9.2. Compartment weight limitations will be IAW T.O. 1E-3A-1.

A2.2.9.3. Crew bunks will only be used for storing pillows and blankets, which will be secured by seatbelts. Nothing will be stored beneath the bunks. Floor rings used to secure bunks to the floor will not be used for luggage/equipment tie down.

A2.2. (18WG) Loading Procedures. The following loading procedures apply to all E-3 operations. For more specific guidelines, refer to the following T.O.s: 1E-3G(II)-1, 1E-3G-5-1, *Sample Basic Weight Checklists*, 1E-3A-5-2, *Loading Data, USAF Series E-3B, E-3C, and E-3G Aircraft*, and 1E-3A-2-7, *Ground Handling-Servicing and Airframe*.

Attachment 3**E-3 PASSENGER BRIEFING GUIDE**

A3.1. Required Briefing Items. The following items are required briefing items unless individuals have been previously briefed during the pre-mission briefing:

- A3.1.1. AC/SLIC names. **(T-3)**
- A3.1.2. ETA to destination. **(T-3)**
- A3.1.3. Cruise altitudes. **(T-3)**
- A3.1.4. Weather enroute and at destination. **(T-3)**
- A3.1.5. Passenger on-/off-load procedures. **(T-3)**

A3.2. Emergency Signals:

- A3.2.1. Ground Evacuation: **(T-3)**
 - A3.2.1.1. Signal for evacuation. **(T-3)**
 - A3.2.1.2. Primary/secondary exits. **(T-3)**
 - A3.2.1.3. Escape slides. **(T-3)**
 - A3.2.1.4. Assembly area. **(T-3)**
- A3.2.2. Crash Landing/Ditching:
 - A3.2.2.1. Signal for preparation. **(T-3)**
 - A3.2.2.2. Signal to brace for impact. **(T-3)**
 - A3.2.2.3. Brace position. **(T-3)**
- A3.2.3. Loss of Pressure: **(T-3)**
 - A3.2.3.1. Signal. **(T-3)**
 - A3.2.3.2. Oxygen requirements. **(T-3)**

A3.3. Oxygen/Survival Equipment:

- A3.3.1. How to check/use assigned oxygen source. **(T-3)**
- A3.3.2. Life vest (LPU-10/P) fitting and use (if applicable). **(T-3)**
- A3.3.3. Survival suit use (if applicable). **(T-3)**

A3.4. Restrictions:

- A3.4.1. Reading lights. **(T-3)**
- A3.4.2. Lavatory. **(T-3)**
- A3.4.3. Seat belts. **(T-3)**
- A3.4.4. Bunks. **(T-3)**
- A3.4.5. Smoking, smokeless tobacco, and electronic cigarettes, are prohibited.

A3.4.6. Operation of electric/electronic devices (except non-smart watches, handheld non-print calculators, hearing aids, medically prescribed physiological instrumentation and portable voice recorders when approved by MAJCOM) will be IAW AFMAN 11-202 Volume 3. Electronic flash attachments will not be used.

A3.4.7. Transportation or use of narcotics, marijuana, or other dangerous drugs is prohibited unless approved by proper medical/legal authority.

A3.4.8. Explosive, flammable, and corrosive materials, or materials with toxic or irritating fumes are prohibited unless approved by competent authority.

A3.4.9. Alcohol consumption is prohibited.

A3.5. Galley Area:

A3.5.1. Restrictions during refueling.

A3.5.2. Oven use.

A3.5.3. Hot Plate.

A3.5.4. Water.

A3.5.5. Flight lunches.

A3.5.6. Noise.

A3.6. Miscellaneous:

A3.6.1. Follow E-3 crewmember instructions at all times.

A3.6.2. If passengers are onboard during the crew coordination drill, they will be briefed but will not participate.

Attachment 4 (Added-18WG)**KOREAN THEATER AIR CONTROL SYSTEM (KTACS) OPERATIONS**

A4.1. (Added-18WG) Purpose. This attachment establishes procedures and guidance for all KTACS sorties. TACON for E-3 operations within the Korean Theater is 7 AF. The E-3 receives mission tasking from “Keyboard,” the 7 AF command element (607 COS/DO). Key coordination agencies in the Korean Theater of Operations (KTO) include the 621 Air Control Squadron, call sign “Cobra” and the 303 Intelligence Squadron (303 IS).

A4.2. (Added-18WG) General.

A4.2.1. **(Added-18WG) Command and Control.** When activated, Keyboard will act as C2 for E-3 missions within the KTO. At all other times, the E-3 will maintain contact with Cobra. Crews should coordinate the day prior to determine Keyboard’s availability for training and connectivity drills.

A4.2.2. **(Added-18WG) KTACS Schedule.** The AC and SLIC will ensure the E-3 is correctly tasked on the Air Tasking Order (ATO), when required.

A4.2.3. **(Added-18WG) Tasking.** Crews will be familiar with Air Component Command Regulation (ACCR) 55-3 (S), *ID and IFF/SIF Procedures (U)*, ACCR 55-20 (S), *Theater Air Control and Employment Procedures (U)*, ACCR 525-4 (S), *UNC/CFC Armistice ROE (U)*, ACCR 55-9 (U), *Procedures for Use of Training Areas*, and weekly and quarterly SPINS. Appropriate KTACS specific briefings will be kept by SQ/DOW and briefed before mission execution.

A4.2.4. (Added-18WG) Aircrew Operating Procedures.

A4.2.4.1. **(Added-18WG) 37th Parallel Restrictions.** The following requirements must be met prior to operating north of the 37th parallel:

A4.2.4.1.1. **(Added-18WG)** The threat level must be confirmed via external sources as “low.”

A4.2.4.1.2. **(Added-18WG)** Flight and required mission systems must be operational.

A4.2.4.1.3. **(Added-18WG)** Training missions may be conducted from established KTACS airspaces with either radar or IFF alone, provided threat level is low and Cobra is on- station and notified of E-3 limiting factors (LIMFACS).

A4.2.4.1.4. **(Added-18WG)** Operational Reconnaissance Missions. O-9 credit will be awarded for KTACS missions IAW 18 Aug 2024 18 OG AAM MFR.

A4.2.4.2. **(Added-18WG) P-518 Restrictions.** Operations within 25 nm of P-518 and 50 nm of the demilitarized zone (DMZ) should be minimized to limit risk to the E-3. Operations within 10 nm of P-518 are restricted under normal circumstances.

A4.2.4.3. **(Added-18WG)** Peacetime operations within 25 nm of a prohibited area and 50 nm from a potentially hostile border will normally be limited to intervals of less than 1 hour.

A4.2.4.4. **(Added-18WG)** The operations supervisor will ensure any delays or cancellations are passed via secure means—when mission profile dictates—to the Korean Air Operations Center (KAO) Battlewatch Officer or Cobra.

A4.3. (Added-18WG) Flight Crew Operating Procedures.

A4.3.1. **(Added-18WG)** Flight Rules in Republic of Korea (ROK). Incheon Center is the controlling agency for all IFR traffic over the ROK. The AC will coordinate all orbit requests, and transit between orbit, and air refueling airspace with Incheon Control.

A4.3.2. **(Added-18WG)** Cobra Coordination. The flight deck will check in with Cobra Control when operations are planned for ROK special use airspaces. Cobra should provide the status of “Hot Areas” (Surface-to-Surface or Surface-to-Air Fire in special use airspace), “Active Areas” (aircraft operations in special use airspace), and any other activity that will impact E-3 flight operations.

A4.3.2.1. **(Added-18WG)** The E-3 will squawk Mode 1 IAW ACCR 55-3, Attachment 1.

A4.3.2.2. **(Added-18WG)** The E-3 will squawk Mode 2 IAW ACCR 55-3, Attachment 2.

A4.3.3. **(Added-18WG)** Mission Changes. All changes to operational missions, to include AAR, will be coordinated through C2. Training missions can be adjusted as required without HHQ; however timings must be coordinated with Cobra to ensure airspace availability and address potential impact to other aircraft.

A4.3.4. **(Added-18WG)** Orbit considerations. File a mixed IFR/VFR flight plan (DD Form 1801 code “Y”) and report “direct (assigned) MOA” at the IFR termination point to Incheon Center. Entry into training airspaces should be made via named entry/exit points defined in ACCR 55-9, Attachment 9.

A4.3.4.1. **(Added-18WG)** Central Complex. The Central Complex consists of MOAs 2/3/15/27N/27S and should normally be utilized for AWACS orbits during training missions. Recommended entry and exit gate is “CLOSE”. When the Central Complex is utilized, a 12NM racetrack orbit with lobe points NW (3612N 12724E) and SE (3533N 12755E) is recommended.

A4.3.4.2. **(Added-18WG)** Other Training Orbits. Other orbit locations are applicable via the training use areas in ACCR 55-9. Coordination between the AC and SLIC is essential to assuring that the MOAs E-3s are operating in are able to support the weapons activity and/or electronic support taskings. When airspace is unavailable, Due Regard orbits and Air Routes are authorized to support training.

A4.3.4.3. **(Added-18WG)** Transitioning to Air Refueling in Mallipo. Mallipo is an unusually short Aerial Refueling (AR) anchor located in MOA 16 and R80. A roll-in point should be considered due to the length of the IP/CP line. If R80 is “hot”, the northern half of Mallipo will be unavailable and the confines of the remaining airspace can make a normal rendezvous challenging. Due to the location of the MOAs along the west coast, there is no direct routing that allows for normal aircraft separation. Coordinate with Cobra Control.

A4.4. (Added-18WG) Mission Crew Operating Procedures.

A4.4.1. **(Added-18WG) Communications.** The ARO will attempt Satellite Communication (SATCOM) contact with Keyboard, Cobra, Cuechalk, or Fireside as soon as practical, but no later than 45 minutes after takeoff. Once SATCOM contact is established, the SLIC or designated crew members will monitor until secure UHF communications are established with C2. Maintain secure UHF throughout the mission, using secure SATCOM as a backup. If secure communication is unavailable, contact will be maintained in the clear and classified traffic will be passed as required using WESTPAC code words. PSO will establish secure UHF or SATCOM with the 303 IS. If unable, the PSO will attempt relay through Keyboard or Cobra while on station.

A4.4.2. **(Added-18WG) Command and Control (C2) Communication.** When Keyboard is not activated, primary C2 communications are with Cobra using secure UHF or SATCOM. The SLIC, SL, or designated crew member(s) will monitor this frequency from preparation for on-station until off-station.

A4.4.3. **(Added-18WG) Sensor Operations.** Under normal conditions, both an operational mission radar and IFF are required for all KTACS missions. Reference *KTACS Armistice SPINS* for the approval authority for radar-only operations. Radar or IFF only operations may be permitted for training sorties IAW [paragraph A4.2.4.1.3](#).

A4.4.4. **(Added-18WG) Radar Malfunctions.** If a radar malfunction occurs, an orbit will be selected based on the current KTACS Defense Readiness Condition level to minimize actual threats to the E-3 and maintain UHF communication with Keyboard and/or Cobra.

A4.4.4.1. **(Added-18WG) Coordination and Troubleshooting.** Radio coordination and troubleshooting with ground maintenance personnel will be via secure means.

A4.4.5. **(Added-18WG) Radar Frequency Limitations.** Aircrew will not operate the radar in the RF5 and RF6 frequencies.

A4.4.6. **(Added-18WG) Data Link Operations.** The E-3 will enter the KTACS link in the receive- only mode, as soon as possible, while en-route to the orbit. Active mode operations should not be conducted until coordination has been accomplished with the Interface Coordination Unit, Cuechalk. The DLO may pre-coordinate link entry prior to stepping to the jet for takeoff. Link-16 terminal synchronization will be attempted as soon as possible.

A4.5. (Added-18WG) On-Station Procedures.

A4.5.1. **(Added-18WG) Requirements.** The SLIC will not call on-station until: 1) the ASO determines the radar and IFF are operational, 2) effective coverage of the Area of Interest (AOI) is established, and 3) communications are established with Keyboard (when activated) or Cobra. Communication may be relayed through other agencies, as required. On-station may be called with degraded systems in order to support training events, but not real world activities.

A4.5.2. **(Added-18WG)** On-Station Reporting. The SLIC will check in with Keyboard via secure means on the UHF C2 command net or SATCOM. The SLIC will provide the following information: (1) Position off Osan AB and altitude, (2) Destination, (3) Timing based on frag/alibis, (4) Projected Bingo time, and (5) Current ATO/SPINS. Example call would be: “Keyboard, Cowboy is on-station, Osan 159 / 70, 29,000 feet. En Route Palace Orbit as fragged minus Passive Detection System (PDS) capability, projected off-island Bingo 1545 India, using ATO EB Change 1, Weekly Spins Change 2, and Exercise Spins Change 0.”

A4.5.3. **(Added-18WG)** Surveillance Procedures. Surveillance will be conducted IAW AFMAN 11-2E-3G, Volume 3, ACCR 55-20, and other governing directives. Although the surveillance section is primarily responsible for this activity, the weapons section will assist, to the maximum extent possible, in detecting tracks originating in non-friendly territory and inbound radar-only tracks. The ASO or DLO establish and maintain contact with Cuechalk on the Data Link Coordination Net (UHF) to establish link entry procedures and link status. The ASO/DLO will contact the Master Control Reporting Center (MCRC) on the Surveillance Coordination ROK Air Force (ROKAF)/AWACS voice-tell net to coordinate and conduct voice-tell and surveillance point-outs. During peacetime, voice-tell will be conducted with ground agencies for at least 30 minutes per agency (crew manning and time permitting).

A4.5.3.1. **(Added-18WG)** Erratic Data Link Performance. When data links are inoperative, voice-tell will be performed with the MCRC for the entire time the E-3 is on-station. The DLO will document problem symptoms and troubleshooting procedures implemented in the lessons learned.

A4.5.3.2. **(Added-18WG)** Priority Tracks. The ASO/MSO will hard copy data of all non-friendly tracks that may be of intelligence interest at 1-3 minute intervals (based on maneuvers), as long as the track remains in the system. If the printer is inoperative, the tracks will be logged by hand.

A4.5.3.3. **(Added-18WG)** Training Procedures. During peacetime, simulation may be conducted during on-station. The SLIC will determine live mission requirements adequate to cover any contingencies. Priority will always be given to real-world mission surveillance. ASO/SLIC/SLs will be notified when simulated tracks are put in the system, with no simulated tracks being initiated over Korea or the surveillance AOI. For training purposes, the E-3 may assume tracking for the entire Korean peninsula. During such training, the data link picture will not be forwarded to the MCRC.

A4.5.4. **(Added-18WG)** Electronic Support Procedures. PSOs will conduct ES operations IAW AFTTP 3-3, *Combat Aircraft Fundamentals -AWACS*, 7AF Special Instructions (SPINS), and other governing directives. Initial coordination with 303 IS will be accomplished prior to reaching Cheju Island (ROK). PSOs should monitor the HVAA (PTN) SATCOM frequency. Emitter parametric data (J14.0) will not be passed over Link-16 or Link-11 (Line of Bearing [LOB] data only) unless coordinated and approved by Keyboard. PSOs will pass electronic intelligence (ELINT) data to other airborne intelligence/surveillance/ reconnaissance (ISR) or C2 via a voice product net (VPN) in the form of “echo” series Tactical Reports (TACREPs) when required criteria are met. VPN frequencies will be used IAW 7AF SPINS. To maintain maximum situational awareness and E-3 self-defense while PDS is operational, PSOs should not normally assume E-3 monitor duties.

A4.5.5. **(Added-18WG)** Weapons Procedures. Control will be conducted IAW AFMAN 11-2E-3G, Volume 3, AFMAN 11-214, *Air Operations Rules and Procedures*, Air Force Tactics, Techniques, and Procedures (AFTTP) 3-1, ACCR 55-3, 55-43, and ALSSA ACC. The weapons section will assist the surveillance section, to the maximum extent possible, in detecting tracks originating in non-friendly territory and inbound radar-only tracks.

A4.5.5.1. **(Added-18WG)** Contact with Cobra. An SL will establish and maintain contact with Cobra on the UHF C2 weapons coordination net. The SL will conduct a correlation check prior to controlling aircraft. The SL will request a C2 situation brief (to include: “hot” areas, factor “active” areas, Airfield Advisories (AIRADS), and status of scheduled activity) with the Cobra SL.

A4.5.5.2. **(Added-18WG)** Flight Deck Coordination. The SL will brief the AC/SLIC on “hot” areas and AIRADS as soon as possible and will request an updated situation brief when the E-3 is changing locations. Any changes will be briefed to the AC/SLIC.

A4.5.5.3. **(Added-18WG)** Mode 5 Procedures. Mode 5 procedures will be conducted IAW local SPINS.

A4.6. (Added-18WG) Off-Station Procedures.

A4.6.1. **(Added-18WG)** Reporting Procedures. The SLIC will report off-station time to Keyboard and/or Cobra. When activated, Keyboard will require an off-station report with timings annotated in the SLIC’s 961 AACS Form 49, *Mission Summary*, via secure means.

A4.6.2. **(Added-18WG)** Maintenance Codes and Additional Communication. The ARO will pass maintenance codes when practical or when within UHF range of Keystone.



A4.6.3. **(Added-18WG)** Debriefing. An intelligence representative will be available to debrief KTACS missions. The ASO/PSO will collect and organize all hardcopies, logs, and emitters of interest as required for their particular debriefings.

Attachment 5 (Added-18WG)

OPERATIONAL RISK MANAGEMENT (ORM)

A5.1. (Added-18WG) Purpose. This attachment established guidance for calculating individual and mission ORM scores. Crewmembers will add score from Individual Risk Assessment card to obtain an overall individual ORM score. If individual ORM score is greater than 10, notify AC. If individual ORM score is greater than 18, the AC will notify the CC/DO.

Table A5.1. (Added-18WG) 961 AACS Operational Risk Assessment Worksheet.

 961 AACS OPERATIONAL RISK ASSESSMENT WORKSHEET 			
VERSION: JAN 2025			
INSTRUCTIONS: HONESTLY ADDRESS ALL OF THE FOLLOWING RISK FACTORS TO COME UP WITH A SORTIE RISK NUMBER. THERE ARE TWO PARTS: PERSONAL RISK FACTOR (BELOW) THAT EVERYONE COMPLETES, AND MISSION RISK FACTORS THAT THE AC/SLIC COMPLETE. THESE ARE INTENTIONALLY SUBJECTIVE AREAS THAT ALLOW YOU TO QUANTIFY YOUR RISK BASED ON YOUR EXPERIENCE LEVEL. AC/SLIC WILL AVERAGE PERSONAL RISK FACTORS FROM THE THREE CREW SECTIONS (FLIGHT DECK, BMTs, AND TECHNICIANS) AND ADD IT TO THE MISSION RISK FACTORS PERFORM INDICATED ACTIONS AS NECESSARY.			
30 DAY LOOKBACK	3 - 7	1 - 2 OR 8 - 9	NONE OR ≥ 10
# OF SORTIES	0	2	4
E-3 POSITIONAL EXPERIENCE LEVEL	EXPERIENCED 0		INEXPERIENCED 4
TOTAL HOURS OF SLEEP LAST NIGHT	SLEEP IN HOURS: 8+ 7	SLEEP IN HOURS: 6 5 4	SLEEP IN HOURS: 3 ≤ 2
	ORM POINTS: 0 2	ORM POINTS: 4 7 10	ORM POINTS: 14 18
SUM OF CUMULATIVE SLEEP OVER LAST 3 NIGHTS	SLEEP IN HOURS: 24+ ORM POINTS: 0	SLEEP IN HOURS: 22 20 18 ORM POINTS: 1 2 3	SLEEP IN HOURS: 16 14 ≤ 12 ORM POINTS: 4 5 6
RATE YOUR PERSONAL STRESS (RELATIONSHIP, FINANCES, FAMILY, ETC.)	LOW: 0 1 2	MEDIUM: 3 4 5	HIGH: 6 7 8
HEALTH CONCERNS WITH SELF/FAMILY	NONE: 0	SOME: 2	SUBSTANTIAL: 4
OTHER JOB, OR OTHER ISSUES	NONE: 0	SOME: 1 2 3	SUBSTANTIAL: 4 5 6
TOTAL YOUR PERSONAL RISK SCORE:	LOW MED HIGH	10 OR LESS 11 TO 18 19 OR MORE	 NOTIFY AC/SLIC NOTIFY CC/DO
INDIVIDUALS ENTER YOUR SCORE ON THE ORDERS. NOTIFY AC/SLIC IF YOUR SCORE IS ≥ 11			
AC AND SLIC COMPLETE MISSION RISK FACTORS			

Attachment 6 (Added-18WG)**PERSONAL EQUIPMENT**

A6.1. (Added-18WG) Personal Equipment. The following is a list of minimum flight clothing and equipment requirements according to AFMAN 11-301, *Aircrew Flight Equipment (AFE)*, and AFMAN 11-202, Volume 3, PACAFSUP.

A6.1.1. **(Added-18WG)** E-3 crew members will wear or carry all required clothing items:

A6.1.1.1. **(Added-18WG)** Nomex Flight Suit.

A6.1.1.2. **(Added-18WG)** Nomex Flight Gloves.

A6.1.1.3. **(Added-18WG)** Flight Boots: Any boots on the USAF safe to fly list found at: <http://www.afpc.af.mil/dress/policy.asp> under certified boots or approved locally.

A6.1.1.4. **(Added-18WG)** Operational Flashlight.

A6.1.1.5. **(Added-18WG)** When operating north of the 40th parallel between 1 October – 15 April, or at Aircraft Commander discretion, add the following:

A6.1.1.5.1. **(Added-18WG)** Winter Weight Nomex Flight Jacket: CWU-45/P (A-2 Leather jacket is not a suitable substitute).

A6.1.1.5.2. **(Added-18WG)** Thermal Underwear: Cotton Knit, or CWU-43/P and CWU- 44/P aramid ensemble, PTU or polypropylene “Thermax”.

A6.1.1.5.3. **(Added-18WG)** Leather gloves with wool inserts, or winter weight Nomex gloves.

A6.1.1.5.4. **(Added-18WG)** B9-B or Wool ski Cap.

A6.1.2. **(Added-18WG)** Mobility Items/Overnight Bag (as required).

A6.1.3. **(Added-18WG)** Restricted Area Badge (“Line Badge”): IAW Kadena AB Plan 31-101, *Integrated Defense Plan (CUI)*, personnel working in the flight line area will have line badges displayed above the waist at all times (except when within 25-feet of running aircraft engines). Personnel working in the immediate vicinity of the aircraft, i.e. performing preflight duties, will stow their line badge.

Attachment 7 (Added-18WG)
REQUIRED PUBLICATIONS

Table A7.1. (Added-18WG) Required Publications by Crew Position.

LIST OF REQUIRED PUBLICATIONS/FORMS

FLIGHT DECK	MISSION CREW
<u>Publications (EFB Library)</u>	<u>Publications (EFB Library)</u>
- AFMAN 11-202V3 + PACAF Supp + GP Supp	- T.O. 1E-3G-43-1-1
- AFMAN 11-2E-3GV3 + WG Supp	- T.O. 1E-3G-43-1-1 CL2
- ATP 3.3.4.2. Air-to-Air Refueling & SRD	- T.O. 1E-3G-43-1-1 E-3G (Gen 3 Final)
- T.O. 1E-3G(II)-1	- Aircrew Aid (Position Specific)
- T.O. 1E-3G(II)-1CL-1	<u>Forms (Hard Copies)</u>
- T.O. 1E-3G(II)-1-1	- 552 ACW Form 6, Program Incident Report
- T.O. 1E-3A-2-7-5CL-1	- 552 OG Form 198, Comm Tech In-Flight Log
- Aircrew Aid (Position Specific)	- 552 OG Form 32G, Comm Configuration Worksheet
- Kadena AB Instruction 13-204	- 552 OG Form 36B, Computer Mission Log
- Minimum Equipment List (MEL)	- 961 AACCS Radar and IFF Chronological Narrative
- FAA Holdover Tables (as published by FCIF)	- 961 AACCS Form 46G, Console Operator's Comm Worksheet
<u>Forms (Hard Copies)</u>	
- Customs Form 6059B, Customs Declaration (Note 1)	
- Customs Form 7507, General Declaration (If required)	
- DD Form 1801, International Flight Plan, DoD	
- DD Form 2131, Passenger Manifest	
- DAF Form 457, Hazard Report	
- AF Form 651, Hazardous Air Traffic Report (HATR)	
- AF Form 853, Air Force Wildlife Strike Report	
- AFTO Form 117, USAF E-3 ITAP Flight Log	
- 18 WG Form 82, 18th Wing Aviation Incident Initial Report	
- 18 WG 3-Hour Report	

Note 1: One form required for each person on-board.

In addition to the Publications listed above, members will refer to **Attachment 8** for required forms and FLIP.

A7.1. (Added-18WG) Publications: Required in-flight publications will be IAW **Attachments 7** and **Attachment 8**. All required publications are available on the 18 OG SharePoint. In the event of an EFB update, only the above publications are required to be immediately updated.

Attachment 8 (Added-18WG)**FLIP REQUIREMENTS**

A8.1. (Added-18WG) Pacific FLIP Requirements. The following FLIP are required to be current and loaded onto Pilot and Copilot EFBs before flight (via ForeFlight or other means). It is recommended that the following FLIP are current and loaded onto Flight Engineer EFBs before flight for situational awareness and crew resource management. Paper FLIP may be used in lieu of/in conjunction with electronic FLIP if requested and available.

Table A8.1. (Added-18WG) Pacific FLIP Requirements.

	Item
1.	FLIP General Planning (GP)
2.	FLIP Area Planning 3 and 3A (AP/3 and AP/3A)
3.	Flight Information Handbook (FIH)
4.	Pacific, Australasia and Antarctica (PAA) En Route Supplement
5.	PAA En Route Charts (1-20, T1/T2)
6.	PAA High/Low Altitude Terminal Approach Volumes 1, 2 and 3
7.	PAA Terminal Change Notice (TCN) (when applicable)
8.	PAA En Route Change Notice (ECN) (when applicable)
9.	Planning Change Notices (PCN) for GP, AP/3 and AP 3/A(when applicable)

A8.2. (Added-18WG) Other FLIP Requirements. When operating outside of the Pacific, current FLIP for the planned route of flight and all planned alternates will be loaded onto Pilot and Copilot EFBs before flight. Paper FLIP may be used in lieu of/in conjunction with electronic FLIP if requested and available.

Attachment 9 (Added-18WG)**AIRCRAFT COCKING PROCEDURES****A9.1. (Added-18WG) Aircraft Cocking Procedures.**

A9.1.1. **(Added-18WG) Restrictions.** Aircrew participating in cocking duties must be qualified and current in the duty position they will be preparing for flight. If a crewmember is DNIF, they must have specific authorization on the DD Form 2992 to perform aircraft preflight duties. Cocking crews will be afforded the same crew rest as flight crews and will be limited to a 16 hour duty day.

A9.2. (Added-18WG) General Aircraft Cocking Procedures. Aircraft will be cocked IAW appropriate technical orders. In addition, cocking crews will accomplish the following steps:

A9.2.1. **(Added-18WG)** Check all oxygen regulators and crew seats for proper operation.

A9.2.2. **(Added-18WG)** Ensure cargo net or adequate cargo straps are on the aircraft.

A9.2.3. **(Added-18WG)** Zeroize all crypto codes if aircraft will be left unattended.

A9.2.4. **(Added-18WG)** Technicians will record system configuration information on respective positional logs.

A9.3. (Added-18WG) Cocking Crew Composition. The cocking crew will consist of personnel listed in T.O. 1E-3G(II)-1 for Level CC1.

A9.4. (Added-18WG) Cocking Level. Unless otherwise directed, aircraft will be cocked to Level CC1.

A9.5. (Added-18WG) Closing Cocked Aircraft. Ensure the following items are checked prior to closing the aircraft door:

A9.5.1. **(Added-18WG)** Gear pins.

A9.5.1.1. **(Added-18WG)** If cocking outdoors and aircraft will remain outdoors: All gear pins will be removed and stowed. The nose gear T-handle and one grounding wire will remain installed. As standard safety requirements, these two items do not require an entry in the aircraft forms.

A9.5.1.2. **(Added-18WG)** If cocking in a hangar or the aircraft will be towed into a hangar, all gear pins and the nose gear T-handle will remain installed for safety. The nose landing gear (NLG) scissors will be disconnected and the tow bar remain connected while the aircraft is in the hangar.

A9.5.1.3. **(Added-18WG)** Both the gear pins and the scissors/tow bar will require individual Red X entries in the aircraft forms and cause an overall Red X status. Also, note these two items in the cocking entry in the AFTO Form 781.

A9.5.2. **(Added-18WG)** Switch Positions.

A9.5.2.1. **(Added-18WG)** FE Upper Panel:

A9.5.2.1.1. **(Added-18WG)** APU Bleed Switch – OFF (ON indicator extinguished)

A9.5.2.1.2. **(Added-18WG)** Emergency Power Switch – OFF.

- A9.5.2.1.3. **(Added-18WG)** Battery Switch – OFF.
 - A9.5.2.2. **(Added-18WG)** FE Auxiliary Panel:
 - A9.5.2.2.1. **(Added-18WG)** APU Door Indicator – extinguished.
 - A9.5.2.3. **(Added-18WG)** Pilot Overhead Panel:
 - A9.5.2.3.1. **(Added-18WG)** Emergency Exit Lights Switch – OFF.
 - A9.5.2.3.2. **(Added-18WG)** P5 STBY ESIS – Open.
 - A9.5.2.4. **(Added-18WG)** P67-2 Panel:
 - A9.5.2.4.1. **(Added-18WG)** Emergency Lights Arming Switch – OFF.
 - A9.5.2.5. **(Added-18WG)** P61-4 ESIS BATTERY – Open.
- A9.5.3. **(Added-18WG)** Complete AFTO Form 781A IAW **paragraph A9.8.** Place forms inside the radio access door.

A9.6. (Added-18WG) Opening Cocked Aircraft.

- A9.6.1. **(Added-18WG)** Except for operational necessity, cocked aircraft will not be routinely opened with expectations of maintaining the cocked status. See the specific procedures for towing or fueling in **paragraph A9.7.**
- A9.6.2. **(Added-18WG)** For a cocked aircraft to be opened and the cocked status maintained, an AC or FE must be onboard. For this purpose, the following AC/FE combinations may be used: 1) AC/FE who cocked the aircraft, 2) AC/FE who will fly the aircraft, 3) AC/FE on duty as cocking crew, 4) Ops Sup (AC) on duty.
- A9.6.3. **(Added-18WG)** If equipment and/or configuration changes are not made, the aircraft may be closed and returned to cocked status without an additional cocking entry in the aircraft forms.
- A9.6.4. **(Added-18WG)** If equipment and/or configuration changes are made, or any new entries are made in the aircraft forms, the cocked status may still be maintained if the following procedures are followed:
- A9.6.4.1. **(Added-18WG)** All aircraft configurations are returned to the original cocked status.
 - A9.6.4.2. **(Added-18WG)** A new Exceptional Release is signed for any new entries in aircraft forms.
 - A9.6.4.3. **(Added-18WG)** The AC/FE will make an Info Note entry, explaining why the aircraft was opened, certifying the onboard presence of the AC/FE, and certifying all aircraft configurations returned to the original cocked status.
- A9.6.5. **(Added-18WG)** Maintenance leadership (AMXS Maintenance Officer, AMXS Superintendent, and AMXS Pro-Supers) may open the radio access door for the purpose of reviewing the forms. Any maintenance actions or changes to the forms will break the cock. The forms will be returned to the radio access bay after review.

A9.7. (Added-18WG) Towing or Fueling Cocked Aircraft.

A9.7.1. **(Added-18WG)** Situations may arise which require a cocked aircraft to be towed or fueled while maintaining its cocked status. The following procedures will apply to maintain the cocked status:

A9.7.1.1. **(Added-18WG)** An AC/FE (meeting one of the criteria from [paragraph A9.6.2](#)) will be onboard to supervise all towing or refueling activities. After these activities are complete, the AC/FE will ensure all aircraft configurations are returned to the original cocked status. In particular, ensure the NLG scissors are reconnected, if required.

A9.7.1.2. **(Added-18WG)** The AC/FE will make an Info Note entry, explaining why the aircraft was opened, certifying the onboard presence of the AC/FE, and certifying all aircraft configurations are returned to the original cocked status.

A9.8. (Added-18WG) Aircraft Status and Forms.

A9.8.1. **(Added-18WG)** The following will result in an overall Red X status: 1) Gear pins installed – if cocking in hangar or preparing for tow, 2) NLG scissors disconnected/tow bar connected – if cocking in a hangar or preparing for tow, 3) SF-6 Cart (if connected). Each of these items will be recorded in a separate Red X entry in the aircraft forms. These entries will be recorded before the cocking entry.

A9.8.2. **(Added-18WG)** Maintenance personnel will perform normal preflight inspections. The Pro Super will verify all discrepancies have been reviewed and corrected prior to the aircrew accepting the aircraft for cocking. In the AFTO Form 781A pages, the Red Line will be initialed below all discrepancies except the Red X entries for the items listed above.

A9.8.3. **(Added-18WG)** Aircraft commanders will ensure the AFTO Form 781A pages meet the following requirements, which have been agreed to by maintenance. **If these requirements are not met, the aircraft will not be accepted for cocking.** 1) The Red Line **will** be drawn below all entries except for the three Red X entries listed above, 2) The Red Line **will** be initialed by the Pro Super, 3) The Red X entries due to the cocking status **will** be below the Red Line.

A9.8.3.1. **(Added-18WG)** An Exceptional Release **will not** be accomplished prior to cocking when any of the three specific Red X conditions exist. In these cases, an Exceptional Release (ER) **must** be accomplished by the Pro Super prior to flight.

A9.8.4. **(Added-18WG)** Cocking Entry in Aircraft Forms. The AC will make the cocking entry. Note the following in the cocking entry, as applicable:

A9.8.4.1. **(Added-18WG)** Cocking Status – CC1, CC2, or CC3.

A9.8.4.2. **(Added-18WG)** Crypto codes zeroized.

A9.8.4.3. **(Added-18WG)** Overall Red X status (if gear pins installed, NLG scissors disconnected, or SF-6 cart connected).

A9.9. (Added-18WG) Cock Expiration. The cock may be maintained through use of the Alert Preflight Procedure IAW T.O. 00-20-1. See [paragraph A9.13](#). To maintain cocked status, the Alert Preflight must be accomplished IAW T.O. 1E-3G(II)-1 a maximum of 72 hours after the oldest of the maintenance preflight inspections is completed and a new cocking write-up will be entered in the aircraft forms. A full maintenance preflight is not required during the Alert period.

A9.10. (Added-18WG) Cold Weather Operations.

A9.10.1. **(Added-18WG)** Cocked aircraft will **not** be deiced unless an AC or FE is present aboard the aircraft.

A9.10.2. **(Added-18WG)** Stabilizer Trim.

A9.10.2.1. **(Added-18WG)** If it is anticipated that ice and snow can accumulate on the airplane after parking, set the horizontal stabilizer 2.5 units airplane nose down IAW T.O. 1E-3G(II)-1. This will minimize any accumulation on the stabilizer. For standardization, this trim setting will be used in all weather conditions.

A9.10.2.2. **(Added-18WG)** Ensure the trim is **NOT** set to **full nose down**. In extreme conditions, the stabilizer could freeze and become stuck in that position.

A9.11. (Added-18WG) SF-6 Ground Service Cart. SF-6 ground carts (if used) may be left connected to cocked aircraft. The following steps will be performed to ensure a fully charged SF-6 system is available for flight operations:

A9.11.1. **(Added-18WG)** Maintenance personnel will connect the SF-6 ground cart to the aircraft and service the onboard SF-6 bottles prior to aircrew arrival for cocking or preflight.

A9.11.2. **(Added-18WG)** Aircraft Status with SF-6 Cart Connected. The SF-6 ground cart will remain connected to the aircraft while the aircraft is cocked. Maintenance personnel will enter a Red X entry into the AFTO Forms 781 annotating that the SF-6 ground cart is connected to the aircraft and the SF-6 access panel has been removed. Once the aircraft is cocked, the SF-6 ground cart **will not** be removed or replaced. Aircraft commanders will ensure the AFTO Form 781A is completed IAW **paragraph A9.8.** The ER will not be signed off until the flying aircrew arrives to launch the cocked aircraft.

A9.11.3. **(Added-18WG)** When the aircrew arrives at the cocked aircraft, the ART will immediately turn on one of the onboard SF-6 bottles. Maintenance personnel will then disconnect the SF-6 ground cart, secure the SF-6 access panel and sign off the AFTO Forms 781 Red X entry.

A9.11.4. **(Added-18WG)** The Pro Super will inspect the SF-6 access panel and sign off the ER.

A9.11.5. **(Added-18WG)** The FE will inspect the aircraft prior to accepting the aircraft for flight operations, ensuring the SF-6 access panel has been re-attached.

A9.12. (Added-18WG) Alert Preflight Procedure. Cocking crews and maintenance will rotate tires and perform the ALERT PREFLIGHT in Section II of T.O. 1E-3G(II)-1. This procedure may be used to indefinitely maintain the cocked status of a previously cocked aircraft. This procedure (to include tire rotation) must be accomplished a maximum of 72 hours from the previous cock to maintain the cocked status, and will be documented with a new cocking write-up in the aircraft forms by the AC. Accomplish the BEFORE ENTERING AIRPLANE checklist and BEFORE INTERIOR INSPECTION checklist before rotating tires. The tires will be rotated by towing the aircraft, using the TOWING AND PUSHBACK checklist. **Note:** Only a few feet of movement is required to roll the tires off the “flat spot”. The crew will then use the BEFORE START checklist to return the aircraft to a cocked state. Perform any necessary items from the EXTERIOR INSPECTION checklist (for example, ensure gear doors are closed).

A9.13. (Added-18WG) Hangar Procedures - Cock and Launch.**A9.13.1. (Added-18WG) Cock Prior to Tow into the hangar.**

A9.13.1.1. **(Added-18WG)** Aircraft may be positioned outside for cocking prior to tow into the hangar.

A9.13.1.2. **(Added-18WG)** Aircrews will cock the jet outside the hangar, but wait to sign off the cock in the aircraft forms until after the jet is pushed into hangar. The AC or FE will remain onboard during the tow to maintain the cocked status.

A9.13.2. (Added-18WG) Cock or Preflight inside the hangar. If the aircraft is already in the hangar, a cock and/or preflight may still be performed with the following limitations:**A9.13.2.1. (Added-18WG) Bleed air system (APU cannot be operated inside hangar).**

A9.13.2.1.1. **(Added-18WG) Case I – Cocking the Aircraft.** Bleed air preflight is required. External air must be available to preflight system. This requires using a ground air cart positioned outside the hangar and connected by a long hose, which may be impractical. **If bleed air is not available, the aircraft cannot be cocked in the hangar.** It must be towed outside the hangar to operate the APU for bleed air.

A9.13.2.1.2. **(Added-18WG) Case II – Normal Preflight for Launch (aircraft is not cocked).** Perform normal bleed air check if external air is available. If external air is not available, bleed air check may be delayed until APU is started during tow out of hangar for engine start.

A9.13.3. (Added-18WG) Conditions inside the hangar.

A9.13.3.1. **(Added-18WG)** Be aware of two potential problems for getting an aircraft out of a hangar. 1) Hangar doors sometimes won't open, especially the tail door. 2) Icy ramp may prevent towing aircraft from hangar.

A9.13.3.2. **(Added-18WG)** Hardstand stairs will be available. Motorized air stairs are not authorized in the hangar.

A9.13.3.3. **(Added-18WG)** External power will be available in the hangar. External air may be available.

A9.13.4. (Added-18WG) Aircraft orientation.

A9.13.4.1. **(Added-18WG)** Aircraft will be backed into the hangar with the nose pointing out.

A9.13.4.2. **(Added-18WG)** Tow bar will be left connected, as required by maintenance regulations (the tow vehicle will not be connected).

A9.13.4.3. **(Added-18WG)** Nose gear scissors will be disconnected.

A9.13.4.4. **(Added-18WG)** All gear pins and nose gear T-handle will be left installed until aircraft has been towed out of hangar for engine start.

A9.13.5. (Added-18WG) Aircraft status in the hangar.

A9.13.5.1. **(Added-18WG)** Aircraft status will be an overall Red X, reflecting Red X entries in aircraft forms for:

- A9.13.5.1.1. **(Added-18WG)** Disconnected nose gear scissors/tow bar connected.
- A9.13.5.1.2. **(Added-18WG)** Gear pins still installed.
- A9.13.5.1.3. **(Added-18WG)** SF-6 Ground Cart, as applicable.
- A9.13.5.2. **(Added-18WG)** For cocking, aircraft commanders will ensure the AFTO Form 781A is completed IAW **paragraph A9.8.**
- A9.13.5.3. **(Added-18WG)** An Exceptional Release must be accomplished once scissors are reconnected and all gear pins/T-handle are removed and stowed (upon completion of towing the aircraft out of the hangar for engine start).
- A9.13.5.4. **(Added-18WG)** Towing aircraft out of hangar for launch. The Towing and Pushback Checklist in T.O. 1E-3G(II)-1 is not designed for preflight operations. Several necessary preflight actions are not addressed.
 - A9.13.5.4.1. **(Added-18WG)** Hangar Launch Procedures Checklist - Aircrews will follow the Hangar Launch Procedures Checklist in **Attachment 14**. This checklist incorporates all items from the Towing and Pushback Checklist in T.O. 1E-3G(II)-1. Therefore, by following this guidance, aircrews will perform the Dash 1 checklist by default as well as perform additional necessary preflight actions.
 - A9.13.5.4.2. **(Added-18WG)** Starting APU - FE will coordinate with ground crew to start APU any time after APU doors are outside hangar.
- A9.13.5.5. **(Added-18WG)** Once aircraft has come to a stop:
 - A9.13.5.5.1. **(Added-18WG)** Ground crew will remove tow bar and reconnect nose gear scissors. After confirming hydraulics system is operating, all gear pins and T-handle will be removed and stowed aboard the aircraft.
 - A9.13.5.5.2. **(Added-18WG)** Ground crew will sign off Red X entries in AFTO Form 781A and sign new Exceptional Release.
 - A9.13.5.5.3. **(Added-18WG)** Pilot will initiate EGI alignment.

Attachment 10 (Added-18WG)

ALTERNATE LISTING

A10.1. (Added-18WG) Note: If an alternate is required for filing purposes or after orbit area weather check (IAW AFMAN 11-202, Volume 3), the AC will ensure that the selected alternate's prevailing surface winds (for ETA +/- 1 hour) are forecast to be within AFMAN 11-2E-3G, Volume 3, crosswind limits (corrected for RCR).

A10.2. (Added-18WG) Pacific Alternate Airfields. The following alternates are suitable for the E-3 (Advise Operations Sup of alternate being used).

Table A10.1. (Added-18WG) Pacific Alternate Airfields.

AIRFIELD (ICAO)	RUNWAY	LENGTH (ft)	LOCATION	COORDINATES
Guam Intl (PGUM)	06/24	12,014	Guam	1329N 14448E
Andersen AFB (PGUA)	06/24	11,200	Guam	1335N 14456E
MCAS Futenma (ROTM)	06/24	9,004	Okinawa	2616N 12745E
Kunsan AB (RKJK)	18/36	9,009	Korea	3554N 12637E
Misawa AB (RJSM)	10/28	9,999	N. Japan	4042N 14122E
Naha AB (ROAH)	18/36	9,843	Okinawa	2612N 12738E
Osan AB (RKSO)	09/27	9,008	Korea	3705N 12702E
Suwon AB (RKSW)	15/33	9,166	Korea	3714N 12700E
Daegu AB (RKTN)	13/31	9,039	Korea	3554N 12840E
Yokota AB (RJTY)	18/36	11,000	C. Japan	3545N 13921E
**Atsugi NAS (RJTA)	01/19	7,999	C. Japan	3527N 13927E
MCAS Iwakuni (RJOI)	02/20	8,007	S. Japan	3409N 13215E
**Note: Will not be considered as missed AAR or weather alternates until all other primary alternates have been considered.				

Table A10.2. (Added-18WG) Hawaiian Alternate Airfields.

AIRFIELD (ICAO)	RUNWAY	LENGTH (ft)	LOCATION	COORDINATES
Hickam AFB (PHNL)	08/26	12,360	Oahu	2119N 15755W
Kaneohe Bay MCAS (PHNG)	04/22	7,771	Oahu	2127N 15746W
Hilo Intl (PHTO)	08/26	9,800	Hawaii	1943N 15503W
Wake Island (PWAK) (Emergency only)	10/28	9,844	C. Pacific	1917N 16638E

Attachment 11 (Added-18WG)

DIVERSION CARD KADENA AREA DIVERT AIRFIELDS

A11.1. (Added-18WG) Note: This chart is a guide for fuel planning. BINGO fuel should be computed based on actual conditions the day of flight. The IAF FUEL listed below is fuel required from the Kadena IAF to make one approach and climb out, and arrive overhead the divert base with 18,000 pounds. Calculations were made using NO WIND and an operating weight of 183,000 pounds. Strong winds associated with the Pacific jet stream can cause large changes in time and fuel requirements. MC is the magnetic course from Kadena direct to the airfield.

Table A11.1. (Added-18WG) Kadena Area Divert Airfields.

BASE	ICAO	COORDS	ROUTE	MC	TIME	ALT	TAS	IAF	RWY INFO
MCAS Iwakuni	RJOI	N3409E13215	A-582	031	1+15	250	420	41K	8007x19702/20
Osan AB	RKSO	N3705E12702	A-586	003	1+48	300	420	46K	9008x15009/27
Yokota AB	RJTY	N3545E13921	G-581	050	2+22	310	420	53K	11000x20018/36
Misawa AB	RJSM	N4042E14122	B-597	041	2+57	310	420	61K	9999x15010/28
Andersen AFB	PGUA	N1335E14456	R-584	131	3+38	310	420	67K	11200x20006/24
MCAS Futenma	ROTM	N2617E12745	Approach Control	198	0+10	040	255	24K	9004x15006/24
Naha AB	ROAH	N2612E12739	Approach Control	221	0+15	040	255	24K	9843x14818/36

Attachment 12 (Added-18WG)**CREW BRIEFING GUIDE (INITIAL AND EXECUTION)**

A12.1. (Added-18WG) Purpose. For most missions, only two briefs should be conducted: an initial coordination brief and an execution brief.

A12.2. (Added-18WG) Initial Brief. The initial brief is to make sure the crew is manned and is aware of the mission tasking. The initial brief should follow the below format.

- A12.2.1. **(Added-18WG)** Briefing security and classification (AC).
- A12.2.2. **(Added-18WG)** Sign in (AC).
- A12.2.3. **(Added-18WG)** Intel.
- A12.2.4. **(Added-18WG)** Mission tasking, mission objectives, and E-3 objectives (SLIC).
- A12.2.5. **(Added-18WG)** Training, currency, & evals (SLIC).
- A12.2.6. **(Added-18WG)** Mission flow (SLIC).
- A12.2.7. **(Added-18WG)** Flight specifics and weather (AC).
- A12.2.8. **(Added-18WG)** Clothing / equipment requirements (AC).
- A12.2.9. **(Added-18WG)** SII's (AC).
- A12.2.10. **(Added-18WG)** Emergency of the Day (AC).
- A12.2.11. **(Added-18WG)** Malfunction of the Day (SLIC).
- A12.2.12. **(Added-18WG)** Additional Equipment required for the mission (SLIC).
- A12.2.13. **(Added-18WG)** Mission Planning Responsibilities & Timing (SLIC).

A12.3. (Added-18WG) Execution Brief. The execution brief should follow the below format. It is to discuss specific mission items/timings.

- A12.3.1. **(Added-18WG)** Briefing security and classification (AC).
- A12.3.2. **(Added-18WG)** Sign in (AC).
- A12.3.3. **(Added-18WG)** Intel update.
- A12.3.4. **(Added-18WG)** Mission tasking, mission objectives, and E-3 objectives (SLIC).
- A12.3.5. **(Added-18WG)** Mission flow (SLIC).
- A12.3.6. **(Added-18WG)** Flight specifics, weather, jet status (AC).
- A12.3.7. **(Added-18WG)** Route brief (AC).
- A12.3.8. **(Added-18WG)** Flight Deck system requirements & contracts (AC).
- A12.3.9. **(Added-18WG)** Emergency signals (AC).
- A12.3.10. **(Added-18WG)** Ground Evacuation Egress Routes (AC).
- A12.3.11. **(Added-18WG)** Ditching Egress Routes (AC).
- A12.3.12. **(Added-18WG)** Midair collision avoidance (AC).

- A12.3.13. **(Added-18WG)** Fundamental elements of basic airmanship (AC).
- A12.3.14. **(Added-18WG)** Flightline safety (AC). (eyeglasses, ear protection, rings, and scarves).
- A12.3.15. **(Added-18WG)** 18 WG/CC safety policy (AC).
- A12.3.16. **(Added-18WG)** Emergency Duties (SLIC).
- A12.3.17. **(Added-18WG)** Crew coordination Drill (SLIC).
- A12.3.18. **(Added-18WG)** Computer system requirements (SLIC).
- A12.3.19. **(Added-18WG)** Communications Plan (SLIC).
- A12.3.20. **(Added-18WG)** Link Information (DLO/Comm).
- A12.3.21. **(Added-18WG)** FE/Techs released (Bus times) (AC or SLIC).
- A12.3.22. **(Added-18WG)** Weapons activity (Control SL).
- A12.3.23. **(Added-18WG)** Surveillance activity (ASO).
- A12.3.24. **(Added-18WG)** Surveillance working area (ASO).
- A12.3.25. **(Added-18WG)** Electronic support (PSO).
- A12.3.26. **(Added-18WG)** SAR (SLIC).
- A12.3.27. **(Added-18WG)** Contingencies (AC).
- A12.3.28. **(Added-18WG)** Questions (Bus times) (AC or SLIC).

Attachment 13 (Added-18WG)**FLIGHT CREW BRIEFING GUIDE (P-SORTIE/SPECIALIZED)**

A13.1. (Added-18WG) Purpose. May be used for P-Sortie specialized and execution briefings, or for flight crew specialized briefing for mission sortie planning. **Note:** For execution briefings the PIC will brief the italicized items at a minimum.

A13.2. (Added-18WG) Sign-in.

- A13.2.1. **(Added-18WG)** Time Hack.
- A13.2.2. **(Added-18WG)** Roll Call.
- A13.2.3. **(Added-18WG)** Flight Orders/Passenger Manifest.
- A13.2.4. **(Added-18WG)** Recall Roster.
- A13.2.5. **(Added-18WG)** FCIF/Read File (Sign off in PEX).
- A13.2.6. **(Added-18WG)** Water Jug.
- A13.2.7. **(Added-18WG)** *Flightline safety – (eyeglasses, ear protection, rings, and scarves).*
- A13.2.8. **(Added-18WG)** *Egress Routes/Emergency Exits.*
- A13.2.9. **(Added-18WG)** *Emergency Signals.*
- A13.2.10. **(Added-18WG)** *Mid-Air Collision Avoidance/Bird Avoidance.*
- A13.2.11. **(Added-18WG)** *Fundamentals Elements of Airmanship.*

A13.3. (Added-18WG) Requirements.

- A13.3.1. **(Added-18WG)** Flight Deck Kit/EFB.
- A13.3.2. **(Added-18WG)** Seasonal Clothing.
- A13.3.3. **(Added-18WG)** Currency requirements (Go/No-Go)/discrepancies.
- A13.3.4. **(Added-18WG)** Personal Electronic Devices/Radio Frequency Interference (RFI) Bag.

A13.4. (Added-18WG) Flight Specifics.

- A13.4.1. **(Added-18WG)** Mission Number.
- A13.4.2. **(Added-18WG)** Callsign.
- A13.4.3. **(Added-18WG)** Pilot in Command.
- A13.4.4. **(Added-18WG)** Aircraft Tail Number/Parking Spot/Status.

A13.5. (Added-18WG) Timing.

- A13.5.1. **(Added-18WG)** Crew Rest.
- A13.5.2. **(Added-18WG)** Show Time.
- A13.5.3. **(Added-18WG)** Takeoff.
- A13.5.4. **(Added-18WG)** ARCT.

A13.5.5. (Added-18WG) Land.

A13.6. (Added-18WG) Weather.

A13.6.1. (Added-18WG) Takeoff.

A13.6.2. (Added-18WG) Enroute.

A13.6.3. (Added-18WG) Air Refueling.

A13.6.4. (Added-18WG) Transition Base.

A13.6.5. (Added-18WG) Arrival.

A13.6.6. (Added-18WG) Alternate.

A13.7. (Added-18WG) Objectives.

A13.8. (Added-18WG) Ground Operations.

A13.8.1. (Added-18WG) Notices to Airman (NOTAMS), Airfield Status (NAVAIDS, Construction/Bird Hazards).

A13.8.2. (Added-18WG) DAFIF/GPWS Database.

A13.8.3. (Added-18WG) RAIM.

A13.9. (Added-18WG) Takeoff.

A13.9.1. (Added-18WG) TOLD review.

A13.9.2. (Added-18WG) Normal Procedures.

A13.9.3. (Added-18WG) Emergency Procedures.

A13.9.3.1. (Added-18WG) Low/High Speed Abort Considerations.

A13.9.4. (Added-18WG) SDP Review (If applicable).

A13.10. (Added-18WG) Departure.

A13.10.1. (Added-18WG) Departure Procedure/Radar Vectors.

A13.10.2. (Added-18WG) High Terrain/Obstacles.

A13.11. (Added-18WG) Flight Profile.

A13.11.1. (Added-18WG) Route.

A13.11.2. (Added-18WG) CPDLC, ADS-C, ACARS.

A13.11.3. (Added-18WG) Emergency Airfields.

A13.11.4. (Added-18WG) Mission Orbit Procedures/ LOA review.

A13.12. (Added-18WG) Fuel Considerations – Fuel required (552 ACW Form 33), Bingo(s), Air Refueling.

A13.13. (Added-18WG) Air Refueling Procedures.

A13.13.1. (Added-18WG) AR Track/ARCT/Altitudes.

A13.13.2. (Added-18WG) Callsigns.

- A13.13.3. **(Added-18WG)** EMCON Procedures.
- A13.13.4. **(Added-18WG)** Comm Plan.
- A13.13.5. **(Added-18WG)** Type Rendezvous.
- A13.13.6. **(Added-18WG)** Overrun Considerations.
- A13.13.7. **(Added-18WG)** Post Air Refueling Procedures.
- A13.13.8. **(Added-18WG)** Emergency/Breakaway Procedures.
- A13.13.9. **(Added-18WG)** Additional Considerations (Night, Cell, KC-10).

A13.14. (Added-18WG) Recovery/Transition Procedures.

- A13.14.1. **(Added-18WG)** Destination Restrictions/Airfield Suitability Restrictions Report (ASRR).
- A13.14.2. **(Added-18WG)** Arrival Procedures/STAR Review.
- A13.14.3. **(Added-18WG)** Obstacles/High Terrain.
- A13.14.4. **(Added-18WG)** Approach/Airfield Diagram Review.
- A13.14.5. **(Added-18WG)** Touch- and-Go Procedures.
- A13.14.6. **(Added-18WG)** Seat Assignments (Training Flow).

A13.15. (Added-18WG) Contingencies.

- A13.15.1. **(Added-18WG)** Latest Departure.
- A13.15.2. **(Added-18WG)** Bingo Fuel/Time/Considerations.
 - A13.15.2.1. **(Added-18WG)** Ops Stop/Missed Air Refueling Base.
- A13.15.3. **(Added-18WG)** Air Refueling Contingencies.
 - A13.15.3.1. **(Added-18WG)** Tanker Delay.
 - A13.15.3.2. **(Added-18WG)** Tanker Canceled Prior To Takeoff.
 - A13.15.3.3. **(Added-18WG)** Tanker Canceled After Takeoff.
 - A13.15.3.4. **(Added-18WG)** No Off-load.
- A13.15.4. **(Added-18WG)** Alternate Mission Possibilities.

A13.16. (Added-18WG) *Fire Fighter Responsibilities.*

A13.17. (Added-18WG) Emergency of the Day.

A13.18. (Added-18WG) Special Interest Items & Trends.

A13.19. (Added-18WG) Briefing/ Training Topics (“Hangar flying,” systems, etc.).

A13.20. (Added-18WG) Lessons Learned.

Attachment 14 (Added-18WG)**HANGAR LAUNCH PROCEDURES**

A14.1. (18WG) Note: This procedure is initiated following the BEFORE START Checklist. If certain items in the BEFORE START Checklist were not able to be accomplished (Radios, NAVAIDS, GPS, IFF...), accomplish them immediately following tow completion and power on the aircraft (APU or ground power).

A14.2. (Added-18WG) Prepare for Tow.

A14.2.1. **(Added-18WG)** All Gear Pins, T-Handle – Installed (E).

A14.2.2. **(Added-18WG)** Plugs and Covers - Removed (E, GC).

A14.2.3. **(Added-18WG)** Battery Switch - On (E).

A14.2.4. **(Added-18WG)** Emergency Power Switch - On (E).

A14.2.5. **(Added-18WG)** Interphone - Checked (P, E, GC).

A14.2.6. **(Added-18WG)** Interconnect Valve Switch - System (E).

A14.2.7. **(Added-18WG)** Hydraulic System - As Required (E, GC).

A14.2.8. **(Added-18WG)** Flaps - UP (P, GC).

A14.2.9. **(Added-18WG)** Parking Brake - SET (P, GC).

A14.2.10. **(Added-18WG)** Brake Pressure - Normal Range (CP).

A14.2.10.1. **(Added-18WG)** When electrical power is removed, brake pressure will read 0.

A14.2.11. **(Added-18WG)** Seat Belt Switch - ON (CP or E).

A14.2.12. **(Added-18WG)** Doors, Slides, Emergency Lights - Closed and Armed (ARO, ART, E).

A14.2.13. **(Added-18WG)** EGIs - Ready for Towing (CP).

A14.2.13.1. **(Added-18WG)** The Co-pilot will ensure EGIs are not frozen and are ready for location movement.

A14.2.14. **(Added-18WG)** Landing Gear - Configured for Tow (E, GC).

A14.2.14.1. **(Added-18WG)** Nose Gear Scissors – Disconnected.

A14.2.14.2. **(Added-18WG)** All gear pins, T-handle – Installed.

A14.2.14.3. **(Added-18WG)** Tow Bar – Connected.

A14.2.15. **(Added-18WG)** Warning Alarm and Lights - Checked (P or CP, E, ART, ADST, ARO).

A14.2.16. **(Added-18WG)** Mission Crew - Ready for Tow (E, SLIC).

A14.2.17. **(Added-18WG)** Security and Tow Clearance - Received (Airfield Ground, GC).

A14.2.18. **(Added-18WG)** Aux Hydraulic Pumps - OFF (E).

A14.2.19. **(Added-18WG)** Fuel Pumps - OFF (E). **Note:** Steps **A14.2.18** and **A14.2.19** reduce electrical load on initial APU power transfer.

A14.2.20. **(Added-18WG)** External Power Switch - OFF (E, GC).

A14.2.21. **(Added-18WG)** Chocks and Ground Equipment - Removed (P, GC). **CAUTION:** Flight crew UHF radio is available for communication as long as power is available on emergency DC bus. Limit transmission to five seconds and receiver operation to five minutes unless draw-through cooling is available. To prevent damage to UHF Radio, open the UHF XCVR, UHF CONT, UHF XCVR CPLR, UHF/ADF AC and UHF/ADF DC circuit breakers on P-5 IAW. TO 1E-3G(II)-1.

A14.2.22. **(Added-18WG)** Hangar Upper Tail Doors – Open (P, GC).

A14.2.23. **(Added-18WG)** Parking Brake – Released (P, GC).

A14.3. (Added-18WG) During Tow.

A14.3.1. **(Added-18WG)** APU - Start as Required (E, GC).

A14.3.2. **(Added-18WG)** Ground Crew advises FE when APU doors clear hangar to start APU.

A14.3.3. **(Added-18WG)** Air Conditioning Flow Control Valves - Checked if required (E).

A14.3.4. **(Added-18WG)** Aux Hydraulic Pumps - ON (E, GC).

A14.3.5. **(Added-18WG)** Fuel Pumps - ON (E).

A14.3.6. **(Added-18WG)** Emergency Power Switch - Normal (E).

A14.4. (Added-18WG) When Tow Complete.

A14.4.1. **(Added-18WG)** Parking Brake - Set (GC, P).

A14.4.2. **(Added-18WG)** Flaps - 14 (CP, GC).

A14.4.3. **(Added-18WG)** IFF - STBY (CP).

A14.4.4. **(Added-18WG)** CVR/DFDR/CPL - Checked if required (E).

A14.4.5. **(Added-18WG)** Landing Gear - Configured for Flight (E, GC).

A14.4.5.1. **(Added-18WG)** Tow Bar – Disconnected.

A14.4.5.2. **(Added-18WG)** Nose Gear Scissors – Connected.

A14.4.5.3. **(Added-18WG)** Gear Pins, T-handle - Removed and Stowed.

A14.4.5.4. **(Added-18WG)** Aircraft Forms - Complete (P, E, GC).

A14.5. (Added-18WG) Proceed to STARTING ENGINES Checklist.