

DEPARTMENT OF THE AIR FORCE  
Headquarters US Air Force  
Washington, DC 20330-1030

QTP 4B071-8  
2 April 2015  
*Certified Current, 7 March 2024*

# AIR FORCE SPECIALTY CODE 4B071 BIOENVIRONMENTAL ENGINEERING

## Confined Spaces



## QUALIFICATION TRAINING PACKAGE

**Accessibility:** *Publications and forms are available on the e-publishing website at <http://www.e-publishing.af.mil> for downloading or ordering.*

**Releasability:** *There are no releasability restrictions on this publication.*

## Table of Contents

<b>STS Line Item 4.8.2: Classify confined spaces (permit / non-permit required)</b> .....	1
TRAINER GUIDANCE.....	1
TASK STEPS.....	2
TRAINEE REVIEW QUESTIONS .....	3
PERFORMANCE CHECKLIST.....	4
ANSWERS.....	5
<b>STS Line Item 4.8.5(a): Combustible Gas Meters MSA Passport® Personal Alarm</b> .....	6
TRAINER GUIDANCE.....	6
TASK STEPS.....	7
PERFORMANCE CHECKLIST.....	8
<b>STS Line Item 4.8.5(b): Combustible Gas Meters MSA Sirius® Multigas Detector</b> .....	9
TRAINER GUIDANCE.....	9
TASK STEPS.....	10
PERFORMANCE CHECKLIST.....	16
<b>STS Line Item 4.8.7: Certify organizational personnel to test confined spaces</b> .....	19
TRAINER GUIDANCE.....	19
TRAINEE REVIEW QUESTIONS .....	21
PERFORMANCE CHECKLIST.....	22
ANSWERS.....	23
<b>STS Line Item 4.8.9: Approve confined space master entry plans and non-routine entry permits</b> .....	24
TRAINER GUIDANCE.....	24
TASK STEPS.....	25
TRAINEE REVIEW QUESTIONS .....	27
PERFORMANCE CHECKLIST.....	28
ANSWERS.....	30

---



---

**STS Line Item 4.8.2: Classify confined spaces (permit / non-permit required)**


---

**TRAINER GUIDANCE**

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed
<b>Prerequisites:</b>	N/A
<b>Training References:</b>	<ul style="list-style-type: none"> <li>• AFI 91-203, <i>Air Force Consolidated Occupational Safety Instruction</i></li> <li>• 29 CFR 1910.146</li> </ul>
<b>Additional Supporting References:</b>	
<b>CDC Reference:</b>	4B051
<b>Training Support Material:</b>	<ul style="list-style-type: none"> <li>• Area of confined space</li> <li>• Description of confined space to be classified</li> </ul>
<b>Specific Techniques:</b>	Question and answer
<b>Criterion Objective:</b>	Given a confined space (CS), confined space description and atmospheric monitoring results, accurately classify the confined space while completing all checklist items with NO trainer assistance.
<b>Notes:</b> Provide trainee with atmospheric monitoring results to use for this QTP.	

### TASK STEPS

1. Review atmospheric monitoring results.
2. Compare results to classification criteria in AFI Std 91-203.
  - a. Determine whether or not atmosphere is Immediately Dangerous to Life or Health (IDLH).
  - b. Determine whether or not oxygen content is acceptable (deficient, acceptable or enriched).
  - c. Determine whether or not atmosphere flammability (gases, vapors, mists, fibers or dusts) is acceptable.
  - d. Determine whether or not toxicity levels are acceptable.
  - e. Determine whether there is a possibility of engulfment or entrapment.
3. Compile and report determination(s) (as per AF Form 55, Employee Safety and Health Record) to the confined space program team (CSPT) with recommended classification: permit-required or non-permit confined space.

**NOTES:**

---

**TRAINEE REVIEW QUESTIONS**

---

---

**STS Line Item 4.8.2: Classify confined spaces (permit / non-permit required)**

---

<p>1. What determines if an area is classified as a confined space?</p>
<p>2. What is the range of oxygen content for a confined space to be classified as a “non-permit” required?</p>
<p>3. When evaluating the presence of flammable gases, what is the classification of a confined space with a 11.5 percent lower explosive limit (LEL) reading?</p>
<p>4. Given each condition below, will a permit be required? Answer each situation independently. Circle the correct answers.</p> <p>a) Yes No An IDLH is present. b) Yes No Atmospheric testing results equal to 8 percent of the LEL. c) Yes No Oxygen content equals 19.5 percent.</p>

**PERFORMANCE CHECKLIST**

**STS Line Item 4.8.2: Classify confined spaces (permit / non-permit required)**

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed

DID THE TRAINEE...		YES	NO
1. Review atmospheric monitoring results?			
2. Compare results to classification criteria in AFI Std 91-203?			
a. Determine whether or not atmosphere is Immediately Dangerous to Life or Health (IDLH)?			
b. Determine whether or not oxygen content is acceptable (deficient, acceptable or enriched)?			
c. Determine whether or not atmosphere flammability (gases, vapors, mists, fibers or dusts) is acceptable?			
d. Determine whether or not toxicity levels are acceptable?			
e. Determine if there is a possibility of engulfment or entrapment?			
3. Compile and report determination(s) (as per AF Form 55, Employee Safety and Health Record) to the confined space program team (CSPT) with recommended classification: permit-required or non-permit confined space?			
<b>Did the trainee successfully complete the task?</b>			

\_\_\_\_\_  
 TRAINEE NAME (PRINT)

\_\_\_\_\_  
 TRAINER NAME (PRINT)

**ANSWERS**

1. What determines if an area is classified as a confined space?

A:

- (1) Is large enough and so configured that an employee can bodily enter and perform assigned work.
- (2) Has limited or restricted means for entry or exit (for example, tanks, vessels, silos, storage bins, hoppers, vaults, and pits are spaces that may have limited means of entry.); and
- (3) Is not designed for continuous employee occupancy.

(Source: CFR 1910.146 (b)-permit required confined spaces)

2. What is the range of oxygen content for a confined space to be classified as a “non-permit” required?

A: 19.5-23.5 %

(Source: 1910.146 (b)-permit required confined spaces)

3. When evaluating the presence of flammable gases, what is the classification of a confined space with a 11.5 percent lower explosive limit (LEL) reading?

A: Permit-required

(Source: AFI 91-203, *Air Force Consolidated Occupational Safety Instruction*)

4. Given each condition below, will a permit be required? Answer each situation independently. Circle the correct answers.

- a) **Yes** No An IDLH is present.
- b) Yes **No** Atmospheric testing results equal to 8 percent of the LEL.
- c) Yes **No** Oxygen content equals 19.5 percent.

(Source: AFI 91-203, *Air Force Consolidated Occupational Safety Instruction*)

## STS Line Item 4.8.5(a): Combustible Gas Meters MSA Passport® Personal Alarm\*

### TRAINER GUIDANCE

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed.
<b>Prerequisites:</b>	None
<b>Training References:</b>	MSA Passport® Personal Alarm Instruction Manual
<b>Additional Supporting References:</b>	MSA Passport® Personal Alarm Technical Manual <a href="http://media.msanet.com/NA/USA/PortableInstruments/CombinationInstrumentsandCombustibleGasIndicators/PassportPersonalAlarm/803919.pdf">http://media.msanet.com/NA/USA/PortableInstruments/CombinationInstrumentsandCombustibleGasIndicators/PassportPersonalAlarm/803919.pdf</a>
<b>CDC Reference:</b>	4B051
<b>Training Support Material:</b>	<ul style="list-style-type: none"> <li>• MSA Passport® Personal Alarm with fully charged battery pack/power source</li> <li>• Calibration gas</li> </ul>
<b>Specific Techniques:</b>	Conduct hands-on training and evaluation of calibration and operation of equipment with verification of steps.
<b>Criterion Objective:</b>	Given a Passport® Personal Alarm, demonstrate how to operate and calibrate it successfully completing all the checklist items with NO trainer assistance.
<p><b>Notes:</b> * The Passport® Personal Alarm detects oxygen (O<sub>2</sub>), carbon monoxide (CO), hydrogen sulfide (H<sub>2</sub>S), and sulfur dioxide (SO<sub>2</sub>). The Passport® Personal Alarm detects gases and vapors in air only. It cannot measure combustible or toxic gases in reducing atmospheres, furnace stacks, or environments with inert gas backgrounds. The Passport Alarm measures combustible gases and vapors; however, it cannot measure the presence of combustible airborne mists such as lubricating oils.</p>	



## TASK STEPS

1. Turn on Passport in clean, fresh air environment.<sup>1</sup>
2. Observe readings to verify no gas present.
3. Check battery condition.
4. Perform calibration check.<sup>2</sup>
5. Attach sampling lines and related equipment, if available and collecting a sample from a remote or inaccessible location.<sup>3</sup>
6. Expose instrument to environment.
7. Record meter readings.
8. Utilize DOEHS or equivalent.

### LOCAL REQUIREMENTS:

### NOTES:

1. When the unit is turned on it responds with the following:
  - backlight flashes
  - screen flashes
  - alarm sounds
  - alarm lights flash
  - major electronic components are tested automatically
2. Calibration checks must be made frequently if materials such as silicone, silicates, or lead-containing compounds such as leaded gasoline are suspected to be present in the tested atmosphere. If you do not recalibrate, the instrument may give false readings and endanger life and health. To perform a calibration check, do the following steps:
  - a. Attach the pump module or calibration cap to the Passport Alarm, orienting the inlet fitting to point toward the battery pack
  - b. Attach the calibration adapter to the calibration cap or pump module
  - c. Attach the regulator to the cylinder
  - d. Connect the black tubing to the regulator
  - e. Open the valve on the regulator and connect the other end of the tubing to the inlet fitting
  - f. Observe readings are within limits stated on the calibration cylinder
3. To attach probe to sampling line, follow these steps:
  - a. Grasp the probe handle by the top two sections [the large section (cap) with the MSA logo and the center section (base) with the label].
  - b. Unscrew lower section (guard) from the label section.
  - c. Feed male end of the sample line through the guard and screw into the exposed connector ring on the probe.
  - d. Screw the guard back onto the base.

**PERFORMANCE CHECKLIST**

**STS Line Item 4.8.5(a): Combustible Gas Meters: MSA Passport® Personal Alarm**

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed.

DID THE TRAINEE...		YES	NO
1. Turn on Passport in clean, fresh air environment?			
2. Observe readings to verify no gas present?			
3. Check battery condition?			
4. Perform calibration check?			
5. Attach sampling lines and related equipment, if available and collecting a sample from a remote or inaccessible location?			
6. Expose instrument to environment?			
7. Record meter readings?			
8. Utilize DOEHS or equivalent.			
<b>Did the trainee successfully complete the task?</b>			

\_\_\_\_\_  
 TRAINEE NAME (PRINT)

\_\_\_\_\_  
 TRAINER NAME (PRINT)

---

**STS Line Item 4.8.5(b): Combustible Gas Meters**  
**MSA Sirius® Multigas Detector\***

---

**TRAINER GUIDANCE**

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed.
<b>Prerequisites:</b>	None
<b>Training References:</b>	MSA Sirius® Multigas Detector Operating Manual
<b>Additional Supporting References:</b>	<a href="http://www.msanorthamerica.com/catalog/product16577.html">http://www.msanorthamerica.com/catalog/product16577.html</a> <a href="http://www.msanorthamerica.com/">http://www.msanorthamerica.com/</a>
<b>CDC Reference:</b>	4B051
<b>Training Support Material:</b>	<ul style="list-style-type: none"> <li>• MSA Sirius® Multigas Detector with fully charged battery/power source</li> <li>• Calibration gas</li> </ul>
<b>Specific Techniques:</b>	Conduct hands-on training and evaluation of calibration and operation of equipment with verification of steps.
<b>Criterion Objective:</b>	Given a Sirius® Multigas Detector, demonstrate how to operate it successfully completing all the checklist items with no trainer assistance.
<p><b>Notes:</b></p> <p>* The Sirius® Multigas Detector is designed to detect gases and vapors in air only and to detect only specified toxic gases for which a sensor is installed.</p> <p>Use only Teflon sampling lines for reactive gases such as chlorine (CL<sub>2</sub>), phosphine (PH<sub>3</sub>), ammonia (NH<sub>3</sub>), hydrogen cyanide (HCN), and for semivolatile organic compounds such as gasoline and jet fuels. Do not use silicone tubing or sampling lines. The operating manual contains additional warnings and acceptable usage limits for the unit as well as a discussion of how the unit functions.</p>	

## TASK STEPS

### Turning ON the Sirius® Multigas Detector

1. Press the **Power ON** button.<sup>1</sup>
  1. Perform Fresh Air Set Up Option for automatic zero adjustment of the Sirius® Multigas Detector sensors.<sup>2</sup>

### Verifying Pump Operation

1. Turn **ON** the Sirius® Multigas Detector.<sup>3</sup>
2. Once gas readings are displayed, plug the free end of the sampling line or probe.<sup>4</sup>
3. Check the pump before each day's use.
4. Press the **RESET/▼** button to reset the alarm and restart the pump.<sup>8</sup>

### Clearing an Alarm

1. Correct any flow blockage.
2. Press the **RESET/▼** button. The Pump will now restart.

### Conducting a Pre-Operational Check

The pre-operational check is simple and should only take about one minute. Perform this check before each day's use for each installed sensor.

1. Turn **ON** the Sirius® Multigas Detector in clean, fresh air.
2. Verify that readings indicate no gas is present.
3. Attach regulator (supplied with calibration kit) to the cylinder.
4. Connect tubing (supplied with calibration kit) to the regulator.
5. Attach other end of tubing to the instrument.
6. Open the valve on the regulator, if so equipped.
7. Determine that the reading on the Sirius® Multigas Detector display is within the limits stated on the calibration cylinder or limits pre-determined by your flight.
8. If necessary, change cylinder to introduce other calibration gases.
9. If readings are not within these limits, the Sirius® Multigas Detector requires recalibration.<sup>6</sup>

### Conducting a Calibration Check

1. Turn **ON** the Sirius® Multigas Detector in clean, fresh air.
2. Verify that readings indicate no gas is present.
3. Attach regulator (supplied with calibration kit) to the cylinder.
4. Connect tubing (supplied with calibration kit) to the regulator.
5. Attach other end of tubing to the instrument.
6. Open the valve on the regulator, if so equipped.<sup>7</sup>

### Performing Recalibration (if necessary)

1. Turn **ON** the instrument and verify that battery has sufficient life.
2. Wait until the Measure Gases page appears.
3. Push and hold the **RESET/▼** button until **CAL ZERO?** flashes on the display.
4. Push the **ON-OFF/ACCEPT** button to zero the instrument.<sup>8</sup>
5. Connect the appropriate calibration gas (MSA recommends 100ppm isobutylene) to the instrument by connecting one end of the tubing to the pump inlet on the instrument and the other end of tubing to the cylinder regulator (supplied in the calibration kit).\*
6. Open the valve on the regulator, if so equipped.
7. Push the **ON-OFF/ACCEPT** button to calibrate (span) the instrument.<sup>9</sup>
8. Remove the tubing from the instrument.

**Measuring Gas Concentrations**<sup>10</sup>

1. Expose instrument to environment
2. Calculate response factor

**Resetting Short Term Exposure Limits (STELs)**<sup>11</sup>

1. Access the STEL page.
2. Press the RESET/▼ button

**Resetting the Time Weighted Average (TWA)**<sup>12</sup>

1. Access the TWA page.
2. Press the RESET/▼ button.

**Recording data**

1. Utilize DOEHRS or equivalent.

**LOCAL REQUIREMENTS:****NOTES:**

1. The instrument displays the following information:
  - a. A self-test:
    - a. Audible alarm sounds
    - b. Alarm LEDs illuminate
    - c. Display backlight illuminates
    - d. Pump activates
    - e. Software version displays
    - f. Internal diagnostics.
  - b. Alarm setpoints:
    - a. Low
    - b. High
    - c. STEL (if activated)
    - d. TWA (if activated)
  - c. Calibration gas (expected calibration gas values)

- d. Time and date (if data logging option installed)
- e. Last CAL date (if data logging option installed) —The Sirius® Multigas Detector is equipped with a “last successful calibration date” feature. The date shown is the last date that all installed sensors were successfully calibrated. **LAST CAL** is displayed with this date in the following format: **MM/DD/YY**
- f. Instrument warm-up period
- g. Fresh Air Setup (FAS) option.

2. Persons responsible for the use of the Sirius® Multigas Detector must determine whether or not the Fresh Air Setup option should be used. The user's abilities, training and normal work practices must be considered when making this decision.

**Warning:** Do not activate the Fresh Air Setup unless you are certain you are in fresh, uncontaminated air; otherwise, inaccurate readings can occur which can falsely indicate that a hazardous atmosphere is safe. If you have any doubts as to the quality of the surrounding air, do not use the Fresh Air Setup feature. Do not use the Fresh Air Setup as a substitute for daily calibration checks. The calibration check is required to verify span accuracy. Failure to follow this warning can result in serious personal injury or death.

To perform a Fresh Air Setup, push the ON/OFF button while **ZERO?** is flashing. The Fresh Air Setup (FAS) has limits. If a hazardous level of gas is present, the Sirius® Multigas Detector ignores the FAS command and goes into alarm.

Once the instrument self check is complete, **ZERO?** flashes for 10 seconds.

If no buttons are pushed, the **ZERO?** automatically stops flashing after the 10 seconds have expired and the FAS is not performed.

To immediately skip the FAS, push the **RESET/▼** button.

3. The pump motor will start fast and then slows down as the instrument adjusts the power to run the pump.

4. If the pump motor shuts down and an alarm sounds, **PUMP ALARM** will flash on the display and the readings on the display may change. When the pump inlet, sample line or probe is blocked, the pump alarm must activate. If the alarm does not activate, check the sample line and probe for leaks. Once leak is fixed, re-check pump alarm by blocking flow.

5. **Warning:** Perform a blocked flow test before each day's use. Do not use the pump, sample line, or probe unless the pump alarm activates when the flow is blocked. Lack of an alarm is an indication that a sample may not be drawn to the sensors, which could cause inaccurate readings. Failure to follow the above can result in serious personal injury or death.

During operation, a pump alarm may occur when the flow system is blocked, pump is inoperative, and sample lines are attached or removed.

When the instrument is in a gas alarm, the pump alarm may not display until gas alarm is cleared.

6. The presence of other calibration gases may cause the PID to under range, indicated by dashes for the displayed **VOC** reading.
  
7. The reading on the Sirius® Multigas Detector display should be within the limits stated on the calibration cylinder or limits which are predetermined by the user. If necessary, change cylinder to introduce other calibration gases. If readings are not within these limits, the Sirius Multigas Detector requires recalibration.
  
8. Instrument must be in fresh air to perform the zero. **CAL ZERO** flashes. To skip the Zero procedure and move directly to the calibration span procedure, push the **RESET/▼** button. If no button is pushed for 30 seconds, the instrument returns to the Measure mode. Once the zeros are set, **CAL SPAN?** flashes
  
9. **CAL SPAN** flashes for approximately 90 seconds. If autocalibration sequence passes, the instrument beeps three times and returns to the Measure mode. To skip calibration and return to the Measure mode, push the **RESET/▼** button. If no button is pushed for 30 seconds, it will return to the Measure page.
  
10. **Warning:** Never let the end of the sampling line touch or go under any liquid surface. If liquid is sucked into the instrument, readings will be inaccurate and the instrument could be damaged. We recommend the use of an MSA Sample Probe (P/N 10042621, 10042622, 10040589, or equivalent) containing a special membrane filter, permeable to gas but impermeable to water, to prevent such an occurrence.

The Sirius® Multigas Detector can be equipped to detect combustible gases in the atmosphere.

a. Alarms sound when concentrations reach:

- i. Alarm Setpoint or
- ii. 100% LEL (Lower Explosive Limit), 5% CH<sub>4</sub>.

b. When the combustible gas indication reaches the Alarm Setpoint:

- i. Alarm sounds
- ii. Alarm lights flash
- iii. % LEL or CH<sub>4</sub> flag above the concentration flashes.

c. To silence the alarm, press the **RESET/▼** button. The alarm will stay silent if the alarm condition has cleared.

d. When the combustible gas indication reaches 100% LEL or 5% CH<sub>4</sub>, the LockAlarm™ circuit locks the combustible gas reading and alarm and:

- i. Alarm sounds
- ii. Alarm lights flash
- iii. 100 (or 5.00 in CH<sub>4</sub> mode) appears on the display and flashes.

- e. This alarm cannot be reset with the RESET/▼ button. After moving to a safe, fresh-air environment, reset the alarm by turning OFF the instrument and turning it ON again.

To determine a response factor for a target chemical, perform the following procedure:

1. Calibrate the Sirius Detector using isobutylene as the span gas.
2. On the monitor, set the sample gas name to isobutylene.
3. Apply a known concentration of the target chemical to the monitor and note the concentration reported in the display.
4. The response factor for the target chemical relative to isobutylene:

$$\text{RF target gas} = \frac{\text{Actual known concentration}}{\text{Concentration reported by instrument}}$$

**For example:**

A monitor is calibrated on isobutylene, and has isobutylene defined as the sample gas. When sampling 106 ppm of benzene in air, the instrument reports a concentration of 200 ppm. In this example, the response factor for benzene relative to isobutylene would be:

$$\text{RF benz} = \frac{106 \text{ ppm known conc. benzene}}{200 \text{ ppm reported}} = 0.53$$

When surveying, if benzene is selected as the sample gas in the Response Factor page, and 0.53 is entered into the monitor as the response factor, the instrument would use this response factor to automatically correct the displayed concentration into PPM benzene.

If a chemical has a response factor between zero and one, the monitor has a higher detector response for this chemical than isobutylene. If the response factor is greater than one, the monitor has a lower detector response for this chemical than isobutylene.

11. The STEL alarm is calculated over a 15-minute exposure. Calculation examples are as follows:

- Assume the detector has been running for at least 15 minutes:

- 15-minute exposure of 35 PPM:

$$\frac{(15 \text{ minutes} \times 35 \text{ PPM})}{15 \text{ minutes}} = 35 \text{ PPM}$$

- 10-minute exposure of 35 PPM

- 5-minute exposure of 15 PPM:

$$\frac{(10 \text{ minutes} \times 35 \text{ PPM}) + (5 \text{ minutes} \times 15 \text{ PPM})}{15 \text{ minutes}} = 28 \text{ PPM}$$



12. The TWA alarm is calculated over an eight-hour exposure. Calculation examples are as follows:

- 1-hour exposure of 50 PPM:

$$\frac{(1 \text{ hour} \times 50 \text{ PPM}) + (7 \text{ hours} \times 0 \text{ PPM})}{8 \text{ hours}} = 6.25 \text{ PPM}$$

- 4-hour exposure of 50 PPM  
4-hour exposure of 100 PPM:

$$\frac{(4 \text{ hours} \times 50 \text{ PPM}) + (4 \text{ hours} \times 100 \text{ PPM})}{8 \text{ hours}} = 75 \text{ PPM}$$

- 12-hour exposure of 100 PPM:

$$\frac{(12 \text{ hours} \times 100 \text{ PPM})}{8 \text{ hours}} = 150 \text{ PPM}$$



**NOTE:** The accumulated reading is always divided by eight hours.

MSA Sirius® MultiGas Detector

**PERFORMANCE CHECKLIST**

**STS Line Item 4.8.5(b): Combustible Gas Meters: MSA Sirius® Multigas Detector**

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed.

DID THE TRAINEE...		YES	NO
<b>TURNING ON THE SIRIUS® MULTIGAS DETECTOR</b>			
1. Press the <b>Power ON</b> button?			
2. Perform Fresh Air Set Up Option for automatic zero adjustment of the Sirius® MultiGas Detector sensors?			
<b>VERIFYING PUMP OPERATION</b>			
1. Turn ON the Sirius® MultiGas Detector?			
2. Once gas readings were displayed, plug the free end of the sampling line or probe?			
3. Check the pump before use?			
4. Press the RESET/▼ button to reset the alarm and restart the pump?			
<b>CLEARING AN ALARM</b>			
1. Correct any flow blockage?			
2. Press the RESET/ ▼ button to restart the pump?			
<b>CONDUCTING A PRE-OPERATIONAL CHECK</b>			
1. Turn ON the Sirius® Multigas Detector in clean, fresh air?			
2. Verify that readings indicate no gas is present?			
3. Attach regulator (supplied with calibration kit) to the cylinder?			
4. Connect tubing (supplied with calibration kit) to the regulator?			
5. Attach other end of tubing to the instrument?			
6. Open the valve on the regulator, if so equipped?			

7. Determine that the reading on the Sirius® Multigas Detector display is within the limits stated on the calibration cylinder or limits pre-determined by your flight?			
8. If necessary, change cylinder to introduce other calibration gases?			
9. If readings are not within these limits, the Sirius® Multigas Detector requires recalibration?			
<b>CONDUCTING A CALIBRATION CHECK</b>			
1. Turn ON the Sirius Multigas Detector in clean, fresh air?			
2. Verify that readings indicate no gas is present?			
3. Attach regulator (supplied with calibration kit) to the cylinder?			
4. Connect tubing (supplied with calibration kit) to the regulator?			
5. Attach other end of tubing to the instrument?			
6. Open the valve on the regulator, if so equipped?			
<b>PERFORMING RECALIBRATION (IF NECESSARY)</b>			
1. Turn ON the instrument and verify that battery has sufficient life?			
2. Wait until the Measure Gases page appears?			
3. Push and hold the <b>RESET/▼</b> button until <b>CAL ZERO?</b> flashes on the display?			
4. Push the <b>ON-OFF/ACCEPT</b> button to zero the instrument?			
5. Connect the appropriate calibration gas to the instrument by connecting one end of the tubing to the pump inlet on the instrument and the other end of tubing to the cylinder regulator (supplied in the calibration kit)?			
6. Open the valve on the regulator, if so equipped?			
7. Push the <b>ON-OFF/ACCEPT</b> button to calibrate (span) the instrument?			
8. Remove the tubing from the instrument?			
<b>MEASURING GAS CONCENTRATIONS</b>			
1. Expose instrument to environment?			
2. Calculate a response factor?			
<b>RESETTING SHORT TERM EXPOSURE LIMITS (STELS)</b>			
1. Access the STEL page			
2. Press the <b>RESET/▼</b> button			
<b>RESETTING THE TIME WEIGHTED AVERAGE (TWA)</b>			

1. Access the TWA page			
2. Press the RESET/▼ button			
<b>RECORDING DATA</b>			
1. Utilize DOEHRS or equivalent.			
<b>Did the trainee successfully complete the task?</b>			

\_\_\_\_\_  
 TRAINEE NAME (PRINT)

\_\_\_\_\_  
 TRAINER NAME (PRINT)

---



---

## STS Line Item 4.8.7: Certify organizational personnel to test confined spaces

---

### TRAINER GUIDANCE

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed.
<b>Prerequisites:</b>	None
<b>Training References:</b>	<ul style="list-style-type: none"> <li>• AFI 91-203, <i>Air Force Consolidated Occupational Safety Instruction</i>, Chapter 23</li> </ul>
<b>Additional Supporting References:</b>	<ul style="list-style-type: none"> <li>• OSHA 1910.146 Appendix C</li> </ul>
<b>CDC Reference:</b>	4B051
<b>Training Support Material:</b>	<ul style="list-style-type: none"> <li>• Atmosphere Monitoring Equipment</li> <li>• Confined Space</li> </ul>
<b>Specific Techniques:</b>	Conduct training and evaluation using a scenario or an actual confined space.
<b>Criterion Objective:</b>	Given a scenario, references, and an atmospheric monitor, certify an individual to test/monitor a confined space successfully completing all steps with NO trainer assistance.
<b>Notes:</b>	<p>AFI 91-203, <i>Air Force Consolidated Occupational Safety Instruction</i>, Chapter 23, para 23.2.4.3 states that BE will provide local training on the use, calibration (user) and care of atmosphere testing and monitoring equipment annually. Certify organizational personnel, as required, to test confined spaces.</p>

**TASK STEPS**

1. Ensure organizations are using approved atmospheric monitoring equipment.<sup>1</sup>
2. Provide local training on the use, calibration, and care of the atmosphere monitoring equipment annually.<sup>2</sup>
3. Ensure personnel know how to evaluate the confined space.<sup>3</sup>
4. Provide certification/documentation to show that the individual has completed the training requirements.

**LOCAL REQUIREMENTS:****NOTES:**

1. Commanders and/or functional managers must obtain BE approval for the purchase of atmospheric monitoring equipment. This is to ensure the equipment has the necessary monitoring capabilities/sensors and does not create a potential health risk when used. Based on this, BE should not certify personnel on equipment that has not been approved for use.
2. See 4.8.6 QTP for further guidance on the use, calibration and care of atmospheric monitoring equipment. In addition to the manufacturer's instructions, training must include local CSPT-determined equipment training requirements and/or entry procedures.
3. Training/certification should be such that entry supervisors/attendants/testers are able to perform their monitoring duties, which include understanding the sequence of testing and the interpretation of results. See QTP 4.8.2 Classify Confined Spaces or 4.8.3 Test Confined Space Atmospheric Conditions and Interpret Results for further guidance on this step. 4. After the trainee has successfully completed the equipment training requirements, the trainer issues a "certificate" stating that the individual understands how to properly operate and maintain the equipment, and is therefore qualified to conduct tests of confined space atmospheric conditions. Certification training must be provided prior to the worker being assigned the duties.

**TRAINEE REVIEW QUESTIONS**

---

**STS Line Item 4.8.7: Certify organizational personnel to test confined spaces**

---

1. Why should organizations coordinate with BE for approval when purchasing atmospheric monitoring equipment?

**PERFORMANCE CHECKLIST**

**STS Line Item 4.8.7: Certify organizational personnel to test confined spaces**

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed.

DID THE TRAINEE...	YES	NO
1. Ensure organizations are using approved atmospheric monitoring equipment?		
2. Provide local training on the use, calibration, and care of the atmosphere monitoring equipment annually?		
3. Ensure personnel know how to evaluate the confined space?		
4. Provide certification/documentation to show that the individual has completed the training requirements?		
<b>Did the trainee successfully complete the task?</b>		

\_\_\_\_\_  
 TRAINEE NAME (PRINT)

\_\_\_\_\_  
 TRAINER NAME (PRINT)



## ANSWERS

1. Why should organizations coordinate with BE for approval when purchasing atmospheric monitoring equipment?

A: To ensure the equipment has the necessary monitoring capabilities/sensors and does not create a potential health risk when used

(Source: 4B051 CDC)

---

**STS Line Item 4.8.9: Approve confined space master entry plans  
and non-routine entry permits**

---

**TRAINER GUIDANCE**

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed.
<b>Prerequisites:</b>	None
<b>Training References:</b>	<ul style="list-style-type: none"> <li>• OSHA 1910.146</li> <li>• AFI 91-203, <i>Air Force Consolidated Occupational Safety Instruction</i></li> </ul>
<b>Additional Supporting References:</b>	None
<b>CDC Reference:</b>	4B051
<b>Training Support Material:</b>	<ul style="list-style-type: none"> <li>• AF Form 1024, <i>Confined Space Permit</i> (completed)</li> <li>• MEP (completed)</li> </ul>
<b>Specific Techniques:</b>	Conduct hands-on training and evaluation.
<b>Criterion Objective:</b>	Given a confined space (CS) permit and/or MEP, review and approve the permit/MEP successfully completing all checklist items with NO trainer assistance.
<b>Notes:</b>	

## TASK STEPS

### **MEP (Master Entry Plan) Review and Approval**

Does the MEP:

1. Describe the acceptable entry conditions, including atmospheric conditions, under which permits may be issued.
2. Identify types and locations of spaces to be entered and types of tasks or operations to be performed.
3. List either by reference or direct statement in the MEP the procedures to be used for entry, e.g., shop OI that cover specific tasks.
4. List PPE, monitoring and rescue equipment, and conditions under which it shall be used.
5. Designate frequency and type of atmospheric monitoring.
6. List other controls required, e.g., lockout and/or tagout, ventilation.
7. List chemicals and quantities authorized for use. List expected exposure levels based on air sampling results.
8. List conditions under which the space may be reclassified.
9. Require verification of the condition of all monitoring equipment and PPE.<sup>1</sup>
10. After all items have been verified, you may sign the MEP.

### **Permits (AF Form 1024) for Non-routine Entry Review and Approval**

Does the AF Form 1024 include:

1. Location and description of CS to be entered<sup>2</sup>
2. Atmospheric and contact hazards within the permit space
3. Personal protective equipment<sup>3</sup>
4. Atmospheric testing/monitoring equipment details<sup>4</sup>
5. Names of authorized entrants<sup>5</sup>
6. Name of attendants<sup>5</sup>
7. Entry preparations (i.e., measures used to control/eliminate all hazards, briefings, etc)<sup>6</sup>
8. Results of initial and periodic tests along with names and initials of testers<sup>7</sup>
9. Acceptable entry conditions
10. Name of entry supervisor
11. After all items have been verified, you may sign the AF Form 1024.
12. Ensure personnel know that the entry permit should be posted at the confined space and remain so until the work is completed<sup>8</sup>

### **LOCAL REQUIREMENTS:**

**NOTES:**

1. Review training documents to ensure workers are trained on the equipment.
2. The work that is to be done in the confined space.
3. The protective equipment and emergency equipment to be used by any person who takes part in a rescue or responds to other emergency situations in the confined space.
4. The details of any atmospheric testing done of the confined space - when, where, results, date monitoring equipment were last calibrated. Ideally, calibration would be done just before each use. If this is not possible, follow the equipment manufacturer's guidelines for frequency of calibration.
5. Documentation to show all individuals have been trained on their roles.
6. The use of mechanical ventilation and other protective equipment needed and any other precautions that will be followed by every worker who is going to enter the confined space.
7. A signature of a worker who did the confined space testing. The signature on the permit would indicate that adequate precautions are being taken to control the anticipated hazards.
8. The entry permit should be posted at the confined space and remain so until the work is completed. The employer should keep a copy of the completed permit on file.

**TRAINEE REVIEW QUESTIONS**

---

**STS Line Item 4.8.9: Approve confined space master entry plans  
and non-routine entry permits**

---

1. What should you do if the conditions in the space are more hazardous than contemplated under the permit?

2. How long should an entry permit be retained by the organization?

**PERFORMANCE CHECKLIST**

**STS Line Item 4.8.9: Approve confined space master entry plans and non-routine entry permits**

<b>Proficiency Code:</b>	3c
<b>PC Definition:</b>	Can do all parts of the task. Needs only a spot check of completed work. Can identify why and when the task must be done and why each step is needed.

DID THE TRAINEE...	YES	NO
<b>MEP (MASTER ENTRY PLAN) REVIEW</b>		
<b>Did the MEP:</b>		
1. Describe the acceptable entry conditions, including atmospheric conditions, under which permits may be issued?		
2. Identify types and locations of spaces to be entered and types of tasks or operations to be performed?		
3. List either by reference or direct statement in the MEP the procedures to be used for entry, e.g., shop OI that cover specific tasks?		
4. List PPE, monitoring and rescue equipment, and conditions under which it shall be used?		
5. Designate frequency and type of atmospheric monitoring?		
6. List other controls required, e.g., lockout and/or tagout, ventilation?		
7. List chemicals and quantities authorized for use. List expected exposure levels based on air sampling results?		
8. List conditions under which the space may be reclassified?		
9. Require verification of the condition of all monitoring equipment and PPE?		
10. After all items have been verified, you may sign the MEP.		
<b>PERMITS (AF FORM 1024) FOR NON-ROUTINE ENTRY REVIEW</b>		
<b>Did the AF Form 1024 include:</b>		
1. Location and description of CS to be entered?		
2. Atmospheric and contact hazards within the permit space?		
3. Personal protective equipment?		

4. Atmospheric testing/monitoring equipment details?		
5. Names of authorized entrants?		
6. Name of attendants?		
7. Entry preparations (i.e., measures used to control/eliminate all hazards, briefings, etc)?		
8. Results of initial and periodic tests along with names and initials of testers?		
9. Acceptable entry conditions?		
10. Name of entry supervisor?		
11. After all items have been verified, sign the AF Form 1024?		
12. Ensure personnel know that the entry permit should be posted at the confined space and remain so until the work is completed?		
<b>Did the trainee successfully complete the task?</b>		

\_\_\_\_\_  
 TRAINEE NAME (PRINT)

\_\_\_\_\_  
 TRAINER NAME (PRINT)

**ANSWERS**

1. What should you do if the conditions in the space are more hazardous than contemplated under the permit?

A: The permit will be revoked if testing shows conditions in the space are more hazardous than contemplated under the permit. The entry supervisor will stop operations and ensure a new permit is issued

(Source: AFI 91-203, *Air Force Consolidated Occupational Safety Instruction*)

2. How long should an entry permit be retained by the organization?

A: Each completed entry permit, including those canceled or revoked, shall be retained for one year by the organization responsible for the entry and be available for review.

(Source: AFI 91-203, *Air Force Consolidated Occupational Safety Instruction*)