

**BY ORDER OF THE COMMANDER
SPACE SYSTEMS COMMAND**

**SPACE SYSTEMS COMMAND MANUAL
91-710, VOLUME 2**

27 DECEMBER 2022

Safety



**RANGE SAFETY USER
REQUIREMENTS MANUAL - FLIGHT
SAFETY REQUIREMENTS**

COMPLIANCE WITH PUBLICATION IS MANDATORY

ACCESSIBILITY: Publication are forms are available for downloading or ordering on the e-Publishing website at www.e-publishing.af.mil.

RELEASABILITY: There are no releasability restrictions on this publication.

OPR: HQ SSC/SEK

Certified by: HQ SSC/SEK
(Mr. John G. Orpen)

Supersedes: AFSPCMAN 91-710V2, 13 July 2017

Pages: 87

This manual implements AFI 91-202, *The U.S. Air Force Mishap Prevention Program*, and is consistent with DoDD 3100.10, *Space Policy*, DoDD 3200.11, *Major Range and Test Facility Base (MRTFB)*, DoDD 3230.3, *DoD Support for Commercial Space Launch Activities*, DoDI 3200.18, *Management and Operation of the Major Range and Test Facility Base*, AFPD 91-1, *Nuclear Weapons and Systems Surety*, AFPD 91-2, *Safety Programs*, and the *Memorandum of Agreement between the Department of the Air Force and the Federal Aviation Administration for Launch and Reentry Activity on Department of the Air Force Ranges and Installations*. This volume establishes the requirements for flight safety for vehicles launched and operations conducted from Space Systems Command (SSC) ranges, including the Eastern Range (ER) and Western Range (WR). The volume includes requirements for the following programs: ballistic missiles and space vehicles; cruise missiles and remotely piloted vehicles; small unguided rockets or probe vehicles; aerostats or balloons systems; projectiles, torpedoes, and non-propulsive air-dropped bodies; air-launched vehicles; intended support plans for aircraft and ships; directed energy systems; and the launch of large nuclear systems into space. Flight Safety Requirements approval is a necessary prerequisite for conducting operations covered by this volume. By itself, Flight Safety Requirements approval does not constitute permission to conduct an operation. Unless otherwise specified in this volume, the term Range Safety/Launch Safety refers to the Space Launch Delta Safety Office (SLD/SE) at the ER and WR.

This volume applies to all Range Users conducting or supporting range operations. Range Users include any individual or organization that conducts or supports any activity on resources (land,

sea, or air) owned or controlled by SSC ranges. This includes such organizations as the DoD, US government agencies, civilian launch operators, and foreign government agencies and other foreign entities that use SSC range facilities and test equipment; conduct prelaunch and launch operations, including payloads to orbital insertion or impact; and/or require on-orbit or other related support. Commercial users intending to provide launch services from one of the ranges shall have a license or license application in process from the Department of Transportation's FAA or have a DoD sponsorship and be accepted by the DoD to use the ER or WR. Foreign government organizations or other foreign entities shall be sponsored by an appropriate US government organization or be a customer of a Range User. This volume does not apply to the Air National Guard or to Air Force Reserve Command units.

In accordance with SSCI 91-701, *The Space Systems Command Launch and Range Safety Program*, all tailored versions of SSCMAN 91-710 are approved by the Space Launch Delta (SLD) Commander.

The authorities to waive SLD/unit level requirements in this publication are identified with a Tier ("T-0, T-1, T-2, T-3") number following the compliance statement. Waiver authority of non-tiered requirements may not be delegated below the Space Launch Delta Commander level unless specifically stated in this publication. See DAFMAN 90-161, *Publishing Processes and Procedures*, and any SSC supplements for a description of the authorities associated with the Tier numbers. Submit requests for waivers through the chain of command to the appropriate Tier waiver approval authority, or alternately, to the Publication OPR. Ensure all records generated as a result of processes prescribed in this publication adhere to AFI 33-322, *Records Management and Information Governance Program*, and are disposed IAW the Air Force Records Disposition Schedule, which is located in the Air Force Records Information Management System. Refer to SSCMAN 91-710, Volume 1, Attachment 6 for submitting/recommended supplemented changes and questions to HQ SSC Directorate of Safety (HQ SSC/SE) using the Range Safety approved change request form or DAF Form 847, *Recommendation for Change of Publication*. Route the change request form through the appropriate functional chain of command.

This publication may be supplemented, but all supplements must be approved by HQ SSC/SE prior to certification and approval for publishing. Each range may incorporate range-unique or program-unique requirements into documents other than a supplement, such as an operating instruction, which is only required to be coordinated internally within the local Range Safety organization structure and approved at the local level by the Chief of Safety.

Note: Volume 7 contains a glossary of references, acronyms and abbreviations, and terms for use with all the volumes. Special publication formatting features are described in [paragraph 1.2](#) of this volume.

SUMMARY OF CHANGES

This document has been updated primarily to reflect organizational changes associated with the establishment of SSC as a USSF Field Command (FLDCOM), and the re-alignment of launch and range safety program management from the former Air Force Space Command publication to an SSC publication.

Chapter 1—INTRODUCTION	5
1.1. Organization of the Volume.....	5
1.2. Impact Restrictions.	6
1.3. Land Overflight.....	6
1.4. Trajectory Safety Margins.	6
1.5. Data Submission.	6
1.6. Range User Responsibilities.	7
Chapter 2—FLIGHT ANALYSIS APPROVAL AND DATA REQUIREMENTS	9
2.1. Introduction.....	9
Table 2.1. Data Requirements Documentation Lead Times.	10
2.2. Flight Plan Approval and Data Requirements Overview.....	10
Figure 2.1. General Format.	11
Figure 2.2. Nominal vehicle altitude versus time.....	15
2.3. Aircraft/Ship Intended Support Plans (ISP) and Data Package Requirements.	19
2.4. Directed Energy Plan Approval and Data Requirements.....	20
2.5. Large Nuclear Systems Approval and Data Requirements.....	25
Chapter 3—PROGRAM-SPECIFIC FLIGHT ANALYSES	26
3.1. Trajectory Analysis.....	26
3.2. Malfunction Turn Analysis.	37
3.3. Debris Analysis.....	37
3.4. Debris Risk Analysis	37
3.5. Acoustic Analysis.	38
3.6. Sonic Boom Analysis.....	38
3.7. FSS Determination Analysis.....	39
3.8. Post-Flight Vehicle Performance Analysis.	40
Attachment 1—GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION	42
Attachment 2—TRAJECTORY DATA	43
Attachment 3—MALFUNCTION TURN DATA	52
Attachment 4—FRAGMENT DATA	59
Attachment 5—JETTISONED BODY DATA	62
Attachment 6—FLIGHT TRAJECTORY DATA PREPARATION, SUBMITTAL AND PROCESSING	64

**Attachment 7—RANGE RISK ANALYSIS TOOL (RRAT) COVARIANCE INPUT FILE
FORMATS**

Chapter 1

INTRODUCTION

1.1. Organization of the Volume.

1.1.1. Main Chapters. The main chapters of this volume include common requirements for all vehicle classes. Attachments include additional requirements to supplement the main chapters.

1.1.2. Open Text. The open text contains the actual mandatory performance-based requirements. Tailoring expected for these requirements includes the deletion of non-applicable requirements, changes to an existing requirement due to a different design or process with rationale acceptable to Range Safety, or addition to a requirement when there are no existing requirements addressing a new technology, when unforeseen hazards are discovered, when federal or industry standards change and for similar reasons. For example, solid rocket motor performance requirements would be deleted for launch systems that do not use solid rocket motors.

1.1.3. Bordered Paragraphs.

1.1.3.1. Bordered paragraphs, or text boxes, identified as tables and notes in this document, are non-mandatory and are used to identify some of the potential detailed technical solutions that meet the performance requirements. In addition, the bordered paragraphs contain lessons learned from previous applications of the performance requirement, where a certain design may have been found successful, or have been tried and failed to meet the requirement. These technical solutions are provided for the following reasons:

1.1.3.1.1. To aid the tailoring process between Range Safety and Range Users in evaluating a potential system against all the performance requirements.

1.1.3.1.2. To aid Range Safety and Range Users in implementing lessons learned.

1.1.3.1.3. To provide benchmarks that demonstrate what Range Safety considers an acceptable technical solution/implementation of the performance requirement and to help convey the level of safety the performance requirement is intended to achieve.

1.1.3.2. The technical solutions in the bordered paragraphs may be adopted into the tailored version of the requirements for a specific program when the Range User intends to use that solution to meet the performance requirement. At this point, they become mandatory requirements to obtain Range Safety approval. This process is done to:

1.1.3.2.1. Provide an appropriate level of detail necessary for contractual efforts and to promote efficiency in the design process.

1.1.3.2.2. Avoid contractual misunderstandings that experience has shown often occur if an appropriate level of detail is not agreed to. The level of detail in the bordered paragraphs is necessary to avoid costly out-of-scope contractual changes and to prevent inadvertently overlooking a critical technical requirement.

1.1.3.3. The Range User always has the option to propose alternatives to the bordered paragraph solutions. Range User proposed alternative solutions shall achieve an equivalent level of safety and be approved by Range Safety. After meeting these two requirements,

the Range User proposed solutions become part of the tailored SSCMAN 91-710 for that specific program.

1.1.3.4. Range Safety has final decision authority in determining whether Range User proposed detailed technical solutions meet SSCMAN 91-710 performance requirements.

1.2. Impact Restrictions.

1.2.1. No launch vehicle, payload, or jettisoned body shall be intentionally impacted on land, high density shipping lanes, or oil and gas fields nor penetrate through occupied airline traffic routes unless approved and meets the public risk criteria in Volume 1 of this publication. Proposed flights shall be planned, and trajectories shaped so that normal impact dispersion areas for such items do not encompass those areas. Range Users must verify that standoff distances are acceptable for jettisoned body normal impact dispersion areas that closely approach, but do not impact land. Normal impact areas within internationally recognized territorial limits or economic zones may affect trajectories.

1.2.2. If any jettisoned body remains buoyant after impact and presents a hazard to maritime vessels or platforms and if the probability of contact with the body during its expected duration of floatation exceeds $1E-5$, a means of sinking or recovering the body shall be provided.

1.2.3. For space vehicles, if a stage contains multiple-burn engines, the impact dispersion area corresponding to any planned cutoff before orbital insertion shall be entirely over water. **Note:** Time permitting, critical events, such as the arming of engine cutoff circuits and the transmission of backup engine cutoff commands, should be sequenced to occur when the impact dispersion areas are entirely over water

1.2.4. In accordance with DoDI 4540.01, *Use of International Airspace by U.S. Military Aircraft and for Missile and Projectile Firings*, all operations shall be conducted with due regard for the safety of all air and surface traffic. Areas for activities shall be selected so as not to interfere with established air routes and ocean shipping lanes.

1.3. Land Overflight. The overflight of any inhabited landmasses is discouraged and is approved only if operation requirements make overflight necessary and risk studies indicate the probability of impact and casualty expectancy is acceptable.

1.4. Trajectory Safety Margins.

1.4.1. The flight trajectory shall be designed to accommodate Range Safety capability to control launch-related risks.

1.4.2. A sufficient safety margin shall be provided between the intended flight path and protected areas, so a normal vehicle does not violate destruct criteria.

1.4.3. During the initial launch phase, the launch profile shall not be so steep that critical coastal areas cannot be protected by standard safety destruct criteria.

1.4.4. No hazardous condition is acceptable if mission objectives can be obtained from a safer approach, methodology, or position.

1.5. Data Submission.

1.5.1. General. The Range User is only required to supply required data once if no changes occur from operation to operation. If this is the case, the Range User shall state, in writing to

Range Safety, that there are no changes. However, if any changes occur from operation to operation, the Range User shall identify, in writing to Range Safety, all data that have changed from a specified baseline mission and specify the document, paragraph, and page number where each change item can be found. This statement shall be submitted to Range Safety according to established lead times.

1.5.2. Statement of Program Justification. The Range User shall provide the following additional supporting data justification before a Range Safety program approval can be made. The level of detail required for this information shall be established in preliminary discussions with Range Safety or in the Chief of Safety's response to a Range User's written request for approval.

1.5.2.1. Detailed explanation of the operation/mission objectives.

1.5.2.2. Operation/mission objectives that will not be met if the proposed plan must be modified as suggested by Range Safety or is not approved.

1.5.2.3. Alternate or modified plans that will accomplish the operation/mission objective.

1.5.2.4. Effects on the operation/mission such as cost, schedule, data requirements, vehicle reliability, reserve propellants, and launch window, if the plan must be modified or if the plan is not approved.

1.5.2.5. Other data the Range User may wish to submit.

1.6. Range User Responsibilities. Range Users shall be responsible for the following:

1.6.1. Submitting all data identified as requirements for Range Safety support of planned operations.

1.6.2. Complying with data submission lead times and Range Safety approval conditions.

1.6.3. Advising Range Safety of changes to operational scenarios to determine if approvals are affected.

1.6.4. Providing specific data required for the scheduled operation day.

1.6.5. Ensuring accuracy and relevancy of all data to support the requests for approvals.

1.6.6. Providing anticipated trajectory data to the lead range when the Program Requirements Document (PRD) is submitted, when trajectories are changed, or when additional trajectories are added. Range Users should contact Range Safety for flight trajectory data preparation, submittal, and processing.

1.6.7. Revising theoretical trajectory data when use of the trajectory, as supplied, will adversely affect the support needed by either the planning or operational phases of the Range User program.

1.6.8. Providing hazard assessments (the process of identifying operation-related hazards, assessments of those hazards, and quantification of risk to establish operation constraints). **Note:** The hazards associated with each source of risk (debris impact, toxic chemical dispersion, and acoustic overpressure) have an associated set of critical parameters and thresholds of acceptability. Changes in the launch parameters, such as azimuth, payload, and launch site, and the need for flight safety controls, including the evacuation of personnel,

enforcement of road-blocks, and restriction of sea lanes or airspace, depend on the results of the hazard assessments.

1.6.9. Range User Range Tracking System Performance Requirements. The following requirements may apply to Range Users for range tracking. The range tracking system (RTS) consists of the hardware, software, and personnel required to transmit, receive, process, and display launch vehicle data for Range Safety purposes.

1.6.9.1. General. An RTS must include at least two adequate and independent instrumentation data sources. At least one of the instrumentation data sources shall be a Global Positioning System Metric Tracking (GPS MT) system, as required by the Under Secretary of the Air Force memorandum (GPS Metric Tracking) dated Sep 20, 2006. This requirement applies to all launches (DoD, Civil and commercial) from the Eastern and Western ranges. Waiver authority for this requirement is the SSC/CC. **Exception:** If an autonomous flight safety system is used, then a GPS tracking source is not mandated.

1.6.9.2. Tracking Source Adequacy and Accuracy. Each tracking source used for range safety, shall provide real-time state vector accuracy (position and velocity), timeliness, and reliability so that when extrapolated to the instantaneous impact point (IIP) space, the following criteria shall meet Range Commanders Council (RCC)-324 for Telemetered Inertial Guidance (TMIG) and GPS sources and shall meet RCC 262 for radar beacons.

1.6.9.2.1. Accuracy. The three-sigma (3σ) present position uncertainty, resulting from all error sources, shall be no greater than the following:

1.6.9.2.1.1. The launch area instantaneous impact point (IIP) ($IIP \leq 66,000$ feet) uncertainties are recommended not to exceed 330 feet for cross-range or down-range. Present position uncertainties, expressed as the square root of the sum of the squares of the errors in the three orthogonal axes, should not exceed 250 feet.

1.6.9.2.1.2. The midcourse IIP ($IIP > 66,000$ feet) cross-range uncertainties should not exceed 0.5 percent of the vacuum IIP range, and down-range uncertainties are recommended not to exceed 1.0 percent of the vacuum range.

1.6.9.2.1.3. The terminal area IIP uncertainties shall be IAW SSCI 91-701.

1.6.9.3. Tracking Source Independence. Each tracking source used for range safety shall be electrically, mechanically, and structurally separate from each other so that one tracking source will not influence another tracking source.

1.6.9.4. RTS Ground System Lightning Protection. All range tracking systems (RTS) must have a ground lightning protection system IAW SSCI 91-701.

1.6.9.5. RTS backup power. The RTS shall have backup electric power that allows failover without affecting operating equipment condition. RTS shall not be interrupted by automated software updates or automated network maintenance or scheduled maintenance during operations.

1.6.9.6. RTS minimum displays requirements. The RTS shall display at a minimum, the present position, predicted impact point, at least two tracking sources, maps that can cover the full range the vehicle can fly, critical event points, flight safety system (FSS) health status, mission time, and altitude.

Chapter 2

FLIGHT ANALYSIS APPROVAL AND DATA REQUIREMENTS

2.1. Introduction. The Range User shall initiate flight analysis approval at the earliest practical date to establish that the proposed program is acceptable from a safety standpoint. Early action by the Range User keeps data requirements to a minimum and ensures that the effort and expense of planning a program or computing pre-operation trajectories is not wasted. The specific approval depends on the type of program activity. Developing the safest operation consistent with program objectives can take several months while changes in the proposed plan are made. This chapter is subdivided into four distinct classes of flight analysis approvals: Flight Plan Approval (FPA) and Data Requirements, Aircraft/Ships Intended Support Plans (ISP) Approval and Data Requirements, Directed Energy Plan (DEP) Approval and Data Requirements, and Large Nuclear Systems Approval and Data Requirements.

2.1.1. Security and Data Delivery Lead Times.

2.1.1.1. Proprietary Data and Security. The Range User shall clearly identify and mark any proprietary data. The Range User shall also provide a Security Classification Guide for all classified program information.

2.1.1.2. Lead Times. Before Range Safety approval is granted, the Range User shall provide required data in specified formats IAW the lead times listed in **Table 2.1** Lead times may be modified depending on the complexity of the program. If the requirements are not provided within the lead-time specified, Range Safety may not be able to prepare all necessary safety criteria in time to support a proposed operation. In this event, the operation shall not be conducted until Range Safety can make adequate safety preparations.

Table 2.1. Data Requirements Documentation Lead Times.

Vehicle/Missile	Lead Time Before Launch (Calendar Days) (New/Existing)
Ballistic Missile	
Preliminary Flight Plan Approval (PFPA)	2Y/1Y
Final Flight Plan Approval (FFPA)	120D/60D
Space Vehicle. Single Flight Azimuth	
PFPA	2Y/1Y
FFPA	120D/60D
Project Firing Tables	7D
Space Vehicle. Variable Flight Azimuth	
PFPA	2Y/1Y
FFPA	12M/6M
Project Firing Tables	45D
Cruise Missile	
PFPA	2Y/1Y
FFPA	120D/60D
Small Unguided Rocket	
PFPA	2Y/1Y
FFPA	120D/60D
Aerostat/Balloon	
PFPA	2Y/1Y
FFPA	120D/60D
Projectile, Torpedo, Air-Launched Device	
PFPA	2Y/1Y
FFPA	120D/60D
Ship and Aircraft ISP	20 D
Directed Energy Systems	1Y/30D
Large Nuclear Systems	See paragraph 2.5.
UAS/UAV	
PFPA	6M/3M
FFPA	60D/30D

2.2. Flight Plan Approval and Data Requirements Overview. Flight plan approval (FPA) is applicable to the following programs: ballistic missile and space vehicles; cruise missiles; small unguided rockets or probes; aerostats or balloon systems; projectiles, torpedoes, non-propulsive air-dropped bodies, or any small devices to be flight tested.

2.2.1. Approval Phases. The FPA process incorporates two formal approval phases: Preliminary Flight Plan Approval (PFPA) and Final Flight Plan Approval (FFPA).

2.2.1.1. Programs usually fall into two categories: new or existing. New programs include existing programs whose FPA supporting data has changed significantly. New programs shall submit the data requirements for both PFPA and FFPA. Existing programs generally shall submit the data requirements for only FFPA. For either new or existing programs that do not involve long lead times for planning or payload development, formal approval may, of necessity, occur only a few months before the desired operation date.

2.2.1.2. In each FPA phase, Range Safety shall respond to the Range User's written request for approval in one of the following ways: (1) by issuing a letter of approval, (2)

by issuing a letter of disapproval, (3) by requesting that a change in the proposed plan be made or evaluated, or (4) by requesting additional data. After all the requested data have been provided and evaluated, the Range User shall be given an “approval,” “conditional approval,” or “disapproval” letter. If the flight plan or mission is approved, the letter shall specify the conditions of approval pertaining to such things as launch azimuth limits, trajectory shaping, wind restrictions, locations of impact areas, times of discrete events, and number of operations for which the approval applies. The approval shall be final as long as the operation(s) remain within the stated conditions. If significant changes to the flight plan occur after approval has been granted, further analysis of the revised plan may be necessary. The Range User is responsible for advising Range Safety of any such changes or anticipated changes as early as possible.

2.2.2. Data Requirements. Data requirements for the PFPA and FFPA are found in two chapters of this volume. The requirements in **Chapter 2** of this volume apply to all programs. Requirements for specific programs, including detailed analyses, are in **Chapter 3** of this volume. All requirements may be tailored by Range Safety, as required. The Preliminary Flight Data Package (PFDP) and the Final Flight Data Package (FFDP) are submitted in support of the PFPA and FFPA, respectively. The following general format, which conforms to the order in which requirements are established, is suggested for any Range User who desires a standard submission form. If this format is adopted and the information submitted in response to a requirement cannot easily be placed in the data package, it should be made an appendix to the specific part. For example, compact disks and listings for trajectories would be an appendix to Part III in the format shown in **Figure 2.1**.

Figure 2.1. General Format.

- | |
|---|
| <ul style="list-style-type: none">• Table of Contents• Part I. Introduction• Part II. General Vehicle Data• Part III. Trajectory Data• Part IV. Additional Data |
|---|

2.2.3. Preliminary Flight Plan Approval (PFPA) and Data Package Requirements.

2.2.3.1. PFPA. The FPA process for all new programs begins with an introductory meeting followed by the submittal of required data and a formal written request for a PFPA. Existing programs shall also request a PFPA when previously approved supporting data is not applicable to the planned operation. The purpose of the PFPA is to ensure range safety requirements are included in the overall system design and to determine if the specific program is conceptually acceptable. In preliminary meetings, Range Safety can define acceptable flight limits and conditions, specify which parts of the flight plan need special emphasis, and identify requirements applicable to the program. Data regarding anticipated flight trajectories, booster configuration, and flight safety system (FSS) configuration shall be included in the PFPA. Lack of some pertinent data should not be cause for delaying the initial written request, particularly if preliminary discussions have not been held. The Range User should begin PFPA action during the Preliminary Design Review (PDR) phase of the program planning or, in any event, immediately after Range Safety has replied to the Program Introduction (PI) in a Statement of Capability. For new programs, the PFPA

usually occurs at least two years (one year for existing programs) before the planned operation.

2.2.3.2. Preliminary Flight Data Package Requirements. In addition to the program-specific requirements listed in **Chapter 3** of this volume, the PFPA data package shall include the following:

2.2.3.2.1. Basic program description and objectives including number, designation, and purpose of operation(s) for which the proposed flight plan is applicable.

2.2.3.2.2. General operation scenarios and proposed target areas and a statement indicating whether the proposed trajectory (or flight plan) is similar to some prior operation.

2.2.3.2.3. Intended launch or flight test date(s).

2.2.3.2.4. Map and listing of downrange and crossrange vacuum instantaneous impact points (IIPs) for each second of powered flight time.

2.2.3.2.5. General description of launch vehicle and payload in sufficient detail for hazard assessment providing the following information:

2.2.3.2.5.1. Type, weight, and trinitrotoluene (TNT) equivalency of all propellants.

2.2.3.2.5.2. Description of ordnance items.

2.2.3.2.5.3. Description of toxic and radioactive materials.

2.2.3.2.5.4. Characteristics of high-pressure vessels, lasers, and batteries.

2.2.3.2.5.5. Description of materials, thickness, and safety factors of pressure vessels.

2.2.3.2.5.6. Thrust and burn times of motors and thrusting devices.

2.2.3.2.5.7. Description of guidance and control system.

2.2.3.2.5.8. Drawings and diagrams showing structural arrangement and layout of significant components in each stage or payload.

2.2.3.2.6. General description and location of the airborne FSS (made up of the command and automatic destruct subsystems) or statement indicating that the planned system is similar to one already in use. Range Safety shall be involved before the PDR time frame if a new design is to be considered.

2.2.3.2.7. Preliminary estimate of fragment characteristics such as number, composition, dimensions, and weight due to all potential modes of vehicle breakup such as destruct and aerodynamic loading.

2.2.3.2.8. Tracking aids such as C-Band transponder, global positioning system (GPS) receivers/translators installed in the vehicle that can be used for flight safety purposes and their locations in the stages or sections.

2.2.3.2.9. Telemetry measurement listing and data word definitions.

2.2.3.2.10. Description of launch site facilities, support buildings, and the structural integrity information for each of these.

- 2.2.3.2.11. Geodetic latitude, longitude, and designation of proposed launch site, or location on the earth's surface for launches that occur above or below the earth's surface; if launch or test initiation can occur inside an area rather than at a single specified location, this area shall be defined.
- 2.2.3.2.12. Launch azimuth for single azimuth launches or desired azimuth sector(s) for variable azimuth launches.
- 2.2.3.2.13. Estimates of the nominal impact point and the three-sigma drag-corrected dispersion area for each jettisoned body.
- 2.2.3.2.14. Buoyancy analysis of all jettisoned bodies that impact water; for bodies that remain buoyant after impact and present a hazard to maritime vessels or platforms, a means of sinking or recovering the body is required. If recovery is desired, a recovery procedure shall be identified. The buoyancy analysis shall include the following:
- 2.2.3.2.14.1. Description of object, size, weight, general description of materials, and color.
 - 2.2.3.2.14.2. Description of object's orientation in water. If more than one orientation is possible, then provide probabilities for each orientation.
 - 2.2.3.2.14.3. Time duration measured from impact it will take the body to completely sink below deepest draft of expected vessels in area. If more than one orientation is possible, then provide time durations for each orientation.
 - 2.2.3.2.14.4. Plot showing potential regions of drift based on nominal impacts. If more than one orientation is possible, then annotate on the map when each orientation would sink.
 - 2.2.3.2.14.5. Description of any hazardous items, such as unexploded ordinance, pressure vessels, and hazardous chemicals.
 - 2.2.3.2.14.6. Description of vessel types that the body would pose a hazard to, and the rationale.
 - 2.2.3.2.14.7. If requested to provide a hazard analysis predicting probability of contact with maritime traffic, include sources of data and vessel classifications.
- 2.2.3.3. Reliability and Malfunction Analysis Data Requirements. Reliability of each stage and probability of a normal mission or failure rate data for each stage shall be provided. The following data shall be provided:
- 2.2.3.3.1. Description of failure modes that can result in an abnormal flight. An analysis of all subsystems shall be made to determine failure modes that would result in a catastrophic event. Typical malfunctions that should be considered include failure of the propulsion system, failure of the hydraulic and electrical systems, failure of the guidance and control system, failure of separation mechanisms between stages, failures that lead to premature thrust termination, overshoot, or shifting of the platform reference.
 - 2.2.3.3.2. An estimate for the probability of occurrence or failure rate (versus time) for each failure mode and an explanation of the method(s) used for the estimate; any other

information considered pertinent with respect to critical portions of flight, such as vehicle stability characteristics and structural limits.

2.2.3.3.3. Description of all credible failed vehicle response modes. A response mode is a category of vehicle dynamic response, including vehicle breakup, which results from one or more failure modes. At a minimum, the response modes should include on-trajectory failures such as thrust termination and explosion and malfunction turn failures (loss of thrust vector control, tumble turn, nozzle burn-through failures). On-trajectory failures should be subdivided according to the type of breakup (for example, aerodynamic or explosive) that will result. Malfunction turn failures should be subdivided into tumble turns and trimmed turns if trimmed turns are a credible response mode.

2.2.3.3.4. Summary of past vehicle performance giving number launched, launch location, number that performed normally, and number that malfunctioned, behavior and actual (if available) or estimated impact location (of the vehicle or vehicle debris) for those that malfunctioned, time and nature of malfunction, and corrective action.

2.2.3.4. Propellant Description. If a vehicle has the capability of exploding as a result of self-initiation, FSS activation, or ground or water impact or if a vehicle uses propellants that are toxic in gaseous or vapor states due to combustion or release to the atmosphere, the following data shall be provided:

2.2.3.4.1. Types of propellant or a statement indicating the same propellant formulation is already in use. The following thermodynamic and chemical information shall be provided for each propellant type used on the vehicle:

2.2.3.4.1.1. List of major chemical constituents. A major constituent is defined as a chemical component that (1) constitutes more than 1 percent of the propellant mass, (2) is a toxic chemical, or (3) produces a toxic combustion product. The list of combined constituents shall account for at least 99 percent of the total propellant mass.

2.2.3.4.1.2. Chemical formula for each major constituent.

2.2.3.4.1.3. Mass fraction of each major constituent relative to the total mass propellant.

2.2.3.4.1.4. Reference temperature of chemical constituents in their normal state; for example, 25 °C.

2.2.3.4.1.5. Enthalpy of formation for each chemical constituent at the reference temperature (calorie/gram-mole).

2.2.3.4.1.6. Designation of each chemical constituent as fuel or oxidizer (F or O).

2.2.3.4.1.7. Molecular weight of each chemical constituent.

2.2.3.4.2. TNT equivalency of remaining propellant versus flight time and explosion scenario for each separate stage (or motor) and each possible combination of stages that could result from malfunction conditions.

2.2.3.4.3. An estimate of the probability of explosion versus flight time for each of the following: self-initiation, FSS activation, and ground or water impact. A comprehensive description of the methods used to derive the estimate shall be provided.

2.2.3.4.4. Description of methods used to minimize the possibility of explosion.

2.2.3.4.5. Time of day when launches will be scheduled and the number of launches.

2.2.3.4.6. Maximum total quantities of liquid and solid propellants.

2.2.3.4.7. Nominal vehicle altitude versus time through 3,000 meters in the format shown in [Figure 2.2](#).

Figure 2.2. Nominal vehicle altitude versus time.

$$t = a * z^b + c$$

Where:

t = time (seconds) after ignition

z = height (meters) of the vehicle above ground

a, b, and c = coefficients found by a least squares fit to an estimated time-height profile

2.2.3.4.8. Exhaust plume heat content (calorie/gram), mass flux (gram/second), and chemical composition (mass fractions and chemical species) for all motors ignited at liftoff. This data shall be evaluated at a point sufficiently far downstream from the nozzle exit plume such that plume afterburning is essentially complete and the plume has expanded and cooled sufficiently to allow high temperature combustion species to have completed recombination actions. Total mass flux shall indicate nominal engine burn propellant mass flux as well as entrained air mass flux. Documentation of this data shall include reference to the method of calculation, distance downstream from the nozzle, possible chemical interactions between main engines and strap-on boosters (if appropriate), and radiation heat loss. Chemical composition of the plume shall cover all major species such that (1) at least 99 percent of total plume mass is represented, and (2) all major toxic species are included. Chemical species of concern to Range Safety include, but are not necessarily limited to, hydrogen chloride (HCl), carbon dioxide (CO₂), carbon monoxide (CO), aluminum oxide (Al₂O₃), hydrazine (N₂H₄), unsymmetrical dimethyl-hydrazine (H₂NN(CH₃)₂), monomethyl hydrazine (CH₃NH₂), nitrogen tetroxide (N₂O₄), nitrogen dioxide (NO₂), nitric acid (HNO₃), nitrosodimethylamine (C₂H₆N₂O), formaldehyde dimethyl hydrazine, benzene (C₆H₆), toluene (C₇H₈), and other volatile organic compounds.

2.2.3.4.9. Solid propellant burn time (seconds) and average burn rate (grams/seconds) for propellant fragments burning at 1 atmosphere of pressure following an accidental FSS-initiated destruct for each motor containing solid propellant. Fuel fragmentation assumptions (number and size of fragments, surface area, inches/second burn rate) used to generate the average solid propellant burn time and mass burn rate shall be included.

2.2.3.4.10. Liquid propellant expenditure rate (grams/seconds) for nominal launch for the first 3,000 meters of vehicle ascent.

- 2.2.3.4.11. For catastrophic abort or FSS vehicle destruct of vehicles using liquid propellants, the information described below is required to support Range Safety toxic risk analyses. Depending on the similarity of the program vehicle's propellants to existing vehicle propellants, the Range User may be required to perform significant additional technical analyses to provide this information.
- 2.2.3.4.11.1. Percentages of available liquid fuel and oxidizer mixed and reacted within each stage during the first several hundred milliseconds of the initiating destruct mechanism.
 - 2.2.3.4.11.2. Percentage of available liquid propellants mixed and reacted during the active fireball burn phase that typically last several seconds past the initiating event. Provide assumptions about the degree of mixing and the nature of chemical reaction between vehicle stages, including solid rocket motors and the extent of air entrainment and after-burning of fuel species.
 - 2.2.3.4.11.3. Percentage of available liquid propellants dispersed by vehicle explosion that do not undergo chemical reactions but remain as vaporized unreacted propellant. The objective of obtaining this information is to characterize and quantify the types of chemical reactions among the vehicle propellants so that the chemical composition and total heat content of the liquid propellant fireball can be computed from input reactant data.
- 2.2.3.4.12. Initial Exhaust Cloud Data. The following information shall be provided to specify the initial parameters required to calculate buoyant cloud rise in support of Range Safety toxic risk analyses. These values describe the exhaust ground cloud when the horizontal momentum produced by the ducting or reflection in the launch mount becomes negligible compared to the buoyant forces within the cloud for the nominal launch scenario. Depending on the similarity of the program vehicle to existing vehicles, the Range User may be required to perform significant additional technical analyses to provide this information.
- 2.2.3.4.12.1. Initial exhaust ground cloud radius for normal launches. Assume a spherical cloud with a volume equivalent to that estimated for the actual ground cloud.
 - 2.2.3.4.12.2. Initial radius of the area over which solid propellant fragments are dispersed due to a vehicle abort on the pad. For aborts during the first 50 seconds of flight, provide estimates of solid propellant fragment number, size, mass, ballistic coefficient, explosion-induced fragment velocity, and nominal vehicle position; and, at 10-second intervals, velocity vector.
 - 2.2.3.4.12.3. Vertical velocity of the ground cloud centroid for nominal launch cases.
 - 2.2.3.4.12.4. Initial ground cloud centroid height (meters above ground level [AGL]).
- 2.2.3.5. Explosive Reentry Vehicle or Warhead Information. An operation that includes the use of an explosive reentry vehicle (RV) or warhead shall not be conducted without the approval of the SLD Commander. For these operations, the following data are required:

- 2.2.3.5.1. A complete justification for the proposed operation.
 - 2.2.3.5.2. The proposed position and altitude of the RV or warhead detonation point.
 - 2.2.3.5.3. The effects of the detonation on the missile and RV or warhead in terms of number, weights, cross-sectional areas, ballistic coefficients, and velocities imparted to the pieces.
 - 2.2.3.5.4. The impact dispersion area for all fragments including diffusion and dispersion of any toxic or radioactive clouds or fragments and the radiation exposure characteristics.
- 2.2.4. Final Flight Plan Approval (FFPA) and Data Package Requirements.

2.2.4.1. FFPA. The FFPA is applicable to each program operation. The FFPA is based on detailed analyses of the operation objectives, vehicle performance, and other data items required. In response to the Range User request, the FFPA is issued when the Chief of Safety is satisfied that a specific operation can be supported within the limits of flight safety control capabilities to provide positive protection to life and property. Any constraints or conditions identified in the PFPA may be superseded by those stated in the FFPA. The FFPA applies to a specific operation and does not guarantee that similar operations will receive an FFPA. If a program consists of identical operations, a blanket FFPA may be granted that would remain in effect throughout the life of the program as long as the operations remain within the specified safety constraints. The request for FFPA and the supporting data are typically received by Range Safety at 120 calendar days (new programs) or 60 calendar days (existing programs) before the planned operation. Past data submittals may be referenced if that data has not changed from previous operations.

2.2.4.2. Final Flight Data Package Requirements.

2.2.4.2.1. General. These data requirements apply to requests for FFPA for all programs specified in [paragraph 2.2](#). The analysis-specific data requirements in [Chapter 3](#), paragraphs [3.1](#) through [3.7](#) of this volume are also required before an FFPA is issued. The FFDP shall include items that were changed from or not provided in the PFDP. The FFDP is made up of the data requirements used to produce the final set of operational rules and flight control criteria and ensures all data complies with the conditions of the PFPA and data format requirements. The request for FFPA shall specify the operation designation, intended operation date, and references to all applicable supporting data products. In meeting the FFPA requirements, some of the information submitted by the Range User may not change from the PFDP or from operation to operation. In such cases, the information need be supplied only once. However, for each operation, the Range User shall state in writing which supporting data are applicable and specify the document, page number, and paragraph where each required item can be found. In other cases where the proposed plan deviates from the PFPA or previously accepted limits, additional data shall be provided.

2.2.4.2.2. Limits of a Useful Mission.

2.2.4.2.2.1. These data requirements apply solely to space operations. They are used to establish guidelines or limits for land overflight prior to orbital insertion.

2.2.4.2.2.2. The permissible limits for overflight depend not only on this data, but

also on estimated overflight hazards, the operational objectives, and the importance of these objectives. The Range User shall provide the following data:

2.2.4.2.2.2.1. Launch azimuth limits for which the primary operation objectives can be met and for which a useful orbit can be attained.

2.2.4.2.2.2.2. Operational objectives that will be met or the extent to which the primary objectives will be degraded.

2.2.4.2.2.2.3. Description of limiting orbit(s) (apogee, perigee, period, and inclination) as a function of overflight azimuth.

2.2.4.2.2.2.4. Circumstances or types of malfunctions that could cause the vehicle to fly outside the three sigma limits of normality, but remain within the limits for which a useful orbit can be attained.

2.2.4.2.2.2.4.1. The probability of occurrence of these malfunctions.

2.2.4.2.2.2.4.2. The effects of these malfunctions on the success of succeeding burns or stages.

2.2.4.2.2.2.5. The most lofted and depressed trajectories for which the primary operation objective can be met and for which a useful orbit can be attained, given the information requested in paragraphs [2.2.4.2.2.2.1](#) through [2.2.4.2.2.2.4.2](#). In deriving these trajectories, only perturbations that result in deviations in the pitch plane shall be considered. If these trajectories cannot be provided to Range Safety, any one of the following may be substituted:

2.2.4.2.2.2.5.1. If the stage that achieves orbit does not contain an FSS, the Range User shall provide the upper and lower altitude limits at shutdown of the last suborbital stage if the succeeding stage is to attain a useful orbit.

2.2.4.2.2.2.5.2. If the stage that achieves orbit contains an FSS, the Range User shall provide the upper and lower altitude limits as the vacuum impact point reaches the continent to be overflowed by the first orbital stage if this stage is to attain a useful orbit.

2.2.4.2.2.2.5.3. The Range User shall provide the minimum impact range that the last suborbital stage must achieve, if the succeeding stage is to attain a useful orbit and a minimum orbit (perigee > 70 nautical miles).

2.2.4.2.3. Solid Propellant Data Requirements. The following data are required for solid propellants:

2.2.4.2.3.1. Burning rate of solid propellants, in inches/second, as a function of pressure, including ambient atmospheric pressures.

2.2.4.2.3.2. Percent propellant TNT equivalency for each stage as a function of relevant impact parameters, such as weight of propellant, impact velocity, surface composition, and impact geometry.

2.2.4.2.3.3. Stage ignition and burn time, propellant weight versus time, and propellant density.

2.3. Aircraft/Ship Intended Support Plans (ISP) and Data Package Requirements.

2.3.1. Purpose. The purpose of the ISP approval is to ensure maximum safety consistent with the operation objectives. To the extent possible, this means that support positions and flight plans can be established outside a 1×10^{-5} hit-probability contour for a specific support aircraft, or outside a 1×10^{-4} hit-probability contour for a specific support vessel. When the required support data cannot be collected from such remote locations, support positions located in relatively hazardous areas shall be carefully planned to minimize the ship or aircraft hit probability. Hazards to ships and aircraft exist primarily in the launch area, along the flight azimuth where jettisoned stages and components reenter and breakup, and in the target area where reentry vehicles and final stages impact. ISP approval is applicable to each ship and aircraft supporting an operation requirement identified in the Universal Documentation System (UDS) or participating in an operation on a non-interference basis. Additional information for control of SLD 45 test support aircraft is provided in Space Launch Delta 45 Instruction 13-201 (SLD45I 13-201), *Eastern Range Airspace*. Similar regulations for ships do not exist.

2.3.2. ISP Development and Submittal. ISPs for ships and aircraft shall be developed either by the Range User or by support agencies that are responding to requirements contained in the PRD or the Operations Requirements (OR). In either case, the developing organization shall furnish the ISP for review and approval, either directly to Range Safety or through the Range Operations Squadron.

2.3.3. ISP Data Package Requirements. For operations requiring support aircraft or ships, the Range User shall provide the following additional information 20 calendar days before the mission. All identifying points and positions shall be time correlated using the operation start time as a reference.

2.3.3.1. Aircraft Flight Profile Requirements.

2.3.3.1.1. Type of aircraft.

2.3.3.1.2. Aircraft physical dimensions as described in Jane's aircraft publications. The following data shall be provided as a minimum:

2.3.3.1.2.1. One-half wingspan – the length of the wing measured from the fuselage to the wing tip edge.

2.3.3.1.2.2. Maximum width of the fuselage measured in the top view.

2.3.3.1.2.3. Average thickness of the wing measured in the side view.

2.3.3.1.2.4. Average fuselage thickness measured in the side view.

2.3.3.1.2.5. Overall area (in square feet) measured in the top view.

2.3.3.1.2.6. Overall perimeter (in feet) measured in the top view.

2.3.3.1.3. Call sign.

2.3.3.1.4. Registration Number ("N" number).

2.3.3.1.5. Tail number.

2.3.3.1.6. Warning area and mission area penetration points (entry and exit).

2.3.3.1.7. Holding fixes and altitudes.

2.3.3.1.8. Primary and alternate Mission Support Positions (MSPs), including geodetic latitude, longitude, heading, speed, and time of arrival.

2.3.3.1.9. Written and graphic flight path location describing the maneuvers within 200 miles of the MSP giving orbit or loiter locations, positions along ground track in latitude and longitude, turn points, turn radii where applicable, speeds, and headings.

2.3.3.1.10. Course, speed, and altitudes from the MSP to the terminal end of the data run.

2.3.3.1.11. Departure route after mission completion, including maneuvers for departure to recovery base.

2.3.3.1.12. Final staging and recovery bases.

2.3.3.2. Ship Cruise Profile Information.

2.3.3.2.1. Class of ship.

2.3.3.2.2. Dimensions of ship measured in the top view.

2.3.3.2.3. Call sign.

2.3.3.2.4. Registration Number.

2.3.3.2.5. Name.

2.3.3.2.6. Warning area and mission area penetration points (entry and exit).

2.3.3.2.7. Primary and alternate MSPs including geodetic latitude, longitude, heading and speed.

2.3.3.2.8. Course and speed from the MSP to the terminal end of the data run.

2.3.3.2.9. Planned location (support plan), both written and graphic, of the vessel during the period from launch until operation termination or impact.

2.4. Directed Energy Plan Approval and Data Requirements. These requirements apply to all forms of directed energy systems. Laser design, test, and documentation requirements are also addressed in SSCMAN 91-710 Volume 3, Chapter 8.2 (Laser Systems). Reasonable and prudent operational procedures shall be established so that hazards from directed energy system operations present virtually no risk to the general public.

2.4.1. Purpose. The purpose of the Directed Energy Plan (DEP) approval is to ensure the operation is conducted safely with consideration for the operation requirements and national need. The DEP approval applies to programs using directed energy systems. These systems include, but are not limited to, lasers and neutral particle and ion beams, with any combination of surface, air, or space locations for the energy source and target. In this volume, the term *laser* is used as a generic reference to all directed energy systems. In general, those laser operations in the following categories are subject to review:

2.4.1.1. Laser operations requesting range support through the provision of the UDS.

2.4.1.2. Laser illumination, for which an Operations Directive (OD) does not exist, conducted in conjunction with a scheduled range operation for which an OD does exist.

2.4.1.3. Laser operations having the potential to impair range safety controls or reduce the reliability of range safety systems.

2.4.2. DEP Submittal.

2.4.2.1. Requests for DEP approval shall be forwarded directly to Range Safety or through either the Plans Office for new programs or the Range Operations Squadron for existing programs. Lead times and requirements may vary and shall be tailored depending on the specific characteristics of the system and proposed operating scenarios. Lead times for data requirements reflect the dependence of mission success on planned laser operations. For instance, laser operations performed on a non-interference basis using scheduled launches as a target of opportunity will have lead times different from directed energy activities that are integral to a scheduled operation.

2.4.2.2. Laser operations considered mandatory by the Range User shall be included as part of the Program Introduction (PI). If the laser operation is not mandatory IAW Range User requirements, the initial request for laser program approval is desired at least one year before the planned operation date.

2.4.2.3. Requests for Range Safety review of recurring laser operations are desired 30 calendar days before each planned operation date.

2.4.2.4. Modifications to existing laser systems or changes to current operating plans should be discussed with Range Safety during the planning phase to determine the need for additional data requirements and establish mutually agreeable lead times for submission of additional data.

2.4.3. Laser Operational Procedures.

2.4.3.1. Avoidance Volume.

2.4.3.1.1. The avoidance volume shall encompass that portion of the laser beam that can cause either permanent or temporary ocular impairment.

2.4.3.1.2. The computation of the avoidance volume radial distance from the center of the laser beam shall consider, at a minimum, the following variables:

2.4.3.1.2.1. Time delays between aircraft detection and laser termination.

2.4.3.1.2.2. Average aircraft speeds.

2.4.3.1.3. Laser operating parameters and the reliability of system controls.

2.4.3.1.4. Laser beam azimuth and elevation restrictions shall be defined so that the laser beam avoidance volume is constrained to airspace for which an approved surveillance capability has been established.

2.4.3.2. Airspace Surveillance.

2.4.3.2.1. Organizations conducting laser operations shall provide for an airspace surveillance capability and procedures that ensure the laser operation can be terminated before a non-participating aircraft enters the pre-defined laser beam avoidance volume.

2.4.3.2.2. The American National Standard Institute (ANSI) ANSI Z136.1, *Safe Use of Lasers*, and ANSI Z136.6, *Safe Use of Lasers Outdoors*, require coordination with

the Federal Aviation Administration when laser programs include the use of Class 3a, 3b, and 4 lasers within navigable airspace. For range safety purposes, airspace control is a desirable safety measure; however, it is considered a secondary protection measure to surveillance requirements. Airspace controls shall be initiated by Range Safety when the value added to safety is justifiable.

2.4.3.3. Weather Constraints. The laser operation shall be terminated during periods when weather conditions obstruct or adversely affect an approved surveillance method.

2.4.4. DEP Data Package Requirements.

2.4.4.1. General Data. The following data are required for each operation or group of operations. Additional data may be required depending on the laser system.

2.4.4.1.1. Complete description of surveillance methods, surveillance range limits, and a description of the procedures used to terminate laser operations when necessary.

2.4.4.1.2. General information on the purpose of the operation.

2.4.4.1.3. Description of the laser and its operation.

2.4.4.1.4. Laser classification IAW ANSI Z136.1.

2.4.4.1.5. Description of operation scenarios and proposed target areas.

2.4.4.1.6. Copies of safety analyses and test procedures conducted on the system.

2.4.4.1.7. Laser Emission Characteristics:

2.4.4.1.7.1. Mode of operation (continuous wave or pulsed).

2.4.4.1.7.2. Wavelength (nanometers).

2.4.4.1.7.3. Energy per pulse in Joules for pulsed lasers or power in watts for continuous wave lasers.

2.4.4.1.7.4. Pulse repetition frequency (Hertz).

2.4.4.1.7.5. Pulse width and separation (seconds).

2.4.4.1.7.6. Beam diameter – the diameter of a circular beam at a point where the intensity drops to $1/e$ (0.368) of its maximum value usually located at the exit aperture or at the waist if convergent beam (centimeters).

2.4.4.1.7.7. Beam divergence angle at the aperture or waist (radians).

2.4.4.1.8. Number and designation of laser operations to which the proposed operation applies.

2.4.4.1.9. A statement indicating whether the proposed operation is similar in its safety aspects to that of some prior operation for which documentation is available.

2.4.4.1.10. Intended operation dates.

2.4.4.1.11. Functional description of the target acquisition and laser firing process and of any error/failure detection and correction or termination capability, including its reliability and response time.

2.4.4.2. Scenario Type. The scenario type can be any combination of the following:

- 2.4.4.2.1. Fixed laser and/or target.
- 2.4.4.2.2. Moving laser and/or target.
- 2.4.4.3. Laser and Target(s) Position Data.
 - 2.4.4.3.1. Fixed – latitude, longitude, and altitude where laser beam exits the protective housing of each target.
 - 2.4.4.3.2. Moving – position and velocity vector versus time of each object in an Earth Centered Earth Fixed (ECEF) Coordinate System.
- 2.4.4.4. Nominal Operation Scenario Data. The following information shall be provided:
 - 2.4.4.4.1. Desired operating azimuth and elevation sectors.
 - 2.4.4.4.2. Event times; for example, acquisition, arming, and firing on/off times.
 - 2.4.4.4.3. Duration of each laser firing (seconds).
 - 2.4.4.4.4. Slew rate (radians/seconds).
 - 2.4.4.4.5. Hardware and software stops (angles from forward direction, radians).
 - 2.4.4.4.6. Pointing accuracy (radians); brief description of laser beam pointing aids including their location.
 - 2.4.4.4.7. Laser platform/vehicle attitude control accuracy (static, radians; dynamic, radians/seconds).
- 2.4.4.5. Target Data.
 - 2.4.4.5.1. Target size - radius or height, width, and length.
 - 2.4.4.5.2. Orientation - angle of each target surface with respect to the incident beam.
 - 2.4.4.5.3. Type of reflection possible, such as specular or diffuse.
 - 2.4.4.5.4. Reflection coefficients.
- 2.4.4.6. Exposure Controls. Exposure controls shall be calculated IAW ANSI Z136.1.
 - 2.4.4.6.1. Maximum Permissible Exposure (MPE) level, nominal optical hazard distance in vacuum, and other applicable hazard ranges for each laser.
 - 2.4.4.6.2. Description of the maximum region around each target that can be subjected to the hazard during a nominal operation.
 - 2.4.4.6.3. Reflection characteristics of other significant objects in the hazard region around each target. The hazard region is the zone where the laser radiation levels may exceed the MPE level.
- 2.4.4.7. Risk Study. In some instances, laser operations may include test parameters or characteristics that may not allow for the laser beam to be safely contained within a predicted control volume. In such cases, Range Safety may require a risk study. If a risk study is required, the following data shall be submitted:
 - 2.4.4.7.1. Probability of Occurrence Data. The probability of occurrence versus time of operation for each of the following generic hazard modes (modes of beam control

error or failure): pointing error, inadvertent slewing, premature firing, delayed firing, beam focusing error, loss of focus, and other modes such as wrong target acquisition applicable to the system. If the probability of occurrence is non-zero for any of these hazard modes, then probability distributions for the random hazard mode parameters describing how each mode can occur over time shall be provided. The following parameters describe each of the stated failure modes:

2.4.4.7.1.1. Pointing Error Hazard Mode. Offset angle (radians) between the correct laser system to target pointing direction and the incorrect pointing direction (angle assumed constant during a firing).

2.4.4.7.1.2. Inadvertent Slewing Hazard Mode.

2.4.4.7.1.2.1. Time (seconds) during firing at which the inadvertent slewing starts.

2.4.4.7.1.2.2. Azimuth angle (radians measured from North) of the slew plane; it is assumed that, over time, the laser-to-target line remains contained in a plane.

2.4.4.7.1.2.3. The angular rate (radians/seconds) of slewing in the plane (rate assumed constant).

2.4.4.7.1.2.4. Duration of the slewing (seconds), if other than that of the nominal firing time remaining after the start of the slewing.

2.4.4.7.1.3. Premature Firing Mode. The number of seconds before the nominal start time that laser firing occurs.

2.4.4.7.1.4. Delayed Firing Termination Mode. The number of seconds after the nominal termination time that laser cutoff occurs.

2.4.4.7.1.5. Beam Focusing Error Mode. The range (meters) along the laser-to-target vector at which the convergent beam is misfocused; the incorrect range can either be too long or too short relative to the nominal focus range.

2.4.4.7.1.6. Loss of Focus Mode.

2.4.4.7.1.6.1. Time (seconds) during firing at which the loss of focus occurs.

2.4.4.7.1.6.2. Beam divergence angle (radians) that measures the spreading of the beam (assumed to remain centered on the laser-to-target vector).

2.4.4.7.2. Failure Modes, Effects, and Criticality Analysis (FMECA):

2.4.4.7.2.1. Applicable hazard modes shall be defined and documented by a FMECA IAW ANSI/American Institute of Aeronautics and Astronautics (AIAA) S-102.2.4-2015, *Capability-Based Product Failure Mode, Effects and Criticality Analysis (FMECA) Requirements*, or an equivalent standard.

2.4.4.7.2.2. Their probabilities of occurrence and the probability distributions of their descriptive parameters shall be quantified with fault tree analysis or the equivalent.

2.4.4.7.2.3. The level of analysis conducted in each case shall be the level at which

appropriate component error/failure data are available.

2.4.4.7.2.4. If necessary for confidence in the results, analyses of the effects of the uncertainties in the component data shall be carried out.

2.4.4.7.3. Alternative Data Submission. The Range User may arrange to have the risk study done by Range Safety. The following data shall be provided to support this option:

2.4.4.7.3.1. System design description and performance data and functional and reliability block diagrams for portions of the system affecting beam control, including platform attitude control.

2.4.4.7.3.2. Associated component (including hardware, software, and human) reliabilities or, at a minimum, component and component environment descriptions allowing the estimation of these reliabilities.

2.4.5. Coordination with the United States Space Command (USSPACECOM) Laser Clearinghouse. Coordination with the USSPACECOM Laser Clearinghouse is required for all Class 3 and 4 lasers operated outside of a confined laboratory environment. Unless waived by the USSPACECOM Laser Clearinghouse, firing time coordination for those systems shall be accomplished to verify that on-orbit objects of national interest are not affected by the laser operation.

2.5. Large Nuclear Systems Approval and Data Requirements. Range Users employing radioactive materials that exceed the limits established by the Office of Science Technology Policy (OSTP) shall comply with National Security Presidential Memorandum 20 (NSPM-20), *Launch of Spacecraft Containing Space Nuclear Systems*. The Range User shall provide Range Safety with a copy of the following documents. **Note:** nuclear system design, test, and documentation requirements are also addressed in SSCMAN 91-710 Volume 3.

2.5.1. Environment Impact Statement: L-3 years.

2.5.2. Final Safety Analysis Report: L-1 year.

2.5.3. Interagency Nuclear Safety Review Board (INSRB) Safety Evaluation Report: L-7 months. In the event that the INSRB is not impaneled by the OSTP, the provisions of the latest version of Department of the Air Force Manual (DAFMAN) 91-110, *Nuclear Safety Review and Launch Approval for Space or Missile Use of Radioactive Material*, shall be performed by the Chief, Weapons, Space and Nuclear Safety Division and the results provided to Range Safety in lieu of the INSRB Safety Evaluation Report.

2.5.4. Certification of Presidential Approval for Flight: L-10 days. A copy of the OSTP approval letter or the National Security Council approval letter meets this certification requirement.

Chapter 3

PROGRAM-SPECIFIC FLIGHT ANALYSES

3.1. Trajectory Analysis.

3.1.1. General. The Range User shall perform a trajectory analysis to determine a vehicle's nominal trajectory and potential three-sigma trajectory dispersions about the nominal trajectory. The Range User's trajectory analysis shall also determine, for any time after liftoff, the limits of a launch vehicle's normal flight. "Normal flight" is defined as a properly performing vehicle whose real-time IIP does not deviate from the nominal IIP by more than those of three-sigma dispersed trajectories generated according to [paragraph A2.2.4](#) of this volume.

3.1.2. Trajectory Analysis Products.

3.1.2.1. Ballistic Missiles and Space Vehicles.

3.1.2.1.1. Ballistic Missile and Space Vehicle PFDP. The following data are required in addition to the data requirements specified above in [paragraph 2.2.3](#).

3.1.2.1.1.1. Nominal Trajectory. Position and velocity vectors as a function of time from liftoff until the vehicle attains an altitude of 100,000 feet (may vary depending on the program). If position and velocity components are not available, ground range and altitude may be substituted for the position vector, and the total earth-fixed velocity and flight path angle may be substituted for the velocity vector. The data should be provided in time increments no larger than 5 seconds (may vary depending on the program).

3.1.2.1.1.2. Maps.

3.1.2.1.1.2.1. A map showing the planned vacuum locus of impact points for the intended flight azimuth or azimuth sector. The vacuum impact points at times of discrete events, such as arming of engine cutoff circuits, ignition of upper stages, firing of retro-rockets, and the end of burns that occur before orbital insertion, shall be indicated.

3.1.2.1.1.2.2. A map showing the best estimates of mean impact points and the three-sigma drag-corrected impact dispersion area for each jettisoned body.

3.1.2.1.1.3. Orbit Parameters and Sequence of Events. The following data should be provided for space vehicles only:

3.1.2.1.1.3.1. Apogee, perigee, period, and inclination of intended orbits.

3.1.2.1.1.3.2. The approximate times from liftoff when engine cutoff circuits are armed, when upper stages will be cutoff by backup devices, and when control modes will be switched.

3.1.2.1.2. Ballistic Missile and Space Vehicle FFDP. The following data are required in addition to the data requirements specified above in [paragraph 2.2.4](#):

3.1.2.1.2.1. Trajectories. These requirements identify the types of trajectories required for the following flight plans. All trajectories shall be developed using the

procedures and format described in [Attachment 2](#) of this volume.

3.1.2.1.2.1.1. Single Flight Azimuths. See [Table A2.1](#) of this volume (Items 1-8).

3.1.2.1.2.1.2. Variable Flight Azimuths. Space vehicle launches with variable flight azimuths shall provide a complete set of firing tables detailing launch times and flight azimuths for each day of the launch window (see [Table A2.2](#) of this volume).

3.1.2.1.2.1.3. Multiple Liquid Propellant Engines Thrusting at Liftoff. For single or variable azimuth flight plans with launch vehicles having multiple liquid propellant engines that normally thrust at liftoff, the trajectories in [Table A2.3](#) of this volume are required for engine-out (not-thrusting) conditions. Range Safety shall specify the precise engine-out condition(s) after the vehicle configuration is known.

3.1.2.1.2.2. Jettisoned Body Data. Nominal impact point, associated drag data, and impact dispersion data for each jettisoned body. See [Attachment 5](#) of this volume.

3.1.2.1.2.3. Sequence of Events. Times from liftoff of discrete events such as ignition, cutoff, and separation of stages, firing of ullage rockets, jettisoning of components, firing of separation rockets, initiation and termination of various control and guidance modes, starting and ending of coast periods and control modes, arming of engine cutoff circuits, and settings for backup engine cutoff signals.

3.1.2.1.2.4. High Q Flight Region. A statement indicating the flight time interval when the vehicle is experiencing the “high q” flight regime. This “high q” flight region is defined as the time during flight when the dynamic pressure can cause vehicle aerodynamic breakup during a malfunction turn with the result of creating little or no cross range displacement.

3.1.2.1.2.5. Orbital Parameters for Space Vehicles.

3.1.2.1.2.5.1. Apogee, perigee, inclination, and period of orbits to be achieved; the time, altitude, latitude, and longitude of the submissile point for injection events such as ignition and cutoff of each stage, separation of payload, and re-ignition of upper stages.

3.1.2.1.2.5.2. The state vector (position and velocity components) at the beginning and ending of each thrusting phase after initial orbital insertion.

3.1.2.1.2.5.3. The state vector for any separated stage or component at the beginning of its final coast or free-flight phase.

3.1.2.1.2.5.4. When requested by Range Safety, provide launch vehicle ephemeris data or position covariance data for any component of the launch vehicle that reaches at least 150 km, for a period of 3 hours, or for the full time it is expected to be above 150 km if less than 3 hours. It is the Range User’s choice on selecting either ephemeris data or position covariance data, and the possible effects that may have on the launch window from Collision Avoidance (COLA) launch holds. For specific data format requirements and other

instructions, refer to guidance found on <https://www.space-track.org>.

3.1.2.1.2.6. Approximate elapsed time from the receipt of an FSS signal at the command antenna until the FSS charges explode.

3.1.2.2. Cruise Missiles. In general, cruise missile operations involving intentional land overflight (except for launch and landing) will not be approved. In highly unusual situations where the operation objectives dictate otherwise and preliminary flight plan approval has been granted, the information requested in [paragraph 3.1.2.2.2.2](#) will be used to establish guidelines or limits for land overflight. The permissible limits will depend not only on this information but also on risk estimates of overflight hazards, the operation objectives, and the importance of these objectives. The following items are required for each flight or group of similar flights. Data shall be updated as vehicle configuration changes occur or whenever revised information becomes available.

3.1.2.2.1. Cruise Missile PFDP. The following data are required in addition to the data requirements specified in [paragraph 2.2.3](#):

3.1.2.2.1.1. Position and velocity vectors expressed in the coordinate system defined in [paragraph A2.2.1](#) of this volume as a function of time from launch until cruise altitude or a cruise condition is reached. If position and velocity components are not available, ground range and altitude may be substituted for the position vector, and the total earth-fixed velocity and flight path angle may be substituted for the velocity vector. The data shall be provided in time increments no larger than 5 seconds. If trajectory data cannot be provided, the steepness of the trajectory in the launch area shall be compared with the trajectory from any prior similar operation.

3.1.2.2.1.2. A map showing the expected flight path over the earth's surface. Times are to be indicated at regular intervals along the path.

3.1.2.2.1.3. A graph showing an altitude profile correlated with the flight path. Times are to be indicated at regular intervals along the path.

3.1.2.2.1.4. A map showing the estimate of nominal impact points and three-sigma drag-corrected impact dispersion areas for each jettisoned body.

3.1.2.2.2. Cruise Missile FFDP. The following data are required in addition to the data requirements specified in [paragraph 2.2.4](#):

3.1.2.2.2.1. General Data.

3.1.2.2.2.1.1. General information concerning the nature and purpose of the flight.

3.1.2.2.2.1.2. A scaled diagram of the general arrangements and dimensions of the vehicle.

3.1.2.2.2.1.3. Tracking aids, such as S- or C-Band transponder or GPS receiver and telemetry transmitter, in the vehicle that can be used for flight safety purposes; the stage or section where each is located. **Note:** SSC strongly advocates the use of non-radar-based tracking sources such as GPS and/or TMIG where ever possible to reduce the range infrastructure burden and

potential for tracking dropouts in flight.

3.1.2.2.2.1.4. Trajectory deviations or other conditions beyond which the Range User is willing to accept flight termination action even though the vehicle has not reached a dangerous position or attitude.

3.1.2.2.2.1.5. Approximate elapsed time from the receipt of an FSS signal at the command antenna until FSS explosive charges explode or the recovery sequence is initiated.

3.1.2.2.2.1.6. Graphs of fuel weight (pounds) versus time (seconds or minutes).

3.1.2.2.2.1.7. Graphs of gross weight (pounds) versus time (seconds or minutes).

3.1.2.2.2.1.8. Graphs of maximum cruising speed (feet/seconds) versus altitude (feet).

3.1.2.2.2.2. Land Overflight Data.

3.1.2.2.2.2.1. The flight azimuth limits or the maximum deviations from the nominal flight path for which the primary operation objectives can be met.

3.1.2.2.2.2.2. The flight azimuth limits or the maximum deviations from the nominal flight path for which a useful operation can be accomplished, even though the vehicle is outside the normal three-sigma limits.

3.1.2.2.2.2.3. The operation objectives that will not be met or the extent to which primary objectives will be degraded if land overflight is not permitted when the missile is outside the three-sigma normal limits.

3.1.2.2.2.2.4. Circumstances or types of malfunctions that can cause the missile to fly outside the three-sigma limits of normality but still accomplish useful objectives.

3.1.2.2.2.2.5. The probability of occurrence of the malfunctions listed in response to the requirements in [paragraph 3.1.2.2.2.4](#).

3.1.2.2.2.3. Trajectories. These requirements identify the types of trajectories required for the following flight plans. All trajectories are to be developed using the procedures and format described in [Attachment 2](#) of this volume.

3.1.2.2.2.3.1. Single Flight Azimuths. See [Table A2.1](#) of this volume.

3.1.2.2.2.3.2. Variable Flight Azimuths. Operations with variable flight azimuths shall provide a complete set of firing tables detailing launch times and flight azimuths for each day of the launch window (see [Table A2.2](#) of this volume).

3.1.2.2.2.3.3. Multiple Liquid Propellant Engines Thrusting at Ignition. For single or variable azimuth flight plans with vehicles having multiple liquid propellant engines that normally thrust at liftoff, the trajectories in [Table A2.3](#) of this volume are required for engine-out (not thrusting) conditions. Range Safety shall specify the precise engine-out conditions after the vehicle configuration is known.

3.1.2.2.2.4. Jettisoned Body Data. Nominal impact point, associated drag data, and impact dispersion data for each jettisoned body. (See [Attachment 5](#) of this volume.)

3.1.2.2.2.5. Sequence of Events. Using the launch or drop time as the zero reference, time of discrete events such as ignition, cutoff, separation of booster stages, jettisoning of components, starting and ending of control modes, and initiation of recovery devices.

3.1.2.3. Small Unguided Rockets and Probe Launch Vehicles. The term small unguided rocket is not precisely defined here; it generally refers to one- or two-stage rockets having maximum impact ranges less than 100 nautical miles. Small rockets are not required to carry FSSs when dispersion analyses and control of launch conditions indicate that all vehicle components can be contained within predetermined safe areas. Unguided rockets of more than two stages or with impact ranges greater than 100 nautical miles are required to carry an FSS. In this event, the data requirements specified in [paragraph 3.1.2.1](#) for ballistic missiles and space vehicles shall apply. The following vehicle-related items are required for each rocket flight or group of similar flights and data shall be updated as vehicle configuration changes occur or revised information becomes available:

3.1.2.3.1. Small Unguided Rocket and Probe Launch Vehicle PFDP. The following data are required in addition to the requirements in [paragraph 2.2.3](#):

3.1.2.3.1.1. Burn time of each stage.

3.1.2.3.1.2. Graphs of impact range versus launch elevation angle for the planned elevation angle sector.

3.1.2.3.1.3. Graphs of ground range versus altitude for the planned elevation angle sector.

3.1.2.3.1.4. Proposed flight azimuth limits and elevation angle limits.

3.1.2.3.1.5. Summary of past vehicle performance giving number launched, launch location, number that performed normally and number that malfunctioned, behavior and impact location for those that malfunctioned, nature of malfunction and corrective action; this requirement can be met by submission of portions of [paragraph 2.2.3.3](#).

3.1.2.3.2. Small Unguided Rocket and Probe Launch Vehicle FFDP. The following data are required in addition to requirements specified in [paragraph 2.2.4](#):

3.1.2.3.2.1. General Data.

3.1.2.3.2.1.1. General information concerning the purpose and objectives of the operation, such as data to be obtained, number of launches planned, and a brief description of the payload, giving approximate weights.

3.1.2.3.2.1.2. Scaled diagram of the vehicle.

3.1.2.3.2.1.3. Geodetic latitude and longitude of launch point or launcher.

3.1.2.3.2.1.4. Desired Launch Azimuth and Launch Elevation Angles. Provide the variation in azimuth and elevation angles that are acceptable from the

standpoint of the operation objectives. Indicate which of the operation objectives actually determine the acceptable limits for azimuth and elevation angles.

3.1.2.3.2.1.5. A brief description of the type of launcher; for example, zero length or short rail, travel distance of the rocket to clear the launcher, the amount of effective guidance, launcher adjustments available in Quadrant Elevation (QE) angle and azimuth, and the smallest increment for these adjustments.

3.1.2.3.2.1.6. Total vehicle weight at liftoff.

3.1.2.3.2.1.7. Total propellant weight in each stage at liftoff.

3.1.2.3.2.1.8. Inert weight of each stage and separable component after burnout or jettison.

3.1.2.3.2.2. Wind Effects Data. In most cases, wind is the largest independent factor causing displacement of unguided vehicle impact points. Accompanied by tabulations, charts, and a comprehensive discussion of their formulation, the following data are required to predict the magnitude and direction of this effect:

3.1.2.3.2.2.1. Ballistic wind-weighting factors versus altitude in feet. The effects of booster and first-stage wind drifts are of prime importance since the first-stage motor impact point is usually near the launch site. The wind-weighting factor shall be presented in percent of wind effect for specific wind altitude intervals or for specific altitude interval as percentage of the total wind effect. The ballistic wind-weighting factors shall include the effects of both weather cocking and drift.

3.1.2.3.2.2.2. Change in the nominal impact point location due to missile weather cocking and drift as a result of ballistic winds (head, tail and cross; or resultant wind effect). The deviation is required in feet or nautical miles per foot per second of the wind. Since deviations vary significantly with a change in launch quadrant elevation angle (QE), values shall be supplied in a table of launcher QE versus unit wind effect. The table shall cover the range of elevation angles for which launches are to occur with an elevation angle interval no greater than 2 degrees and include plus and minus 12 degrees from the desired resultant QE up to a maximum launcher setting of 88 degrees.

3.1.2.3.2.2.3. Launcher adjustment curve or launcher tilt effect to correct the launcher in azimuth and elevation for wind effects. A discussion of methods to be used in adjusting the launcher settings to compensate for winds is required. This data is required only if the Range User desires to adjust the launcher azimuth and elevation to correct for wind effects and shall be supplied for all desired resultant QEs. Wind compensation minimizes the area clearance problem by maintaining a constant impact point. A thorough description of the correction method and the expected accuracies to be achieved are required in addition to the proper curves and tabulation data.

3.1.2.3.2.2.4. A graphical and tabular presentation of the impact point

displacement due to earth rotation versus QE. Calculations for this information are based on the latitude of the launcher and the desired launch azimuth. The table shall cover the range of elevation angles for which launches are to occur with an elevation angle interval no greater than 2 degrees and include plus and minus 12 degrees from the desired resultant QE up to a maximum of 88 degrees.

3.1.2.3.2.2.5. When a computer program is used to perform the calculation required for adjustment of the launcher in QE and azimuth or to verify the impact predictions of all stages, the Range User shall include a discussion of the intended use of the program. If the Range User uses one of the computer programs available at the range, Range Safety should be consulted to make sure that requirements in [paragraph 3.1.2.3.2.2.1](#) are presented in a form compatible with the computer input requirements.

3.1.2.3.2.3. Analyses for Long Range Probes. All analyses for long-range probes (500 nautical miles plus) shall be calculated using a rotating spherical or ellipsoidal gravity field. In contrast to the majority of probe vehicles, long-range probes normally require an FSS incorporated into the vehicle. The data requirements are the same as those specified in [paragraph 3.1.2.1](#) for guided ballistic missiles. A debris risk analysis (see [paragraph 3.4](#)) is required to evaluate requests to waive the requirement for an FSS on a long-range probe vehicle.

3.1.2.3.2.4. Trajectory Requirements. See [Attachment 2](#) of this volume.

3.1.2.3.2.5. Graphs. In addition to the tabular nominal trajectory data, graphs of the following shall be provided for each stage and payload weight:

3.1.2.3.2.5.1. Impact range versus launch elevation angle (feet or nautical miles versus degrees).

3.1.2.3.2.5.2. Apogee altitude versus launch elevation angle (feet or nautical miles versus degrees).

3.1.2.3.2.5.3. Altitude versus ground range (feet versus feet or nautical miles).

3.1.2.3.2.6. Six Degree-of-Freedom Data. The Range User may be required to provide additional data on the launch vehicle and launcher to enable Range Safety to perform six degree-of-freedom trajectory analyses. If required, Range Safety shall contact the Range User and specify the data required to perform the analyses.

3.1.2.4. Aerostats and Balloon Systems. These trajectory and performance data requirements apply to “large” (per FAA 14 Code of Federal Regulations (CFR) § 101.1) unmanned, untethered, and tethered aerostats and balloons. They do not apply to small weather balloons and other such objects that are released routinely throughout the country and the world for scientific purposes.

3.1.2.4.1. Aerostat and Balloon System PFDP. The following data are required:

3.1.2.4.1.1. Description of the proposed flight plan giving particulars about the location and boundaries of the proposed test area, time sequence and description of significant events, flight duration, altitude, and speed limits.

3.1.2.4.1.2. Method of control, including emergency control procedures.

3.1.2.4.2. Aerostat and Balloon System FFDP. The following data are required:

3.1.2.4.2.1. Untethered Aerostats and Balloons. Large unmanned and untethered aerostats and/or balloons flight tested on the range shall carry an approved FSS capable of causing rapid deflation upon command. The following vehicle-related items are required for each flight or group of similar flights. The data shall be updated as vehicle configurations vary, or revised information becomes available.

3.1.2.4.2.1.1. Detailed information concerning the purpose and objectives of the mission, data to be obtained, number of flights planned, and proposed flight dates.

3.1.2.4.2.1.2. A statement indicating whether the vehicle and proposed flights are similar to prior flights either on the range or elsewhere.

3.1.2.4.2.1.3. A description of the vehicle giving dimensions, component weights, materials, and characteristics of propulsion, control, and recovery systems, including estimates of system reliability.

3.1.2.4.2.1.4. Accuracy of the guidance and control system in maintaining the desired aerostat position.

3.1.2.4.2.1.5. Description and location of the FSS.

3.1.2.4.2.1.6. Description and location of tracking aids.

3.1.2.4.2.1.7. Wind restrictions for launch and flight.

3.1.2.4.2.1.8. Description of the Proposed Flight Plan:

3.1.2.4.2.1.8.1. Location of the proposed test area.

3.1.2.4.2.1.8.2. Graph of altitude (feet) versus time (minutes) from release until float altitude is reached.

3.1.2.4.2.1.8.3. Total duration of flight.

3.1.2.4.2.1.8.4. Graph of altitude (feet) versus time (minutes) for the entire operation or indication of how altitude will be varied throughout the flight.

3.1.2.4.2.1.8.5. Maximum possible altitude without bursting.

3.1.2.4.2.1.8.6. Maximum aerostat speed in still air as a function of altitude.

3.1.2.4.2.1.8.7. Location and size of impact dispersion areas for any bodies jettisoned during flight.

3.1.2.4.2.1.8.8. Location and size of final impact dispersion area or intended recovery area.

3.1.2.4.2.1.9. Drag coefficient (C_d) versus Mach number giving reference area and weight for each jettisoned body and for the entire vehicle (or resulting components) after activation of the FSS; the same data should also be provided for a normal recovery sequence if different from the above.

3.1.2.4.2.2. Tethered Aerostats and Balloons. Tethered aerostats and/or balloons shall carry an approved automatic FSS that will cause rapid deflation if the balloon

escapes its mooring or the tether breaks. The following vehicle-related items are required for each flight or group of similar flights. The data shall be updated as vehicle configurations vary, or revised information becomes available.

3.1.2.4.2.2.1. Detailed information concerning the purpose and objectives of the mission, data to be obtained, number of flights planned, and proposed flight dates.

3.1.2.4.2.2.2. Description and location of the FSS.

3.1.2.4.2.2.3. Description of the mooring tethering system giving lengths and breaking strength of the tether.

3.1.2.4.2.2.4. Operational method of measuring tension in the tether.

3.1.2.4.2.2.5. Wind and weather restriction for launch and flight.

3.1.2.4.2.2.6. Maximum float altitude.

3.1.2.4.2.2.7. Planned and maximum duration of flight.

3.1.2.5. Projectiles, Torpedoes, Air-Dropped Bodies, and Small Devices. These data requirements apply to projectiles, torpedoes, air-dropped bodies, and small devices that normally would not contain an FSS and that may or may not be propulsive.

3.1.2.5.1. Projectiles, Torpedoes, Air-Dropped Bodies, and Small Device PFDP. The following data are required in addition to the requirements in [paragraph 2.2.3](#):

3.1.2.5.1.1. Description of the proposed flight plan giving particulars about the location and boundaries of the proposed operation area, time sequence, and description of significant events.

3.1.2.5.1.2. Burn or thrust time of each thrusting item.

3.1.2.5.1.3. Graphs of the impact range (nautical miles) versus launch elevation angle (degrees) for the planned elevation angle sector or drop altitude sector.

3.1.2.5.1.4. Ground range (nautical miles) versus altitude (feet) for the planned elevation angle sector.

3.1.2.5.1.5. Nominal impact location in geodetic latitude (degrees) and longitude (degrees) for each jettisoned or impacting body.

3.1.2.5.1.6. Estimates of the three-sigma dispersion area in downrange (feet or nautical miles) and cross-range (feet or nautical miles) measured from the nominal impact location.

3.1.2.5.2. Projectiles, Torpedoes, Air-Dropped Bodies, and Small Device FFDP. The following data are required in addition to the requirements specified in [paragraph 2.2.4](#):

3.1.2.5.2.1. Detailed information concerning the purpose of the operation, data to be obtained, description of objects, number of operations in the program, and proposed operation dates.

3.1.2.5.2.2. Scaled diagram of vehicle.

3.1.2.5.2.3. Latitude and longitude of the desired drop point and the maximum region around the point where launch could occur. This information may be provided in distances downrange and cross-range relative to the expected drop point or by providing the geodetic latitude and longitude of the corners of the area.

3.1.2.5.2.4. Jettisoned Body Data. See [Attachment 5](#) of this volume.

3.1.2.5.2.4.1. Latitude and longitude of the desired impact or target point.

3.1.2.5.2.4.2. The three-sigma downrange and cross-range impact dispersions or circular error probability (CEP) of impact points for each impacting body. This information may be provided in distances downrange and cross-range relative to the expected launch point or by providing the geodetic latitude and longitude of the corners of the area.

3.1.2.5.2.4.3. For air-dropped bodies, the effect of the three-sigma aircraft position and velocity error at drop.

3.1.2.5.2.4.4. If the body descends on a parachute or other device, drag data before and after chute opening.

3.1.2.5.2.5. For air-dropped bodies, the data items in [paragraph 3.1.2.6](#) shall be provided.

3.1.2.5.2.6. The effect of head wind, tail wind, and cross wind on the impact point location in terms of displacement distance (feet or nautical miles) per knot (or feet/seconds) of wind.

3.1.2.5.2.7. Trajectory Requirements. The following trajectory data items are required for each operation or group of similar operations:

3.1.2.5.2.7.1. A graph of the nominal trajectory, including a plot of altitude (feet) versus downrange distance (feet or nautical miles); timing marks (seconds), including the impact time, shall be indicated along the trajectory; separate graphs are required for each planned launch point or other condition.

3.1.2.5.2.7.2. The maximum horizontal distance (feet or nautical miles) that can be traveled by the objects from the launch point to impact.

3.1.2.5.2.7.3. If the objects descend on a parachute, a plot of altitude (feet) versus range (feet or nautical miles) for the case where the chute fails to open.

3.1.2.6. Air-Launched Vehicle Data Requirements. These data requirements apply to all programs that use an aircraft as the originating platform for the operation. If the air-launched vehicle is a space vehicle, the requirements of [paragraph 3.1.2.1](#) also apply.

3.1.2.6.1. General Data Requirements.

3.1.2.6.1.1. General information concerning the nature and purpose of the flight.

3.1.2.6.1.2. The minimum weather requirements for the operation.

3.1.2.6.1.3. Emergency Requirements. Special emergency requirements shall be specified, including:

3.1.2.6.1.3.1. Search and rescue support requirements.

- 3.1.2.6.1.3.2. Emergency Recovery Plan, including minimum field length(s).
 - 3.1.2.6.1.3.3. Description of ditching characteristics, if known.
 - 3.1.2.6.1.3.4. Description of secondary communication procedures to be used in the event of primary communications failure.
 - 3.1.2.6.1.3.5. If structural flight and system tests are to be conducted, any weather minimums and special requirements.
- 3.1.2.6.2. Aircraft Data Requirements.
- 3.1.2.6.2.1. Aircraft type (such as chase, tanker), aircraft registration number/serial number, and the performance capability of aircraft, such as turn rate, climb rate, and velocity.
 - 3.1.2.6.2.2. For other than level flight launches, an additional statement describing how the aircraft path angle and launch azimuth are determined for vehicle release.
 - 3.1.2.6.2.3. Description of guidance system used and how ignition and altitude are determined.
- 3.1.2.6.3. Aircraft Flight Plan Data Requirements.
- 3.1.2.6.3.1. Description of drop aircraft flight plan, such as aircraft flight azimuth (degrees from true North), speed (knots), altitude (feet), flight path angle (degrees) of the velocity vector relative to local horizontal at the vehicle launch point; a map showing the flight path over the earth's surface with altitudes and speeds indicated at appropriate way points.
 - 3.1.2.6.3.2. The expected maximum region around the launch point (a launch point envelope where the operation is conducted) provided as distances in altitude, downrange, up-range, and cross-range relative to the expected launch point and perpendicular to the launch azimuth or by the geodetic latitude and longitude of the corners of the launch box.
 - 3.1.2.6.3.3. A definition and description of events occurring before vehicle release and to the time of vehicle engine ignition.
 - 3.1.2.6.3.4. For ballistic air-launched bodies, altitude of the aircraft, true air speed, and dive angle beginning 60 seconds before launch and continuing through launch.
- 3.1.2.6.4. Launched Vehicle Data Requirements.
- 3.1.2.6.4.1. A nominal flight profile for each stage from launch to impact, showing altitude (feet) versus downrange (feet) is required. Profiles shall include parachute opening, parachute not opening, all unignited and non-separation conditions of the vehicle. Timing marks in seconds shall be indicated on the trajectory, as well as total time of flight for each object dropped. Drag data before and after chute opening shall be provided.
 - 3.1.2.6.4.2. The drop rate of launched vehicles and description of control system used.
 - 3.1.2.6.4.3. Method of booster ignition and position of the vehicle relative to the

earth at ignition.

3.1.2.7. Unmanned Aerial System/Unmanned Air Vehicles (UAS/UAV). Range safety requirements and guidance for use of UAVs are provided in RCC 323-18, *Range Safety Criteria for Unmanned Air Vehicles*, and RCC 555-19, *User Guide for Unmanned Aircraft System (UAS) Operations on the National Ranges*.

3.2. Malfunction Turn Analysis. These requirements apply to the following programs: ballistic missiles, space vehicles, cruise missiles, small unguided rockets, and probe launch vehicles.

3.2.1. General. The Range User shall perform a malfunction turn analysis to determine a vehicle's maximum turning capability as a function of trajectory time. The Range User shall use the products of the malfunction turn analysis as input to its Launch Safety analysis and other analyses where it is necessary to determine how far a vehicle's impact point can deviate from the nominal impact point after a malfunction occurs.

3.2.2. Malfunction Turn Analysis Products.

3.2.2.1. Malfunction Turn Analysis PFDP. The Range User shall provide the vehicle maximum turn capability that will cause the furthest distance the vehicle impact point can deviate from nominal if a thrust vector offset or other malfunction were to occur. The corresponding changes in vehicle velocity vector flight path angle and magnitude shall also be provided. The Range User shall generate the detailed information described in [Attachment 3](#) of this volume.

3.2.2.2. Malfunction Turn Analysis FFDP. The Range User shall provide the same information as in the PFDP but updated to reflect performance caused by changes in flight plans or vehicle configuration.

3.3. Debris Analysis. These requirements apply to the following programs: ballistic missiles, space vehicles, cruise missiles, small unguided rockets, and probe launch vehicles.

3.3.1. General. Range Safety shall perform a debris risk analysis utilizing Range Safety approved Range User provided data, characterizing inert, explosive, and other hazardous vehicle debris resulting from a vehicle malfunction and from any planned jettison of vehicle components.

3.3.2. Debris Analysis Products.

3.3.2.1. Debris Analysis PFDP. The Range User shall provide a preliminary estimate of fragment characteristics such as number, composition, dimensions, and weight due to all potential modes of vehicle breakup such as destruct and aerodynamic loading.

3.3.2.2. Debris Analysis FFDP. The Range User shall generate the detailed information described in [Attachment 4](#) of this volume. In addition, the PFDP shall be updated to reflect any changes in the results presented.

3.4. Debris Risk Analysis . These requirements apply to the following programs: ballistic missiles and space vehicles, cruise missiles, UAS/UAVs, and small unguided rockets and probe launch vehicles.

3.4.1. General.

3.4.1.1. Range Safety shall perform an overall (launch area/downrange overflight) debris risk analysis to determine the collective average expectation of casualties (E_c) to the public, personnel, and Range assets exposed to inert and explosive debris hazards from the proposed vehicle flight. The results of the analysis shall be used to demonstrate compliance with the public risk criteria in SSCMAN 91-710 Volume 1 and shall be shared with the Range User.

3.4.2. Debris Risk Analysis Products.

3.4.2.1. Debris Risk Analysis PFDP. The Range User shall generate the reliability and malfunction data requirements of [paragraph 2.2.3](#) In addition, the Range User shall generate the following information:

3.4.2.1.1. The Range User shall provide launch vehicle position and velocity covariance data from liftoff through 5 seconds after vacuum IIP liftoff. The Range User may select from one of three possible formats with coordinate system and method specified in [Attachment 7](#) of this volume. The frequency will be such that linear interpolation offers negligible error, at least once every 5 seconds.

3.4.2.1.2. The Range User shall comply with population data requests.

3.4.2.2. Debris Risk Analysis FFDP. The Range User shall provide the same information as in the PFDP but updated to reflect performance caused by changes in flight plans, vehicle configuration, or more accurate analyses.

3.5. Acoustic Analysis. These requirements apply to ballistic missiles, space vehicles, cruise missiles, small unguided rockets, probe launch vehicles, and air-launched vehicles.

3.5.1. Acoustic Analysis Products.

3.5.1.1. Acoustic Analysis PFDP. The Range User shall provide the following information. If the information is not available at the PFDP delivery date, it shall be included as part of the FFDP.

3.5.1.1.1. Acoustic intensity contours above 85 decibels (dB) at 10dB intervals that are generated during launch of the vehicle.

3.5.1.1.2. The predominant acoustical bands above 85dB at distances of .5, 1, 2, and 3 nautical miles surrounding the launch pad.

3.5.1.2. Acoustic Analysis FFDP. The data requirements for the FFDP are the same as those for the PFDP but updated to reflect the performance caused by changes in flight plans, vehicle configuration, or more accurate analyses.

3.6. Sonic Boom Analysis. These requirements apply to reusable/re-entry space vehicles, cruise missiles, and air-launched vehicles. In addition to these requirements, the Range User shall comply with the requirements of DAFMAN 13-201, *Airspace Management*.

3.6.1. Sonic Boom Analysis Products.

3.6.1.1. Sonic Boom Analysis PFDP. The Range User shall provide as part of the PFDP, a sonic boom analysis/assessment to determine if the vehicle can generate a sonic boom at ground level during atmospheric flight.

3.7. FSS Determination Analysis. These requirements apply to ballistic missiles, space vehicles, cruise missiles, small unguided rockets, probe launch vehicles, and air-launched vehicles.

3.7.1. General. The threat from any payload or stage without an FSS shall be analyzed to determine the risk associated with a malfunctioned vehicle whose payload or stage may separate prematurely.

3.7.2. FSS Determination Analysis Products.

3.7.2.1. FSS Determination Analysis PFDP. The Range User shall provide the data and analyses listed below for the payload or stage deemed hazardous by Range Safety. The data and the results of these analyses shall be provided to Range Safety at least three months (time will vary with program) before the time that a waiver of the FSS is required. If the resulting impact dispersions are small enough for inclusion as offsets in the Range Safety destruct computations, there may be no need for a risk study.

3.7.2.1.1. Functional description of structural, mechanical, and electrical inhibits or safeguards for preventing premature separation and ignition of payload or stage propulsion systems; extent to which such inhibits are independent; simplified schematics and operational description of propulsion system ignition circuits; extent to which circuits and systems are shielded.

3.7.2.1.2. Failure modes that can lead to premature separation and/or ignition of upper-stage propulsion systems; probability of occurrence for each failure mode including method of derivation and a fault tree analysis if multiple components or subsystems are involved

3.7.2.1.3. Probability of stable flight and stability characteristics of prematurely separated and thrusting stage, stage and payload, and payload alone, both within and outside the sensible atmosphere; effects of structural confinement such as payload fairing on prematurely separated upper stage or payload.

3.7.2.1.4. Risk Study. Results of the risk study shall include the impact probability for critical facilities and land areas that can be endangered by the payload or stage before orbital insertion.

3.7.2.1.5. Residual Thrust Dispersion Analysis. The residual thrust dispersion analysis shall show the extent to which the impact points(s) can deviate from nominal if the payload or stage separates prematurely, and the propulsion system ignites. Computations are generally required from liftoff until upper stage fuel depletion or orbit insertion.

3.7.2.1.6. Intact Impact Analysis. The intact impact analysis shall address the explosive effects of solid rocket and liquid motors upon ground impact. The Range User shall supply stage or payload data requested by Range Safety to support this analysis. The analysis shall contain piece description, number of pieces, and the range the explosion propels pieces from the motor impact point.

3.7.2.2. FSS Determination Analysis FFDP. The Range User shall provide the same information as in the PFDP but updated to reflect performance caused by changes in flight plans or vehicle configuration.

3.8. Post-Flight Vehicle Performance Analysis. These requirements apply to all programs identified in this volume.

3.8.1. Within three months after an operation has been conducted, the Range User shall provide Range Safety a statement of vehicle performance. This information may be provided in a special report or by supplying performance evaluation documents prepared for other purposes. This information is needed for evaluation of vehicle performance capabilities upon which changes in safety abort criteria are based and for updating the failure rate information used in the various risk analysis models.

3.8.2. The report(s) shall include the following information:

3.8.2.1. Qualitative statement about the performance of each stage and various subsystems.

3.8.2.2. Failures that occurred and resulting flight conditions produced.

3.8.2.3. Probable cause of failure and corrective action taken.

3.8.2.4. Actual (if available) or estimated impact points for stages.

3.8.2.5. Miss distances for weapon system tests and orbital parameters for space vehicle flights.

3.8.2.6. Comparison of planned and achieved cutoff conditions for each stage.

3.8.2.7. Performance of on-board safety instrumentation.

3.8.2.8. Small Unguided Rockets and Probe Launch Vehicles. The following additional data are required for small unguided rockets and probe launch vehicles:

3.8.2.8.1. Vehicle type and number, launch location, operation number, payload type and weight.

3.8.2.8.2. Actual launcher azimuth and elevation settings (degrees).

3.8.2.8.3. For each stage and payload, the predicted range (nautical miles) from launcher to impact point and the azimuth of the impact point. The impact point prediction is based on the predicted winds at time of launch.

3.8.2.8.4. Actual range (nautical miles) and azimuth (degrees from true North) from the launcher to impact points for all stages and payload(s).

3.8.2.8.5. Actual impact range (nautical miles) for each stage and payload giving components measured along and perpendicular to the predicted impact azimuth. Where a stage is not tracked to impact, the impact point shall be computed using the best estimates of the drag characteristics and of the winds at launch.

3.8.2.8.6. Predicted QE (degrees) of trajectory for each stage.

3.8.2.8.7. Actual QE (degrees) of trajectory for each stage.

3.8.2.8.8. Predicted range (nautical miles) and altitude (feet) of apogee for each stage.

3.8.2.8.9. Actual range (nautical miles) and altitude (feet) of apogee for each stage.

3.8.2.8.10. A tabulation of the reduced wind data used in the launcher-setting calculations giving speed (feet/seconds) and direction (degrees) as a function of altitude (feet).

3.8.2.8.11. A reference list of all documents, graphs, and tabulations that were used in making the launcher-setting calculations (wind-weighting curves, ballistic wind-weighting factors, and unit wind effect).

3.8.2.8.12. Description of the tracking data source.

PAUL J. MEJASICH, NH-04, DAFC
Director of Safety

Attachment 1**GLOSSARY OF REFERENCES AND SUPPORTING INFORMATION**

See SSCMAN 91-710 Volume 7, *Range Safety User Requirements Manual - Glossary of References and Supporting Information*, which contains the references, forms, abbreviations, acronyms, office symbols, and terms used within all volumes of the 91-710 publication.

Attachment 2

TRAJECTORY DATA

A2.1. Introduction. This attachment provides background information and details about range safety trajectory requirements. It is applicable to ballistic, space, cruise, unmanned, and small unguided vehicles. The format specification and acceptable media type are described in [Attachment 6](#) of this volume titled “FLIGHT TRAJECTORY DATA PREPARATION, SUBMITTAL, and PROCESSING.” Range Users should contact Range Safety for flight trajectory data preparation, submittal, and processing. The trajectory and two copies (compact disc (CD) format acceptable) with a letter of transmittal are required. **Note:** the double asterisks (**) used in this attachment mean that the magnitude, interval, or duration for the required item varies from program to program, and the value given is the typical value.

A2.2. Trajectory Details.

A2.2.1. XYZ Coordinates. The X, Y, Z, coordinates referred to in Volume 2 shall be referenced to an orthogonal, earth-fixed, left-handed system with its origin at the launch point or at a point on the earth's surface above or below the launch point. The XY plane shall be tangent to the ellipsoidal earth centered at the origin, the positive X axis shall coincide with the launch azimuth, and the positive Z axis shall be directed away from the earth, and the Y axis shall be positive to the right looking downrange.

A2.2.2. Trajectory Data Item Requirements. The required trajectories from [Table A2.1](#) through [Table A2.3](#) shall be calculated using a 6 degree-of-freedom program. [Table A2.4](#) lists the data items to be provided for each required trajectory. The data items are required in 1-second intervals.

A2.2.2.1. Ballistic Missiles and Space Vehicles. All trajectories except the three-sigma launch area trajectories shall be provided from launch up to a point in flight where effective thrust of the final stage has terminated, or to thrust termination of that stage or burn that places the vehicle in orbit. The launch area trajectories are required from liftoff until the vehicle attains an altitude of 100,000** feet.

A2.2.2.2. Cruise Missiles. The data items are required in tabular form in 1-second intervals for the first 2 minutes of flight, in 15-second intervals from this point until the missile reaches cruise altitude, in 1-minute intervals throughout the cruise phase until the terminal phase of flight is reached, and at 15-second intervals thereafter until operation termination or impact. For each program, Range Safety provides the Range User with the specific value to use for each parameter marked with the double asterisks. The time 0.0 seconds shall correspond to first motion for pad-launched missiles and to the instant of drop for air launches.

A2.2.2.3. Small Unguided Rockets or Probe Vehicles. [Table A2.4](#) (Items 5 - 13) lists the data items to be provided for each trajectory from launch until burnout of the final stage for each desired nominal quadrant elevation angle and payload weight. These items shall be provided in tabular form as a function of time with each column of the table containing only a single parameter. Time shall be given at even intervals, not to exceed 1-second increments during thrusting flight, and for times corresponding to ignition, thrust

termination or burnout, and separation of each stage. If stage burning times are less than 4 seconds, time intervals should be reduced to 0.2 seconds or less.

A2.2.3. Nominal (Reference) Trajectory. The nominal or reference trajectory is the trajectory that the vehicle would fly if all vehicle parameters were exactly as expected, if all vehicle systems performed exactly as planned, and there were no external perturbing influences.

A2.2.4. Three-Sigma Dispersed Trajectories. The three-sigma dispersed trajectories define the downrange and cross-range limits of normality for the vehicle IIP at any time after launch. The three-sigma trajectories shall be computed using annual wind profiles unless the launch is to be conducted at a particular time of the year and only at that time. Care should be exercised in the selection of the cumulative percentage frequency of the wind profile used for the computation of these trajectories. Selecting a wind profile as severe as the worst wind conditions when a launch would be attempted is usually recommended. In critical instances, this has the disadvantage of limiting the allowable launch azimuth or reducing the allowable launch day winds in the flight safety restrictions for wind drift of vehicle fragments resulting from FSS action. The flight termination criteria allow for as much vehicle deviation due to wind as shown in these trajectories but does not account for wind conditions that exceed those used in these computations.

Table A2.1. Trajectory Types for Single Flight Azimuths.

Item #	Program	Trajectory Type	Reference
1	All Programs	Nominal or reference	A2.2.3.
2	Ballistic Missiles and Space Vehicles	Three-sigma maximum-performance	A2.2.4.2.
3		Three-sigma minimum-performance	A2.2.4.2.
4		Three-sigma lateral left	A2.2.4.3.
5		Three-sigma lateral right	A2.2.4.3.
6		Three-sigma steep launch area	A2.2.4.4.
7		Three-sigma lateral launch area	A2.2.4.4.
8		Fuel-exhaustion	A2.2.4.5.
9		Cruise Missile	Three-sigma maximum-altitude. The maximum altitude deviations (feet) above nominal as a function of ground range from the launch or drop point may be substituted for Table A2.4 , Item 3.
10	Three-sigma minimum-altitude. The maximum altitude deviations (feet) below nominal as a function of ground range from the launch or drop point may be substituted for Table A2.4 , Item 3.		A2.2.4.2. A2.2.4.2.1.
11	Three-sigma lateral. The maximum lateral deviations (feet or nautical miles) from the nominal flight path as a function of ground range from the launch or drop point may be substituted for Table A2.4 , Item 3.		A2.2.4.3. A2.2.4.3.4.
12	Fuel-exhaustion. The three-sigma high performance trajectory should define the vehicle capability limits in climbing to the maximum altitude at the maximum possible rate. Table A2.4 , Items 3 & 4 are required from launch or drop until the vehicle reaches a steady-state cruise condition.		A2.2.4.5. A2.2.4.5.1.

Table A2.2. Trajectory Types for Variable Flight Azimuths.

Item #	Trajectory Type	Reference
1	Nominal, reference, central, or middle trajectory	A2.2.3.
2	Extreme right-hand nominal or steepest nominal trajectory	A2.2.3.
3	Extreme left-hand nominal or shallowest nominal trajectory	A2.2.3.
4	Three-sigma maximum-performance trajectory for the centrally located flight azimuth	A2.2.4.2.
5	Three-sigma minimum-performance trajectory for the centrally located flight azimuth	A2.2.4.2.
6	Three-sigma lateral trajectories for the centrally located flight azimuth	A2.2.4.3.
7	Three-sigma left for smallest flight azimuth	A2.2.4.2.
8	Three-sigma right for largest flight azimuth	A2.2.4.2.
9	Three-sigma steep launch area	A2.2.4.4.
10	Three-sigma lateral launch area	A2.2.4.3.
11	Fuel-exhaustion	A2.2.4.5.

Table A2.3. Trajectory Types for Multiple Liquid Propellant Engines Thrusting at Liftoff.

Item #	Trajectory Type	Reference
1	Three-sigma steep launch area trajectory with one or more engines not thrusting	A2.2.4.4.
2	Three-sigma lateral launch area trajectory with one or more engines not thrusting	A2.2.4.3.

Table A2.4. Trajectory Data Items.

Item #	Data Item	Comments
1	A brief discussion of the parameters considered, their standard deviations, and all assumptions and procedures used in deriving each of the dispersed trajectories.	
2	A graph and tabular listing of the wind profiles used (wind magnitude and direction versus altitude)	The source of the wind profiles used in the computations shall be identified.
3	X, Y, Z versus Time (feet and seconds)	Cruise Missile: Units are feet or nautical miles and seconds or minutes. After the first 2** minutes of flight, with Range Safety approval, X, Y, Z, may be replaced by ground range along the earth's surface from launch point to sub-missile point versus time, altitude above earth's surface versus time, and cross range displacement from nominal versus time.
4	XDOT, YDOT, ZDOT versus time (feet/seconds and seconds)	Cruise Missile Units are the nearest one-tenth foot/second and seconds or minutes.

		After the first 2** minutes of flight, with Range Safety approval, XDOT, YDOT, ZDOT may be replaced by speed (feet/second) versus time and path angle (degree) of velocity vector relative to local horizontal versus time.
5	Speed versus time (feet/second and seconds)	
6	Path angle of velocity vector relative to local horizontal versus time (degree and seconds)	
7	Altitude above the sub-vehicle point on the reference spheroid versus time (feet and seconds)	
8	Total weight versus time (pounds and seconds)	
9	Ground range along reference spheroid from the origin (launch point) to a point directly beneath the missile versus time (nautical miles and seconds)	For Small Unguided Rocket or Probe Vehicle: Ground range units are feet.
10	Thrust versus time (pounds and seconds)	
11	Instantaneous impact point data	Geodetic latitude, longitude, impact range (nautical miles) and remaining flight time (seconds) versus time (seconds).
12	Launch azimuth	Degrees measured clockwise from true North.
13	The name, coordinates, and mean sea level elevation of the coordinate system origin (launch pad).	
14	Name of reference spheroid used in trajectory calculations.	

A2.2.4.1. Generating a Single Composite Three-Sigma Trajectory. To generate a single composite three-sigma trajectory in terms of instantaneous impact range, the following procedure is suggested. If the following procedure is not used, a description of the method used to generate the three-sigma trajectories shall be provided.

A2.2.4.1.1. Step 1: Identify individual parameters such as thrust, weight, specific impulse, and atmospheric density that significantly affect the performance of the vehicle IIP. Estimate three-sigma dispersions for these parameters.

A2.2.4.1.2. Step 2: Run a series of trajectory computations or simulations where three-sigma values of significant perturbing parameters are introduced one at a time. At a suitable number of time points, tabulate the IIP deviations from nominal that have been caused by perturbing each parameter.

A2.2.4.1.3. Step 3: At each time point and direction, calculate the square root of the sum of the squares of all deviations to arrive at the three-sigma IIP deviations.

A2.2.4.1.4. Step 4: By further trajectory computations or simulations, generate a thrusting flight trajectory (a three-sigma, no-wind trajectory) that matches as closely as possible the three-sigma deviations calculated in Step 3. This may be done by perturbing only a few key parameters at varying magnitudes throughout the run.

A2.2.4.1.5. Step 5: Compute the required three-sigma trajectory using worst case winds together with the parameter magnitudes used to calculate the three-sigma, no-wind trajectory. The wind dispersed trajectories indicate vehicle performance deviations due to the effects of severe winds. This data should be supplied until the vehicle attains an altitude where there is essentially no wind effect. It is usually sufficient to use 100,000 feet as this altitude limit. Computations should not be limited to wind drift but include all wind effects.

A2.2.4.2. Three-Sigma Maximum and Minimum Performance Trajectories. The three-sigma maximum and three-sigma minimum-performance trajectories define at any time after launch the limits of normality as far as impact downrange is concerned. The three-sigma maximum-performance trajectory provides the maximum downrange distance of the vacuum IIP for any given time and the three-sigma minimum-performance trajectory provides the minimum downrange distance of the IIP for any time. In calculating these trajectories, head and tail wind profiles should be used that represent the worst wind conditions for which a launch would be attempted. For any particular time after launch, approximately 99.73 percent of all normal vehicles (assuming a normal Gaussian distribution) that are subjected to the assumed wind will have impact ranges lying between the extremes, achieved at that time by three-sigma maximum performance and three-sigma minimum-performance vehicles. Of the 0.27 percent of the normal vehicles that fall outside the three-sigma limits, approximately half would be short, and half would be long. It is recognized that it may not be possible for a normally performing, fully guided vehicle to fly either the three-sigma maximum or minimum-performance trajectory as defined above. However, what is wanted is a single trajectory having an impact range at any time greater than the impact range of 99.865 percent of all normal vehicles, and a single trajectory with an impact range at any time less than the impact range of 99.865 percent of all normal vehicles. Any deviation outside of three-sigma limits indicates that the vehicle is probably behaving in an abnormal, though not necessarily dangerous, fashion. Those parameters having a significant effect upon impact range, such as thrust, specific impulse, weight, variation in firing times of different stages, and fuel flow rates, should be combined in the best considered fashion to produce the required results.

A2.2.4.2.1. Cruise Missiles. The three-sigma high performance trajectory should define the vehicle capability limits in climbing to maximum altitude at the maximum possible rate. It defines, at any time after launch, the limits of normality as far as impact range is concerned. The three-sigma high-performance trajectory provides the maximum downrange distance of the vacuum instantaneous impact point (IIP) for any given time. The three-sigma maximum and minimum-altitude trajectories define for any ground range the limits of normality as far as altitude is concerned. In other words, for any particular ground range approximately 99.73 percent of all normal vehicles (assuming a normal Gaussian distribution) will have altitudes between the extremes

defined by three-sigma maximum altitude and three-sigma minimum-altitude trajectories. Any deviation outside these limits indicates that the vehicle is behaving in an abnormal, though not necessarily dangerous, fashion. However, the Mission Flight Control Officer (MFCO)/Autonomous Flight Safety System (AFSS) may destroy such a vehicle if it is approaching land or threatening to get outside or below the command destruct coverage area.

A2.2.4.3. Three-Sigma Lateral Trajectory Requirements.

A2.2.4.3.1. Definition. Three-sigma lateral trajectories define the cross-range limits of normality for the vacuum instantaneous impact point (IIP). Both a three-sigma left and a three-sigma right trajectory shall be provided. These trajectories should be calculated using the worst lateral wind conditions for which a launch would be attempted. For any downrange distance, the IIP traces for 99.73 percent of all normal vehicles subjected to the assumed winds lie between the three-sigma lateral IIP traces. For variable azimuth launches, a three-sigma left trajectory for the smallest flight azimuth in the approved azimuth sector and a three-sigma right trajectory for the largest flight azimuth in the approved sector are required in addition to three-sigma lateral trajectories for a centrally located flight azimuth. Unless the procedure is invalid, the assumption will be made that the three-sigma left and right trajectories provided for the centrally located azimuth can be used to produce a reasonable approximation of the three-sigma left and right trajectories for other flight azimuths by reorienting the X and Y axis of the data. For example, if the three-sigma lateral trajectories have been computed for a central flight azimuth of 100 degrees, the three-sigma lateral trajectories for a 90-degree flight azimuth will be determined simply by assuming that the X axis is 90 degrees instead of 100 degrees. If this assumption is not reasonable, additional trajectories shall be provided to define the extreme left and right lateral limits.

A2.2.4.3.2. Use. Three-sigma lateral trajectories are needed to determine whether a normal vehicle experiencing a three-sigma deviation will violate flight safety destruct criteria. They may also be used as guidelines by the MFCO/AFSS in deciding whether a vehicle will be allowed to continue in flight or to over fly land. When used for comparison with the impact predictor destruct criteria, the vacuum IIP data are required. When used on the present-position display, values of X, Y, Z along the three-sigma lateral trajectories are required. The three-sigma lateral trajectories, as defined in [paragraph A2.2.4.3.1](#) in terms of IIP, may not provide three-sigma deviations of the lateral position Y as a function of X, although this is normally assumed to be the case. If this assumption is not valid, the Range User should also submit three-sigma trajectories that define the lateral limits of Y in terms of X.

A2.2.4.3.3. Calculation. In calculating a three-sigma lateral trajectory, those parameters having a significant effect on the lateral deviation of the IIP (or of the position Y in terms of X) should be combined in the best considered fashion to produce the required results. The procedures described in paragraphs [A2.2.4.2](#) and [A2.2.4.2.1](#) for calculating three-sigma maximum and minimum-performance trajectories are also suggested here.

A2.2.4.3.4. Cruise Missiles. The three-sigma lateral trajectory defines the lateral limits within which 99.73 percent of all normal missiles are expected to remain. This

trajectory should be calculated using the worst lateral wind condition for which a launching would be attempted. Since only one three-sigma lateral trajectory is requested, the assumption will be made that the three-sigma left and three-sigma right trajectories are symmetric about the nominal trajectory. If this assumption is not reasonable, then both three-sigma left and three-sigma right trajectories shall be provided. A missile that deviates outside the three-sigma lateral limits is subject to possible destruction if it is approaching land or threatening to get outside or below the command destruct coverage area.

A2.2.4.4. Dispersed Launch Area Trajectories. If the dispersed launch area trajectories are computed as specified and the proposed flight plan is approved, the launch agency can be certain that a normal vehicle will not violate the safety destruct criteria in the launch area, irrespective of the actual winds existing at launch. Unfortunately, there is also a distinct disadvantage in using extreme winds to calculate the dispersed trajectories. To arrive at destruct lines that will not be violated by vehicles flying the extreme trajectories, the allowances made for wind effects in the destruct line computations must be kept small. This, in turn, means that wind restrictions must be imposed on launch day. The wind profile used in the destruct calculations may be much smaller than the extreme wind profiles used to calculate the dispersed trajectories. In general, the greater the wind profile used in calculating the dispersed launch area trajectories, the steeper the trajectories are and the steeper the dispersed trajectories, the more severe the Launch Safety wind restriction must be on launch day to have acceptable destruct criteria. Reducing the wind profile in calculating the dispersed trajectories lessens the probability of a hold due to wind but increases the probability that a normal vehicle will fly outside the limits defined by the dispersed trajectories. This, in turn, increases the probability that a normal vehicle will be destroyed. For those vehicle flights for which severe launch area wind restrictions are required, it may be necessary for the Range User to supply dispersed launch area trajectories for two or three different wind profiles. By so doing, the probability of a safety hold due to wind is thus reduced.

A2.2.4.4.1. Three-Sigma Steep Launch Area Trajectory. The three-sigma steep launch area trajectory should maximize Z as a function of X' , where the azimuth of the X' axis must be specified by Range Safety for each program or group of similar flights. The positive X' axis is directed downrange from the launch point directly away from the uprange impact limit line, so the negative X' axis intersects the impact limit line at right angles. In calculating this trajectory, a head wind (or tail wind) blowing toward (or away from) the impact limit line, that is, blowing from (or toward) the positive X' direction, normally is used. This wind profile should, but may not always, represent the worst conditions for which a launch would be attempted. Therefore, other wind azimuths may need to be examined for worst conditions depending on the particular vehicle's guidance system response to wind direction. If other perturbing factors such as gyro drift or high thrust add significantly to the uprange deviations caused by wind, these factors should also be included in the calculations. The steep launch area trajectory is a three-sigma trajectory in that, for any X' , the value of Z along the three-sigma steepest trajectory would be greater than the corresponding values of Z achieved by 99.865 percent of all normal missiles subjected to the assumed head wind.

A2.2.4.4.2. Three-Sigma Lateral Launch Area Trajectory. The three-sigma lateral launch area trajectory should maximize Z as a function of Y' , where the azimuth of the Y' axis must be specified by the Flight Analysis Office for each program or group of similar flights. When looking down-range, the negative Y' axis is laterally directed to the right with respect to the intended flight line, the actual direction being perpendicular to the lateral impact limit line being protected. In calculating this trajectory, a lateral wind blowing toward (or away from) the impact limit line, that is, blowing from (or toward) the positive Y' direction normally is used. This wind profile should, but may not always, represent the worst conditions for which a launch would be attempted. Therefore, other wind azimuths may need to be examined for worst conditions depending on the particular vehicle's guidance system response to wind direction. Other perturbing factors that add significantly to the vehicle lateral movement, such as gyro drift, roll program error, and alignment errors, should also be included in the calculations. The lateral launch area trajectory is a three-sigma trajectory in that, for any Y' , the value of Z along the three-sigma lateral launch area trajectory would be greater than the corresponding values of Z achieved by 99.865 percent of all normal missiles subjected to the assumed lateral wind.

A2.2.4.5. Fuel-Exhaustion Trajectory. For many flights, a programmed thrust termination may be scheduled well in advance of fuel exhaustion. To know whether a potential safety problem can arise if the vehicle should fail to cut off, trajectory data through fuel exhaustion are needed. For ballistic missile flights, the information should be provided only for the last stage IAW assumptions mutually agreed to by the Range User and Range Safety. For orbital flights, the fuel exhaustion trajectory should be provided for the last suborbital stage. The requirement should be met by extending either the nominal or three-sigma maximum-performance trajectory through fuel exhaustion, depending on which produces a greater impact range.

A2.2.4.5.1. Cruise Missiles. In calculating this trajectory, a tail-wind profile should be used that represents the worst wind conditions for which a launching would be attempted. For any particular time after launch, approximately 99.73 percent of all normal vehicles (assuming a normal Gaussian distribution) will have impact ranges less than the range achieved at that time by a three-sigma high performance mission.

Attachment 3

MALFUNCTION TURN DATA

A3.1. Introduction. This attachment provides background information and details about range safety malfunction turn data requirements. It is applicable to ballistic missiles, space vehicles, cruise missiles. The turn data shall describe the turning capability of the vehicle velocity vector as a function of thrust vector offset or other parameters characterizing the turns. This information is used to determine how fast a vehicle or, more exactly, a vehicle impact point can deviate from the nominal if a malfunction occurs. Velocity vector turn data is required only for the thrusting periods from launch up to a point in flight where effective thrust of the final stage has terminated or to thrust termination of that stage or burn that places the vehicle in orbit. **Note:** the double asterisks (**) used in this attachment mean that the magnitude, interval, or duration for the required item varies from program to program, and the value given is the typical value.

A3.2. Turn Definitions.

A3.2.1. Yaw turn – the angle turned in the lateral direction by the total velocity vector. The *lateral plane* is defined as the plane normal to the vector generated by the cross-product of the unit vectors of the total velocity and the normal to the nominal trajectory plane, not the angle turned in the horizontal plane by the horizontal component.

A3.2.2. Maximum turn capability – the envelope of the maximum-rate trim and all tumble velocity vector turn angle curves for a given malfunction time, irrespective of how unlikely this rate is to occur.

A3.2.3. Trim turn – a turn resulting from a malfunction that causes the launch vehicle thrust moment to balance the aerodynamic moment while imparting a constant rotation rate to the vehicle longitudinal axis. The maximum-rate trim turn is the trim turn made at or near the greatest angle of attack that can be maintained while the aerodynamic moment is just balanced by the thrust moment, whether the vehicle is stable or unstable.

A3.2.4. Tumble turn – the family of tumble turns that results if the airframe rotates in an uncontrolled fashion at various angular rates, each rate being brought about by a different, constant value of the thrust vector offset angle or constant value of another parameter that defines the tumble turn.

A3.2.5. 90-degree option – the turn produced by directing and maintaining the vehicle thrust at about 90 degrees to the velocity vector without regard for how this situation can be brought about.

A3.2.6. Turn Angle Envelope – the maximum turn angle curve created by selecting the points from a variety of individual engine deflection curves that provide maximum turn angle for the shortest malfunction duration. The associated velocity curve will be derived by selecting the velocity that physically corresponds to the final maximum turn angle curve.

A3.2.7. Turn Curve – Simplified data format used to represent the malfunction turn in terms of how the velocity vector magnitude and direction in a plane changes with time.

A3.2.8. Turn Trajectories – Data format that represents numerous malfunction turn simulations in a standard trajectory format.

A3.3. Malfunction Turn Computation Requirements.

A3.3.1. Turning information need be computed for the nominal or reference trajectory only.

A3.3.2. In the various velocity vector turn computations, it should be assumed that the vehicle performance is normal up to the point of the malfunction that produces the turn.

A3.3.3. If turn curve data is to be provided, the effects of gravity shall be omitted from the final turn data calculations.

A3.3.4. If pitch and yaw turn angles are essentially the same except for the effects of gravity, the yaw turn angles may be determined from pitch calculations that, in effect, have had the gravity component subtracted out at each step in the computations.

A3.3.5. During the first 100** seconds of flight both pitch and yaw turns shall be provided. After 100** seconds, turns need be computed only in the yaw plane. For each program, Range Safety provides the Range User with the specific value to use for each parameter marked with the double asterisks. **Exception:** During the first 100** seconds of flight, when neglecting gravity, if the pitch and yaw turns are the same, only the yaw turns are required.

A3.3.6. Malfunction turn data are required for malfunctions initiated at even 4** second intervals beginning 4** seconds after first motion continuing for the first 100** seconds of flight or through the first-stage thrusting phase and into the second-stage phase for at least one time point, and at even 8** second intervals thereafter.

A3.3.7. One possible difficulty needs to be mentioned in connection with calculating tumble turns for aerodynamically unstable missiles. In the high aerodynamic region, it often turns out that no matter how small the initial deflection of the rocket engine, the airframe tumbles through 180 degrees or one-half cycle in less than the specified time period for which the calculations are to be carried out. In such a case, if the computation is carried out for the specified time period, part of the angle turned by the velocity vector during the first half cycle is then canceled out during the second half cycle of the turn. If only tumble turns were considered in such cases, the conclusion would be reached that the vehicle velocity vector can turn through a greater angle in a shorter time period than it can in a longer time period. This is an unacceptable conclusion from a safety viewpoint. The envelope of the family of tumble turns must rise continuously throughout the specified malfunction time period. One generally acceptable way to satisfy this requirement is to compute tumble turn angles without considering aerodynamic forces. Although such a vacuum turn cannot actually be simulated in the atmosphere by means of a constant engine deflection, in all likelihood there is some particular intelligent behavior of the engine that can approximate the turn fairly closely. If, however, vacuum tumble turns are considered unrealistic and unjustifiable, other types of malfunctions shall be considered.

A3.3.8. The turn data shall be defined for a series of malfunction modes such as thrust vector offset. Turn data computations shall include a credible distribution (range) of parameter values to demonstrate the variation of the turn characteristics caused by each malfunction mode. If the turns can occur as a function of more than one malfunction mode (for example, solid rocket motor (SRM) thrust vector offset angle for thrust vector control failures and thrust dissipation time for SRM nozzle burn through), turn data are required for each mode. Where possible, the same set of malfunction modes shall be used for each turn initiation time.

A3.4. Malfunction Turns off of Guidance and Performance Dispersed Trajectories. Although velocity vector turning computations are not required for the three-sigma maximum and three-sigma minimum performance trajectories, a method for applying the turn angles to these trajectories shall be provided. The trajectory data items listed in [paragraph A2.2.2](#) shall also be applied for the trajectory used to start the turn computations, if this trajectory is not one of those provided in response to [paragraph A2.2.1](#) Range Users should contact Range Safety regarding data format requirements. A columnar or block printout is acceptable. In addition, a complete discussion is required of assumptions made, methods of calculation, and equations used in deriving the malfunction turns.

A3.5. Determining Types of Data to Submit. In determining the maximum turn capability of a vehicle, the usual procedure is for the Range User to consider both trim turns and tumble turns, in both the pitch and yaw planes. However, with Range Safety approval, the Range User may elect to calculate turn rates using the 90-degree option in lieu of trim and tumble turns. If the 90-degree option is ruled out, the criteria for each of the vehicle conditions listed in paragraphs [A3.5.2](#) through [A3.5.4](#) should be used to determine whether trim turns, tumble turns, or both should be provided at each turn initiation time. For determining the format (of turn curves vs turn trajectories) to deliver refer to [paragraph A3.5.5](#).

A3.5.1. 90-Degree Option. In some cases, Range Safety may accept turning angles or rates computed on the basis of the 90-degree assumption even though it is extremely unlikely for the missile to achieve these turn rates. This option is usually quite disadvantageous to the Range User, since larger turning angles (higher turn rates) lead to more restrictive destruct criteria. Such unduly restrictive criteria could necessitate the revision of a proposed flight plan that may otherwise have been allowed or could result in somewhat earlier destruction of an erratic missile.

A3.5.2. Condition 1. For Vehicles Aerodynamically Unstable at All Angles of Attack. During that part of flight where the maximum trim angle of attack is small, it may be obvious that tumble turns lead to greater turning angles. If the maximum trim angle of attack is large, trim turns will in all probability lead to higher turning angles than tumble turns and to more restrictive destruct criteria.

A3.5.2.1. If the Range User can state that the probability of flying a trim turn even for a period of only a few seconds is virtually zero, only tumble turns are required.

A3.5.2.2. If the Range User cannot so state, a series of trim turns (that includes the maximum-rate trim turn) and the family of tumble turns shall be provided.

A3.5.3. Condition 2. For Vehicles Stable at All Angles of Attack.

A3.5.3.1. If the vehicle is so stable that the maximum thrust moment cannot produce tumbling but produces a maximum-rate trim turn at some angle of attack less than 90 degrees, a series of trim turns that includes the maximum-rate trim turn shall be provided.

A3.5.3.2. If the maximum thrust moment results in a maximum-rate trim turn at some angle of attack greater than 90 degrees, a series of trim turns shall be provided only for angles of attack up to and including 90 degrees.

A3.5.4. Condition 3. For Vehicles Unstable at Low Angles of Attack but Stable at Some Higher Angle of Attack Region:

A3.5.4.1. If large engine deflections result in tumbling, whereas small engine deflections do not, a series of trim and tumble turns should be generated as prescribed in [paragraph A3.5.2](#) for aerodynamically unstable missiles. The same difficulty discussed in [paragraph A3.3.5](#) with tumble turns may arise here; namely, the envelope of the computed tumble turns may fail to rise continuously throughout the entire time period for which the calculations are to be carried out. In this event, either tumble-turn calculations neglecting aerodynamic forces or trim-turn calculations must be made as discussed in [paragraph A3.5.2](#).

A3.5.4.2. If both large and small constant engine deflections result in tumbling, irrespective of how small the deflection might be, the turn data achieved at the stability angle of attack, assuming no upsetting thrust moment, are required in addition to the turn data achieved by a tumbling vehicle. This situation arises because the stability at high angles of attack is insufficient to arrest the angular velocity that is built up during the initial part of a tumble turn where the vehicle is unstable. Although the missile cannot arrive at this stability angle of attack as a result of the constant engine deflection, there is some deflection behavior that will produce this result. If arriving at such a deflection program is too difficult or too time consuming, it may be assumed that the vehicle somehow instantaneously rotated to the trim angle of attack and stabilizes at this point. If so, tumble turn angles may be used in range safety destruct calculations during that part of flight for which the envelope rises continuously for the duration of the computation.

A3.5.5. For vehicles thrusting during a nominal high velocity and high angle of attack portion of flight, or vehicles that have large thrust vector(s) offset away from the center of gravity, or vehicles that have large aerodynamic moments not typical of a standard launch vehicle.

A3.5.5.1. Turn curve data becomes hard to apply for Range Safety assessments. For phases of flight where nominal angle of attack is high or the vehicle has asymmetry, many (100s to 1000s) simulated turn trajectories are required per failure time. Turn trajectories should contain multiple thrust vector offsets in multiple turn planes per failure time. Additionally, each turn trajectory should initiate from a randomly selected trajectory within the family of guidance and performance trajectories. Malfunction turn trajectories should follow the data format and data items specified in [paragraph A6.3.7](#) and requirements in paragraphs [A3.3](#) and [A3.6](#).

A3.6. Turn Duration. The malfunction turn data (turn curves or turn trajectories) are to be provided at 1** second intervals, for at least 12** seconds into the turn and until one of the following two conditions are met. Various time intervals or time delays shall be considered, since the delays that are built into the Range Safety destruct calculations depend upon the accuracy, sensitivity, and type of presentation associated with a particular instrumentation system as well as missile characteristics.

A3.6.1. The vehicle reaches a critical loading condition that will cause breakup.

A3.6.2. The vehicle is tumbling so rapidly that the effective thrust acceleration is negligible; for example, the projected vacuum impact point is no longer moving significantly.

A3.7. Turn Curve Data Format. Malfunction turn data shall be delivered in the form of graphs and digital data files. Scale factors of plots shall be selected so the plotting and reading accuracies do not degrade the basic accuracy of the data. In addition, tabular listings of the data used to

generate the graphs are required in American Standard Code for Information Interchange (ASCII) format files on floppy or compact disks or other electronic media, with corresponding hard copies. The 5 data files required shall provide textual information about the files, time and thrust information, the maximum turn envelope of the family of curves, associated velocities for this envelope, and special time points for the family of curves presented in the graphs.

A3.7.1. Velocity Turn Angle Graphs. For turn angle graphs, the ordinate represents the total angle turned by the velocity vector in degrees, and the abscissa, the time duration of the turn in seconds.

A3.7.2. Velocity Magnitude Graphs. For velocity magnitude graphs, the ordinate represents the magnitude of the velocity vector in feet per second, and the abscissa, the time duration of the turn in seconds.

A3.7.3. Digital Data Files. The required data consists of five data files. Data units shall be in the English system. Files 2 through 5 shall contain related data and must have the same number of records. Each record in an individual file should have the same number of words. Each line of the records in File 3 – 5 shall contain 6 words (suggested format is 6E20.12). File contents shall be as shown in [Figure A3.1](#).

Figure A3.1. Digital File Contents.

- File 1. The information file. This file is for documentation purposes only and format is not defined here. However, it should carefully specify data file record and word lengths for the following four files. It should also define the appropriate application of the data and may contain any other descriptive information felt necessary.
- File 2. Time, thrust, and weight data presented at standard incremental times (see paragraph [A3.3.6](#)). The time corresponds to flight time at the start of each malfunction. Thrust and weight should correspond to the flight time. Time will be used to tag each record in subsequent files and should therefore correspond to records in files 3 through 5. Each record contains the following three words:
 - Word 1 = flight time (seconds)
 - Word 2 = thrust (lbs)
 - Word 3 = weight (lbs)
- File 3. Turn angle data for the maximum turn angle envelope. Each record shall provide turn angle data beginning at 0.0 seconds for a minimum of 12 seconds following malfunction (see paragraph [A3.6](#)). The turn information may be presented for a longer period, but this information should be stated in the information file and remain consistent throughout the file. The data words shall be at 0.1 second intervals and the record shall correspond to the flight time of malfunction initiation in File 2. Time interval spacing of less than 0.1 seconds is acceptable but must be documented in File 1 and remain consistent throughout the file. This file will contain a minimum of 121 words (12 seconds at 0.1 second intervals).
- File 4. Velocity data for the maximum turn angle envelope. Each record shall contain velocities corresponding to each max turn angle in File 3, with each record corresponding

to a flight time in File 2. File format must be the same as File 3. Type of velocity information included in this file should be clearly stated in File 1 (see paragraph **A3.8.2**).

- **File 5.** Special time points for the maximum turn angle envelope. Time, turn angle, and velocity data for the maximum negative turn angle point and the inflection point for each curve for the maximum turn envelope described in each record of File 3 and File 4, corresponding to a flight time in File 2. Each record contains six words:
 - Word 1 = time (seconds) of maximum negative turn angle point
 - Word 2 = turn angle (degrees) at maximum negative turn angle point
 - Word 3 = total velocity (ft/sec) at maximum negative turn angle point
 - Word 4 = time (seconds) of inflection point of maximum turn angle envelope
 - Word 5 = turn angle (degrees) at inflection point of maximum turn angle envelope
 - Word 6 = velocity (ft/sec) at inflection point of maximum turn angle envelope

A3.8. Turn Curve Data Items. The following data items are required for each malfunction initiation time. The information that describes the turn is required at intervals of 1 second or less.

A3.8.1. Velocity Turn Angle. One graph is required for each malfunction mode at each initiation time. For tumble turns, each graph is to include the envelope of all tumble turns for all possible constant thrust vector offset angles (or other parameter). In this case, plots of the individual tumble turn curves that are used to define the envelope are required on the same sheet with the envelope. For trim turns, a series of trim turn curves for representative values of thrust vector offset (or other parameter) is required. The series of trim turn curves shall include the maximum-rate trim turn.

A3.8.2. Velocity Magnitude. Either total velocity magnitude or incremental change in velocity magnitude from time of malfunction can be presented although the incremental change in the velocity is desired. For each thrust vector offset angle (or other parameter), the point on the velocity graph corresponding to the point of tangency on the tumble turn-angle envelope shall be indicated. For tumble turns, velocity magnitudes are required in graphical form as a function of time for each thrust vector offset (or other parameter) used to define the tumble turn envelope.

A3.8.3. Vehicle Orientation. If the vehicle has thrust augmenting rocket motors, then the vehicle attitude (in the form of the angular orientation of the vehicle longitudinal axis) as a function of time into the turn is required for each turn initiation time.

A3.8.4. Onset Conditions. The vehicle state at the beginning of the turn, including the thrust, weight, and state vector (including velocity magnitude) shall be provided for each set of curves.

A3.8.5. Breakup Information. The Range User shall specify if the vehicle will remain intact throughout the turn. If the vehicle will breakup during a turn, then the point (time) for which vehicle breakup is expected to occur shall be indicated. The time into the turn at which vehicle breakup would occur can be a specific value or a probability distribution for time to breakup.

A3.8.6. Probability of Occurrence. The distribution for the probability of occurrence for the value of the parameter defining the turns, such as thrust vector offset, shall be defined for each parameter (as a function of turn initiation time if the distribution varies with time). Also, information defining how the probability distribution was determined shall be provided.

A3.9. Velocity Vector Turn Data for Cruise Missiles.

A3.9.1. From launch or drop until cruise altitude is reached, this information is required to provide a means of determining the maximum angle through which the missile velocity vector can turn in the event of a malfunction. The maximum angles turned for time intervals up to about 30** seconds in duration are required. (The actual times will depend on the delays included in the FSS as well as other factors). Both pitch and yaw turns should be investigated and the larger presented. It should be assumed that the missile has followed the nominal trajectory up to the point of malfunction that produces the maximum-rate trim turn. Thereafter, it should be assumed that the missile is trimmed to the maximum air load that the structure can stand, or that the missile is flying out of control in an attitude that produces maximum lateral acceleration (for example, a near 90-degree bank with a maximum pitch turn). During the launch phase, the missile may not be able to fly for 30** seconds under these extreme conditions. In this event, it should be assumed that the missile is turning at the maximum rate for which these flight conditions can be maintained for required time duration. A complete discussion of the methods used in the calculations shall be provided. This discussion should include assumptions made, types of malfunctions considered, forces producing turns, equations used, and sample computations.

A3.9.2. During the cruise phase, the maximum turn capability of the velocity vector as a function of altitude is required. Rates should be based on normal missile weights and the expected cruising speeds at each altitude. For this phase of flight, the data may be expressed in the form of maximum lateral accelerations, if desired. A complete discussion similar to that requested for in [paragraph A3.9.1](#) is required. Also required is the maximum turn capability that the guidance system and the autopilot can command during the cruise phase.

A3.9.3. A cruise missile may be boosted from the launch pad by separable rockets or by a booster motor that is an integral part of the missile. While the booster motor is thrusting, the missile may perform more as a ballistic missile or space vehicle than as a cruise missile. In such cases, maximum turning capability data during the boost phase will be required as specified in [paragraph A3.5](#) rather than as specified in [paragraph A3.9.1](#) For each missile program, Range Safety shall indicate which procedures are to be used in computing malfunction turn data during the boost phase.

Attachment 4

FRAGMENT DATA

A4.1. Introduction. Fragment listings and characteristics for all potential modes of vehicle breakup are required. At a minimum, the following modes of vehicle breakup shall be considered: (1) breakup due to FSS activation, (2) breakup due to an explosion, and (3) breakup due to aerodynamic loads, inertial loads, and atmospheric reentry heating. Fragment data is required up to thrust termination of the last stage that carries a destruct system. All fragments of 0.5 lbm/sqft and greater, based on the minimum projected area, shall be included; and, as much as possible (best estimate), all fragments down to a mass of 1.0 gram shall be included. Similar fragments can be accounted for in fragment groups, however it is preferred that a list of each of the individual fragments be provided.

A4.2. Describing Fragment Groups. A fragment group is one or more fragments whose characteristics are similar enough to allow all the fragments to be described by a single “average” set of characteristics. The following information is provided to aid in determining fragment groups:

A4.2.1. Fragment Type. All fragments shall be of the same type (for example solid propellant, explosive, or inert), including whether propellant fragments are burning following breakup.

A4.2.2. Ballistic Coefficient (beta). The maximum beta in the group should be no more than about a factor of 3 times the minimum (except for very low beta fragments where betas ranging from near 0 to about 3 pounds per square foot [lb/ft²] can be grouped together).

A4.2.3. Weight. If the fragments contain propellant that is burning during free fall, the maximum weight of propellant in a fragment group should be no more than a factor of 1.2 times the minimum weight of propellant. The fragments included in a group should be such that the kinetic energies (KE) based on terminal velocity ($KE = 13 \times \text{weight} \times \text{beta}$, foot pounds force {ft-lbf} [The 13 has units of ft³/lb_f]) are within the following guidelines:

A4.2.3.1. Fragments having $KE < 35$ are grouped.

A4.2.3.2. Fragments having $35 < KE < 100$ are grouped.

A4.2.3.3. Fragments having $100 < KE < 6,200$ should be grouped so that the maximum fragment KE is no more than about three times the minimum.

A4.2.3.4. Fragments having $6,200 < KE < 33,670$ should be grouped so that the maximum fragment KE is no more than about three times the minimum.

A4.2.3.5. Fragments having $33,670 < KE < 74,000$ should be grouped so that the maximum fragment KE is no more than about three times the minimum.

A4.2.3.6. Fragments having $74,000 < KE < 1,616,000$ should be grouped so that the maximum fragment KE is no more than about three times the minimum.

A4.2.3.7. Fragments having $KE > 1,616,000$ are grouped.

A4.2.4. Velocity Perturbation. The maximum expected destruct explosion or pressure rupture induced velocity in the group should be no more than a factor of 1.2 times the minimum induced velocity.

A4.2.5. Projected Area. For explosive fragments, the range of projected areas should be controlled by requiring that the maximum value of the weight of propellant at impact is no more than a factor of two times the minimum; however, if the propellant is burning during free fall the factor is 1.2. There is no limit on the range of projected areas for inert fragments.

A4.3. Fragment Data Items. These requirements provide a description of the data items required for each fragment or fragment group for each potential mode of vehicle breakup. The variation of the fragment characteristics with flight time shall be defined. Normally this is accomplished by specifying multiple fragment lists, each of which is applicable over a specified period of flight.

A4.3.1. That fragment that, in the absence of winds, is expected to travel a maximum distance, and that fragment(s) that, in the absence of winds, is expected to travel a minimum distance shall be included.

A4.3.2. Fragment group name.

A4.3.3. Number of fragments.

A4.3.4. General description(s) of fragments such as part/component, shape, dimensions, and figure.

A4.3.5. Breakup Altitude. For breakup due to atmospheric reentry, the altitude at which breakup is expected to occur shall be provided.

A4.3.6. Ballistic Coefficient (beta). Nominal, plus three-sigma, and minus three-sigma values (pounds per square foot) for each fragment or group; including graphs of the coefficient of drag (C_d) versus Mach number for the nominal and three-sigma beta variations for each fragment or group. Each graph shall be labeled with the shape represented by the curve and reference area used to develop the curve. A C_d versus Mach curve for axial, transverse, and tumble orientations (when applicable) shall be provided for fragments not expected to stabilize during free-fall conditions. For fragments that may stabilize during free-fall, C_d versus Mach curves should be provided for the stability angle of attack. If the angle of attack where the fragment stabilizes is other than 0 degrees, both the coefficient of lift (C_L) versus Mach number and the C_d versus Mach number curves should be provided. If available, equations for C_d versus Mach curves should be provided. The difficulty of estimating drag coefficient curves and weights for vehicle pieces is fully realized. If this cannot be done satisfactorily, an estimate of the subsonic and supersonic $W/C_d A$ for each major piece may be provided instead. In either case, three-sigma tolerance limits shall be included for the drag coefficients for the maximum and minimum-distance pieces.

A4.3.7. Weight per Fragment. Include the possible three-sigma weight (pounds) variation for the fragment or group. The fragment data shall approximately add up to the total weight of inert material in the vehicle plus the weight of contained liquid propellants and solid propellant that is not consumed in the initial breakup and/or conflagration.

A4.3.8. Projected Area per Fragment (ft^2). Include the axial, transverse, and tumbling area for the fragment or group. This information is not required for those fragment groups classed as uncontained propellant fragments (as described below).

A4.3.9. Estimates of the maximum incremental velocities (feet/seconds) imparted to the vehicle pieces due to FSS activation, explosive and/or overpressure loads at breakup. The velocity is normally assumed to be Maxwellian distributed with the specified maximum value

equal to the 97th percentile. If the distribution is known to be significantly different than the Maxwellian, the correct distribution is required, including if the specified value should be interpreted as a fixed value with no uncertainty.

A4.3.10. Fragment Group Type.

A4.3.10.1. Type 1 = inert fragments; for example, no volatile type material that could be burning or could explode.

A4.3.10.2. Type 2 = uncontained solid propellant fragments; for example, solid propellant exposed directly to the atmosphere and will not explode upon impact.

A4.3.10.3. Type 3 = contained propellant fragments; for example, propellant that is enclosed in a container, such as a motor case or pressure vessel, and will not explode upon impact.

A4.3.10.4. Type 4 = contained explosive propellant fragments; for example, propellant that is enclosed in a container, such as motor case or pressure vessel, and will explode upon impact.

A4.3.10.5. Type 5 = uncontained explosive solid propellant fragments; for example, solid propellant exposed directly to the atmosphere and will explode upon impact.

A4.3.11. Casualty Area per Fragment (ft^2). The casualty area per fragment shall be based on a fragment falling vertically at impact and should reflect the credible fragment orientation giving the maximum projected area.

A4.3.12. Vehicle stage where fragment group originated.

A4.3.13. For those fragment groups defined as uncontained propellant fragments, contained propellant fragments, and explosive fragments, an indication as to whether the propellant fragments are burning during free fall.

A4.3.14. For those fragment groups defined as contained propellant fragments, explosive or non-explosive, the initial weight of contained propellant (pounds) and the consumption rate during free fall (pounds per second); the initial weight of the propellant in a contained propellant fragment is the weight of the propellant before and after the anomalous event.

A4.3.15. Diffusion and dispersion of any fragments containing toxic or radioactive materials and the radiation and exposure characteristics.

A4.4. Residual Thrust Dispersion. If an upper stage can be ignited as a result of FSS activation on a lower stage, sufficient information is required to evaluate the effects and duration of thrust, and the maximum deviation of the impact point that can be brought about by this thrust. The explosion effects on remaining fuels, pressurized tanks, and remaining stages are required, particularly with respect to ignition or detonation of upper stages if destruct action is taken during the burning period of a lower stage. For each thrusting or non-thrusting stage having residual thrust capability following FSS activation, provide either the total residual impulse (pounds-seconds) imparted after "arm" and "destruct," or the full-residual thrust (pounds-feet) versus time (s). Otherwise, a detailed analysis that clearly shows the stages are not capable of thrusting after FSS activation is required.

Attachment 5

JETTISONED BODY DATA

A5.1. General Data Requirements. The following data shall be provided for each jettisoned body:

A5.1.1. The nominal impact point. The nominal impact point (or aiming point) for each jettisoned body shall be given in terms of geodetic latitude and longitude in decimal degrees, and range (nautical miles) from the pad. Computations shall be made for an ellipsoidal rotating earth taking into account drag and, if applicable, lift.

A5.1.2. The number of fragments resulting from a specific scheduled jettison. If the jettisoned body is expected to break up during reentry, an estimate of the number of pieces, their approximate weights, cross-sectional areas, ballistic coefficients, and their impact ranges are required.

A5.1.3. Jettison flight time (seconds), total weight (pounds) jettisoned and weight per fragment (pounds), reference area per fragment (ft^2), and the best estimate of C_d versus Mach number and sub-sonic and supersonic ballistic coefficient for each stage or piece. The C_d versus Mach number data are to be provided in graphical and tabular format for the nominal, minus three-sigma and plus three-sigma drag coefficients and shall cover the range of possible Mach numbers from 0 to the maximum values expected during free fall. Also indicate whether bodies are stable and, if so, at what angles of attack. For pieces that can possibly stabilize during free flight, drag coefficient curves shall be provided for the stability angle of attack. If the stability angle of attack is other than 0 degrees, both coefficient of lift (C_L) versus Mach number and C_d versus Mach number curves shall be provided. State briefly how drag curves were determined.

A5.1.4. The three-sigma uprange-downrange (nautical miles) and crossrange (nautical miles) impact dispersions and the azimuth orientation of the dispersion major axis (degrees clockwise from true North), assuming a normally functioning vehicle. Three-sigma wind effects acting upon the descending body or pieces shall be included in the dispersion area. A brief discussion of the method used to determine dispersions is also required. The magnitude of the wind contribution in the total dispersions is required.

A5.1.5. The resultant ballistic coefficient at time of debris impact.

A5.1.6. Maximum possible impact range of each impacting stage or reentry vehicle for a missile burning to fuel exhaustion.

A5.2. Reentry Vehicle Data. The items below are required as part of the trajectory or with general vehicle data:

A5.2.1. Type of reentry vehicle (RV) heat protection (ablation or heat sink); if ablation, provide ablation tables. The ablation table is a listing of Mach number or altitude versus the ratio W/W_0 , where W equals the instantaneous RV weight during reentry and W_0 equals the vehicle weight before ablation.

A5.2.2. The RV weight before ablation.

A5.2.3. A table of RV drag coefficient versus Mach number.

A5.2.4. A table of RV drag coefficient as a function of altitude.

A5.2.5. RV aerodynamic reference area associated with the drag coefficients.

A5.3. Small Unguided Rockets and Probe Vehicles. Three-sigma range and cross-range dispersions are required for each stage, separable fragment or component, and payload. Since the magnitude of these dispersions may determine whether a destruct system deviation equivalent level of safety certification or waiver will be granted or the extent to which shipping must be clear of impact areas, a careful analysis is essential.

A5.3.1. The following factors should be considered in determining three-sigma impact dispersions about predicted impact points:

A5.3.1.1. Variation in thrust.

A5.3.1.2. Error in drag estimates.

A5.3.1.3. Thrust misalignment.

A5.3.1.4. Fin and body misalignment.

A5.3.1.5. Variation in weight.

A5.3.1.6. Variation in ignition times of stages.

A5.3.1.7. Impulse errors.

A5.3.1.8. Tip-off and separation perturbations.

A5.3.1.9. Errors in wind velocity measurements.

A5.3.1.10. Errors in launcher setting.

A5.3.1.11. Other significant perturbing influences, such as wind effects.

A5.3.2. The three-sigma variation in each factor shall be provided in tabular format in addition to the extent to which each factor displaces the impact point of each stage in the downrange and cross-range directions. Then, total impact dispersion is computed by a statistical combination of the individual displacements.

A5.3.3. A brief discussion of the assumptions made, method of analysis, and method of computation is required. The extent to which the three-sigma impact dispersion areas change with quadrant elevation angle is also required.

Attachment 6

FLIGHT TRAJECTORY DATA PREPARATION, SUBMITTAL AND PROCESSING

A6.1. Introduction : This attachment describes the requirements, procedures, format, and instructions for preparing, submitting, and processing standard theoretical trajectory data in the format to be determined. It applies to SSC Range Users.

A6.1.1. Scope. The present theoretical trajectory data format accommodates the following basic types of launches supported by the Eastern and Western ranges:

A6.1.1.1. Single and Multiple Reentry Ballistic launches where support is necessary from launch through midcourse, reentry, and to impact (Option 1).

A6.1.1.2. Orbital launches with fixed flight azimuths where trajectory data generally is provided to orbit insertion and to meet additional support requirements which may continue for varying periods (Option 2).

A6.1.1.3. Orbital launches with variable flight azimuths (VFA) for a specified launch window where multiple trajectories to orbit insertion may be required to adequately characterize the mission and meet lead range requirements. These windows are intended to be flight azimuth variable as a function of time, although other parameters may also be varying. Variable azimuth missions can be categorized as step-wise (SVFA, Option 3) or continuous (CVFA, Option 4), where the trajectory flight azimuth varies discretely or continuously, respectively, throughout the launch window. Specific trajectory requirements for each option are specified by the lead range.

A6.1.2. Range support for which the Range User provides all or part of the required trajectory data may terminate at or near final thrusting. In all cases, the Range User will provide trajectory data from lift off through the end of program support requirements. When complete trajectory data are not provided, supplementary data are required to enable the lead range to generate the additional necessary trajectories which may include free fall and powered flight.

A6.2. Responsibilities.

A6.2.1. Lead Range. The lead range will:

A6.2.1.1. Provide the Range User with instructions on submission and distribution of trajectory data media when assignment of a program is received by a range.

A6.2.1.2. Receive, prepare, and make distribution of copies of trajectory data to range support agencies as required.

A6.2.2. Range Users. Range Users will:

A6.2.2.1. Provide two copies via appropriate media (CD acceptable) of the theoretical trajectory data in the format described in [paragraph A6.3.2](#) to the lead range when:

A6.2.2.1.1. The Program Requirements Document (PRD) is submitted. An appropriate medium will be provided that contains the best estimate of each trajectory for which the Program Support Plan (PSP) is expected to reply.

A6.2.2.1.2. The mission trajectories are changed, or additional trajectories are added.

A6.2.2.2. Revise the theoretical trajectory data in the format described in [paragraph A6.3.2](#) when use of the trajectory, as supplied, will adversely affect the support needed by either planning or operational phases of the user's programs.

A6.2.2.3. Provide the final required theoretical trajectory via the appropriate media (CD acceptable), in the format described in [paragraph A6.3.2](#) This shall be complete with any additional trajectories that may be required by the range per the Minimum Lead Times specified in SSCMAN 91-710.

A6.3. Theoretical Trajectory Data Format.

A6.3.1. General Requirements. This paragraph describes the theoretical trajectory data format required by the Eastern and Western ranges in support of the various types of launch programs:

A6.3.1.1. The Range User will supply completed trajectories from liftoff to the end of the range safety requirements and Range User metric data requirements. Trajectory requirements for variable flight azimuth missions may be specialized for the individual ranges and the input is described in one of the options that follow or in discussions with the Range User. If the Range User's type of launch does not fit into one of these options or if any doubt exists, the lead range will be contacted through the local program office in order that a discussion can be arranged to determine the inputs required and Range User metric data requirements.

A6.3.1.2. Theoretical trajectory data will be in the format described in paragraphs [A6.3.7](#) and [A6.3.8](#) on one of the media selected from [paragraph A6.4](#) and shall contain the following:

A6.3.1.2.1. Trajectory data and information file common to all categories of launches from Eastern and Western ranges.

A6.3.1.2.2. Trajectory/vehicle parameters for the variable window or other launch programs in which the lead range generates certain trajectory data.

A6.3.1.2.3. Dispersed trajectory data for Range Safety use.

A6.3.2. Description of the Standard Theoretical Trajectory Data Format.

A6.3.2.1. The trajectory data package submitted shall be on one of the media described in [paragraph A6.4](#) All data must be written 8-bit ASCII. The data should contain a file for each trajectory and a separate file containing identification information. Information on the trajectory types is described in [paragraph A6.3.3](#).

A6.3.2.2. A listing of the identification information and trajectory parameters should also be provided in printed form. The trajectory parameters listing should contain all 38 words as described in [paragraph A6.3.7](#).

A6.3.2.3. The identification information file shall contain the information described in [paragraph A6.3.5](#) The items included in the identification information shall be formatted as described in the examples in [paragraph A6.3.5](#), in ASCII test report format, suitable for printing on standard output devices, or processing with common commercial-off-the-shelf (COTS) tools/editors (e.g., Microsoft MS Word).

A6.3.2.4. The trajectory files must contain 38 parameters for each time sample. The description of each of the parameters is given in [paragraph A6.3.7](#) Only words 1 through

38 should be provided. If any of the 38 parameters are not available they should be left blank.

A6.3.2.5. The earth fixed pad-centered coordinates x and y should have values of zero at time zero (i.e., words 1, 2, and 3 equal 0.0). The z coordinate (word 4) should have a value reflecting the vehicle's tracking point referenced to the pad (see [paragraph A6.3.5.6](#)). Sampling times should be included immediately prior and after (resulting in duplicate times) all discrete event times. The times at which events are sampled are described in [paragraph A6.3.4](#).

A6.3.2.6. Each applicable parameter in the information file and each trajectory parameter indicate the decimal digits desired, i.e. (4D) means four decimal places of resolution. The requirement is not intended to imply precision or accuracy of the data. In the event that machine limitations do not permit listing all digits, including the desired decimal portion, the maximum number of digits available is to be provided. Items 1 through 13 are common to all types of launch programs and are referred to as General Information File Items. Items 14 and later are dependent on the type of launch program option and are identified in this manner.

A6.3.2.7. Trajectory data file format is an ASCII text file of records containing up to thirty-eight comma delimited parameters. Each parameter is presented in exponential form to 10 significant digits (.3356233478E 02). Records containing all thirty-eight parameters will consist of ten lines: The first nine lines will contain four values and the last line will contain two values. The end of each line will be indicated by ASCII <CR> (carriage return X0D) and <LF> (line feed X0A) control characters. The relative positional relationship of parameters and parameter slot definition will be maintained by the use of the comma delimiter. It is permissible to replace two or more contiguous lines containing unused parameter slots (i.e., two or more consecutive commas, optionally separated by blanks) by one line as long as the number of characters in the new line is less than eighty. Several examples are provided below. [Figure A6.1](#) is provided to show column positions only and must not be included in the file. [Figure A6.2](#) is for a 0 second time sample, [Figure A6.3](#) is for a 1 second time sample, and [Figure A6.4](#) is for a 2 second time sample. The first nine lines contain four parameters each and the tenth line contains the remaining two parameters. Explanatory notes are in parenthesis, bolded and italicized ASCII control characters are denoted in bolded angle brackets (<CR>).

Figure A6.1. Trajectory data files format, first two lines.

00000000011111111112222222222333333333334444444444555555555566666666667777
1234567890123456789012345678901234567890123456789012345678901234567890123

Figure A6.2. Trajectory data files format, 0 second time sample.

```
(start record 1, all parameters words present)

.0000000000E+00, .0000000000E+00, .0000000000E+00, .0000000000E+00,<CR><LF>
.0000000000E+00, .0000000000E+00, .0000000000E+00, -.4186876542E+00,<CR><LF>
-.7081567869E+00, .5648473556E+00, -.8026938867E+00, -.4242876547E+02,<CR><LF>
-.5964502456E+00, .4248568766E+00, -.7060105643E+00, .5667876544E+00,<CR><LF>
.2668470000E+00, .3321654200E+06, .0000000000E+00, .0000000000E+00,<CR><LF>
.7908283505E+01, .6046492754E+00, .7890578745E+00, .7876655544E+00,<CR><LF>
.0000000000E+00, .7902333144E+01, .0000000000E+00, .1523456654E+01,<CR><LF>
.0000000000E+00, .6046496782E+00, .2134567777E+01, .0000000000E+00,<CR><LF>
-.8771234564E+07, -.1456786448E+08, .1187655443E+08, .2229032314E+01,<CR><LF>
.3637978807E+11, .7234567801E+25,<CR><LF> (end record 1)
```

Figure A6.3. Trajectory data files format, 1 second time sample.

```
(start record 2, example of two (2) missing parameters words, ASCII (/X20) space padded)

.1000000000E+01, .3860607956E+01, .1818612308E+01, .7081585349E+00,<CR><LF>
-.5964502471E+00, .4247599996E+00, .7060410519E+00, .5322435932E+00,<CR><LF>
.2652945623E+06, .3948653893E+06, .3978008577E+01, .2116736416E+01,<CR><LF>
-.7081567869E+00, .5648473556E+00, .8026938867E+00, .4242876547E+02,<CR><LF>
-.5964502456E+00, .4248568766E+00, .7060105643E+00, .5667876544E+00,<CR><LF>
.2668470000E+00, .3321654200E+06, .0000000000E+00, .0000000000E+00,<CR><LF>
.7908283505E+01, .6046492754E+00, .7890578745E+00, .7876655544E+00,<CR><LF>
.0000000000E+00, .7902333144E+01, .0000000000E+00, .1523456654E+01,<CR><LF>
.1187655443E+08, .2229032314E+01,<CR><LF>
-.1013140805E+02, .8187252815E+01,<CR><LF> (end record 2)
```

Figure A6.4. Trajectory data files format, 2 second time sample.

```
(start record 3, example of four (4) missing parameters words, unpadding, comma delimited)

-.2000000000E+01, .4247599996E+00, -.7060410519E+00, -.5322435932E+00,<CR><LF>
.2652945623E+06, .3948653893E+06, -.3978008577E+01, -.2116736416E+01,<CR><LF>
-.7081567869E+00, .5648473556E+00, -.8026938867E+00, -.4242876547E+02,<CR><LF>
-.5964502456E+00, .4248568766E+00, -.7060105643E+00, .5667876544E+00,<CR><LF>
.2668470000E+00, .3321654200E+06, .0000000000E+00, .0000000000E+00,<CR><LF>
.7908283505E+01, .6046492754E+00, .7890578745E+00, .7876655544E+00,<CR><LF>
.2462453555E+05, .2604555324E+02, .1408251890E+08, .4299696085E+03,<CR><LF>
,,,,-.1289041949E+08, -.1936247060E+08, -.1647622631E+07,<CR><LF>
-.4454435512E+03, .2394739071E+04, -.2450753812E+05,<CR><LF> (end record 3)
```

A6.3.3. Trajectory Information. Except as noted for special trajectory cases, each set of trajectory data will include the nominal trajectory from liftoff to impact or insertion of the payload into final orbit for each critical azimuth and for each new series of missiles. The lead range, Flight Analysis Office, will also normally require the following 3-sigma trajectories: maximum performance IIP, minimum performance IIP, lateral left and right IIP, steepest launch area PP, and lateral launch area PP. These trajectories are defined in SSCMAN 91-710. When dispersed trajectories are waived by Flight Analysis, dispersion increments may be required, as applicable, for calculation of dispersed launch conditions.

A6.3.3.1. For VFA missions (normally time varying), the trajectory media should record the trajectory data files in the order of increasing flight azimuth and day of the firing period. For CVFA missions, trajectories are required at 3° increments across the azimuth range desired by the Range User in which a common reference azimuth is always included. The reference azimuth should correspond to the trajectories that could be used at any flight

azimuth in the desired range with minimal error in representing the vehicle's expected position. Since trajectory data will be provided left and right of the reference azimuth this may result in increments at the minimum and maximum azimuths of less than 3°. For SVFA missions, trajectories will be defined by the Flight Analysis Office at the respective ranges, basically defining the planar nominal (median or modal) trajectory, and the extreme left and right yaw nominal trajectories for each fixed or discrete azimuth. Any remaining trajectory needs at the range will be generated from discussions with the range and Flight Analysis during mission or program introduction. Flight Analysis Office dispersed trajectory data is normally required at least for the reference azimuth (in the middle of the window for CVFA options and at the in-plane azimuth for SVFA options).

A6.3.3.2. If recovery, or track, of any boost stage is required, a complete trajectory of each such stage must be furnished. The booster trajectory, both the information file and the trajectory data, will be recorded on a separate medium. Each applicable parameter in the information file and each trajectory parameter indicate the decimal digits desired. The requirement is not intended to imply significant digits or accuracy of the data.

A6.3.3.3. Printouts from the Range User should be double-spaced between items and single-spaced within the information and data items.

A6.3.4. Sampling Rates. Normally, the time intervals at which trajectory data will be supplied are:

A6.3.4.1. From liftoff to final thrust termination of the last thrusting stage, to thrust termination of that stage or burn which places vehicle in orbit or to impact of any boost segment/stage on which track or recovery is required 1-second intervals.

A6.3.4.2. During programmed changes in thrust of all other stages on which track or recovery is required 1-second intervals.

A6.3.4.3. During free flight or coast periods not exceeding five minutes duration 1-second intervals.

A6.3.4.4. During free flight or coast periods exceeding five minutes duration 5-second intervals.

A6.3.4.5. From 400,000 feet altitude to impact, including reentry (300,000 feet altitude) 2 second intervals.

A6.3.4.6. During programmed changes in altitude 1-second intervals.

A6.3.4.7. At all critical times, such as burnouts, ignitions, separation events, control mode changes, arming functions, and vehicle reorientation (change in pitch, roll or yaw), data points will be inserted in the trajectory as to maintain a monotonic increase in time.

A6.3.4.8. During flight periods in which cameras will be used for coverage, data will be required at least at 2-second intervals. The trajectory data need not be correlated to the time of strobe flash or flare ejection. It is required that at least one trajectory data point be supplied prior to the first strobe flash or flare ejection and at least one data point after the last strobe or flare event. If the strobe or flare events occur in volleys, points are required at the beginning and end of each volley.

A6.3.4.9. Sampling rates will be varied from this table only with approval of the Flight Analysis Office at the lead range. The trajectory requirements will be modified by letter from the Flight Analysis Office when not sufficient for their purposes.

A6.3.5. General Information File Items.

A6.3.5.1. Item 1.

A6.3.5.1.1. Identification of the trajectory to which data applies including program name, PRD number and test code, missile name and number, trajectory identifier if applicable, and Operation Number if available.

A6.3.5.1.2. EXAMPLE: This trajectory applies to the Atlas 50E/NOAA-D, PRD E0D31 Test Code B, Atlas 50E Launch Vehicle and NOAA-D Spacecraft, Operation Number A0069.

A6.3.5.2. Item 2.

A6.3.5.2.1. The date of medium issue, issue number, and whether the medium replaces, or adds to previous identified issues. However, if any changes are made to the data, a new medium should be prepared and transmitted to the range.

A6.3.5.2.2. EXAMPLE: Issued 21 June 1990. Third Revision.

A6.3.5.3. Item 3.

A6.3.5.3.1. The program office assigned to the program, the name of the contractor originating the trajectory data, and enough other information to enable the range to contact the originating range if the need arises.

A6.3.5.3.2. EXAMPLE: Through WS 107A Project Office (6555/DWTD) from ACE Missile Company, PO Box 123, Los Angeles CA 90045. John Watson, Project Engineer, Telephone Bradshaw 272-5262, Ext. 123, TWX West Los Angeles, 6284.

A6.3.5.4. Item 4.

A6.3.5.4.1. Designation of the pad, launcher, or launch point for the vehicle.

A6.3.5.4.2. EXAMPLE: This vehicle will be launched from Pad 17A.

A6.3.5.5. Item 5.

A6.3.5.5.1. The Geodetic latitude (6D), longitude (6D), and height (3D) of the origin of the XYZ data. This is necessary to correlate such items as trajectory and impact point given in the trajectory files. It is also desired that the origin be identified by name when possible. The lead range prefers that longitude be considered positive east of Greenwich and negative from 0 degrees to 180 degrees west of Greenwich. However, for those Range Users not following this convention, the lead range will provide for changes in sign within its computer programs. Longitude values provided should specify East or West. Southerly latitudes will be considered as negative.

A6.3.5.5.2. EXAMPLE: The origin of the XYZ data is the intersection of the launch stand pin plane and the missile center line and is located at 28.327621 degrees north Geodetic latitude and -80.326241 degrees west longitude and 42.826 feet above mean sea level.

A6.3.5.6. Item 6.

A6.3.5.6.1. Physical relationship (2D) of the tracking point on the missile to the trajectory data origin.

A6.3.5.7. Item 7.

A6.3.5.7.1. Azimuth (3D) of the X-axis of the XYZ system measured from true north. This azimuth would normally be the final flight azimuth or rolled azimuth. For VFA launches, the azimuths of the X-axis are specified in the information items as set forth under this option. When this condition is used, the words "Variable Window Launch" should be mentioned.

A6.3.5.7.2. EXAMPLE: The azimuth of the X axis is 105.001 degrees from true north.

A6.3.5.8. Item 8.

A6.3.5.8.1. Name of earth model used in calculations.

A6.3.5.8.2. EXAMPLE: The earth model used in DoD/WGS 1984 (or currently applicable DoD earth model.)

A6.3.5.9. Item 9. Data units of parameters used. English or SI units are acceptable.

A6.3.5.10. Item 10.

A6.3.5.10.1. All critical times (3D) in seconds. For VFA launches, critical times are requested in specific options.

A6.3.5.10.2. EXAMPLE: see [Figure A6.5](#).

Figure A6.5. Example for item 10, all critical times (seconds).

<u>Time (seconds)</u>	<u>Event</u>
0.000	Liftoff
101.210	First stage burnout
105.236	Second stage ignition
109.345	Vehicle reorientation

A6.3.5.11. Item 11. Any special comments of interest may be provided here.

A6.3.5.12. Item 12.

A6.3.5.12.1. Description of the files of trajectory data and the file names.

A6.3.5.12.2. EXAMPLE: see [Figure A6.6](#) for non-variable window trajectory launches, and [Figure A6.7](#) for space vehicles using a variable window.

Figure A6.6. Example for item 12, non-variable window.

FILE 1 (INFO)	CONTAINS the Binary Coded Decimal (BCD) information
FILE 2 (NOML)	CONTAINS the nominal trajectory
FILE 3 (3SIGL)	CONTAINS the 3 sigma left trajectory
FILE 4 (3SIGR)	CONTAINS the 3 sigma right trajectory

Figure A6.7. Example for item 12, variable window.

FILE 1 (INFO)	CONTAINS the Binary Coded Decimal (BCD) information
FILE 2 (NOM1)	CONTAINS the nominal trajectory from liftoff to injection into the parking orbit for a flight azimuth of 90 degrees
FILE 3 (NOM2)	CONTAINS the nominal trajectory from liftoff to injection into the parking orbit for a flight azimuth of 93 degrees
FILE 4 (NOM3)	CONTAINS the nominal trajectory from liftoff to injection into the parking orbit for a flight azimuth of 96 degrees
FILE 5 (3SIGL)	CONTAINS the 3 sigma left trajectory from liftoff to injection into the parking orbit for a flight azimuth of 90 degrees
FILE 6 (SIGR)	CONTAINS the 3 sigma right trajectory from liftoff to injection into the parking orbit for a flight azimuth of 111 degrees

A6.3.5.13. Item 13.

A6.3.5.13.1. Positive direction of the yaw axis. The direction of the yaw axis in the right-handed system may be positive in the downrange direction or in the up-range direction. This assumes the system is in the initial vertical position with the positive roll axis vertical.

A6.3.5.13.2. EXAMPLE: Yaw axis is positive downrange.

A6.3.6. Launch Program Information Item Options. The remaining information items will be used with a specific category of launch vehicles. The categories of launch vehicles to be defined are ballistic, fixed azimuth orbital, and variable flight azimuth-orbital (continuously variable, CVFA, or step-wise variable, SVFA). The Range User will determine from the information in this package description the category which best describes his vehicle objectives and use only that option. In the event that one of the options does not fit a Range User's launch description, or if doubts exist, the lead range will be contacted to discuss a complete package. It is anticipated that launch programs will arise which will not fit into one of the categories.

A6.3.6.1. Option 1A. Ballistic Type Launch with single R/V (reentry vehicle). The additional information items for single R/V ballistic type programs are:

A6.3.6.1.1. Item 14.

A6.3.6.1.1.1. Total time (3D) of flight in seconds.

A6.3.6.1.1.2. EXAMPLE: The total time of flight from liftoff to impact is 1456.080 seconds.

A6.3.6.1.2. Item 15.

A6.3.6.1.2.1. Range (4D) to target.

A6.3.6.1.2.2. EXAMPLE: The range from launch pad to target is 13,200.6231 Nautical Miles.

A6.3.6.1.3. Item 16.

A6.3.6.1.3.1. Geodetic latitude (6D) and longitude (6D) of target. See information Item 5 for the definition of longitude.

A6.3.6.1.3.2. EXAMPLE: The target is 2.621486 degrees north geodetic latitude

and -1.421634 degrees west longitude.

A6.3.6.1.4. Item 17.

A6.3.6.1.4.1. Weight (1D) of reentry vehicle for drag calculations.

A6.3.6.1.4.2. EXAMPLE. The reentry vehicle weighs 1062.3 pounds.

A6.3.6.1.5. Item 18.

A6.3.6.1.5.1. Reference cross-sectional area (3D) for drag calculations.

A6.3.6.1.5.2. EXAMPLE. Cross-sectional area of the reentry vehicle is 93.321 square feet.

A6.3.6.1.6. Item 19.

A6.3.6.1.6.1. Table of coefficients of drag (2D) versus Mach number (2D) for defining drag curve of re-entry vehicle, when there is to be a recovery.

A6.3.6.1.6.2. EXAMPLE: See [Figure A6.8](#).

Figure A6.8. Example for item 19, Coefficients of Drag vs. Mach Number.

<u>Mach No.</u>	<u>CD</u>
0.00	0.85
1.00	0.85
2.00	0.86
3.00	0.87
...	...
20.00	1.19
30.00	1.18
40.00	1.17

A6.3.6.1.6.3. This table should contain a minimum of 30 points. Sufficient points should be chosen such that a series of straight lines will reproduce the curve. Coefficients of drag should be included for a zero Mach number and for at least two Mach numbers greater than the expected performance maximum.

A6.3.6.1.6.4. For booster recovery data or track, the coefficient of drag table for the boost body should reflect what the Range User considers will be the most likely flight configuration. **Note:** Where the cross-sectional area, weight, and coefficients of drag are Restricted Data, place the statement "See Item 19" in both Items 17 and 18. Replace the table of coefficients in Item 19 with a table of CDA/W for the same range of Mach numbers. If any of these parameters change as a result of ablation or other reasons, the revised values will be noted.

A6.3.6.2. Option 1B. Ballistic Type Launch with Multiple R/Vs. Units of measure may be English or metric. The additional information items for multiple R/V ballistic type programs are:

A6.3.6.2.1. Item 14. Statement such as "See Item 16."

A6.3.6.2.2. Item 15. Statement such as "See Item 16."

A6.3.6.2.3. Item 16.

A6.3.6.2.3.1. Table of all R/V total times of flight (3D) from liftoff to impact, ranges (4D) of all R/Vs from launch point to impacts, geodetic latitudes (6D) and longitudes (6D) of all R/V impacts, and reentry azimuths (1D) for all R/Vs at impact.

A6.3.6.2.3.2. EXAMPLE: See [Figure A6.9](#).

Figure A6.9. Example for item 16, Table of all R/V Times of Flight.

<u>R/V</u>	<u>Flight time</u>	<u>Range</u>	<u>Latitude</u>	<u>Longitude</u>	<u>Azimuth</u>
1					
2					
3					
...					

A6.3.6.2.4. Item 17.

A6.3.6.2.4.1. Weights of all R/Vs.

A6.3.6.2.4.2. EXAMPLE: R/V is 200 pounds. All other R/Vs are 225 pounds.

A6.3.6.2.5. Item 18.

A6.3.6.2.5.1. Cross-sectional areas of all R/Vs.

A6.3.6.2.5.2. EXAMPLE: All R/Vs are 3 ft squared.

A6.3.6.2.6. Item 19.

A6.3.6.2.6.1. Drag coefficients of all R/Vs. Drag coefficients should be provided in table with Mach number.

A6.3.6.2.6.2. EXAMPLE: See example for single R/V ballistic launch.

A6.3.6.3. Option 2. Fixed Azimuth Orbital Missions. The additional information items for an orbital or non-ballistic type programs are:

A6.3.6.3.1. Item 14. Description of the orbits (parking or other) to be attained in terms of the following parameters which define ordinary orbital elements of the osculating ellipse at epoch.

A6.3.6.3.1.1. Time of epoch (sec). The time from liftoff at which the orbital elements are calculated. The elements are desired after thrust drop-off and injection into orbit (2D).

A6.3.6.3.1.2. Semi major axis (NM) of the orbit. For the case of the hyperbolic orbit, the reciprocal of the semi major axis should be provided in units of nautical miles (NM) (4D).

A6.3.6.3.1.3. Eccentricity of the orbit (8D).

A6.3.6.3.1.4. Inclination (deg). The angle between the plane of the orbit and the plane of the equator measured from the plane of the equator at the ascending node. If the direction of motion of the satellite is the same as the earth's rotation, it is called direct and the inclination will be less than 90 degrees. However, if the motion

is opposite to the rotation of the earth, the orbit is called retrograde, and the inclination will be greater than 90 degrees. The limits of the inclination (i) will be $0^\circ \leq i \leq 180^\circ$ (4D).

A6.3.6.3.1.5. Longitude of the ascending node (deg). The angle measured eastward from the Greenwich meridian to the intersection of the equatorial plane and the orbital plane fixed at the time of epoch conditions when the path crosses the equatorial plane from south to north. The limits for the angle (Ω) will be $0^\circ \leq \Omega \leq 360^\circ$ (4D).

A6.3.6.3.1.6. Argument of Perigee (deg). The angle between the ascending node and the perigee is measured at the elliptical focus (center of the earth) in the plane of the orbit and in the direction of the satellite's motion. For a circular orbit, the argument of the perigee will be computed at the epoch point. The limits for the argument of perigee (ω) will be $0^\circ \leq \omega \leq 360^\circ$ (4D).

A6.3.6.3.1.7. Sum of True Anomaly and Argument of Perigee (deg). The true anomaly is the angle from the perigee point to the satellite at epoch measured at the elliptical focus in the direction of satellite motion. For circular orbits, perigee is taken at the time of epoch and thus the true anomaly would be zero. The limits for ($v+\omega$) will be $0^\circ \leq \omega \leq 360^\circ$ (4D).

A6.3.6.3.1.8. Period (min). The time between two successive perigee passages in Keplerian motion, defined in terms of semi major axis of the osculating ellipse (4D).

A6.3.6.3.1.9. Mean Anomaly (deg). The angle at the focus described by the radius vector moving at a mean angular rate n ($n=2\pi$ /period). Measured from perigee to the satellite at the time of epoch. The limits for the mean anomaly (M) will be $0^\circ \leq M \leq 360^\circ$ (4D).

A6.3.6.3.1.10. Time of Apogee (min). Time from liftoff to apogee passage. For the hyperbolic orbit this item should be the time of perigee and would be the time from liftoff to perigee passage (4D).

A6.3.6.3.1.11. Height of Apogee (NM). Height above ellipsoidal earth along the local geocentric vertical. For the hyperbolic orbit this item is not applicable, and the term "hyperbolic orbit" should be inserted in this location (4D).

A6.3.6.3.1.12. Height of Perigee (NM). Height above ellipsoidal earth along the local geocentric vertical (4D). (The parabolic orbit is not discussed but rather is considered as a special case of the hyperbolic orbit.)

A6.3.6.3.1.13. EXAMPLE: See [Figure A6.10](#).

Figure A6.10. Example for item 14, Orbit Descriptions.

The elements defining the orbit attained are:		
Time of epoch	308.00	seconds
Semi major axis	3562.4713	nautical miles
Eccentricity	0.000977859	-
Inclination	32.5892	degrees
Longitude of ascending node	345.5846	degrees
Argument of perigee	70.6536	degrees
Sum of true anomaly and argument of perigee	70.3391	degrees
Period	88.8833	minutes
Mean anomaly	359.6916	degrees
Time of apogee	44.3671	minutes
Height of apogee	153.3104	nautical miles
Height of perigee	83.6386	nautical miles

A6.3.6.3.2. Item 15. The constants defining the Potential Model used in computing the orbital information of item 14. The quantities are to be provided in units of kilometers and seconds only, where:

A6.3.6.3.2.1. The nautical mile is to be 6076.11549 international feet.

A6.3.6.3.2.2. The international foot is 0.3048 meters exactly.

A6.3.6.3.2.3. The nautical mile is 1852.00000 meters.

A6.3.6.3.2.4. GM gravitational parameter in km^3/sec^2 (1D).

A6.3.6.3.2.5. R_0 the mean equatorial radius of the earth in kilometers (3D).

A6.3.6.3.2.6. Harmonic coefficients in expansion of the Earth's potential (J2, J3, J4).

A6.3.6.3.2.7. For the notation recommendations of the J2, J3, and J4 terms, reference should be made to the Astronomical Journal, Volume 67, No 1, February 1962 No 1296, p. 108, "Recommendations on Notation of the Earth Potential."

A6.3.6.3.2.8. EXAMPLE: See [Figure A6.11](#).

Figure A6.11. Example for item 15, Constants Defining the Potential Model.

GME	398603.2 km^3/sec^2
RE	6378.165 km
J2	-0.00008230
J3	0.00000230
J4	-0.00000180

A6.3.6.3.3. Item 16.

A6.3.6.3.3.1. Geodetic latitude (6D) and longitude (6D) of target when there is to be a recovery.

A6.3.6.3.3.2. EXAMPLE: The target is 2.621486 degrees north latitude and -1.421634 degrees west longitude.

A6.3.6.3.4. Item 17.

A6.3.6.3.4.1. Weight (1D) of reentry vehicle when there is to be a recovery.

A6.3.6.3.4.2. EXAMPLE: The reentry vehicle weighs 1062.3 pounds.

A6.3.6.3.5. Item 18.

A6.3.6.3.5.1. Referenced cross-sectional area (3D) when there is to be a recovery.

A6.3.6.3.5.2. EXAMPLE: Cross-sectional area of the reentry vehicle data in item 16 is 93.321 square feet.

A6.3.6.3.6. Item 19.

A6.3.6.3.6.1. Table of coefficients of drag (2D) versus Mach number (2D) for defining drag curve of reentry vehicle, when there is to be a recovery.

A6.3.6.3.6.2. EXAMPLE: See [Figure A6.12](#).

Figure A6.12. Example for item 19, Coefficients of Drag vs. Mach Number.

<u>Mach No.</u>	<u>CD</u>
0.00	0.85
1.00	0.85
2.00	0.86
3.00	0.87
...	...
20.00	1.19
30.00	1.18
40.00	1.17

A6.3.6.3.6.3. This table will contain a minimum of 30 points, sufficiently chosen such that a series of straight lines would reproduce the curve. Coefficients of drag will be included for zero Mach number and for at least two Mach numbers greater than the expected performance maximum.

A6.3.6.3.6.4. For booster recovery data, the coefficient of drag table for the boost body should reflect what the Range User considers will be the most likely flight configuration. (Where the cross-sectional area, weight, and coefficients of drag are Restricted Data, place the stated "See Item 19" in both items 17 and 18. Replace the Table of Coefficients in item 19 with a Table of CDA/W for the same range of Mach numbers.)

A6.3.6.4. Option 3. Continuously Variable Flight Azimuth Missions. Additional items to complete the information required for variable flight azimuth missions are as described below. Reference will be made to the comments in other portions of this description for the assumptions made for this type program.

A6.3.6.4.1. Item 14.

A6.3.6.4.1.1. Orbital elements describing the parking orbit (see list of required elements and definitions under Option 2, Item 14). The orbital elements will be provided for each nominal trajectory identified.

A6.3.6.4.1.2. EXAMPLE: Refer to similar example under Option 2, Item 14.

A6.3.6.4.2. Item 15. The constants defining the Potential Model used in computing the orbital information of item 14. See requirements for Item 15 of Option 2.

A6.3.6.4.3. Item 16.

A6.3.6.4.3.1. The calendar dates of the possible launch period.

A6.3.6.4.3.2. EXAMPLE: The launch period will be from 4 May through 19 May 2021.

A6.3.6.4.4. Item 17.

A6.3.6.4.4.1. Launch Reference Table. A matrix relating the provided nominal trajectories for each calendar day in the launch period to the following values:

A6.3.6.4.4.1.1. Flight azimuth (2D).

A6.3.6.4.4.1.2. Greenwich Mean Time of Liftoff in hours, minutes, seconds (0D).

A6.3.6.4.4.2. EXAMPLE: See [Figure A6.13](#).

Figure A6.13. Example for item 17, Launch Reference Table.

	<u>4 May 2021</u>	<u>5 May 2021</u>	<u>6 May 2021</u>	...	<u>19 May 2021</u>
Planar 90 deg	12:24:30	12:25:33	12:26:45	...	12:51:15
Planar 93 deg	12:30:15	12:32:45	12:33:55	...	12:58:00
...
Planar 112 deg	14:25:42	14:27:02	14:28:35	...	14:45:50

A6.3.6.4.5. Item 18.

A6.3.6.4.5.1. Orbital elements describing the final orbit. (See the list of required elements and definitions under Option 2, Item 14.)

A6.3.6.4.5.2. EXAMPLE: Refer to similar example under Option 2, Item 14.

A6.3.6.4.6. Item 19.

A6.3.6.4.6.1. The constants defining the potential model used in computing the orbital elements. (Refer to the description under Option 2, Item 15.)

A6.3.6.4.6.2. EXAMPLE: Refer to the similar example under Option 2, Item 15.

A6.3.6.5. Option 4. Stepwise Variable Flight Azimuth Missions. The present trajectory package is to include complete trajectories for each reference azimuth for each day of any launch opportunity under consideration. The package also specifies flight azimuth increments, sampling rates, listing of orbital parameters and critical event times, and other associated items. Dispersion trajectories as such (i.e., 3 sigma Maximum IIP, 3 sigma Minimum IIP, 3 sigma Left and Right Lateral IIP) are also required. Additional items to complete the information required for stepwise variable flight azimuth missions are as described below. Reference will be made to the comments in other portions of this description for the assumptions made for this type program.

A6.3.6.5.1. Item 14.

A6.3.6.5.1.1. Orbital elements describing the parking orbit (see list of required elements and definitions under Option 2, Item 14). The orbital elements will be provided for each nominal trajectory identified.

A6.3.6.5.1.2. EXAMPLE: Refer to similar example under Option 2, Item 14.

A6.3.6.5.2. Item 15. The constants defining the Potential Model used in computing the orbital information of item 14. See requirements for Item 15 of Option 2.

A6.3.6.5.3. Item 16.

A6.3.6.5.3.1. The calendar dates of the possible launch period.

A6.3.6.5.3.2. EXAMPLE: The launch period will be from 4 May through 19 May 2021.

A6.3.6.5.4. Item 17.

A6.3.6.5.4.1. Launch Reference Table. A matrix relating the provided nominal trajectories for each calendar day in the launch period to the following values:

A6.3.6.5.4.1.1. Flight azimuth (2D).

A6.3.6.5.4.1.2. Greenwich Mean Time of Liftoff in hours, minutes, seconds (0D).

A6.3.6.5.4.1.3. EXAMPLE: See [Figure A6.14](#).

Figure A6.14. Example for item 17, Launch Reference Table.

		<u>4 May 2021</u>	<u>5 May 2021</u>	<u>6 May 2021</u>	...	<u>19 May 2021</u>
Yaw left	93 deg	12:24:30	12:25:33	12:26:45	...	12:51:15
Planar	93 deg	12:30:15	12:32:45	12:33:55	...	12:58:00
Yaw right	93 deg	12:36:15	12:38:23	12:40:10	...	13:05:22
...	
Yaw left	112 deg	14:25:42	14:27:02	14:28:35	...	14:45:50
Planar	112 deg	14:27:30	14:28:39	14:29:56	...	14:46:33
Yaw right	112 deg	14:29:21	14:30:24	14:31:45	...	14:48:12

A6.3.6.5.5. Item 18.

A6.3.6.5.5.1. Orbital elements describing the final orbit. (See the list of required elements and definitions under Option 2, Item 14.)

A6.3.6.5.5.2. EXAMPLE: Refer to similar example under Option 2, Item 14.

A6.3.6.5.6. Item 19.

A6.3.6.5.6.1. The constants defining the potential model used in computing the orbital elements. (Refer to the description under Option 2, Item 15.)

A6.3.6.5.6.2. EXAMPLE: Refer to the similar example under Option 2, Item 15.

A6.3.7. Contents of the Trajectory Data Files. See [Table A6.1](#) for detailed descriptions of trajectory data file content. **Note:** English units are used throughout the description of the file and are the preferred input. However, metric units may be used throughout the trajectory data files.

Table A6.1. Contents of the Trajectory Data Files.

WORD	DESCRIPTION	
1	Time in seconds (4D) Definition: Time will be measured from first motion of the first stage. This time will correspond to 0.0000 seconds and all trajectory data will be referenced to it.	
2	X position coordinate in feet (1D)	Definition: The earth-fixed, pad-centered coordinate system must be left-handed with the X-Y axis lying in the plane tangent to the ellipsoidal earth at the launching pad. The X-axis coincides with the initial flight azimuth and the azimuth of the positive Y-axis is 90 degrees less. The positive Z-axis is perpendicular to the X-Y plane and directed away from the earth.
3	Y position coordinate in feet (1D)	
4	Z position coordinate in feet (1D)	
5	X velocity (2D) in feet/second (VX)	
6	Y velocity (2D) in feet/second (VY)	
7	Z velocity in (2D) feet/second (VZ)	
8	X acceleration in (2D) feet/second/second (AX)	
9	Y acceleration in (2D) feet/second/second (AY)	
10	Z acceleration in (2D) feet/second/second (AZ)	
11	L11	
12	L21	
13	L31	
14	L12	Word Positions 14, 15, and 16 are Direction Cosines of pitch axis (8D)
15	L22	
16	L32	
17	L13	Word Positions 17, 18, and 19 are Direction Cosines of yaw axis (8D)
18	L23	
19	L33	
Definition: The reference system for the direction cosines must be the Earth-fixed Greenwich (EFG) Coordinate System which is a right-handed, earth-centered, earth-fixed coordinate system whose positive G axis is the north polar axis. The E and F axis are in the equatorial plane and the positive E axis cuts the prime meridian. The positive F axis cuts the 90° East meridian.		

$$\begin{bmatrix} \mathbf{E} \\ \mathbf{F} \\ \mathbf{G} \end{bmatrix} = \begin{bmatrix} L_{11} & L_{12} & L_{13} \\ L_{21} & L_{22} & L_{23} \\ L_{31} & L_{32} & L_{33} \end{bmatrix} \begin{bmatrix} \mathbf{X}_n \\ \mathbf{Y}_n \\ \mathbf{Z}_n \end{bmatrix}$$

Where :

\mathbf{X}_n , \mathbf{Y}_n , and \mathbf{Z}_n are the unit vectors along the roll, pitch, and yaw axis, respectively. \mathbf{E} , \mathbf{F} , and \mathbf{G} are the unit vectors along the E, F, and G axis, respectively.

The roll axis is a line identical to the vehicle's longitudinal axis. Its origin is at the vehicle's nominal center of gravity with the positive portion through a point on the nose.

The roll plane is a plane normal to the roll axis at the vehicle's nominal center of gravity.

The yaw axis and the pitch axis are two orthogonal axes (chosen at the contractor's discretion) lying in the roll plane. Roll, pitch, and yaw axis must be right-handed system (that is, when looking along the roll-axis toward the nose, a clockwise rotation around the roll axis will send the pitch axis toward the yaw axis).

(1) The right-handed system may be oriented such that the yaw axis is positive in the downrange direction while in the vertical position (roll axis upward from surface) or positive at an angle of 180° to the downrange direction. The axis, if desired, may be related to the vehicle's normal orientation with respect to the vehicle's trajectory but once defined remain fixed with respect to the vehicle's body.

(2) The positive direction of the yaw axis should be indicated in information item 13.

20	Geodetic latitude (6D) of submissile point degrees (LATT)	Definition. The submissile point is that point on the referenced spheroid which is located by the normal to the spheroid which passes through the tracking point on the vehicle.
21	Longitude (6D) of submissile point in degrees (LONG). See information item 5 for the system of indicating East and West values.	
22	Altitude (1D) of vehicle in feet (ALT). Definition. Altitude is the distance from the submissile point to the tracking point on the vehicle.	
23	Total earth-fixed velocity (2D) in feet/second (VR). Definition. Total earth-fixed velocity: $(VX^2+VY^2+VZ^2)^{1/2}$.	
24	Total earth-fixed acceleration (2D) in feet/second/second (AR). Definition. Total earth-fixed acceleration = $(AX^2+AY^2+AZ^2)^{1/2}$.	

25	Arc range (4D) along earth's surface to submissile point in nautical miles (RA). The distance would be measured in the downrange direction from the launch pad.
26	Path angle of velocity vector (1D) relative to local horizontal in degrees (PAV). Definition. The path angle is the angle between the local horizontal (Horizontal plane) and the velocity vector measured upward from the local horizontal. The local horizontal is a plane tangent to the ellipsoidal earth at the submissile point.
27	Time of flight (2D) remaining to instantaneous vacuum impact point in seconds (TIIP). Definition. The time of flight is the flight time remaining to an instantaneous vacuum impact point assuming that all vehicle thrust is terminated at some time after launch. The instantaneous vacuum impact point is a Keplerian solution only. The instantaneous impact point is the location at which the vehicle would meet the spheroid and is measured in the downrange direction from the launch point in the flight plane.
28	Geodetic latitude (5D) of instantaneous vacuum impact point in degrees (PHI)
29	Longitude (5D) of instantaneous vacuum point in degrees (LAMBDA). See information item 5 for the system of indicating east and west values.
30	Arc ground range (2D) from launching pad to instantaneous vacuum impact point in nautical miles measured downrange from the launch pad (RIIP).
31	Total thrust (1D) in pounds. Note: Total thrust is a scalar.
32	Total weight (1D) in pounds
33	E position coordinate in feet (1D)
34	F position coordinate in feet (1D)
35	G position coordinate in feet (1D)
36	E velocity component (2D) in feet/second (VE)
37	F velocity component (2D) in feet/second (VF)
38	G velocity component (2D) in feet/second (VGG)

A6.3.8. Format of the Tabulated Data. All the values associated with a time will be tabulated with that time in the format shown in [Figure A6.15](#) Time is Word 1, and the other values will be referred to by their word numbers. (See Contents of the Trajectory Files.) If data words of a record are missing from a normally filled position, a code word should be printed on the tab copy each time this occurs. The code word in the printout corresponding to missing data will be MISSING.

Figure A6.15. Format of the Tabulated Data.

Word 1	Word 2	Word 3	Word 4
Word 5	Word 6	Word 7	Word 8
Word 9	Word 10	Word 11	Word 12
Word 13	Word 14	Word 15	Word 16
Word 17	Word 18	Word 19	Word 20
Word 21	Word 22	Word 23	Word 24
Word 25	Word 26	Word 27	Word 28
Word 29	Word 30	Word 31	Word 32
Word 33	Word 34	Word 35	Word 36
Word 37	Word 38		

A6.3.8.1. English System. When the English system of data units is used, at the start of the first page of trajectory data, the heading will be printed as shown in [Figure A6.16](#).

Figure A6.16. English System.

TIME (S)	X (FT)	Y (FT)	Z (FT)
VX (FT/SEC)	VY (FT/SEC)	VZ (FT/SEC)	AX (FT/SEC/SEC)
AY (FT/SEC/SEC)	AZ (FT/SEC/SEC)	L11	L21
L31	L12	L22	L32
L13	L23	L33	LATT (DEG)
LONG (DEG)	ALT (FT)	VR (FT/SEC)	AR (FT/SEC/SEC)
RA (NM)	PAV (DEG)	TIIP (SEC)	PHI (DEG)
LAMBDA (DEG)	RIIP (NM)	THRUST (LBS)	WEIGHT (LBS)
E (FT)	F (FT)	G (FT)	VE (FT/SEC)
VF (FT/SEC)	VG (FT/SEC)		

A6.3.8.2. Metric System. When the metric system of data units is used, the heading will be printed as shown in [Figure A6.17](#).

Figure A6.17.

TIME (S)	X (M)	Y (M)	Z (M)
VX (M/SEC)	VY (M/SEC)	VZ (M/SEC)	AX (M/SEC/SEC)
AY (M/SEC/SEC)	AZ (M/SEC/SEC)	L11	L21
L31	L12	L22	L32
L13	L23	L33	LATT (DEG)
LONG (DEG)	ALT (M)	VR (M/SEC)	AR (M/SEC/SEC)
RA (KM)	PAV (DEG)	TIIP (SEC)	PHI (DEG)
LAMBDA (DEG)	RIIP (KM)	THRUST (N)	WEIGHT (KG)
E (M)	F (M)	G (M)	VE (M/SEC)
VF (M/SEC)	VG (M/SEC)		

A6.3.8.3. Paper Size. The paper size for the tabulated data will be 11-by 15-inches, or 8 1/2-by 11-inches.

A6.4. Media.

A6.4.1. Range Safety will work with the Range User on the delivery method and what is the latest Range supportable media to be used.

A6.4.1.1. Medium Identification.

A6.4.1.1.1. Each delivery medium must have a means of identification attached to it. This identification must include:

A6.4.1.1.1.1. The name or number of the missile program.

A6.4.1.1.1.2. Identification as to which medium of a series; for example, medium 2 of 3.

A6.4.1.1.1.3. Filename of each file on the disk.

A6.4.1.1.1.4. Volume or serial number.

A6.4.1.1.2. The identification can be items such as computer run number identifier, an internal work request or a similar identifier which is listed in the tab copy heading.

A6.4.1.1.3. Give a unique method of correlating the filenames and tab copy. The lead range can devise its own system of internal identification using the information on the tab printout.

Attachment 7

RANGE RISK ANALYSIS TOOL (RRAT) COVARIANCE INPUT FILE FORMATS

A7.1. Introduction. The debris risk program used by the SSC ranges and FAA accept three file formats that define the uncertainty in position and velocity of the nominal trajectory due to guidance and performance uncertainties. The Metric Covariance (MCOV), and Guidance and Performance State Vector (GPSV) formats are the preferred formats. The Metric Body Axis Data (MBOD) format uses a vehicle velocity-based coordinate system and the GPSV format is used when providing Monte Carlo trajectory results. The three formats are detailed below:

A7.1.1. The Metric Covariance (MCOV) data file format allows the user to input directly the full 6x6 covariance matrix in Earth centered, rotating (ECR, consisting of EFG axes fixed in the rotating Earth) coordinates. The MCOV representation of uncertainty is the same as is used internally in the Common Real-Time Debris Footprint (CRTF) program operating inside RRAT; all other inputs are transformed to this coordinate system. Therefore, this input method provides the most control for the user, but the file is more difficult to create and to understand than other formats. Note that in the current version of the computation, the off-diagonal 3x3 position and velocity covariance matrices (top right 3x3 and bottom left 3x3) are not used due to problems with numerical decomposition of near-singular matrices—instead, they are replaced with zeroes. Neglecting these terms typically has little effect on the resulting dispersions.

A7.1.2. A second input format, MBOD, is similar to the MCOV format but it is in a different coordinate system. The MBOD format looks the same as MCOV as it includes the full covariance matrix. The coordinate system is relative to the vehicle velocity vector. The body-axis system is defined such that (1,1) is the variance along the axial vector of the vehicle (assumed to be in the direction of the velocity vector), (2,2) is the variance in the yaw direction, and (3,3) is the variance in the pitch direction. These correspond to the standard xyz coordinates of the body-axis system. Like the MCOV format, the off-diagonal 3x3 covariance matrices are not used and are replaced by zeroes.

A7.1.3. Guidance and Performance State Vector (GPSV) data file format allows for the input of Monte Carlo simulations of the nominal trajectory. These sources of metric uncertainty may represent variations of the initial conditions or variations of the forces on the vehicle as it moves along its flight path. Several hundred simulation trajectories are usually required to obtain sufficient statistics to accurately sample the uncertainty. When a GPSV file is used in an analysis, the position-velocity covariance is computed from all the state vectors at each state time, and that uncertainty is used. CRTF also writes the covariance to an MCOV format file called “Metric_Cov.Dat”. Use of the MCOV format is faster than the GPSV format, and therefore it is often more efficient to generate the “Metric_Cov.Dat” file once (by running CRTF), and then change the metric file specification to point to this generated file. This is particularly important when CRTF is run remotely, because CRTF is executed many times with the same metric file.

A7.2. RRAT File Format Requirements.

A7.2.1. MCOV File Format. The MCOV file is ASCII and is in a free field format so the data must obey Ada standards. See [Table A7.1](#) for an explanation of the MCOV file data record format.

Table A7.1. MCOV File Data Record Format.

<u>Entry</u>	<u>Name</u>	<u>Description</u>	<u>Units</u>
1	TIME	Plus count from liftoff	sec
2	E	Mean E position coordinate in ECR coordinates	ft
3	F	Mean F position coordinate in ECR coordinates	ft
4	G	Mean G position coordinate in ECR coordinates	ft
5	EDOT	Mean E velocity coordinate in ECR coordinates	ft/sec
6	FDOT	Mean F velocity coordinate in ECR coordinates	ft/sec
7	GDOT	Mean G velocity coordinate in ECR coordinates	ft/sec
8-42	COV	6X6 position-velocity metric covariance in ECR coordinates	ft ² , ft ² /sec ²

A7.2.1.1. A sample of an MCOV data file is shown in [Figure A7.1](#).

Figure A7.1. MCOV Data File Example.

```

MCOV
0.000E+00 -1.820E+07 -6.705E+06 7.810E+06 -2.059E+00 -5.825E-01 1.187E+00
0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00
0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00
0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00 0.0000E+00
0.0000E+00 0.0000E+00 0.0000E+00 1.1280E-03 2.1042E-04 -4.9996E-04
0.0000E+00 0.0000E+00 0.0000E+00 2.1042E-04 2.0750E-04 -1.0759E-04
0.0000E+00 0.0000E+00 0.0000E+00 -4.9996E-04 -1.0759E-04 2.6822E-04
1.000E+00 -1.821E+07 -6.705E+06 7.810E+06 -3.543E+01 -7.137E+00 2.402E+01
8.1862E-02 1.7294E-02 -4.0779E-02 9.0999E-02 2.2957E-02 -5.8802E-02
1.7294E-02 3.4077E-02 -4.3490E-03 -5.9089E-02 9.5624E-04 4.0541E-02
-4.0779E-02 -4.3490E-03 3.6000E-02 -9.3347E-02 -2.4412E-02 6.5740E-02
9.0999E-02 -5.9089E-02 -9.3347E-02 1.1773E+00 3.1494E-01 -6.4752E-01
2.2957E-02 9.5624E-04 -2.4412E-02 3.1494E-01 1.0653E-01 -1.6508E-01
-5.8802E-02 4.0541E-02 6.5740E-02 -6.4752E-01 -1.6508E-01 3.8530E-01
2.000E+00 -1.822E+07 -6.705E+06 7.810E+06 -7.272E+01 -1.510E+01 4.910E+01

```

A7.2.1.2. Although shown in the example, the position-velocity correlations are ignored by CRTF; only the position 3x3 variance submatrix and velocity 3x3 variance submatrix are employed.

A7.2.2. MBOD File Format. The MBOD file is ASCII and is in a free field format so the data must obey Ada standards. See [Table A7.2](#) for an explanation of the MBOD file data record format.

Table A7.2. MBOD File Data Record Format.

Entry	Name	Description	Units
1	TIME	Plus count from liftoff	sec
2	E	Mean E position coordinate in ECR coordinates	ft
3	F	Mean F position coordinate in ECR coordinates	ft
4	G	Mean G position coordinate in ECR coordinates	ft
5	EDOT	Mean E velocity coordinate in ECR coordinates	ft/sec
6	FDOT	Mean F velocity coordinate in ECR coordinates	ft/sec
7	GDOT	Mean G velocity coordinate in ECR coordinates	ft/sec
8-42	COV	6X6 position-velocity metric covariance in body axis (axial, yaw, pitch) coordinates	ft ² , ft ² /sec ²

A7.2.2.1. A sample of an MBOD data file is shown in [Figure A7.2](#).

Figure A7.2. MBOD Data File Example.

MBOD						
0.000E+00	-1.820E+07	-6.705E+06	7.810E+06	-2.059E+00	-5.825E-01	1.187E+00
0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
0.0000E+00	0.0000E+00	0.0000E+00	1.1280E-03	2.1042E-04	-4.9996E-04	
0.0000E+00	0.0000E+00	0.0000E+00	2.1042E-04	2.0750E-04	-1.0759E-04	
0.0000E+00	0.0000E+00	0.0000E+00	-4.9996E-04	-1.0759E-04	2.6822E-04	
1.000E+00	-1.821E+07	-6.705E+06	7.810E+06	-3.543E+01	-7.137E+00	2.402E+01
8.1862E-02	1.7294E-02	-4.0779E-02	9.0999E-02	2.2957E-02	-5.8802E-02	
1.7294E-02	3.4077E-02	-4.3490E-03	-5.9089E-02	9.5624E-04	4.0541E-02	
-4.0779E-02	-4.3490E-03	3.6000E-02	-9.3347E-02	-2.4412E-02	6.5740E-02	
9.0999E-02	-5.9089E-02	-9.3347E-02	1.1773E+00	3.1494E-01	-6.4752E-01	
2.2957E-02	9.5624E-04	-2.4412E-02	3.1494E-01	1.0653E-01	-1.6508E-01	
-5.8802E-02	4.0541E-02	6.5740E-02	-6.4752E-01	-1.6508E-01	3.8530E-01	
2.000E+00	-1.822E+07	-6.705E+06	7.810E+06	-7.272E+01	-1.510E+01	4.910E+01

A7.2.2.2. Although shown in the example, the position-velocity correlations are ignored by CRTF; only the position 3x3 variance submatrix and velocity 3x3 variance submatrix are employed.

A7.2.2.3. Note for both MCOV and MBOD formats, the off diagonal 3x3 covariances are not required. Additionally, entries 2-7 are also not required for uncertainty calculations.

A7.2.3. GPSV File Format. The GPSV file is ASCII and is in a free field format so the data must obey Ada standards. See [Table A7.3](#) for an explanation of the GPSV file data record format.

Table A7.3. GPSV File Data Record Format.

<u>Entry</u>	<u>Name</u>	<u>Description</u>	<u>Unit</u>
1	TOF	Time of vehicle failure	sec
2	LON	Longitude of G&P trajectory point	deg
3	GDLAT	Geodetic latitude of G&P trajectory point	deg
4	ALT	Geodetic elevation above mean sea level of G&P trajectory point	ft
5	VNORTH	Northward velocity component of G&P trajectory velocity vector	ft/sec
6	VEAST	Eastward velocity component of G&P trajectory velocity vector	ft/sec
7	VDOWN	Downward velocity component of G&P trajectory velocity vector	ft/sec

A7.2.3.1. A sample of a GPSV file, which shows portions of the first three Monte Carlo cycles, is as shown in [Figure A7.3](#).

Figure A7.3. GPSV Data File Example.

TOF (sec)	LON (deg)	GDLAT (deg)	ALT (ft)	VNORTH (fps)	VEAST (fps)	VDOWN (fps)
0.000	-159.782	22.05926	98.4	0.3	-0.16	-2.46
1.000	-159.782	22.05927	118.1	8.43	-5.22	-42.22
2.000	-159.782	22.05931	183.7	17.72	-10.96	-86.61
0.000	-159.782	22.05926	98.4	0.3	-0.16	-2.43
1.000	-159.782	22.05927	118.1	8.83	-5.35	-41.99
2.000	-159.782	22.05931	180.4	17.91	-10.63	-86.25
0.000	-159.782	22.05926	98.4	0.3	-0.16	-2.43
1.000	-159.782	22.05927	118.1	9.06	-5.51	-41.73

A7.2.3.2. There is no limit on the number of trajectories, or their duration, that may be input. Note that there is no identifier for the Monte Carlo cycle value. The example above also shows that the start and stop times for each Monte Carlo cycle need not agree. Fewer cycles at a given time will simply result in weaker statistics when covariance matrices are generated for each state time using the GPSV data.